

## FCC§15.247 (i), §1.1307 (b) (3) &§2.1091 – RF EXPOSURE

### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2f$ .
1,500-100,000	$19.2R^2$ .

R is the minimum separation distance in meters  
 f = frequency in MHz

### Result

Mode	Frequency (MHz)	Antenna Gain		★Tune up conducted Power (dBm)	ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBi)	(dBd)		(dBm)	(W)		
Wi-Fi	2412-2462	2.7	0.55	22.50	23.05	0.202	0.2	0.768
BLE	2402-2480	2.7	0.55	3.00	3.55	0.002	0.2	0.768

- Note: 1. Wi-Fi and Bluetooth cannot transmit simultaneous  
 2. For the above tune-up output power were all declared by the manufacturer.

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

### Result: Compliance