



According to 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

--f(GHz) is the RF channel transmit frequency in GHz

--Power and distance are rounded to the nearest mW and mm before calculation

--The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,  $\text{---}10^{((\text{dBuV/m})/20)} / 10^6$

d = measurement distance in meters (m)  $\text{---}3\text{m}$

$$\text{So pt} = (\text{EXd})^2 / 30 \times \text{gt}$$

Field strength = 95.60dBuV/m @3m

Ant gain = 0.00dBi, so Ant numeric gain = 1.00

$$\text{So pt} = \{ [10^{(95.60/20)} / 10^6 \times 3]^2 / 30 \times 1 \} \times 1000 \text{ mW} = 1.089\text{mW}$$

$$\text{So } (1.089\text{mW} / 5\text{mm}) \times 2.480 = 0.343 < 3$$

Then SAR evaluation is not required