

Test Report No.: FM190226N009

# RF EXPOSURE REPORT

Applicant	Innovative Technology Electronics, LLC
Address	1 Channel Drive, Port Washington, NY 11050, USA

Manufacturer or Supplier	Guangdong Leetac Electronics Technology Co .,Ltd.		
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.		
Product	Jusic Center with Bluetooth		
Brand Name	Victrola, Innovative Technology		
Model	VTA-600B(PC)		
Additional Model & Model Difference	VTA-600B(PC)-MAH, VTA-600B(PC)-ESP, VTA-600B(PC)-WHT, etc.; see item 1		
Date of tests	Feb. 26, 2019 ~ Apr. 04, 2019		

- FCC Part 2 (Section 2.1091)
- **KDB 447498 D01**
- **⊠** IEEE C95.1

#### CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Tom Chen Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department
Tom	Date: Apr. 19, 2019

Date: Apr. 19, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



# Test Report No.: FM190226N009

# **TABLE OF CONTENTS**

RELE	ASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	.5
3.	MPE CALCULATION FORMULA	.5
4.	CLASSIFICATION	.5
5.	ANTENNA GAIN	.6
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM190226N009	Original release	Apr. 19, 2019

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 3 of 6



## 1. CERTIFICATION

FCC ID:	D: 2AFHW-VTA600BPC		
PRODUCT:	Music Center with Bluetooth		
BRAND NAME:	Victrola, Innovative Technology		
MODEL NO.: VTA-600B(PC)			
ADDITIONAL NO.:	VTA-600B(PC)-MAH, VTA-600B(PC)-ESP, VTA-600B(PC)-WHT, VTA-600B(PC)-BLK, VTA-600B(PC)xxxx, ITVS-600B(PC), ITVS-600B(PC)xxxx (where x can be "0-9", "A-Z", "-" or blank and means color code of unit)		
APPLICANT:	Innovative Technology Electronics, LLC		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

#### NOTES:

Additional models (see above table) are identical in electrical, mechanical and physical
construction with the test model VTA-600B(PC) except with different model No., brand name for
trading purpose.

Victrola can be used for VTA-600B(PC), VTA-600B(PC)-MAH, VTA-600B(PC)-ESP, VTA-600B(PC)-WHT, VTA-600B(PC)-BLK, VTA-600B(PC)xxxx;

Innovative Technology can be used for ITVS-600B(PC), ITVS-600B(PC)xxxx.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



# 2. RF EXPOSURE LIMIT

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD MAGNETIC FIELD STRENGTH (V/m)		POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

## 3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



Test Report No.: FM190226N009

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	0	PCB Antenna	

# 6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

The tanea dendadica / Welage Fewer (declared by elient)						
Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)	
GFSK	2402-2480	-4	+-2	-6	-2	
8DPSK	2402-2480	-4	+-2	-6	-2	

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2441	-3.84
8DPSK	2441	-3.80

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	-2	0	20	1.25524e-4	1.0

--- END ---

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>