

FCC 47 CFR PART 15 SUBPART C**TEST REPORT****For****Product Name: Xiaoyi Mirror-less Camera****Brand Name: YI****Model No.: YI-M1****Series Model.: N/A****FCC ID: 2AFIB-DCM116****Test Report Number:****C160630R01-RPW****Issued for****Shanghai Xiaoyi Technology Co., Ltd.****6F,Building E,No.2889,Jinke Road,Shanghai,China****Issued by****Compliance Certification Services Inc.****Kun shan Laboratory****No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China****TEL: 86-512-57355888****FAX: 86-512-57370818**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1.	TEST RESULT CERTIFICATION.....	4
2.	EUT DESCRIPTION.....	5
3.	TEST METHODOLOGY	6
3.1.	EUT CONFIGURATION	6
3.2.	EUT EXERCISE	6
3.3.	GENERAL TEST PROCEDURES.....	6
3.4.	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	7
3.5.	DESCRIPTION OF TEST MODES.....	8
3.6.	ANTENNA DESCRIPTION	8
4.	INSTRUMENT CALIBRATION.....	9
4.1.	MEASURING INSTRUMENT CALIBRATION	9
5.	FACILITIES AND ACCREDITATIONS	11
5.1.	FACILITIES	11
5.2.	EQUIPMENT.....	11
5.3.	LABORATORY ACCREDITATIONS AND LISTING	11
5.4.	TABLE OF ACCREDITATIONS AND LISTINGS	12
6.	SETUP OF EQUIPMENT UNDER TEST.....	13
6.1.	SETUP CONFIGURATION OF EUT	13
6.2.	SUPPORT EQUIPMENT.....	13
7.	FCC PART 15.247 REQUIREMENTS.....	14
7.1.	6DB BANDWIDTH	14
7.2.	PEAK POWER	20
7.3.	PEAK POWER SPECTRAL DENSITY	22
7.4.	SPURIOUS EMISSIONS	29
7.5.	RADIATED EMISSIONS.....	47
7.6.	POWERLINE CONDUCTED EMISSIONS	62



Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	August 23, 2016	C160630R01-RPW	ALL	N/A

1. TEST RESULT CERTIFICATION

Product Name:	Xiaoyi Mirror-less Camera
Trade Name:	YI
Model Name.:	YI-M1
Series Model:	N/A
Applicant Discrepancy:	Initial
Device Category:	Mobile unit
Date of Test:	August 2, 2016 ~ August 10, 2016
Applicant:	Shanghai Xiaoyi Technology Co., Ltd. 6F,Building E,No.2889,Jinke Road,Shanghai,China
Manufacturer:	Shanghai Xiaoyi Technology Co., Ltd. 6F,Building E,No.2889,Jinke Road,Shanghai,China
Application Type:	Certification


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.


The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:



Jeff.Fang
 RF Manager
 Compliance Certification Service Inc.

Tested by:



Lily.Wang
 Test Engineer
 Compliance Certification Service Inc.

2. EUT DESCRIPTION

Product Name:	Xiaoyi Mirror-less Camera
Brand Name:	YI
Model Name:	YI-M1
Series Model:	N/A
Model Discrepancy:	N/A
Power Adapter:	For SUN-0500300 Model:A8-501000 INPUT: 100-240V~50/60Hz 0.2A Max OUTPUT : 5 V $\overline{\overline{=}}$ 1.0A
Frequency Range:	IEEE 802.11b/g: 2412MHz to 2462 MHz IEEE 802.11n HT20: 2412MHz to 2462 MHz
Transmit Power:	IEEE 802.11b mode: 17.80dBm IEEE 802.11g mode: 18.21 dBm IEEE 802.11n HT20 mode: 18.23 dBm
Modulation Technique:	IEEE802.11b mode: DSSS (1,2,5.5 and 11 Mbps) IEEE802.11g mode: DSSS /OFDM (6,9,12,18,24,36,48 and 54 Mbps) IEEE802.11n HT20 mode: OFDM (MCS0~MCS7)
Number of Channels:	IEEE 802.11b/g mode: 11 Channels IEEE 802.11n HT20 : 11 Channels
Antenna Specification:	PCB Antenna Gain: -6.4 dBi

Remark:

- 1.The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
- 2.This submittal(s) (test report) is intended for **FCC ID: 2AFIB-DCM116** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 2013 and FCC CFR 47 15.207, 15.209 and 15.247.

3.1.EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2.EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3.GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10 2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

Under 1GHz

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

Above 1GHz

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

3.4.FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5. DESCRIPTION OF TEST MODES

The worst-case data rates:

IEEE802.11b mode:

Channel Low (2412MHz)

Channel Mid (2437MHz)

Channel High (2462MHz) with 1Mbps data rate was chosen for full testing.

IEEE802.11g mode:

Channel Low (2412MHz)

Channel Mid (2437MHz)

Channel High (2462MHz) with 6Mbps data rate was chosen for full testing.

IEEE 802.11n HT20 MHz Channel mode:

Channel Low (2412MHz)

Channel Mid (2437MHz)


Channel High (2462MHz) with MCS0 data rate was chosen for full testing.

3.6. ANTENNA DESCRIPTION

an intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached or an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section”

* the antenna of this EUT is a unique(PCB Antenna for WiFi and Bluetooth).

* the EUT complies with the requirement of 15.203.



4. INSTRUMENT CALIBRATION

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Equipment Used for Emissions Measurement

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2015-9-11	2016-9-10
OSCILLOSCOPE	Agilent	DS06104A	MY44002585	2016-3-2	2017-3-1
Power meter	Anritsu	ML2495A	1445010	2016-5-16	2017-5-15
Power sensor	Anritsu	MA2411B	1339220	2016-5-16	2017-5-15
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	N.C.R	N.C.R
DC Power Supply	AGILENT	E3632A	MY50340053	N.C.R	N.C.R
Temp. / Humidity Chamber	TERCHY	MHK-120AK	X30109	2016-5-16	2017-5-15
Test Software			EZ-EMC		

977 Chamber					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2015-9-11	2016-9-10
EMI Test Receiver	R&S	ESCI	101378	2016-1-6	2017-1-5
Pre-Amplifier	MINI	ZFL-1000VH2	070306	2016-1-13	2017-1-12
Pre-Amplifier	Miteq	JS41-00101800-32-10P	1675713	2015-8-10	2016-8-9
Bilog Antenna	Sunol	JB1	A062604	2016-5-29	2017-5-28
Bilog Antenna	Sunol	JB1	A110204-1	2016-5-29	2017-5-28
Loop Antenna	SCHWARZBECK	HXYZ9170	9170-108	2016-4-7	2017-4-6
Horn-antenna	SCHWARZBECK	9120D	266	2016-3-6	2017-3-5
Horn-antenna	SCHWARZBECK	9120D	267	2015-11-10	2016-11-9
Turn Table	CT	CT123	4165	N.C.R	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R	N.C.R
Controller	CT	CT100	95637	N.C.R	N.C.R
Test Software			EZ-EMC		

Conducted Emission					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI TEST RECEIVER	R&S	ESCI	100781	2016-3-2	2017-3-1
LISN	SCHWARZBECK	NNLK 8129	8129-143	2015-11-2	2016-11-1
LISN (EUT)	FCC	FCC-LISN-50/250-50-2-02	05012	2015-9-16	2016-9-15
Pulse LIMITER	R&S	ESH3-Z2	100524	2016-1-6	2017-1-5
Test Software			EZ-EMC		

Remark: The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Expanded Uncertainty (95% CONFIDENCE INTERVAL): K=2

5. FACILITIES AND ACCREDITATIONS

5.1.FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300), CHINA.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 2013 and CISPR Publication 22.

5.2.EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.



Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3.LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with Industry Canada, Certification and Engineering Bureau, 2324E-1 for 10m chamber 10m, 2324E-2 for 10m chamber 3m; the test facilities are listed with USA, Certification and Engineering Bureau, 424105 for 10m chamber 10m, 238958 for 10m chamber 3m.

5.4. TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	47 CFR FCC Part 15/18 (using ANSI C63.10 :2013); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997 +A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998 +A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24	
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707 G-216

** No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.*

6. SETUP OF EQUIPMENT UNDER TEST

6.1.SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2.SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID
1.	Monitor	U2410f	KSLCD-03	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


7. FCC PART 15.247 REQUIREMENTS

7.1.6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, and 2400 - 2483.5 MHz bands, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW set as 100kHz., The VBW set as 3 times the RBW, set detector as Peak, the sweep time is auto.

TEST RESULTS

No non-compliance noted

Test Data

IEEE 802.11b mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	9.231	>500	PASS
Mid	2437	8.510		PASS
High	2462	8.317		PASS

IEEE 802.11g mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.142	>500	PASS
Mid	2437	15.144		PASS
High	2462	15.144		PASS


IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.337	>500	PASS
Mid	2437	15.577		PASS
High	2462	15.385		PASS


Test Plot

IEEE 802.11b MODE


6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)




6dB Bandwidth (CH High)




IEEE 802.11g MODE


6dB Bandwidth (CH Low)




6dB Bandwidth (CH Mid)




6dB Bandwidth (CH High)



IEEE 802.11n HT20 mode
6dB Bandwidth (CH Low)




6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)



1 PK
MAXH




7.2. PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, and 2400-2483.5 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

1. The EUT transmitter output is connected to the Power meter.
The Power meter is set to the peak power detection.
2. The testing follows the Measurement Procedure FCC KDB No. 558074 D01 DTS Meas.
3. Guidance v03r05. 9.1.2 PKPM1 Peak power meter method.

TEST RESULTS

No non-compliance noted

Test Data**Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
Low	2412	17.80	30.00
Mid	2437	17.65	30.00
High	2462	17.34	30.00

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
Low	2412	18.21	30.00
Mid	2437	17.76	30.00
High	2462	17.61	30.00

Test mode: IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
Low	2412	18.23	30.00
Mid	2437	17.93	30.00
High	2462	17.74	30.00

Average Power Test Data**Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Conducted Average Power (dBm)	Limit (dBm)
Low	2412	15.92	N/A
Mid	2437	15.65	N/A
High	2462	15.48	N/A

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Conducted Average Power (dBm)	Limit (dBm)
Low	2412	12.92	N/A
Mid	2437	12.53	N/A
High	2462	12.50	N/A

Test mode: IEEE 802.11n HT20 mode


Channel	Frequency (MHz)	Conducted Average Power (dBm)	Limit (dBm)
Low	2412	12.61	N/A
Mid	2437	12.42	N/A
High	2462	12.75	N/A

7.3. PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 1.5 times the DTS bandwidth, Sweep = auto
3. Record the max reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

Test Data**Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-7.16	8.00	PASS
Mid	2437	-8.15	8.00	PASS
High	2462	-7.09	8.00	PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-12.69	8.00	PASS
Mid	2437	-12.96	8.00	PASS
High	2462	-12.65	8.00	PASS


Test mode: IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-12.83	8.00	PASS
Mid	2437	-12.25	8.00	PASS
High	2462	-13.32	8.00	PASS


Test Plot

IEEE 802.11b mode


PPSD (CH Low)



PPSD(CH Mid)




PPSD (CH High)



IEEE 802.11g mode


PPSD (CH Low)



PPSD (CH Mid)




* RBW 3 kHz Marker 1 [T1]
 * VBW 10 kHz -12.96 dBm
 SWT 2.6 s 2.435712533 GHz



PPSD (CH High)




* RBW 3 kHz Marker 1 [T1]
 * VBW 10 kHz -12.65 dBm
 SWT 2.6 s 2.462568000 GHz




IEEE 802.11n HT20 mode

PPSD (CH Low)




PPSD (CH Mid)



PPSD (CH High)



* RBW 3 kHz
* VBW 10 kHz
SWT 2.6 s
Marker 1 [T1]
-13.32 dBm
2.462272650 GHz




7.4.SPURIOUS EMISSIONS

Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 30MHz to 40GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS



No non-compliance noted

Test Plot

OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT


IEEE 802.11b mode

CH Low






1 PK
MAXH




1 PK
MAXH




CH Mid



1 PK
MAXH




1 PK
MAXH






Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 1 [T1] -54.69 dBm
 * VBW 300 kHz 16.355365854 GHz
 SWT 2.3 s



CH High




Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 1 [T1] 6.81 dBm
 * VBW 300 kHz 2.462507833 GHz
 SWT 5 ms






Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 2 [T1] -38.58 dBm
*VBW 300 kHz 2.484428049 GHz
SWT 35 ms



Start 2.43 GHz 13.5 MHz/ Stop 2.565 GHz




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] -42.38 dBm
*VBW 300 kHz 147.713414634 MHz
SWT 300 ms



Start 30 MHz 297 MHz/ Stop 3 GHz



Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] -54.37 dBm
 *VBW 300 kHz 13.169024390 GHz
 SWT 2.3 s




IEEE 802.11g mode

CH Low




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] 2.91 dBm
 *VBW 300 kHz 2.413249600 GHz
 SWT 10 ms






Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 2 [T1] -22.79 dBm
 * VBW 300 kHz 2.397914634 GHz
 SWT 35 ms




Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 1 [T1] -50.65 dBm
 * VBW 300 kHz 97.006097561 MHz
 SWT 300 ms






Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 1 [T1] -55.00 dBm
 * VBW 300 kHz 23.314268293 GHz
 SWT 2.3 s



CH Mid




Ref 20 dBm * Att 20 dB * RBW 100 kHz Marker 1 [T1] 2.69 dBm
 * VBW 300 kHz 2.438249600 GHz
 SWT 10 ms






* RBW 100 kHz Marker 1 [T1]
 * VEW 300 kHz -48.23 dBm
 * Att 20 dB SWT 300 ms 121.997560976 MHz

1 PK
 MAXH





* RBW 100 kHz Marker 1 [T1]
 * VEW 300 kHz -54.98 dBm
 * Att 20 dB SWT 2.3 s 22.643902439 GHz

1 PK
 MAXH




CH High






* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -50.75 dBm
 * Att 20 dB 146.989024390 MHz
 * Att 20 dB SWT 300 ms



* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -54.28 dBm
 * Att 20 dB 4.973170732 GHz
 * Att 20 dB SWT 2.3 s




IEEE 802.11n HT20 mode


CH Low



1 PK
MAXH




1 PK
MAXH






* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -48.46 dBm
 SWT 300 ms 98.092682927 MHz




* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -54.44 dBm
 SWT 2.3 s 19.056463415 GHz




CH Mid



Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] *VW 300 kHz 2.66 dBm SWT 10 ms 2.438246400 GHz




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] *VW 300 kHz -53.32 dBm SWT 300 ms 122.359756098 MHz






* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -54.45 dBm
 * Att 20 dB SWT 2.3 s 5.478048780 GHz



CH High



* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz 2.33 dBm
 * Att 20 dB SWT 10 ms 2.463246400 GHz






* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -37.67 dBm
SWT 35 ms 2.483500000 GHz

Ref 20 dBm

* Att 20 dB

1 PK
MAXH



Start 2.43 GHz 13.5 MHz/ Stop 2.565 GHz




* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -54.82 dBm
SWT 300 ms 692.817073171 MHz

Ref 20 dBm

* Att 20 dB

1 PK
MAXH




Start 30 MHz 297 MHz/ Stop 3 GHz



* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -54.45 dBm
SWT 2.3 s 23.084268293 GHz

Ref 20 dBm

* Att 20 dB



7.5.RADIATED EMISSIONS

LIMIT

Radiated emissions from 9 kHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT was placed above the ground plane, 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


Test Configuration

Below 30MHz



Below 1 GHz



Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable above ground plane, which is 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

PEAK: RBW=VBW=1MHz / Sweep=AUTO


AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

RESTRICTED BANDEDGE (b Mode, Low Channel, Horizontal)


112.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2383.750	58.90	-7.31	51.59	74.00	-22.41	100	280	peak
2	2389.583	58.68	-7.26	51.42	74.00	-22.58	100	280	peak
3	2390.000	56.35	-7.25	49.10	74.00	-24.90	100	1	peak


RESTRICTED BANDEDGE (b Mode, Low Channel, Vertical)

112.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2382.500	65.20	-7.32	57.88	74.00	-16.12	100	61	peak
2	2382.500	50.94	-7.32	43.62	54.00	-10.38	100	58	AVG
3	2384.583	65.42	-7.30	58.12	74.00	-15.88	100	62	peak
4	2384.583	50.72	-7.30	43.42	54.00	-10.58	100	59	AVG
5	2390.000	63.38	-7.25	56.13	74.00	-17.87	100	60	peak
6	2390.000	52.20	-7.25	44.95	54.00	-9.05	100	60	AVG

RESTRICTED BANDEDGE (b Mode, High Channel, Horizontal)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	55.92	-6.44	49.48	74.00	-24.52	100	307	peak
2	2483.500	45.69	-6.44	39.25	54.00	-14.75	100	307	AVG
3	2484.375	57.65	-6.43	51.22	74.00	-22.78	100	304	peak
4	2484.375	48.02	-6.43	41.59	54.00	-12.41	100	304	AVG
5	2491.827	57.33	-6.37	50.96	74.00	-23.04	100	304	peak
6	2491.827	49.26	-6.37	42.89	54.00	-11.11	100	304	AVG


RESTRICTED BANDEDGE (b Mode, High Channel, Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	57.48	-6.44	51.04	74.00	-22.96	100	241	peak
2	2483.500	46.54	-6.44	40.10	54.00	-13.90	100	241	AVG
3	2484.615	60.31	-6.43	53.88	74.00	-20.12	100	116	peak
4	2484.615	46.01	-6.43	39.58	54.00	-14.42	100	116	AVG
5	2491.346	60.79	-6.37	54.42	74.00	-19.58	100	114	peak
6	2491.346	47.12	-6.37	40.75	54.00	-13.25	100	114	AVG

RESTRICTED BANDEDGE (g Mode, Low Channel, Horizontal)


110.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2390.000	60.74	-7.25	53.49	74.00	-20.51	100	258	peak
2	2390.000	44.37	-7.25	37.12	54.00	-16.88	150	296	AVG

RESTRICTED BANDEDGE (g Mode, Low Channel, Vertical)


110.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2390.000	70.38	-7.25	63.13	74.00	-10.87	100	53	peak
2	2390.000	46.37	-7.25	39.12	54.00	-14.88	100	53	AVG

RESTRICTED BANDEDGE (g Mode, High Channel, Horizontal)


110.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	64.76	-6.44	58.32	74.00	-15.68	100	227	peak
2	2483.500	43.94	-6.44	37.50	54.00	-16.50	100	227	AVG

RESTRICTED BANDEDGE (g Mode, High Channel, Vertical)


110.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	64.36	-6.44	57.92	74.00	-16.08	100	99	peak
2	2483.500	43.98	-6.44	37.54	54.00	-16.46	100	99	AVG
3	2484.375	64.55	-6.43	58.12	74.00	-15.88	100	99	peak
4	2484.375	42.78	-6.43	36.35	54.00	-17.65	100	99	AVG

RESTRICTED BANDEDGE (IEEE 802.11n HT20 mode, Low Channel, Horizontal)


110.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2390.000	62.81	-7.25	55.56	74.00	-18.44	100	78	peak
2	2390.000	44.48	-7.25	37.23	54.00	-16.77	100	78	AVG


RESTRICTED BANDEDGE (IEEE 802.11n HT20 mode, Low Channel, Vertical)

110.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2387.500	69.44	-7.27	62.17	74.00	-11.83	100	57	peak
2	2387.500	44.60	-7.27	37.33	54.00	-16.67	100	57	AVG
3	2390.000	70.00	-7.25	62.75	74.00	-11.25	100	57	peak
4	2390.000	46.42	-7.25	39.17	54.00	-14.83	100	57	AVG

RESTRICTED BANDEDGE (IEEE 802.11n HT20 mode, High Channel, Horizontal)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	66.11	-6.44	59.67	74.00	-14.33	100	250	peak
2	2483.500	46.70	-6.44	40.26	54.00	-13.74	100	250	AVG

RESTRICTED BANDEDGE (IEEE 802.11n HT20 mode, High Channel, Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	65.81	-6.44	59.37	74.00	-14.63	100	115	peak
2	2483.500	44.94	-6.44	38.50	54.00	-15.50	100	115	AVG
3	2484.135	68.40	-6.43	61.97	74.00	-12.03	100	260	peak
4	2484.135	44.49	-6.43	38.06	54.00	-15.94	100	260	AVG

Test Result of Radiated Emission**Below 30MHz**

The interference of the frequency value is lower than the limit below 20 db, measured as the background noise values and will not be recorded.

30MHz-1GHz

Operation Mode:	Normal Link	Test Date:	2016-8-5
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	48% RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
32.9100	V	12.40	20.65	33.05	40.00	-6.95	peak
223.0300	V	14.97	16.41	31.38	46.00	-14.62	peak
231.7600	V	15.06	16.41	31.47	46.00	-14.53	peak
662.4400	V	12.94	24.46	37.40	46.00	-8.60	peak
733.2500	V	13.21	25.35	38.56	46.00	-7.44	peak
762.3500	V	13.49	25.30	38.79	46.00	-7.21	peak
30.9700	H	11.69	21.62	33.31	40.00	-6.69	peak
228.8500	H	13.98	16.41	30.39	46.00	-15.61	peak
440.3100	H	12.61	21.18	33.79	46.00	-12.21	peak
467.4700	H	13.14	21.64	34.78	46.00	-11.22	peak
535.3700	H	12.13	22.44	34.57	46.00	-11.43	peak
820.5500	H	13.22	25.51	38.73	46.00	-7.27	peak

Remark:

Measuring frequencies from 30 MHz to the 1GHz (No emission found between lowest internal used/generated frequency to 30 MH).

Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.

Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Above 1 GHz
Operation Mode: TX / IEEE 802.11b / CH Low

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4814.103	44.45	-4.54	39.91	74.00	-34.09	100	188	peak
2	7293.269	42.56	6.86	49.42	74.00	-24.58	100	193	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4977.564	42.40	-4.33	38.07	74.00	-35.93	100	202	peak
2	7565.705	42.28	7.53	49.81	74.00	-24.19	100	116	peak
N/A									

Operation Mode: TX / IEEE 802.11b / CH Mid

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4868.590	46.16	-4.47	41.69	74.00	-32.31	100	73	peak
2	7347.756	41.32	7.00	48.32	74.00	-25.68	100	295	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4923.077	41.53	-4.40	37.13	74.00	-36.87	100	171	peak
2	7211.538	41.41	6.66	48.07	74.00	-25.93	100	313	peak
N/A									



Compliance Certification Services (KunShan) Inc.

Date of Issue :August 23, 2016
FCC ID: 2AFIB-DCM116

Report No: C160630R01-RPW

Operation Mode: TX / IEEE 802.11b / CH High

Test Date: 2016-8-5

Temperature: 24°C

Tested by:Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4923.077	44.36	-4.40	39.96	74.00	-34.04	100	150	peak
2	7184.295	42.13	6.59	48.72	74.00	-25.28	100	35	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4950.320	40.94	-4.36	36.58	74.00	-37.42	100	318	peak
2	7020.833	42.18	6.19	48.37	74.00	-25.63	100	158	peak
N/A									

Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: 2016-8-5

Temperature: 24°C

Tested by:Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4950.320	42.00	-4.36	37.64	74.00	-36.36	100	24	peak
2	7238.782	41.18	6.73	47.91	74.00	-26.09	100	118	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4841.346	42.49	-4.51	37.98	74.00	-36.02	100	229	peak
2	7102.564	42.78	6.39	49.17	74.00	-24.83	100	39	peak
N/A									



Compliance Certification Services (KunShan) Inc.

Date of Issue :August 23, 2016
FCC ID: 2AFIB-DCM116

Report No: C160630R01-RPW

Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4895.833	41.97	-4.44	37.53	74.00	-36.47	100	81	peak
2	7266.026	41.65	6.79	48.44	74.00	-25.56	100	356	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4786.859	41.93	-4.58	37.35	74.00	-36.65	100	225	peak
2	7320.513	40.34	6.93	47.27	74.00	-26.73	100	122	peak
N/A									

Operation Mode: TX / IEEE 802.11g / CH High

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4895.833	41.30	-4.44	36.86	74.00	-37.14	100	155	peak
2	7729.167	43.07	7.93	51.00	74.00	-23.00	100	140	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5059.295	42.96	-4.02	38.94	74.00	-35.06	100	288	peak
2	7293.269	42.23	6.86	49.09	74.00	-24.91	100	142	peak
N/A									

Operation Mode: TX / IEEE 802.11n HT20 mode / CH Low

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4841.346	42.33	-4.51	37.82	74.00	-36.18	100	33	peak
2	7211.538	41.05	6.66	47.71	74.00	-26.29	100	4	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4868.590	42.61	-4.47	38.14	74.00	-35.86	100	363	peak
2	7129.808	42.10	6.46	48.56	74.00	-25.44	100	363	peak
N/A									

Operation Mode: TX / IEEE 802.11n HT20 mode / CH Mid

Test Date: 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4895.833	41.80	-4.44	37.36	74.00	-36.64	100	29	peak
2	7157.051	43.06	6.53	49.59	74.00	-24.41	100	341	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4923.077	40.72	-4.40	36.32	74.00	-37.68	100	275	peak
2	7293.269	41.26	6.86	48.12	74.00	-25.88	100	95	peak
N/A									



Operation Mode: TX / IEEE 802.11n HT20 mode / CH High **Test Date:** 2016-8-5

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4786.859	41.50	-4.58	36.92	74.00	-37.08	100	265	peak
2	7347.756	40.39	7.00	47.39	74.00	-26.61	100	73	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4923.077	41.07	-4.40	36.67	74.00	-37.33	100	335	peak
2	7266.026	41.78	6.79	48.57	74.00	-25.43	100	31	peak
N/A									

7.6.POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE


- 1.The EUT was placed on a table, which is 0.8m above ground plane.
- 2.Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3.Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

TEST DATA

Job No.:	C160630R01	Date:	2016-8-10
Model No.:	YI-M1	Time:	AM 09:24:02
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 120V/60Hz
Model:		Description:	




No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.1566	36.31	21.60	19.79	56.10	41.39	65.64	55.64	-9.54	-14.25	Pass
2	0.2084	30.11	15.66	19.79	49.90	35.45	63.27	53.27	-13.37	-17.82	Pass
3	0.2607	25.11	10.92	19.80	44.91	30.72	61.41	51.41	-16.50	-20.69	Pass
4	0.3118	21.27	8.45	19.80	41.07	28.25	59.92	49.92	-18.85	-21.67	Pass
5	0.3666	18.38	5.06	19.80	38.18	24.86	58.58	48.58	-20.40	-23.72	Pass
6	0.4163	18.89	6.69	19.81	38.70	26.50	57.52	47.52	-18.82	-21.02	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C160630R01	Date:	2016-8-10
Model No.:	YI-M1	Time:	AM 09:29:06
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 120V/60Hz
Model:		Description:	

L2




No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.1570	36.01	21.27	19.74	55.75	41.01	65.62	55.62	-9.87	-14.61	Pass
2	0.2087	29.91	15.32	19.74	49.65	35.06	63.26	53.26	-13.61	-18.20	Pass
3	0.2617	24.71	10.34	19.75	44.46	30.09	61.38	51.38	-16.92	-21.29	Pass
4	0.3140	21.20	7.05	19.75	40.95	26.80	59.86	49.86	-18.91	-23.06	Pass
5	0.3657	18.77	5.75	19.75	38.52	25.50	58.60	48.60	-20.08	-23.10	Pass
6	0.4180	18.29	5.17	19.75	38.04	24.92	57.49	47.49	-19.45	-22.57	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C160630R01	Date:	2016-8-10
Model No.:	YI-M1	Time:	AM 09:13:00
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 240V/60Hz
Model:		Description:	

L1




No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.1560	34.13	18.78	19.79	53.92	38.57	65.67	55.67	-11.75	-17.10	Pass
2	0.2050	29.84	15.14	19.79	49.63	34.93	63.41	53.41	-13.78	-18.48	Pass
3	0.2567	25.98	12.23	19.80	45.78	32.03	61.54	51.54	-15.76	-19.51	Pass
4	0.3068	22.40	9.25	19.80	42.20	29.05	60.06	50.06	-17.86	-21.01	Pass
5	0.3584	18.26	7.09	19.80	38.06	26.89	58.77	48.77	-20.71	-21.88	Pass
6	19.3405	9.64	1.02	20.10	29.74	21.12	60.00	50.00	-30.26	-28.88	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C160630R01	Date:	2016-8-10
Model No.:	YI-M1	Time:	AM 09:18:49
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 240V/60Hz
Model:		Description:	

L2



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.1547	29.26	14.63	19.74	49.00	34.37	65.74	55.74	-16.74	-21.37	Pass
2	0.2068	26.11	12.62	19.74	45.85	32.36	63.33	53.33	-17.48	-20.97	Pass
3	0.2616	21.65	8.70	19.75	41.40	28.45	61.38	51.38	-19.98	-22.93	Pass
4	0.3121	20.64	8.69	19.75	40.39	28.44	59.91	49.91	-19.52	-21.47	Pass
5	0.3609	16.84	6.82	19.75	36.59	26.57	58.71	48.71	-22.12	-22.14	Pass
6	0.4621	13.31	7.20	19.75	33.06	26.95	56.65	46.65	-23.59	-19.70	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

END OF REPORT