

**RF TEST REPORT for Intentional Radiator**  
**No. 150800160SHA-001**

Applicant : Shanghai Xiaoyi Technology Co., Ltd.  
6F, Building E, No. 2889, Jinke Road, Shanghai, China

Manufacturer : Shanghai Xiaoyi Technology Co., Ltd.  
6F, Building E, No. 2889, Jinke Road, Shanghai, China

Product Name : Smart Wireless Camera

Type/Model : YHS-113-IR

**TEST RESULT : PASS**

**SUMMARY**

The equipment complies with the requirements according to the following standard(s):

**47CFR Part 15 (2014):** Radio Frequency Devices

**ANSI C63.10 (2013):** American National Standard for Testing Unlicensed Wireless Devices

**RSS-247 Issue 1 (May 2015):** Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

**RSS-Gen Issue 4 (December 2014):** General Requirements for Compliance of Radio Apparatus

Date of issue: Sep 16, 2015

Prepared by:



Wade Zhang (*Project Engineer*)

Reviewed by:



Daniel Zhao (*Reviewer*)



## Description of Test Facility

Name: Intertek Testing Services Limited Shanghai  
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R.  
China  
FCC Registration Number: 236597  
IC Assigned Code: 2042B-1  
Name of contact: Jonny Jing  
Tel: +86 21 61278271  
Fax: +86 21 54262353

## Content

<b>SUMMARY</b> .....	<b>1</b>
<b>DESCRIPTION OF TEST FACILITY</b> .....	<b>2</b>
<b>1. TEST SUMMARY</b> .....	<b>4</b>
<b>2. GENERAL INFORMATION</b> .....	<b>5</b>
2.1 Applicant Information.....	5
2.2 Identification of the EUT .....	5
<b>3. TEST SPECIFICATION</b> .....	<b>6</b>
3.1 Instrument list .....	6
3.2 Test Standard .....	6
3.3 Mode of operation during the test / Test peripherals used.....	7
<b>4. MINIMUM 6dB BANDWIDTH</b> .....	<b>9</b>
4.1 Limit.....	9
4.2 Test Configuration .....	9
4.3 Test Procedure and test setup.....	9
4.4 Test Protocol .....	10
<b>5. MAXIMUM CONDUCTED OUTPUT POWER</b> .....	<b>17</b>
5.1 Test limit .....	17
5.2 Test Configuration .....	17
5.3 Test procedure and test setup.....	17
5.4 Test protocol .....	18
<b>6. POWER SPECTRUM DENSITY</b> .....	<b>19</b>
6.1 Test limit .....	19
6.2 Test Configuration .....	19
6.3 Test procedure and test setup.....	20
6.4 Test Protocol .....	20
<b>7. EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS</b> .....	<b>27</b>
7.1 Test limit .....	27
7.2 Test Configuration .....	27
7.3 Test procedure and test setup.....	27
7.4 Test Protocol .....	28
<b>8. RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS</b> .....	<b>41</b>
8.1 Test limit .....	41
8.2 Test Configuration .....	41
8.3 Test procedure and test setup.....	42
8.4 Test Protocol .....	43
<b>9. POWER LINE CONDUCTED EMISSION</b> .....	<b>49</b>
9.1 Limit.....	49
9.2 Test configuration .....	49
9.3 Test procedure and test set up.....	50
9.4 Test protocol .....	51
<b>10. ANTENNA REQUIREMENT</b> .....	<b>53</b>

## 1. Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

Test Items	FCC Reference	Result
Minimum 6dB Bandwidth	15.247(a)(2)	Pass
Output power	15.247(b)	Pass
Power spectrum density	15.247(e)	Pass
Emissions in non-restricted frequency bands	15.247(d)	Pass
Emissions in restricted frequency bands	15.247(d) & 15.205 & 15.209	Pass
Power line conducted emission	15.207	NA

Note: NA =Not Applicable

## 2. General Information

### 2.1 Applicant Information

Applicant : Shanghai Xiaoyi Technology Co., Ltd.  
6F, Building E, No. 2889, Jinke Road, Shanghai, China

Name of contact : Weiming Chu

Tel : +86-21-61656722

Fax : +86-21-61656722

Manufacturer : Shanghai Xiaoyi Technology Co., Ltd.  
6F, Building E, No. 2889, Jinke Road, Shanghai, China

### 2.2 Identification of the EUT

Equipment : Smart Wireless Camera

Type/model : YHS-113-IR

Operation Frequency : 2412~2462 MHz

Band

Type of Modulation : DBPSK, DQPSK, CCK, BPSK, QPSK, 16-QAM, 64QAM

Transfer Rate : 802.11b: 11.0/5.5/2.0/1.0Mbps  
802.11g: 54.0/48.0/36.0/24.0/18.0/12.0/9.0/6.0Mbps  
802.11n: up to 150Mbps

Modulation : 802.11b/g/n HT20/n HT40;

Channel Number : 11Channel for 2412MHz~2462MHz for 11b,11g,11n HT20;  
9 Channel for 2422MHz~2462MHz for 11n HT40

Description of EUT : The EUT is an action camera which supports WIFI and BT function, and it has only one model. We tested it and listed the WIFI result in this report.

Antenna : FIFA antenna with peak gain 2.5dBi

Rating : DC5V 1A

Declared Temperature : 0°C ~ 45°C

range

Category of EUT : Class B

EUT type :  Table top  Floor standing

Sample received date : 2015.07.23

Date of test : 2015.07.23 ~ 2015.09.11

### 3. Test Specification

#### 3.1 Instrument list

Equipment	Type	Manu.	Internal no.	Cal. Date	Due date
Test Receiver	ESCS 30	R&S	EC 2107	2014-10-20	2015-10-19
Test Receiver	ESIB 26	R&S	EC 3045	2014-10-19	2015-10-18
Test Receiver	ESCI 7	R&S	EC4501	2014-12-24	2015-12-23
Spectrum Analyzer	N9030	Agilent	EC4890	2014-10-20	2015-10-19
A.M.N.	ESH2-Z5	R&S	EC 3119	2015-1-8	2016-1-7
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2015-4-26	2016-4-25
Horn antenna	HF 906	R&S	EC 3049	2015-4-26	2016-4-25
Horn antenna	3117	ETS	EC 4792-1	2015-4-16	2016-4-15
Horn antenna	HAP18-26W		EC 4792-3	2015-4-8	2016-4-7
Pre-amplifier	Pre-amp 18	R&S	EC 3222	2015-4-11	2016-4-10
Pre-amplifier	Tpa0118-40	R&S	EC 4792-2	2015-4-10	2016-4-9
Semi-anechoic chamber	-	Albatross project	EC 3048	2015-5-10	2016-5-9
Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3323	2015-4-13	2016-4-12
Pressure meter	YM3	Shanghai Mengde	EC 3320	2015-6-12	2016-6-11
Shielded room	-	Zhongyu	EC 2838	2015-1-11	2016-1-9
High Pass Filter	WHKX 1.0/15G-10SS	Wainwright	EC4297-1	2015-1-7	2016-1-6
High Pass Filter	WHKX 2.8/18G-12SS	Wainwright	EC4297-2	2015-1-7	2016-1-6
High Pass Filter	WHKX 7.0/1.8G-8SS	Wainwright	EC4297-3	2015-1-7	2016-1-6
Band Reject Filter	WRCGV 2400/2483- 2390/2493- 35/10SS	Wainwright	EC4297-4	2015-1-7	2016-1-6
Power sensor / Power meter	N1911A/N1921A	Agilent	EC4318	2015-4-8	2016-4-7

#### 3.2 Test Standard

47CFR Part 15 (2014): Radio Frequency Devices

ANSI C63.10 (2013): American National Standard for Testing Unlicensed Wireless Devices

RSS-247 Issue 1 (May 2015): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 4 (December 2014): General Requirements for Compliance of Radio Apparatus

**3.3 Mode of operation during the test / Test peripherals used**

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test as representatives, and the selected channel see below:

Modulation	Lowest(MHz)	Middle(MHz)	Highest(MHz)
802.11b	2412	2437	2462
802.11g	2412	2437	2462
802.11n(HT20)	2412	2437	2462
802.11n(HT40)	2422	2437	2452

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

The test setting software and command is offered by the manufactory.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, the pre-scan for all data rates in each modulation and bands was tested, and the worst case was found and used in all test cases.

After this pre-scan, we choose the following table of the data rata as the final test mode.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n HT20	6.5Mbps
802.11n HT40	13Mbps

Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.

Radiated test construction:

Mode 1: EUT transmitted signal with WIFI antenna;

Conducted test construction:

Mode 2: EUT transmitted signal from RF port connected to SPA directly;

Test peripherals used:

Item No	Description	Band and Model	S/No
1	Laptop computer	HP ProBook 6470b	NA
2	Adaptor	YI, A8-501000	NA

Note: The accessories are used for configuration only and not used during test.




## 4. Minimum 6dB Bandwidth

Test result: PASS

### 4.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 4.2 Test Configuration



### 4.3 Test Procedure and test setup

The minimum 6dB bandwidth per FCC §15.247(a)(2) is measured using the Spectrum Analyzer according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance v03r02" for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**4.4 Test Protocol**

Temperature: 22°C


Relative Humidity: 53%

Mode	CH	6dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b	L	9.936	≥0.5
	M	9.938	
	H	9.937	
802.11g	L	16.48	
	M	16.48	
	H	16.47	
802.11n(HT20)	L	17.64	
	M	17.66	
	H	17.64	
802.11n(HT40)	L	36.36	
	M	36.43	
	H	36.39	

Mode	CH	99% Occupy Bandwidth (MHz)	Limit (MHz)
802.11b	L	12.172	NA
	M	12.169	
	H	12.164	
802.11g	L	16.443	
	M	16.444	
	H	16.435	
802.11n(HT20)	L	17.588	
	M	17.589	
	H	17.584	
802.11n(HT40)	L	36.206	
	M	36.229	
	H	36.209	

Test plot as follows:


### 802.11b Frequency L




### Frequency M




### Frequency H




### 802.11g Frequency L




Frequency M




Frequency H




### 802.11n (HT20) Frequency L




### Frequency M




Frequency H




802.11n (HT40)  
Frequency L



Frequency M



Frequency H





## 5. Maximum Conducted Output power


**Test result: Pass**

### 5.1 Test limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt
- For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts
- For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

### 5.2 Test Configuration



### 5.3 Test procedure and test setup

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r02” for compliance to FCC 47CFR 15.247 requirements (clause 9.1.2).

**5.4 Test protocol**

Temperature: 22 °C

Relative Humidity: 53 %

<b>Mode</b>	<b>CH</b>	<b>Conducted Power (dBm)</b>	<b>Limit (dBm)</b>
802.11b	L	18.95	≤30
	M	17.42	
	H	16.38	
802.11g	L	21.27	≤30
	M	20.51	
	H	19.55	
802.11n (HT20)	L	21.37	≤30
	M	20.34	
	H	19.31	
802.11n (HT40)	L	20.35	≤30
	M	19.32	
	H	18.28	

## 6. Power spectrum density


Test result: Pass

### 6.1 Test limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and  $8 + (6 - \text{antenna gain} - \text{beam forming gain})$ .

### 6.2 Test Configuration



**6.3 Test procedure and test setup**

The power output per FCC §15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r02” (clause 10.2 Method PKPSD) for compliance to FCC 47CFR 15.247 requirements.

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 4) Set the VBW  $\geq 3 \times \text{RBW}$ .
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**6.4 Test Protocol**

Temperature: 22 °C

Relative Humidity: 53 %

Mode	CH	Spectrum Density (dBm/100kHz)	Limit (dBm/3kHz)
802.11b	L	4.182	≤8.00
	M	2.850	
	H	2.183	
802.11g	L	-1.321	≤8.00
	M	-1.830	
	H	-2.478	
802.11n (HT20)	L	-0.726	≤8.00
	M	-1.795	
	H	-2.443	
802.11n (HT40)	L	-3.612	≤8.00
	M	-4.330	
	H	-4.795	

Test plot as follows:

### 802.11b Frequency L




### Frequency M




Frequency H




802.11g  
Frequency L



### Frequency M



### Frequency H



**802.11n (HT20)  
Frequency L**




**Frequency M**






Frequency H




802.11n (HT20)  
Frequency L



Frequency M



Frequency H




## 7. Emissions in non-restricted frequency bands

**Test result:** Pass

### 7.1 Test limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### 7.2 Test Configuration



### 7.3 Test procedure and test setup

The Emission outside the frequency Band per FCC § 15.247(d) is measured using the Spectrum Analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW.

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r02” (clause 11.0) for compliance to FCC 47CFR 15.247 requirements.



**7.4 Test Protocol**

Temperature: 22 °C  
 Relative Humidity: 53 %



Test Mode	Frequency (MHz)	Results	Limit
802.11b	2412	Pass	>20dB
	2437	Pass	
	2462	Pass	
802.11g	2412	Pass	
	2437	Pass	
	2462	Pass	
802.11n (HT20)	2412	Pass	
	2437	Pass	
	2462	Pass	
802.11n (HT40)	2422	Pass	
	2437	Pass	
	2452	Pass	

Test plot as follows:



802.11b  
Frequency L





Frequency M



Frequency H





### 802.11g Frequency L









Frequency M





Frequency H





802.11n (HT20)  
Frequency L





Frequency M





Frequency H





### 802.11n (HT40) Frequency L



Frequency M



Frequency H





## 8. Radiated Emissions in restricted frequency bands


**Test result:** Pass

### 8.1 Test limit

The radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### 8.2 Test Configuration



### 8.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The EUT was tested according to DTS test procedure of KDB558074 D01 DTS “Meas Guidance v03r02” for compliance to FCC 47CFR 15.247 requirements.

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100 kHz, VBW = 300 kHz (30MHz-1GHz)

RBW = 1MHz, VBW = 3MHz (>1GHz for PK);

RBW = 1MHz, VBW = 10Hz (>1GHz for AV);

Remark:

1. Factor= Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Measured level= Original Receiver Reading + Factor
3. Margin = limit – Measured level
4. If the PK measured level is lower than AV limit, the AV test can be elided.

Example:

Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV.

Then Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;

Measured level = 10dBuV + 0.20dB/m = 10.20dBuV/m

Assuming limit = 54dBuV/m,

Measured level = 10.20dBuV/m, then Margin = 54 -10.20 = 43.80dBuV/m.


### 8.4 Test Protocol

Temperature: 25 °C


Relative Humidity: 55 %

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

30MHz~1GHz, Horizontal



30MHz~1GHz, Vertical



**Test data at 30MHz~1GHz (Channel L):**

Polarization	Frequency (MHz)	Measured level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector
H	30.00	24.7	40.0	15.3	PK
	111.64	20.9	43.5	22.6	PK
	125.25	20.8	43.5	22.7	PK
	224.39	29.0	46.0	17.0	PK
	325.47	40.2	46.0	5.8	PK
	376.01	44.0	46.0	2.0	PK
	576.23	39.4	46.0	6.6	PK
	825.05	38.7	46.0	7.3	PK
V	30.00	26.5	40.0	13.5	PK
	47.49	32.9	40.0	7.1	PK
	61.10	23.1	40.0	16.9	PK
	111.64	24.1	43.5	19.4	PK
	142.75	24.7	43.5	18.8	PK
	224.39	21.6	46.0	24.4	PK
	325.47	31.0	46.0	15.0	PK
	449.88	39.8	46.0	6.2	PK
	576.23	41.3	46.0	4.7	PK
	825.05	40.7	46.0	5.3	PK

Note: The worst test result (30MHz to 1GHz) of channel L (2412MHz) was chosen to list in the report as representative.

**Test result above 1GHz:**

The emission was conducted from 1GHz to 25GHz.

1: 2.4G band 802.11b

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	51.15	74	-7.80	100	190	22.85	PK
		41.25	54	-7.80	100	190	12.75	AV
	2412	108.21	-	-7.80	100	190	-	PK
		99.33	-	-7.80	100	190	-	AV
	4824	51.11	74	-2.10	100	190	22.89	PK
		40.44	54	-2.10	100	190	13.56	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	107.51	-	-7.80	100	190	-	PK
		99.83	-	-7.80	100	190	-	AV
	4874	51.33	74	-2.10	100	190	22.82	PK
		40.37	54	-2.10	100	190	13.63	AV
	7311	48.48	74	6.50	100	190	25.52	PK
		38.45	54	6.50	100	190	15.55	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	107.80	-	-7.80	100	190	-	PK
		98.23	-	-7.80	100	190	-	AV
	2483.5	50.33	74	-7.50	100	190	23.67	PK
		41.17	54	-7.50	100	190	12.83	AV
	4924	51.51	74	-2.10	100	190	22.49	PK
		41.81	54	-2.10	100	190	12.19	AV
	7386	48.12	74	6.50	100	190	25.88	PK
		38.54	54	6.50	100	190	15.46	AV
Note:	2462MHz is fundamental signal.							

2: 2.4G band 802.11g

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	50.62	74	-7.80	100	190	23.38	PK
		41.47	54	-7.80	100	190	12.53	AV
	2412	105.66	-	-7.80	100	190	-	PK
		96.25	-	-7.80	100	190	-	AV
	4824	49.55	74	-2.10	100	190	24.45	PK
		36.44	54	-2.10	100	190	17.56	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	105.46	-	-7.80	100	190	-	PK
		95.36	-	-7.80	100	190	-	AV
	4874	51.15	74	-2.10	100	190	22.85	PK
		41.24	54	-2.10	100	190	12.76	AV
	7311	46.85	74	6.50	100	190	25.15	PK
		39.52	54	6.50	100	190	14.48	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	106.88	-	-7.80	100	190	-	PK
		94.52	-	-7.80	100	190	-	AV
	2483.5	50.08	74	-7.50	100	190	23.92	PK
		40.12	54	-7.50	100	190	13.88	AV
	4924	52.08	74	-2.10	100	190	21.92	PK
		42.58	54	-2.10	100	190	11.42	AV
	7386	45.15	74	6.50	100	190	28.85	PK
		36.25	54	6.50	100	190	17.75	AV
Note:	2462MHz is fundamental signal.							

3: 2.4G band 802.11n HT20

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	51.40	74	-7.80	100	190	22.60	PK
		42.33	54	-7.80	100	190	11.67	AV
	2412	106.45	-	-7.80	100	190	-	PK
		93.66	-	-7.80	100	190	-	AV
	4824	49.86	74	-2.10	100	190	24.14	PK
		38.94	54	-2.10	100	190	15.06	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	105.45	-	-7.80	100	190	-	PK
		94.52	-	-7.80	100	190	-	AV
	4874	47.87	74	-2.10	100	190	26.13	PK
		39.67	54	-2.10	100	190	14.33	AV
	7311	45.77	74	6.50	100	190	28.23	PK
		38.97	54	6.50	100	190	14.03	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuv/m)	Limit (dBuv/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	103.93	-	-7.80	100	190	-	PK
		92.16	-	-7.80	100	190	-	AV
	2483.5	50.77	74	-7.50	100	190	23.23	PK
		40.45	54	-7.50	100	190	13.55	AV
	4924	48.48	74	-2.10	100	190	25.52	PK
		37.98	54	-2.10	100	190	16.02	AV
	7386	44.08	74	6.50	100	190	29.92	PK
		38.07	54	6.50	100	190	15.93	AV
Note:	2462MHz is fundamental signal.							

4: 2.4G band 802.11n HT40

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	51.30	74	-7.80	100	190	22.70	PK
		41.23	54	-7.80	100	190	12.77	AV
	2422	104.64	-	-7.80	100	190	-	PK
		91.26	-	-7.80	100	190	-	AV
	4844	48.55	74	-2.10	100	190	25.45	PK
		38.67	54	-2.10	100	190	15.33	AV
Note:	2422MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	104.15	-	-7.80	100	190	-	PK
		92.35	-	-7.80	100	190	-	AV
	4874	48.83	74	-2.10	100	190	25.17	PK
		38.34	54	-2.10	100	190	15.66	AV
	7311	45.44	74	6.50	100	190	28.56	PK
		38.37	54	6.50	100	190	14.63	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2452	103.55	-	-7.80	100	190	-	PK
		91.46	-	-7.80	100	190	-	AV
	2483.5	49.51	74	-7.50	100	190	24.49	PK
		40.25	54	-7.50	100	190	13.75	AV
	4904	48.68	74	-2.10	100	190	25.32	PK
		35.95	54	-2.10	100	190	18.05	AV
	7356	43.18	74	6.50	100	190	30.82	PK
		36.57	54	6.50	100	190	17.43	AV
Note:	2452MHz is fundamental signal.							



## 9. Power line conducted emission


**Test result:** Pass

### 9.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### 9.2 Test configuration



For table top equipment, wooden support is 0.8m height table

For floor standing equipment, wooden support is 0.1m height rack.


### 9.3 Test procedure and test set up

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a  $50\Omega/50\mu\text{H}$  coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a  $50\Omega/50\mu\text{H}$  coupling impedance with  $50\Omega$  termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.


### 9.4 Test protocol

Temperature : 22°C  
 Relative Humidity : 52%



**Test Data:**

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.177	43.78	64.61	20.83	28.42	54.61	26.19
0.247	37.91	61.86	23.95	26.33	51.86	25.53
0.461	42.39	56.68	14.29	39.42	46.68	7.26
0.497	32.92	56.05	23.13	31.35	46.05	14.70
0.922	32.06	56.00	23.94	28.14	46.00	17.86
1.280	32.60	56.00	23.40	25.55	46.00	20.45



**Test Data:**

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.177	43.80	64.61	20.81	28.29	54.61	26.32
0.248	39.00	61.82	22.82	26.17	51.82	25.65
0.462	43.79	56.65	12.86	38.11	46.65	8.54
0.922	35.24	56.00	20.76	28.41	46.00	17.59
0.960	37.22	56.00	18.78	26.64	46.00	19.36
2.310	33.89	56.00	22.11	24.50	46.00	21.50

Note: The worst test results of channel L (2412MHz, 802.11b, 1Mbps) was chosen to list in the report as representative.

## 10. Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**The manufacturer used a unique connector. This antenna connector is a non-standard connector, so fulfill this requirement.**