



Statement of compliance to Maximum Permissible Exposure (MPE) No. 150800160SHA-002

Applicant : Shanghai Xiaoyi Technology Co., Ltd.
6F, Building E, No. 2889, Jinke Road, Shanghai, China

Manufacturer : Shanghai Xiaoyi Technology Co., Ltd.
6F, Building E, No. 2889, Jinke Road, Shanghai, China

Product Name : Smart Wireless Camera

Type/Model : YHS-113-IR

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band (MHz)	Power		Antenna Gain		R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
	dBm	mW	dBi	(Numeric)			
2412 -2462	21.37	137.09	2.5	1.78	20	0.049	1

Note: 1 mW/cm² from 1.310 Table 1

Date of issue: Sep 16, 2015

Prepared by:

Wade Zhang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of **20** cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.