

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 1 of 7

**Applicant** : Shanghai XiaoYi Technology Co., Ltd  
**Address of Applicant** : Building 18, Lane 55, Chuanhe Road, China(Shanghai) Pilot Free Trade Zone, Shanghai, China , 201203

**Product Name** : Kami Doorbell Camera  
**Model No.** : YDS.20120  
**Sample No.** : E21030014-01 #01  
E21030014-01 #16  
**FCC ID** : 2AFIB-YDS20121

**Standards** : FCC CFR47 Part 2&1.1307(b)(1)

**Date of Receipt** : 2020-03-19  
**Date of Test** : 2020-03-19 ~ 2021-04-02  
**Date of Issue** : 2020-04-12

**Remark:**

*This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.*

Prepared by: Jennifer Zhou  
(Jennifer Zhou)

Reviewed by: Oliver Xiang  
(Oliver Xiang)

Approved by: Guoyou Chi  
(Authorized signatory: Guoyou Chi)

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 2 of 7

## Contents

- 1 GENERAL INFORMATION ..... 3**
- 1.1 TESTING LABORATORY ..... 3
- 1.2 DETAILS OF APPLICATION ..... 3
- 1.3 DETAILS OF EUT ..... 3
- 1.4 TEST METHODOLOGY ..... 4
- 1.5 TEST VERDICT ..... 5
- RF EXPOSURE ..... 5**
- REQUIREMENTS ..... 5
- THE PROCEDURES / LIMIT ..... 5
- MPE CALCULATION METHOD ..... 7
- TEST RESULT ..... 7

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 3 of 7

## 1 General Information

### 1.1 Testing Laboratory

Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd.
Address	No.1298 Pingan Rd, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

### 1.2 Details of Application

Applicant Company Name	Shanghai XiaoYi Technology Co., Ltd
Address	Building 18, Lane 55, Chuanhe Road, China(Shanghai) Pilot Free Trade Zone, Shanghai, China , 201203
Contact Person	Jackie Han
Telephone	18017858789
Email	han.guangbao@xiaoyi.com
Manufacturer Company Name	Kami Vision Incorporated
Address	182 South Murphy Ave, Floor #2, Sunnyale CA 94086, United States

### 1.3 Details of EUT

Product Name	Kami Doorbell Camera
Brand Name	Kami
Model No.	YDS.20120
FCC ID	2AFIB-YDS20121
Mode of Operation	WLAN 802.11b/g/n(HT20) WLAN 802.11a/n(HT20)
Frequency Range	2400MHz ~ 2483.5MHz Band I: 5150 MHz ~ 5250 MHz Band IV: 5725 MHz ~ 5850 MHz
Channel Separation	5 MHz
Modulation Type	DSSS, OFDM, 256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type	FPC Antenna
Antenna Gain	See below

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 4 of 7

## 1.4 Test Methodology

47 CFR Part 15, Subpart C (10-1-16 Edition)	Miscellaneous Wireless Communications Services
--	--

**Note(s):**

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 5 of 7

## 1.5 Test Verdict

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

## RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

## Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

## The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time $ E ^2,  H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 6 of 7

1500-100,000	/	/	5	6
--------------	---	---	---	---

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

# TEST REPORT

Report No.: SHE21030014-02FE

Date: 2021-04-12

Page 7 of 7

## MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$Pd = \frac{30 \times P \times G}{377 \times d^2}$  From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## Test Result

Item	Antenna Gain (dBi)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
WIFI 2.4G	1.88	19.81	95.72	0.0294	1	Pass
WIFI 5.2G	3.15	13.45	22.13	0.0091	1	Pass
WIFI 5.8G	3.15	11.40	13.80	0.0057	1	Pass

\*\*\*End of the report\*\*\*