

# FCC Radio Test Report

## FCC ID: 2AFIH-2930

### Original Grant

**Report No.** : TB-FCC146825  
**Applicant** : Brand New Days Limited  
**Equipment Under Test (EUT)**  
**EUT Name** : Folding wireless keyboard  
**Model No.** : 2930  
**Series Model No.** : N/A  
**Brand Name** : X  
**Receipt Date** : 2016-01-28  
**Test Date** : 2016-01-29 to 2016-01-18  
**Issue Date** : 2016-01-20  
**Standards** : FCC Part 15: 2015, Subpart C(15.247)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :

*Wan Su*

**Approved & Authorized** :

*Ray Shi*



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



---

---

## Contents

<b>CONTENTS</b> .....	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT</b> .....	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	7
1.7 Measurement Uncertainty .....	8
1.8 Test Facility.....	8
<b>2. TEST SUMMARY</b> .....	<b>9</b>
<b>3. TEST EQUIPMENT</b> .....	<b>10</b>
<b>4. CONDUCTED EMISSION TEST</b> .....	<b>11</b>
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode .....	12
4.5 Test Data.....	12
<b>5. RADIATED EMISSION TEST</b> .....	<b>17</b>
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition .....	19
<b>6. RESTRICTED BANDS REQUIREMENT</b> .....	<b>28</b>
6.1 Test Standard and Limit.....	28
6.2 Test Setup.....	28
6.3 Test Procedure.....	28
6.4 EUT Operating Condition .....	29
6.4 Test Data.....	29
<b>7. NUMBER OF HOPPING CHANNEL</b> .....	<b>36</b>
7.1 Test Standard and Limit.....	36
7.2 Test Setup.....	36
7.3 Test Procedure.....	36
7.4 EUT Operating Condition .....	36
7.5 Test Data.....	36
<b>8. AVERAGE TIME OF OCCUPANCY</b> .....	<b>38</b>
8.1 Test Standard and Limit.....	38
8.2 Test Setup.....	38
8.3 Test Procedure.....	38



---

8.4 EUT Operating Condition .....	38
8.5 Test Data.....	39
<b>9. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>45</b>
9.1 Test Standard and Limit.....	45
9.2 Test Setup.....	45
9.3 Test Procedure.....	45
9.4 EUT Operating Condition .....	45
9.5 Test Data.....	46
<b>10. PEAK OUTPUT POWER TEST.....</b>	<b>50</b>
10.1 Test Standard and Limit .....	50
10.2 Test Setup.....	50
10.3 Test Procedure.....	50
10.4 EUT Operating Condition .....	50
10.5 Test Data.....	51
<b>11. ANTENNA REQUIREMENT.....</b>	<b>53</b>
11.1 Standard Requirement.....	53
11.2 Antenna Connected Construction.....	53

# 1. General Information about EUT

## 1.1 Client Information

**Applicant** : Brand New Days Limited  
**Address** : Flat B, 6/F, Tong Yuen Factory Building, 505 Castle Peak Road, Lai Chi Kok, Kowloon, Hong Kong  
**Manufacturer** : Shenzhen Gtide Technology Co.,Ltd  
**Address** : 5th Building C, 6 Block, Dongcai Industrial Zone, Gushu,Baoan District, Shenzhen, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Folding wireless keyboard			
<b>Models No.</b>	:	2930			
<b>Model Difference</b>	:	N/A			
<b>Product Description</b>	:	Operation Frequency: Bluetooth:2402~2480MHz			
	:	Number of Channel:	Bluetooth:79 Channels See Note 2		
	:	Max Peak Output Power:	Bluetooth: -11.89 dBm(GFSK)		
	:	Antenna Gain:	0 dBi PCB Antenna		
	:	Modulation Type:	GFSK 1Mbps(1 Mbps)		
<b>Power Supply</b>	:	DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.			
<b>Power Rating</b>	:	DC 5.0V by USB cable. DC 3.7V 110mAh Li-ion Battery.			
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual			

### Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Channel List:

Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460



---


---

05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	<b>39</b>	<b>2441</b>	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	<b>78</b>	<b>2480</b>
25	2427	52	2454		
26	2428	53	2455		


(3) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### TX Mode



#### USB Charging with TX Mode



### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/DOC	Manufacturer	Used “√”
Netbook	T60P	DOC	Thinkpad	√
----	----	----	----	
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	YES	0.6M	
----	----	----	----	



## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Charging with TX GFSK Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Charging with TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	Hopping Mode(GFSK)

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test mode above.  
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
TX Mode: GFSK (1 Mbps)
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	Broadcom BlueTool		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF



## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz	$\pm 3.42$ dB
	150kHz to 30MHz	$\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **FCC List No.: (811562)**

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(c)	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW GFSK:966.00kHz

**Note:** N/A is an abbreviation for Not Applicable.

### 3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Aug. 07, 2015	Aug. 06, 2016
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Aug. 07, 2015	Aug. 06, 2016
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 07, 2015	Aug. 06, 2016
LISN	Rohde & Schwarz	ENV216	101131	Aug. 07, 2015	Aug. 06, 2016
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Aug. 29, 2015	Aug. 28, 2016
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Aug. 07, 2015	Aug. 06, 2016
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 28, 2015	Mar. 27, 2016
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 28, 2015	Mar. 27, 2016
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 28, 2015	Mar. 27, 2016
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 28, 2015	Mar. 27, 2016
Pre-amplifier	Sonoma	310N	185903	Mar. 28, 2015	Mar. 27, 2016
Pre-amplifier	HP	8447B	3008A00849	Mar. 28, 2015	Mar. 27, 2016
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 28, 2015	Mar. 27, 2016
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A



## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

4.1.1 Test Standard  
FCC Part 15.207

4.1.2 Test Limit


**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode


Please refer to the description of test mode.

#### 4.5 Test Data

Please see the next page.




<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2500	38.83	10.02	48.85	61.75	-12.90	QP
2	*	0.2500	31.18	10.02	41.20	51.75	-10.55	AVG
3		0.4980	34.53	10.02	44.55	56.03	-11.48	QP
4		0.4980	22.09	10.02	32.11	46.03	-13.92	AVG
5		0.6220	34.90	10.08	44.98	56.00	-11.02	QP
6		0.6220	22.82	10.08	32.90	46.00	-13.10	AVG
7		0.7539	34.49	10.11	44.60	56.00	-11.40	QP
8		0.7539	20.61	10.11	30.72	46.00	-15.28	AVG
9		1.2380	32.11	10.06	42.17	56.00	-13.83	QP
10		1.2380	20.08	10.06	30.14	46.00	-15.86	AVG
11		2.1820	27.71	10.05	37.76	56.00	-18.24	QP
12		2.1820	18.43	10.05	28.48	46.00	-17.52	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	0.1940	29.67	10.01	39.68	63.86	-24.18	QP
2	0.1940	16.76	10.01	26.77	53.86	-27.09	AVG
3	0.2580	30.60	10.02	40.62	61.49	-20.87	QP
4	0.2580	21.97	10.02	31.99	51.49	-19.50	AVG
5	0.3940	22.26	10.02	32.28	57.98	-25.70	QP
6	0.3940	12.68	10.02	22.70	47.98	-25.28	AVG
7	0.5140	26.74	10.03	36.77	56.00	-19.23	QP
8	0.5140	16.68	10.03	26.71	46.00	-19.29	AVG
9 *	0.5820	34.39	10.06	44.45	56.00	-11.55	QP
10	0.5820	21.55	10.06	31.61	46.00	-14.39	AVG
11	0.7220	30.97	10.12	41.09	56.00	-14.91	QP
12	0.7220	19.84	10.12	29.96	46.00	-16.04	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2260	37.60	10.02	47.62	62.59	-14.97	QP
2		0.2260	28.16	10.02	38.18	52.59	-14.41	AVG
3		0.3820	35.41	10.02	45.43	58.23	-12.80	QP
4		0.3820	23.42	10.02	33.44	48.23	-14.79	AVG
5	*	0.5820	37.12	10.06	47.18	56.00	-8.82	QP
6		0.5820	21.71	10.06	31.77	46.00	-14.23	AVG
7		0.7220	35.72	10.12	45.84	56.00	-10.16	QP
8		0.7220	21.19	10.12	31.31	46.00	-14.69	AVG
9		0.9740	30.94	10.07	41.01	56.00	-14.99	QP
10		0.9740	21.34	10.07	31.41	46.00	-14.59	AVG
11		1.4700	28.26	10.06	38.32	56.00	-17.68	QP
12		1.4700	19.90	10.06	29.96	46.00	-16.04	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1940	31.01	10.01	41.02	63.86	-22.84	QP
2		0.1940	20.99	10.01	31.00	53.86	-22.86	AVG
3	*	0.5140	39.19	10.03	49.22	56.00	-6.78	QP
4		0.5140	23.64	10.03	33.67	46.00	-12.33	AVG
5		0.5820	36.90	10.06	46.96	56.00	-9.04	QP
6		0.5820	22.30	10.06	32.36	46.00	-13.64	AVG
7		0.7220	35.47	10.12	45.59	56.00	-10.41	QP
8		0.7220	22.06	10.12	32.18	46.00	-13.82	AVG
9		0.9580	33.50	10.07	43.57	56.00	-12.43	QP
10		0.9580	23.83	10.07	33.90	46.00	-12.10	AVG
11		1.6660	29.66	10.06	39.72	56.00	-16.28	QP
12		1.6660	20.89	10.06	30.95	46.00	-15.05	AVG

Emission Level= Read Level+ Correct Factor



## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209

#### 5.1.2 Test Limit

#### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


#### Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

5.2 Test Setup




Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup





**Above 1GHz Test Setup**

### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 5.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

### 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Kz with Peak Detector for Average Values.

Test data please refer the following pages.

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	96.0986	56.76	-22.16	34.60	43.50	-8.90	peak
2		119.8556	56.43	-22.50	33.93	43.50	-9.57	peak
3		143.8295	56.04	-21.67	34.37	43.50	-9.13	peak
4		167.8243	52.71	-21.04	31.67	43.50	-11.83	peak
5		191.7450	50.37	-20.81	29.56	43.50	-13.94	peak
6		299.3158	49.96	-17.10	32.86	46.00	-13.14	peak

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		54.2610	48.31	-24.45	23.86	40.00	-16.14	peak
2		72.0843	49.12	-23.54	25.58	40.00	-14.42	peak
3		96.0986	51.31	-22.16	29.15	43.50	-14.35	peak
4		143.8295	49.30	-21.67	27.63	43.50	-15.87	peak
5		189.0743	44.70	-20.88	23.82	43.50	-19.68	peak
6	*	379.9141	50.20	-14.14	36.06	46.00	-9.94	peak

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	*	4802.506	32.17	13.43	45.60	54.00	-8.40	AVG
2		4803.643	43.40	13.44	56.84	74.00	-17.16	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4802.935	32.71	13.43	46.14	54.00	-7.86	AVG
2		4804.381	43.29	13.44	56.73	74.00	-17.27	peak

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4880.974	32.54	13.89	46.43	54.00	-7.57	AVG
2		4881.130	43.90	13.90	57.80	74.00	-16.20	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4882.384	44.23	13.90	58.13	74.00	-15.87	peak
2	*	4882.387	32.80	13.90	46.70	54.00	-7.30	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	*	4960.054	32.07	14.36	46.43	54.00	-7.57	AVG
2		4960.609	43.79	14.36	58.15	74.00	-15.85	peak

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1		4959.973	43.92	14.36	58.28	74.00	-15.72	peak
2	*	4960.054	31.73	14.36	46.09	54.00	-7.91	AVG

Emission Level= Read Level+ Correct Factor

## 6. Restricted Bands Requirement


### 6.1 Test Standard and Limit

- 6.1.1 Test Standard
  - FCC Part 15.209
  - FCC Part 15.205
- 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

**Note: All restriction bands have been tested, only the worst case is reported.**

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.



- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.


#### 6.4 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 KHz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

**(1) Radiation Test**

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2378.100	36.01	0.73	36.74	54.00	-17.26	AVG
2		2378.200	45.28	0.73	46.01	74.00	-27.99	peak
3		2390.000	42.02	0.77	42.79	74.00	-31.21	peak
4		2390.000	31.86	0.77	32.63	54.00	-21.37	AVG
5	X	2401.800	79.05	0.82	79.87	Fundamental Frequency		peak
6	*	2402.100	75.40	0.82	76.22	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.70	0.77	43.47	74.00	-30.53	peak
2		2390.000	32.13	0.77	32.90	54.00	-21.10	AVG
3	X	2401.900	74.86	0.82	75.68	Fundamental Frequency		peak
4	*	2402.100	70.70	0.82	71.52	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2479.900	73.98	1.15	75.13	Fundamental Frequency		AVG
2	X	2480.000	77.80	1.15	78.95	Fundamental Frequency		peak
3		2483.500	42.85	1.17	44.02	74.00	-29.98	peak
4		2483.500	34.49	1.17	35.66	54.00	-18.34	AVG

Emission Level= Read Level+ Correct Factor



<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2479.900	73.21	1.15	74.36	Fundamental Frequency		peak
2	*	2480.000	70.13	1.15	71.28	Fundamental Frequency		AVG
3		2483.500	43.20	1.17	44.37	74.00	-29.63	peak
4		2483.500	32.51	1.17	33.68	54.00	-20.32	AVG


Emission Level= Read Level+ Correct Factor

**(2) Conducted Test**

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz / 2480 MHz		
<b>Remark:</b>	N/A		




Date: 18.FEB.2016 17:14:34




Date: 18.FEB.2016 17:12:24



<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	GFSK Hopping Mode		
<b>Remark:</b>	N/A		



Date: 18.FEB.2016 17:34:10



Date: 18.FEB.2016 17:40:49


## 7. Number of Hopping Channel

### 7.1 Test Standard and Limit

- 6.1.1 Test Standard  
FCC Part 15.247 (a)(1)
- 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 7.4 EUT Operating Condition


The EUT was set to the Hopping Mode by the Customer.

### 7.5 Test Data



<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode (GFSK)		
<b>Frequency Range</b>	<b>Quantity of Hopping Channel</b>		<b>Limit</b>
2402MHz~2480MHz	79		>15

**GFSK Mode**



Date: 18.FEB.2016 17:28:04


## 8. Average Time of Occupancy

### 8.1 Test Standard and Limit

- 8.1.1 Test Standard  
FCC Part 15.247 (a)(1)
- 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 8.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.




### 8.5 Test Data

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930		
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%		
<b>Test Voltage:</b>	DC 3.7V				
<b>Test Mode:</b>	Hopping Mode (GFSK DH1)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	0.472	151.04	31.60	400	PASS
2441	0.472	151.04			
2480	0.472	151.04			

#### GFSK Hopping Mode DH1


2402 MHz



Date: 18.FEB.2016 17:42:02

**GFSK Hopping Mode DH1**


**2441 MHz**



Date: 18.FEB.2016 17:43:17

**GFSK Hopping Mode DH1**

**2480 MHz**




Date: 18.FEB.2016 17:44:10



<b>EUT:</b>	Folding wireless keyboard		<b>Model Name :</b>	2930	
<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%	
<b>Test Voltage:</b>	DC 3.7V				
<b>Test Mode:</b>	Hopping Mode (GFSK DH3)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	1.744	279.04	31.60	400	<b>PASS</b>
2441	1.760	281.60			
2480	1.744	279.04			
<b>GFSK Hopping Mode DH3</b>					
<b>2402 MHz</b>					
<p>             RBW 1 MHz    Delta 1 [T1 ]              *VBW 1 MHz    -1.41 dB              Ref 0 dBm    *Att 25 dB    SWT 8 ms    1.744000 ms              Marker 1 [T1 ]              -66.37 dBm              1.744000 ms              1 PK MAXH              0 Offset 1 dB              SGL              LVL              PS              3DB              Center 2.402 GHz    800 μs/         </p>					
Date: 18.FEB.2016 17:52:26					

**GFSK Hopping Mode DH3**


**2441 MHz**



Date: 18.FEB.2016 17:52:59

**GFSK Hopping Mode DH3**

**2480 MHz**




Date: 18.FEB.2016 17:53:28





**GFSK Hopping Mode DH5**


**2441 MHz**



Date: 18.FEB.2016 17:58:07

**GFSK Hopping Mode DH5**

**2480 MHz**



Date: 18.FEB.2016 17:58:51




## 9. Channel Separation and Bandwidth Test

### 9.1 Test Standard and Limit

- 9.1.1 Test Standard  
FCC Part 15.247
- 9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25$ KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=30 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

### 9.5 Test Data

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	966.00	1032.00	688.00
2441	954.00	1032.00	688.00
2480	948.00	1032.00	688.00

**GFSK TX Mode**

**2402 MHz**

\*RBW 30 kHz    Delta 1 [T1]    0.95 dB  
 \*VBW 100 kHz  
 Ref 0 dBm    \*Att 25 dB    SWT 5 ms    1.032000000 MHz

OBW966.000000000 kHz	Marker 1 [T1]	-32.48 dBm
2.401442000 GHz	Temp 1 [T1 OBW]	-32.51 dBm
2.401484000 GHz	Temp 2 [T1 OBW]	-30.73 dBm
2.402450000 GHz		

0 Offset 1 dB  
 D1 -12.32 dBm  
 D2 -32.32 dBm  
 T1  
 T2  
 F1  
 F2  
 3dB  
 LVL  
 PS


Center 2.402 GHz    300 kHz/    Span 3 MHz

Date: 18.FEB.2016 17:04:32



**GFSK TX Mode**


**2441 MHz**



Date: 18.FEB.2016 17:09:15

**GFSK TX Mode**

**2480 MHz**




Date: 18.FEB.2016 17:10:53





**GFSK Hopping Mode**


**2441 MHz**



Date: 18.FEB.2016 17:19:26

**GFSK Hopping Mode**

**2480 MHz**



Date: 18.FEB.2016 17:21:46

## 10. Peak Output Power Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.  
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.




### 10.5 Test Data

<b>EUT:</b>	Folding wireless keyboard	<b>Model Name :</b>	2930
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
<b>Channel frequency (MHz)</b>	<b>Test Result (dBm)</b>	<b>Limit (dBm)</b>	
2402	-11.89	<b>21</b>	
2441	-12.01		
2480	-12.92		
<b>GFSK TX Mode</b>			
<b>2402 MHz</b>			
<p>                 *RBW 3 MHz      Marker 1 [T1]      -11.89 dBm                  *VBW 3 MHz                  *Att 25 dB      SWT 2.5 ms      2.402100000 GHz                  Ref 0 dBm      Offset 1 dB             </p> <p>                 Center 2.402 GHz      500 kHz/      Span 5 MHz             </p>			
Date: 18.FEB.2016 17:05:20			

**GFSK TX Mode**


**2441 MHz**



Date: 18.FEB.2016 17:06:21

**GFSK TX Mode**

**2480 MHz**



Date: 18.FEB.2016 17:09:48



---

---

## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

The EUT antenna is a PCB antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna