FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f ²)	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$\mathbf{S} = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

- P = power input to the antenna (in appropriate units, e.g., mW).
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

Bay Area Compliance Laboratories Corp. (Shenzhen)

Mode	Frequency (MHz)	Antenna Gain		Max Tune Up Conducted Power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	$(\mathbf{mW/cm}^2)$	$(\mathrm{mW/cm}^2)$
2.4G Wi-Fi	2412-2472	6.93	4.93	21.0	125.89	20	0.124	1.0
BLE	2402-2480	-0.042	0.99	9.0	7.94	20	0.002	1.0
5G Wi-Fi	5150-5250	8.56	7.18	20.0	100.0	20	0.143	1.0
5G Wi-Fi	5725-5850	7.53	5.66	20.0	100.0	20	0.113	1.0

Note: 1. the tune up conducted power was declared by the applicant

 the BLE, 2.4G Wi-Fi functions can transmit at the same time with 5G Wi-Fi.
For the Wi-Fi, as it can support the beam-forming function, so the antenna gain should add the 10lg2.

So the worst simultaneous transmitting consideration:

The ratio=MPE_{2.4GWi-Fi}/limit + MPE_{5GWi-Fi}/limit + MPE_{BLE}/limit =0.124/1.0+0.143/1.0+0.002/1.0 =0.269 \leq 1.0

so simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance