



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

GL Technologies (Hong Kong) Limited

FLAT/RM 103B, Enterprise Place 5W Science Park, Shatin,
N.T.Shatin,Hong Kong

FCC ID: 2AFIW-MV1000W


Report Type: Original Report	Product Name: Edge Computing Gateway
Report Number:	RDG190930003-00B
Report Date:	2019-11-26
Reviewed By:	Gavin Xu RF Engineer 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS.....	11
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
APPLICABLE STANDARD	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP.....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	34
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41

TEST EQUIPMENT LIST AND DETAILS.....41

FCC §15.247(d)- 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....43

 APPLICABLE STANDARD43

 TEST PROCEDURE43

 TEST EQUIPMENT LIST AND DETAILS.....43

 TEST DATA44

FCC §15.247(e) - POWER SPECTRAL DENSITY53

 APPLICABLE STANDARD53

 TEST PROCEDURE53

 TEST EQUIPMENT LIST AND DETAILS.....53

 TEST DATA53

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Edge Computing Gateway
EUT Model:		GL-MV1000W
Operation Frequency:		802.11b/g/n: 2412-2462MHz 802.11n 40: 2422-2452MHz
Maximum Peak Output Power (Conducted):		23.5 dBm
Rated Input Voltage:		DC 5V from adapter
Adapter Information	Model:	KA1517-0502000USU
	Input:	100-240VAC 50/60Hz 0.35A Max
	Output:	DC 5V 2000mA
Serial Number:		RDG190930003-RF-S1
EUT Received Date:		2019/10/8
EUT Received Status:		Good

Objective

This report is prepared on behalf of *GL Technologies (Hong Kong) Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “Δ”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n20 modes were test with channel 1,6,11.

For 802.11n40 mode was test with channel 3,6,9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

EUT Exercise Software


The software “MobaXterm_Personal_11.0” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Mode	Channel	Frequency (MHz)	Data rate (Mbps)		Power level	
			Chain 0	Chain 1	Chain 0	Chain 1
802.11 b	Low	2412	1M	1M	default	default
	Middle	2437	1M	1M	default	default
	High	2462	1M	1M	default	default
802.11 g	Low	2412	6M	6M	default	default
	Middle	2437	6M	6M	default	default
	High	2462	6M	6M	default	default
802.11 n20	Low	2412	MCS8	MCS8	default	default
	Middle	2437	MCS8	MCS8	default	default
	High	2462	MCS8	MCS8	default	default
802.11 n40	Low	2422	MCS8	MCS8	default	default
	Middle	2437	MCS8	MCS8	default	default
	High	2452	MCS8	MCS8	default	default

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	2.1159	2.2319	94.80
802.11n20	1.9478	2.0406	95.45
802.11n40	0.9565	1.0435	91.66

802.11b




Date: 9.NOV.2019 14:31:10

802.11g




Date: 9.NOV.2019 13:52:23

802.11n20



Date: 9.NOV.2019 13:48:05

802.11n40



Date: 9.NOV.2019 13:37:20

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Kingston	USB Flash Disk	DataTraveler	122775
DELL	Laptop1	PP11L	QDS-BRCM1017
Lenovo	Laptop 2	ThinkPad E450	PF-0MRADG
DELL	Laptop	PP11L	QDS-BRCM1017

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Power Cable	yes	No	1.2	Adapter	EUT
RJ45 Cable	yes	yes	5	Ethernet port of EUT	Laptop
RJ45 Cable	yes	yes	5	Ethernet port of EUT	Laptop 1
RJ45 Cable	yes	yes	5	Ethernet port of EUT	Laptop 2

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
FCC §15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	3	2.00	24	251.19	20.00	0.10	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has two antennas permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
PCB	50	3 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	EMI Test Receiver	ESPI	100120	2019-05-09	2020-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	25.7°C
Relative Humidity:	45 %
ATM Pressure:	101.2kPa
Tester:	Sem Xiang
Test Date:	2019-11-14

Test Mode: Transmitting (802.11n20 mode middle channel was the worst)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	44.2	9.000	L1	11.2	21.8	66.0
0.200176	36.4	9.000	L1	10.6	27.2	63.6
0.426418	36.3	9.000	L1	9.9	21.0	57.3
0.536077	43.6	9.000	L1	9.9	12.4	56.0
0.737074	35.9	9.000	L1	9.8	20.1	56.0
1.286792	34.9	9.000	L1	9.8	21.1	56.0

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.422196	33.8	9.000	L1	9.9	13.6	47.4
0.536077	37.7	9.000	L1	9.9	8.3	46.0
0.983629	31.3	9.000	L1	9.8	14.7	46.0
1.274051	30.0	9.000	L1	9.8	16.0	46.0
2.137462	28.4	9.000	L1	9.7	17.6	46.0
3.621856	26.7	9.000	L1	9.8	19.3	46.0

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154545	41.3	9.000	N	11.1	24.5	65.8
0.256712	32.0	9.000	N	10.3	29.5	61.5
0.546852	33.6	9.000	N	9.8	22.4	56.0
0.798146	26.7	9.000	N	9.8	29.3	56.0
2.246494	22.6	9.000	N	9.8	33.4	56.0
15.794085	26.7	9.000	N	9.9	33.3	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.156091	23.8	9.000	N	11.1	31.9	55.7
0.401705	17.0	9.000	N	10.0	30.8	47.8
0.515160	23.9	9.000	N	9.9	22.1	46.0
0.806127	16.2	9.000	N	9.8	29.8	46.0
1.769262	13.6	9.000	N	9.8	32.4	46.0
15.794085	17.5	9.000	N	9.9	32.5	50.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESCI	100035	2019-08-03	2020-08-03
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2019-09-24	2020-09-24
Sonoma	Amplifier	310N	185914	2019-10-13	2020-10-13
Radiation Above 1GHz					
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2019/11/18	2022/11/18
MICRO-COAX	Coaxial Cable	UFA147-1-2362-100100	64639 231029-001	2019-02-24	2020-02-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019/6/27	2020/6/27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019/6/16	2020/6/16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25 °C	25°C
Relative Humidity:	46%	46%
ATM Pressure:	101.2kPa	100.5 kPa
Tester:	Jackson Zhang	Vern Shen
Test Date:	2019-11-16	2019-11-19

Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting


1) 30MHz-1GHz(802.11n20 mode Middle channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
151.2500	45.40	QP	-9.44	35.96	43.50	7.54
176.4700	45.58	QP	-9.89	35.69	43.50	7.81
191.9900	45.01	QP	-10.42	34.59	43.50	8.91
625.5800	37.84	peak	-0.80	37.04	46.00	8.96
928.2200	35.31	QP	4.23	39.54	46.00	6.46
993.2100	41.94	peak	5.34	47.28	54.00	6.72

Vertical:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
76.5600	48.26	peak	-16.21	32.05	40.00	7.95
125.0600	44.45	peak	-11.41	33.04	43.50	10.46
625.5800	43.45	QP	-0.80	42.65	46.00	3.35
662.4400	40.14	QP	-0.14	40.00	46.00	6.00
721.6100	39.09	QP	0.62	39.71	46.00	6.29
929.1900	33.92	QP	4.23	38.15	46.00	7.85

2) 1-25GHz:

802.11b Mode Chain 0:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	62.70	PK	H	24.84	3.35	0.00	90.89	N/A	N/A
2412.00	57.90	AV	H	24.84	3.35	0.00	86.09	N/A	N/A
2412.00	71.19	PK	V	24.84	3.35	0.00	99.38	N/A	N/A
2412.00	66.69	AV	V	24.84	3.35	0.00	94.88	N/A	N/A
2390.00	29.33	PK	V	24.80	3.33	0.00	57.46	74.00	16.54
2390.00	15.53	AV	V	24.80	3.33	0.00	43.66	54.00	10.34
4824.00	47.36	PK	V	29.75	4.58	27.41	54.28	74.00	19.72
4824.00	44.09	AV	V	29.75	4.58	27.41	51.01	54.00	2.99
7236.00	37.63	PK	V	33.98	5.62	27.22	50.01	74.00	23.99
7236.00	27.30	AV	V	33.98	5.62	27.22	39.68	54.00	14.32
Middle Channel: 2437 MHz									
2437.00	62.84	PK	H	24.89	3.36	0.00	91.09	N/A	N/A
2437.00	57.91	AV	H	24.89	3.36	0.00	86.16	N/A	N/A
2437.00	72.03	PK	V	24.89	3.36	0.00	100.28	N/A	N/A
2437.00	67.87	AV	V	24.89	3.36	0.00	96.12	N/A	N/A
4874.00	48.01	PK	V	29.85	4.57	27.54	54.89	74.00	19.11
4874.00	44.64	AV	V	29.85	4.57	27.54	51.52	54.00	2.48
7311.00	37.20	PK	V	34.10	5.68	27.28	49.70	74.00	24.30
7311.00	25.70	AV	V	34.10	5.68	27.28	38.20	54.00	15.80
High Channel: 2462 MHz									
2462.00	62.97	PK	H	24.93	3.37	0.00	91.27	N/A	N/A
2462.00	57.94	AV	H	24.93	3.37	0.00	86.24	N/A	N/A
2462.00	72.56	PK	V	24.93	3.37	0.00	100.86	N/A	N/A
2462.00	68.82	AV	V	24.93	3.37	0.00	97.12	N/A	N/A
2483.50	29.37	PK	V	24.97	3.38	0.00	57.72	74.00	16.28
2483.50	18.17	AV	V	24.97	3.38	0.00	46.52	54.00	7.48
4924.00	48.51	PK	V	29.95	4.57	27.51	55.52	74.00	18.48
4924.00	44.95	AV	V	29.95	4.57	27.51	51.96	54.00	2.04
7386.00	36.66	PK	V	34.22	5.74	27.18	49.44	74.00	24.56
7386.00	25.78	AV	V	34.22	5.74	27.18	38.56	54.00	15.44

802.11b Mode Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	59.64	PK	H	24.84	3.35	0.00	87.83	N/A	N/A
2412.00	55.51	AV	H	24.84	3.35	0.00	83.70	N/A	N/A
2412.00	68.04	PK	V	24.84	3.35	0.00	96.23	N/A	N/A
2412.00	63.76	AV	V	24.84	3.35	0.00	91.95	N/A	N/A
2390.00	30.00	PK	V	24.80	3.33	0.00	58.13	74.00	15.87
2390.00	17.55	AV	V	24.80	3.33	0.00	45.68	54.00	8.32
4824.00	42.39	PK	V	29.75	4.58	27.41	49.31	74.00	24.69
4824.00	37.40	AV	V	29.75	4.58	27.41	44.32	54.00	9.68
7236.00	36.70	PK	V	33.98	5.62	27.22	49.08	74.00	24.92
7236.00	25.87	AV	V	33.98	5.62	27.22	38.25	54.00	15.75
Middle Channel: 2437 MHz									
2437.00	60.45	PK	H	24.89	3.36	0.00	88.70	N/A	N/A
2437.00	56.45	AV	H	24.89	3.36	0.00	84.70	N/A	N/A
2437.00	69.21	PK	V	24.89	3.36	0.00	97.46	N/A	N/A
2437.00	65.17	AV	V	24.89	3.36	0.00	93.42	N/A	N/A
4874.00	42.21	PK	V	29.85	4.57	27.54	49.09	74.00	24.91
4874.00	37.21	AV	V	29.85	4.57	27.54	44.09	54.00	9.91
7311.00	36.40	PK	V	34.10	5.68	27.28	48.90	74.00	25.10
7311.00	25.47	AV	V	34.10	5.68	27.28	37.97	54.00	16.03
High Channel: 2462 MHz									
2462.00	60.87	PK	H	24.93	3.37	0.00	89.17	N/A	N/A
2462.00	56.84	AV	H	24.93	3.37	0.00	85.14	N/A	N/A
2462.00	69.36	PK	V	24.93	3.37	0.00	97.66	N/A	N/A
2462.00	65.27	AV	V	24.93	3.37	0.00	93.57	N/A	N/A
2483.50	29.40	PK	V	24.97	3.38	0.00	57.75	74.00	16.25
2483.50	17.77	AV	V	24.97	3.38	0.00	46.12	54.00	7.88
4924.00	41.80	PK	V	29.95	4.57	27.51	48.81	74.00	25.19
4924.00	36.24	AV	V	29.95	4.57	27.51	43.25	54.00	10.75
7386.00	35.54	PK	V	34.22	5.74	27.18	48.32	74.00	25.68
7386.00	24.21	AV	V	34.22	5.74	27.18	36.99	54.00	17.01

802.11g Mode Chain 0:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	61.69	PK	H	24.84	3.35	0.00	89.88	N/A	N/A
2412.00	51.01	AV	H	24.84	3.35	0.00	79.20	N/A	N/A
2412.00	68.79	PK	V	24.84	3.35	0.00	96.98	N/A	N/A
2412.00	60.11	AV	V	24.84	3.35	0.00	88.30	N/A	N/A
2390.00	29.84	PK	V	24.80	3.33	0.00	57.97	74.00	16.03
2390.00	18.15	AV	V	24.80	3.33	0.00	46.28	54.00	7.72
4824.00	42.32	PK	V	29.75	4.58	27.41	49.24	74.00	24.76
4824.00	29.52	AV	V	29.75	4.58	27.41	36.44	54.00	17.56
7236.00	36.89	PK	V	33.98	5.62	27.22	49.27	74.00	24.73
7236.00	24.92	AV	V	33.98	5.62	27.22	37.30	54.00	16.70
Middle Channel: 2437 MHz									
2437.00	61.87	PK	H	24.89	3.36	0.00	90.12	N/A	N/A
2437.00	51.57	AV	H	24.89	3.36	0.00	79.82	N/A	N/A
2437.00	69.78	PK	V	24.89	3.36	0.00	98.03	N/A	N/A
2437.00	61.52	AV	V	24.89	3.36	0.00	89.77	N/A	N/A
4874.00	43.10	PK	V	29.85	4.57	27.54	49.98	74.00	24.02
4874.00	30.21	AV	V	29.85	4.57	27.54	37.09	54.00	16.91
7311.00	36.97	PK	V	34.10	5.68	27.28	49.47	74.00	24.53
7311.00	25.14	AV	V	34.10	5.68	27.28	37.64	54.00	16.36
High Channel: 2462 MHz									
2462.00	63.10	PK	H	24.93	3.37	0.00	91.40	N/A	N/A
2462.00	53.07	AV	H	24.93	3.37	0.00	81.37	N/A	N/A
2462.00	70.02	PK	V	24.93	3.37	0.00	98.32	N/A	N/A
2462.00	61.94	AV	V	24.93	3.37	0.00	90.24	N/A	N/A
2483.50	32.21	PK	V	24.97	3.38	0.00	60.56	74.00	13.44
2483.50	20.49	AV	V	24.97	3.38	0.00	48.84	54.00	5.16
4924.00	43.21	PK	V	29.95	4.57	27.51	50.22	74.00	23.78
4924.00	30.31	AV	V	29.95	4.57	27.51	37.32	54.00	16.68
7386.00	37.00	PK	V	34.22	5.74	27.18	49.78	74.00	24.22
7386.00	25.17	AV	V	34.22	5.74	27.18	37.95	54.00	16.05

802.11g Mode Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	64.32	PK	H	24.84	3.35	0.00	92.51	N/A	N/A
2412.00	54.87	AV	H	24.84	3.35	0.00	83.06	N/A	N/A
2412.00	67.47	PK	V	24.84	3.35	0.00	95.66	N/A	N/A
2412.00	59.79	AV	V	24.84	3.35	0.00	87.98	N/A	N/A
2390.00	32.84	PK	V	24.80	3.33	0.00	60.97	74.00	13.03
2390.00	18.03	AV	V	24.80	3.33	0.00	46.16	54.00	7.84
4824.00	39.20	PK	V	29.75	4.58	27.41	46.12	74.00	27.88
4824.00	25.21	AV	V	29.75	4.58	27.41	32.13	54.00	21.87
7236.00	36.27	PK	V	33.98	5.62	27.22	48.65	74.00	25.35
7236.00	24.61	AV	V	33.98	5.62	27.22	36.99	54.00	17.01
Middle Channel: 2437 MHz									
2437.00	65.01	PK	H	24.89	3.36	0.00	93.26	N/A	N/A
2437.00	54.80	AV	H	24.89	3.36	0.00	83.05	N/A	N/A
2437.00	68.24	PK	V	24.89	3.36	0.00	96.49	N/A	N/A
2437.00	59.11	AV	V	24.89	3.36	0.00	87.36	N/A	N/A
4874.00	39.14	PK	V	29.85	4.57	27.54	46.02	74.00	27.98
4874.00	25.12	AV	V	29.85	4.57	27.54	32.00	54.00	22.00
7311.00	36.17	PK	V	34.10	5.68	27.28	48.67	74.00	25.33
7311.00	24.54	AV	V	34.10	5.68	27.28	37.04	54.00	16.96
High Channel: 2462 MHz									
2462.00	65.20	PK	H	24.93	3.37	0.00	93.50	N/A	N/A
2462.00	55.17	AV	H	24.93	3.37	0.00	83.47	N/A	N/A
2462.00	68.66	PK	V	24.93	3.37	0.00	96.96	N/A	N/A
2462.00	59.33	AV	V	24.93	3.37	0.00	87.63	N/A	N/A
2483.50	31.83	PK	V	24.97	3.38	0.00	60.18	74.00	13.82
2483.50	19.11	AV	V	24.97	3.38	0.00	47.46	54.00	6.54
4924.00	39.54	PK	V	29.95	4.57	27.51	46.55	74.00	27.45
4924.00	25.54	AV	V	29.95	4.57	27.51	32.55	54.00	21.45
7386.00	36.70	PK	V	34.22	5.74	27.18	49.48	74.00	24.52
7386.00	24.87	AV	V	34.22	5.74	27.18	37.65	54.00	16.35

802.11n20 Mode (2TX was the worst):



Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	60.24	PK	H	24.84	3.35	0.00	88.43	N/A	N/A
2412.00	49.10	AV	H	24.84	3.35	0.00	77.29	N/A	N/A
2412.00	69.06	PK	V	24.84	3.35	0.00	97.25	N/A	N/A
2412.00	59.77	AV	V	24.84	3.35	0.00	87.96	N/A	N/A
2390.00	31.46	PK	V	24.80	3.33	0.00	59.59	74.00	14.41
2390.00	18.96	AV	V	24.80	3.33	0.00	47.09	54.00	6.91
4824.00	41.78	PK	V	29.75	4.58	27.41	48.70	74.00	25.30
4824.00	29.56	AV	V	29.75	4.58	27.41	36.48	54.00	17.52
7236.00	35.97	PK	V	33.98	5.62	27.22	48.35	74.00	25.65
7236.00	25.87	AV	V	33.98	5.62	27.22	38.25	54.00	15.75
Middle Channel: 2437 MHz									
2437.00	61.70	PK	H	24.89	3.36	0.00	89.95	N/A	N/A
2437.00	50.57	AV	H	24.89	3.36	0.00	78.82	N/A	N/A
2437.00	70.57	PK	V	24.89	3.36	0.00	98.82	N/A	N/A
2437.00	59.41	AV	V	24.89	3.36	0.00	87.66	N/A	N/A
4874.00	42.10	PK	V	29.85	4.57	27.54	48.98	74.00	25.02
4874.00	30.24	AV	V	29.85	4.57	27.54	37.12	54.00	16.88
7311.00	36.40	PK	V	34.10	5.68	27.28	48.90	74.00	25.10
7311.00	25.87	AV	V	34.10	5.68	27.28	38.37	54.00	15.63
High Channel: 2462 MHz									
2462.00	62.78	PK	H	24.93	3.37	0.00	91.08	N/A	N/A
2462.00	51.71	AV	H	24.93	3.37	0.00	80.01	N/A	N/A
2462.00	71.81	PK	V	24.93	3.37	0.00	100.11	N/A	N/A
2462.00	60.34	AV	V	24.93	3.37	0.00	88.64	N/A	N/A
2483.50	31.81	PK	V	24.97	3.38	0.00	60.16	74.00	13.84
2483.50	20.30	AV	V	24.97	3.38	0.00	48.65	54.00	5.35
4924.00	42.54	PK	V	29.95	4.57	27.51	49.55	74.00	24.45
4924.00	30.64	AV	V	29.95	4.57	27.51	37.65	54.00	16.35
7386.00	36.47	PK	V	34.22	5.74	27.18	49.25	74.00	24.75
7386.00	25.89	AV	V	34.22	5.74	27.18	38.67	54.00	15.33


802.11n 40 Mode (2TX was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	56.32	PK	H	24.86	3.35	0.00	84.53	N/A	N/A
2422.00	45.96	AV	H	24.86	3.35	0.00	74.17	N/A	N/A
2422.00	66.08	PK	V	24.86	3.35	0.00	94.29	N/A	N/A
2422.00	56.59	AV	V	24.86	3.35	0.00	84.80	N/A	N/A
2390.00	30.08	PK	V	24.80	3.33	0.00	58.21	74.00	15.79
2390.00	19.30	AV	V	24.80	3.33	0.00	47.43	54.00	6.57
4844.00	40.47	PK	V	29.79	4.57	27.46	47.37	74.00	26.63
4844.00	27.40	AV	V	29.79	4.57	27.46	34.30	54.00	19.70
7266.00	36.41	PK	V	34.03	5.64	27.25	48.83	74.00	25.17
7266.00	24.18	AV	V	34.03	5.64	27.25	36.60	54.00	17.40
Middle Channel: 2437 MHz									
2437.00	57.56	PK	H	24.89	3.36	0.00	85.81	N/A	N/A
2437.00	47.51	AV	H	24.89	3.36	0.00	75.76	N/A	N/A
2437.00	67.87	PK	V	24.89	3.36	0.00	96.12	N/A	N/A
2437.00	57.45	AV	V	24.89	3.36	0.00	85.70	N/A	N/A
4874.00	40.24	PK	V	29.85	4.57	27.54	47.12	74.00	26.88
4874.00	28.74	AV	V	29.85	4.57	27.54	35.62	54.00	18.38
7311.00	36.74	PK	V	34.10	5.68	27.28	49.24	74.00	24.76
7311.00	25.99	AV	V	34.10	5.68	27.28	38.49	54.00	15.51
High Channel: 2452MHz									
2452.00	57.21	PK	H	24.91	3.37	0.00	85.49	N/A	N/A
2452.00	47.47	AV	H	24.91	3.37	0.00	75.75	N/A	N/A
2452.00	67.32	PK	V	24.91	3.37	0.00	95.60	N/A	N/A
2452.00	57.06	AV	V	24.91	3.37	0.00	85.34	N/A	N/A
2483.50	31.69	PK	V	24.97	3.38	0.00	60.04	74.00	13.96
2483.50	20.64	AV	V	24.97	3.38	0.00	48.99	54.00	5.01
4904.00	39.82	PK	V	29.91	4.56	27.58	46.71	74.00	27.29
4904.00	28.47	AV	V	29.91	4.56	27.58	35.36	54.00	18.64
7356.00	36.51	PK	V	34.17	5.72	27.22	49.18	74.00	24.82
7356.00	25.93	AV	V	34.17	5.72	27.22	38.60	54.00	15.40



Test plots(802.11b mode chain 0 high channel was the worst)


Horizontal:





Vertical:





FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	OE01203218	2019-05-06	2020-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.1°C
Relative Humidity:	41%
ATM Pressure:	101.1 kPa
Tester:	LilyXie
Test Date:	2019-11-09


Test Mode: Transmitting (Test only performed at chain 0)

Test Result: Compliance. Please refer to the following table and plots.

Mode	Channel	Frequency (MHz)	Result (MHz)	Limit (MHz)
802.11 b	Low	2412	10.080	0.5
	Middle	2437	10.080	
	High	2462	10.000	
802.11 g	Low	2412	16.480	
	Middle	2437	16.480	
	High	2462	16.480	
802.11 n20	Low	2412	17.440	
	Middle	2437	17.440	
	High	2462	17.440	
802.11 n40	Low	2422	35.680	
	Middle	2437	35.680	
	High	2452	35.680	


Please refer to following plots:

802.11 b_Low




Date: 9.NOV.2019 10:59:40

802.11 b_Middle




Date: 9.NOV.2019 11:02:36

802.11 b High




Date: 9.NOV.2019 11:04:39

802.11 g Low




Date: 9.NOV.2019 11:12:35

802.11 g Middle




Date: 9.NOV.2019 11:11:11

802.11 g High




Date: 9.NOV.2019 11:08:24

802.11 n20 Low




Date: 9.NOV.2019 11:16:16

802.11 n20 Middle



Date: 9.NOV.2019 11:43:35

802.11 n20_High




Date: 9.NOV.2019 11:44:49

802.11 n40_Low




Date: 9.NOV.2019 13:39:22

802.11 n40 Middle



Date: 9.NOV.2019 13:37:45

802.11 n40 High



Date: 9.NOV.2019 11:53:25

FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	OE01203218	2019-05-06	2020-05-06
Weinschel	Coaxial Attenuators	53-20-34	LN749	2019-09-06	2020-09-06
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.1°C
Relative Humidity:	41%
ATM Pressure:	101.1 kPa
Tester:	LilyXie
Test Date:	2019-11-09

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Peak channel power

Mode	Channel	Frequency (MHz)	Result (dBm)			Limit (dBm)
			Chain 0	Chain 1	Total	
802.11 b	Low	2412	17.75	16.74	/	30
	Middle	2437	18.02	16.91	/	
	High	2462	17.65	16.68	/	
802.11 g	Low	2412	21.78	20.87	/	
	Middle	2437	21.82	20.83	/	
	High	2462	21.57	20.81	/	
802.11 n20	Low	2412	20.89	20.05	23.50	
	Middle	2437	20.77	20.20	23.50	
	High	2462	19.84	20.07	22.97	
802.11 n40	Low	2422	20.06	19.24	22.68	
	Middle	2437	20.17	19.15	22.70	
	High	2452	20.65	19.49	23.12	

Note:

- 1) The data above was tested in conducted mode.
- 2) The maximum antenna gain is 3.0 dBi.

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

So:

Directional gain = $G_{ANT} + \text{Array Gain} = 3.0 \text{ dBi} < 6 \text{ dBi}$

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	OE01203218	2019-05-06	2020-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	26.1°C
Relative Humidity:	41%
ATM Pressure:	101.1 kPa
Tester:	LilyXie
Test Date:	2019-11-09


Please refer to following plots:

802.11 b_Low_Chain 0




Date: 9.NOV.2019 11:00:37

802.11 b Low_Chain 1




Date: 9.NOV.2019 14:08:04


802.11 b High Chain 0



802.11 b High Chain 1




802.11 g Low Chain 0




Date: 9.NOV.2019 11:13:15

802.11 g Low Chain 1




Date: 9.NOV.2019 14:02:46

802.11 g High Chain 0




Date: 9.NOV.2019 11:09:11

802.11 g High Chain 1




Date: 9.NOV.2019 14:00:27

802.11 n20 Low Chain 0




Date: 9.NOV.2019 11:18:54

802.11 n20 Low Chain 1




Date: 9.NOV.2019 11:35:40

802.11 n20 High Chain 0




Date: 9.NOV.2019 11:45:40

802.11 n20 High Chain 1




Date: 9.NOV.2019 11:47:13

802.11 n40 Low Chain 0




Date: 9.NOV.2019 13:40:07

802.11 n40 Low Chain 1




Date: 9.NOV.2019 13:42:14

802.11 n40 High Chain 0



Date: 9.NOV.2019 11:54:12

802.11 n40 High Chain 1



Date: 9.NOV.2019 11:52:43

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	OE01203218	2019-05-06	2020-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.1°C
Relative Humidity:	41%
ATM Pressure:	101.1 kPa
Tester:	LilyXie
Test Date:	2019-11-09

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Please refer to following plots:

Mode	Channel	Frequency (MHz)	Result (dBm/3kHz)			Limit (dBm/3kHz)
			Chain 0	Chain 1	Total	
802.11 b	Low	2412	-6.18	-6.30	/	8
	Middle	2437	-5.90	-6.56	/	
	High	2462	-5.73	-7.73	/	
802.11 g	Low	2412	-12.46	-12.38	/	
	Middle	2437	-11.88	-12.26	/	
	High	2462	-11.88	-12.59	/	
802.11 n20	Low	2412	-14.32	-14.47	-11.38	
	Middle	2437	-14.09	-14.05	-11.06	
	High	2462	-14.30	-15.16	-11.70	
802.11 n40	Low	2422	-18.58	-18.98	-15.77	
	Middle	2437	-18.23	-19.42	-15.77	
	High	2452	-17.31	-18.21	-14.73	

Note:

The maximum antenna gain is 3.0 dBi.

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:


$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{SS}}) \text{ dB.}$$

So:

$$\text{Directional gain} = G_{\text{ANT}} + \text{Array Gain} = 3.0\text{dBi} + 10 * \log(2/1) = 6.0\text{dBi}$$


Please refer to following plots:

802.11 b Low Chain 0




Date: 9.NOV.2019 11:00:13

802.11 b Low Chain 1




Date: 9.NOV.2019 14:07:47

802.11 b Middle Chain 0




Date: 9.NOV.2019 11:03:13

802.11 b Middle Chain 1




Date: 9.NOV.2019 14:09:48

802.11 b High Chain 0




Date: 9.NOV.2019 11:05:13

802.11 b High Chain 1




Date: 9.NOV.2019 14:11:08

802.11 g Low Chain 0




Date: 9.NOV.2019 11:12:58

802.11 g Low Chain 1




Date: 9.NOV.2019 14:02:31

802.11 g Middle Chain 0




Date: 9.NOV.2019 11:11:38

802.11 g Middle Chain 1




Date: 9.NOV.2019 14:01:19

802.11 g High Chain 0




Date: 9.NOV.2019 11:08:51

802.11 g High Chain 1




Date: 9.NOV.2019 14:00:03

802.11 n20 Low Chain 0




Date: 9.NOV.2019 11:18:28

802.11 n20 Low Chain 1




Date: 9.NOV.2019 11:35:17

802.11 n20 Middle Chain 0




Date: 9.NOV.2019 11:44:00

802.11 n20 Middle Chain 1




Date: 9.NOV.2019 11:38:37

802.11 n20 High Chain 0




Date: 9.NOV.2019 11:45:23

802.11 n20 High Chain 1




Date: 9.NOV.2019 11:46:53

802.11 n40 Low Chain 0




Date: 9.NOV.2019 13:39:46

802.11 n40 Low Chain 1




Date: 9.NOV.2019 13:41:56

802.11 n40 Middle Chain 0




Date: 9.NOV.2019 13:38:12

802.11 n40 Middle Chain 1




Date: 9.NOV.2019 13:32:18

802.11 n40 High Chain 0



Date: 9.NOV.2019 11:53:52

802.11 n40 High Chain 1



Date: 9.NOV.2019 11:52:22

***** END OF REPORT *****