

Report No.: FYCR220500016903

Page: 1 of 12

RF Exposure Report

Application No.: FYCR2205000169AT

Applicant: GL Technologies (Hong Kong) Limited

Address of Applicant: Unit203, 19W Science Park West Avenue, HKSP, ShaTin, Hong Kong

Manufacturer: Shenzhen Guanglian Zhitong Technology Co., LTD

Address of Manufacturer: Room 305, 306, Chuangwei Digital Building, Songbai Road, Shiyan Street,

Baoan District, Shenzhen

Factory: Shenzhen Guanglian Zhitong Technology Co., LTD

Address of Factory:

Room 305, 306, Chuangwei Digital Building, Songbai Road, Shiyan Street,

Baoan District, Shenzhen

**Equipment Under Test (EUT):** 

**EUT Name:** Industrial 4G LTE Gateway

Model No.: GL-X300BGC4

Trade Mark: GL.iNET

 FCC ID:
 2AFIW-X300BGC4

 Contain FCC ID:
 XMR201903EG25G

Standard(s): FCC Rules 47 CFR §2.1091

KDB 447498 D04 interim General RF Exposure Guidance v01

**Date of Receipt:** 2022-05-13

**Date of Test:** 2022-05-19 to 2022-05-27

**Date of Issue:** 2022-06-01

Test Result: Pass\*

Winkey Wang
Winkey Wang
EMC Technical Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Conditions/Terms

Fuyong lab. Xiniong TechnoPark, Fenglang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: FYCR220500016903

Page: 2 of 12

Revision Record									
Version	Chapter	Date	Modifier	Remark					
01		2022-06-01		Original					

Authorized for issue by:		
	Tree Zhan	
	Tree Zhan/Project Engineer	-
	WinkeyWarg	
	Winkey Wang/Reviewer	-



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CAD Doccheck@sas.com

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 3 of 12

#### 1 Contents

		Pa	age
1	С	ONTENTS	. 3
2	G	ENERAL INFORMATION	.4
	2.1	GENERAL DESCRIPTION OF E.U.T.	. 4
	2.2	DETAILS OF E.U.T.	.4
	2.3	SEPARATION DISTANCE	.6
	2.4	TEST LOCATION	.6
	2.5	TEST FACILITY	.6
3	F	CC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	.7
	3.1	BLANKET 1 MW BLANKET EXEMPTION	.7
	3.2	MPE-BASED EXEMPTION	.7
	3.3	SAR-BASED EXEMPTION	.8
4	M	EASUREMENT AND CALCULATION1	10
	4.1	MAXIMUM TRANSMIT POWER	10
	RFE	XPOSURE CALCULATION	11



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CAD Doccheck@sas.com

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 4 of 12

### 2 General Information

### 2.1 General Description of E.U.T.

	☐ Portable device
Product Type:	
	☐ Fixed device

### 2.2 Details of E.U.T.

Power supply:	DC 12V 1A.		
	Adapter Model: ICP12-120-1000D		
	Input: AC 100-240V 50/60Hz 0.3A		
	Output: DC 12V 1A.		
Operation Fraguency	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to		
Operation Frequency:	2452MHz		
Madulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM,		
Modulation Type:	16QAM, QPSK, BPSK)		
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7		
Channel Spacing:	5MHz		
Antenna Type:	Dipole Antenna		
Antenna Gain:	ANT1: 3.2dBi; ANT2: 3.2dBi		

For GSM/WCDMA/LTE	For GSM/WCDMA/LTE (Module: EG25-G)				
Operation Frequency Band:  GSM850/1900 WCDMA Band II/ WCDMA Band V/ WCDMA Band IV LTE FDD Band 2, 4, 5, 7, 12, 13, 25, 26, 38, 41					
Modulation Type:	GMSK for GPRS/EGPRS;  8PSK for EGPRS;  WCDMA: UL up to 16QAM, DL up to 64QAM  LTE: UL&DL up to 256QAM				
Antenna Type:	Dipole Antenna				
Antenna Gain:	GSM850: 3.16dBi, GSM1900: 4.15dBi  WCDMA Band II/IV/V: 4.12dBi				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CAD Doccheck@sas.com

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 5 of 12

LTE FDD Band 2, 4, 5, 7, 12, 13, 25, 26, 38, 41: 4.12dBi

Based on Module certification(FCC ID: XMR201903EG25G)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CAD Doccheck@sas.com



Report No.: FYCR220500016903

Page: 6 of 12

### 2.3 Separation Distance

Minimum test separation distance: 20cm

Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

#### 2.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China

Tel: +86 755 8866 3988 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 2.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

#### • FCC –Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

### • Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.apxx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documents">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documents at advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 samples (56-755) 8307 1443, or email: No proceber 47 sam



Report No.: FYCR220500016903

Page: 7 of 12

### 3 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

### 3.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

#### 3.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f∟ MHz		f <sub>H</sub> MHz	$\lambda_L / 2\pi$		λ <sub>H</sub> / 2π	W
0.3	_	1.34	159 m	_	35.6 m	1,920 R <sup>2</sup>
1.34	_	30	35.6 m	_	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>
30	_	300	1.6 m	_	159 mm	3.83 R <sup>2</sup>
300	_	1,500	159 mm	_	31.8 mm	0.0128 R <sup>2</sup> f
1,500	_	100,000	31.8 mm	_	0.5 mm	19.2R <sup>2</sup>

Subscripts L and H are low and high; λ is wavelength.

From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Comditions/Terms

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdistrict, Bao'an, Sherazhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 8 of 12

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than *ERP*<sub>20cm</sub> in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{\text{th }}(\text{mW}) = ERP_{20 \text{ cm }}(\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation							
Frequency range Frequency(MHz) $R(\lambda/2\pi)(m)$ Threshold ERP(W)							
300~1500MHz	915	0.0522	0.032				
1500~100000MHz	2462	0.0194	0.007				

#### 3.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.</a>
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

This company is a such as a such sample(s) tested and such sample(s) are retained for 30 days only.

This company is a such sample (s) tested and such sample(s) are retained for 30 days only.

This company is a such sample (s) tested and such sample(s) are retained for 30 days only.

This company is a such sample (s) tested and such sample(s) are retained for 30 days only.

This company is a such sample (s) tested and such sample(s) tested and such sample(s) are retained for 30 days only.

This company is a such sample (s) tested and such sample(s) tested only the sample (s) tested on the sample (s) test

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Sherather, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 9 of 12

The SAR-based exemption formula of  $\S1.1307(b)(3)(i)(B)$ , repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B. 2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and  $ERP_{20cm}$  is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Tuble Biz Example Fower Fill esticide (IIIV)										
Frequency					Distanc	ce(mm)				
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation							
Frequency range(GHz)	Frequency(GHz)	Χ	Distance(cm)	Pth (mW)			
0.3~1.5 <b>0.01356</b> -1.270 <b>20 27.662</b>							
1.5~6	2.462	1.903	20	3060.000			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

As a content is a telephone: (86-755) 8307 1443



Report No.: FYCR220500016903

Page: 10 of 12

### 4 Measurement and Calculation

#### 4.1 Maximum transmit power

2.4G WIFI

The Power Data is based on the RF Test Report FYCR220500016901

Test Mode	Test Channel	Max RF conducted power	Power[dBm] EIRP	Power[mW] EIRP
	2412	18.64	21.84	152.76
2.4G WIFI	2437	19.37	22.57	180.72
	2462	19.20	22.40	173.78

#### For GSM/WCDMA/LTE

Based on Module certification(FCC ID: XMR201903EG25G), refer to report No. HR/2019/1001602 for GSM/WCDMA/LTE Module test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the far-field transmission formula is at distances 20 cm or greater from any object.

Test Mode	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Power (mW)
GSM850	25.81	3.16	788.86
GSM900	22.81	4.15	496.59
WCDMA B2	25.00	4.12	816.58
WCDMA B4	25.00	4.12	816.58
WCDMA B5	25.00	4.12	816.58
LTE B2	25.00	4.12	816.58
LTE B4	25.00	4.12	816.58
LTE B5	25.00	4.12	816.58
LTE B7	25.00	4.12	816.58
LTE B12	25.00	4.12	816.58



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents as the time of the Terms and Conditions for Electronic Documents as the Tittp://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-And-Con

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdishrid, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 11 of 12

LTE B13	25.00	4.12	816.58
LTE B25	25.00	4.12	816.58
LTE B26	25.00	4.12	816.58
(814-824)			
LTE B26	25.00	4.12	816.58
(824-849)			
LTE B38	25.00	4.12	816.58
LTE B41	25.00	4.12	816.58

#### **RF Exposure Calculation**

#### Standalone For WIFI transmitter and GSM/WCDMA/LTE transmitter:

Remark: we used the maximum ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
$\boxtimes$	SAR-based Exemption( $P_{th}$ )	3060mW	Yes

So, the device is qualified for SAR test exemption, the exemption report is in lieu of the SAR report.

#### Exposure condition for simultaneous transmission operations

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluatedk term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^{a} \frac{P_i}{P_{\text{th},i}} + \sum_{i=1}^{b} \frac{ERP_j}{ERP_{\text{th},j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$
 (C. 1)

#### Remark:

- a -number of fixed, mobile, or portable RF sources claiming exemption using the §1.1307(b)(3)(i)(B) formula for Pth, including existing exempt transmitters and those being added.
- b -number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.
- c -number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

As a content is a telephone: (86-755) 8307 1443

| Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrid, Bao'an, Shenzben, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



Report No.: FYCR220500016903

Page: 12 of 12

Pi -the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i -the exemption threshold power (Pth) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i.

ERPj -the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j. ERPth,j -exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$ , according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

Evaluated<sub>k</sub> -the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.

Exposure Limit<sub>k</sub> -either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

The sum of the ratios = 180.72mW/3060mW + 816.58mW/3060mW = 0.33 < 1

Therefore, the device is to qualify for simultaneous transmission SAR test exemption, the exemption report is in lieu of the SAR report.

-- End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Comditions/Terms