

## MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

### **1. Evaluation method**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

**2. Limits for General Population/Uncontrolled Exposure**

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

**3. Calculation Method**

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to anisotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the maximum gain of the used as follows, the RF power density can be obtained.

Frequency Band	Antenna type and antenna number	Internal Identification	Maximum antenna gain
2.4GHz	WLAN Antenna	Antenna 0	2.78dBi
		Antenna 1	2.86dBi
5GHz	WLAN Antenna	Antenna 2	5.37dBi

#### 4. Estimation Result

##### 4.1 Conducted Power Results

##### *2.4GHz WIFI*

Antenna	Mode	Frequency(MHz)	Peak Conducted Output Power (dBm)
Antenna 0	IEEE802.11b	2412	14.53
		2437	13.67
		2462	13.03
Antenna 1		2412	10.63
		2437	11.65
		2462	12.72
Antenna 0	IEEE802.11g	2412	26.14
		2437	25.26
		2462	24.07
Antenna 1		2412	24.46
		2437	25.37
		2462	24.81
Antenna 0	IEEE802.11n HT20	2412	23.95
		2437	23.68
		2462	22.88
Antenna 1		2412	20.59
		2437	22.10
		2462	22.60
Antenna 0	IEEE802.11n HT40	2422	21.45
		2437	21.28
		2452	21.20
Antenna 1		2422	18.40
		2437	18.92
		2452	19.61



**5GHz WIFI**

<b>Antenna</b>	<b>Mode</b>	<b>Frequency(MHz)</b>	<b>AVGConducted Output Power (dBm)</b>
Antenna 2	IEEE 802.11a	5180	11.52
		5200	11.97
		5240	12.79
		5745	7.01
		5785	9.35
		5825	9.74
Antenna 2	IEEE 802.11n HT20	5180	10.76
		5200	11.29
		5240	12.19
		5745	7.69
		5785	9.97
		5825	10.57
Antenna 2	IEEE 802.11n HT40	5190	11.01
		5230	13.00
		5755	8.11
		5795	9.62
Antenna 2	IEEE 802.11ac 80	5210	7.83
		5775	8.99

**4.2 Manufacturing tolerance****2.4GHz WIFI**

<b>IEEE 802.11b (Peak)</b>						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	14.0	13.0	13.0	10.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

<b>IEEE 802.11 g (Peak)</b>						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	26.0	25.0	24.0	24.0	25.0	24.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

<b>IEEE 802.11 n HT20 (Peak)</b>						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	23.0	23.0	22.0	20.0	22.0	22.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

<b>IEEE 802.11 n HT40 (Peak)</b>						
Frequency (MHz)	Antenna 0			Antenna 1		
	2422	2437	2452	2422	2437	2452
Target (dBm)	21.0	21.0	21.0	18.0	18.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0



**5GHz WIFI**

<b>IEEE 802.11 a (AVG)</b>						
Frequency (MHz)	Antenna 2			Antenna 2		
		5180	5200	5240	5745	5785
Target (dBm)	11.0	11.0	12.0	7.0	9.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0

<b>IEEE 802.11n HT20(AVG)</b>						
Frequency (MHz)	Antenna 2			Antenna 2		
		5180	5200	5240	5745	5785
Target (dBm)	10.0	11.0	12.0	7.0	9.0	10.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0

<b>IEEE 802.11n HT40( AVG)</b>						
Frequency (MHz)	Antenna 2			Antenna 2		
		5190	---	5230	5755	---
Target (dBm)	11.0	---	13.0	8.0	---	9.0
Tolerance ±(dB)	1.0	---	1.0	1.0	---	1.0

<b>IEEE 802.11ac 80(AVG)</b>			
Frequency (MHz)	Antenna 2		
		5210	---
Target (dBm)	7.0	---	8.0
Tolerance ±(dB)	1.0	---	1.0

### 4.3 Measurement Results

#### 4.3.1 Standalone MPE

##### 2.4GWLAN

###### Antenna 0

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	(dBm)	(mW)					
IEEE 802.11 b	15	31.6228	2.78	1.8967	100%	0.0119	1.0000
IEEE 802.11 g	27	501.1872	2.78	1.8967	100%	0.1892	1.0000
IEEE 802.11 n HT20	24	251.1886	2.78	1.8967	100%	0.0948	1.0000
IEEE 802.11 n HT40	22	158.4893	2.78	1.8967	100%	0.0598	1.0000

###### Antenna 1

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	(dBm)	(mW)					
IEEE 802.11 b	13	19.9526	2.86	1.8967	100%	0.0075	1.0000
IEEE 802.11 g	26	398.1072	2.86	1.8967	100%	0.1503	1.0000
IEEE 802.11 n HT20	23	199.5262	2.86	1.8967	100%	0.0753	1.0000
IEEE 802.11 n HT40	20	100.0000	2.86	1.8967	100%	0.0378	1.0000

##### 5GWLAN

###### Antenna 2

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	(dBm)	(mW)					
IEEE 802.11 a	13.0	19.9526	5.37	3.4435	100%	0.0137	1.0000
IEEE 802.11 n HT20	13.0	19.9526	5.37	3.4435	100%	0.0137	1.0000
IEEE 802.11 n HT40	14.0	25.1189	5.37	3.4435	100%	0.0172	1.0000
IEEE 802.11 ac 80	9.0	7.9433	5.37	3.4435	100%	0.0054	1.0000

**Remark:**

1. Maximum average power including tune-up tolerance;
2. MPE use distance is 20cm from manufacturer declaration of user manual.

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\Sigma$ of MPE ratios  $\leq$  1.0

**Antenna 0 and Antenna 1 for 2.4GWLAN**

Mode	MPE Ratio Antenna 0	MPE Ratio Antenna 1	$\Sigma$ MPEratios	Limit	Results
IEEE 802.11b	0.0119	0.0075	N/A	1.000	Pass
IEEE 802.11g	0.1892	0.1503	N/A	1.000	Pass
IEEE 802.11n HT20	0.0948	0.0753	0.1701	1.000	Pass
IEEE 802.11n HT40	0.0598	0.0378	0.0976	1.000	Pass

**Antenna 2for 5GWLAN**

Mode	MPE Ratio Antenna 2	$\Sigma$ MPEratios	Limit	Results
IEEE 802.11a	0.0137	N/A	1.000	Pass
IEEE 802.11n HT20	0.0137	0.0137	1.000	Pass
IEEE 802.11n HT40	0.0172	0.0172	1.000	Pass
IEEE 802.11ac 80	0.0054	0.0054	1.000	Pass

**Maximum MPE Radios**

Maximum MPERatio <sub>2.4GHzWLAN</sub>	Maximum MPERatio <sub>5GHzWLAN</sub>	Maximum MPE Ratio Celluar	Maximum MPE Ratio BT/ZigBee	$\Sigma$ MPEratios	Limit	Results
0.1701	0.0172	0.4562	0.1566	0.8	1.000	Pass

**Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- END OF REPORT -----