

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Mode	Frequency (MHz)	Antenna Gain		Max Tune Up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G Wi-Fi	2412-2472	6.93	4.93	21.0	125.89	20	0.124	1.0
BLE	2402-2480	-0.042	0.99	9.0	7.94	20	0.002	1.0
5G Wi-Fi	5150-5250	8.56	7.18	20.0	100.0	20	0.143	1.0
5G Wi-Fi	5725-5850	7.53	5.66	20.0	100.0	20	0.113	1.0
WCDMA Band 2	1850-1910	2.71	1.87	25.0	316.23	20	0.118	1.0
WCDMA Band 4	1710-1755	1.25	1.33	25.0	316.23	20	0.084	1.0
WCDMA Band 5	824-849	0.19	1.04	25.0	316.23	20	0.065	0.55
LTE Band 2	1850-1910	2.71	1.87	25.0	316.23	20	0.118	1.0
LTE Band 4	1710-1755	1.25	1.33	25.0	316.23	20	0.084	1.0
LTE Band 5	824-849	0.19	1.04	25.0	316.23	20	0.065	0.55
LTE Band 12	699-716	-1.55	0.70	25.0	316.23	20	0.044	0.466
LTE Band 13	777-787	-0.50	0.89	25.0	316.23	20	0.056	0.518
LTE Band 14	788-798	-0.50	0.89	25.0	316.23	20	0.056	0.525
LTE Band 66	1710-1780	1.25	1.33	25.0	316.23	20	0.084	1.0
LTE Band 71	663-698	-2.15	0.61	25.0	316.23	20	0.038	0.442

Note:

1. the tune up conducted power was declared by the applicant
2. the BLE, Wi-Fi function can transmit at the same time with the LTE.
3. For the Wi-Fi, as it can support the beam-forming function, so the antenna gain should add the $10\lg 2$.
4. Please refer to the MPE report of the FCC ID: XMR201808EC25AF for the LTE output power.

So the worst simultaneous transmitting consideration:

The ratio = $MPE_{2.4GWi-Fi}/limit + MPE_{5GWi-Fi}/limit + MPE_{Band\ 5}/limit = 0.124/1.0 + 0.143/1.0 + 0.065/0.55 = 0.385 < 1.0$

so simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance