

RF EXPOSURE EVALUATION METHOD**FCC ID: 2AFJH-ALPHA1S****SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT 3.0

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	-4.16	0.384
CH39	2441	-4.02	0.396
CH78	2480	-4.31	0.371
2Mbps			
CH00	2402	-4.10	0.389
CH39	2441	-3.94	0.404
CH78	2480	-4.21	0.379
3Mbps			
CH00	2402	-4.08	0.391
CH39	2441	-3.93	0.405
CH78	2480	-4.25	0.376

BT 4.0

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(PK)
		(dBm)	mW
CH00	2402	3.02	2.004
CH19	2440	3.43	2.203
CH39	2480	2.98	1.986

Remark: The best case gain of the antenna is 1.84dBi.

1.84 dBi logarithmic terms convert to numeric result is nearly 1.53

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

BT 3.0

Test Channel	Range	tune up max power (dBm)	$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$	$[\sqrt{f(\text{GHz})}]$	Result	Limit
1Mbps						
CH00	-5~-3	-3	0.501	5	2.402	0.155
CH39	-5~-3	-3	0.501	5	2.441	0.157
CH78	-5~-3	-3	0.501	5	2.480	0.158
2Mbps						
CH00	-5~-3	-3	0.501	5	2.402	0.155
CH39	-5~-3	-3	0.501	5	2.441	0.157
CH78	-5~-3	-3	0.501	5	2.480	0.158
3Mbps						
CH00	-5~-3	-3	0.501	5	2.402	0.155
CH39	-5~-3	-3	0.501	5	2.441	0.157
CH78	-5~-3	-3	0.501	5	2.480	0.158

BT 4.0

Test Channel	Range	tune up max power (dBm)	$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$	$[\sqrt{f(\text{GHz})}]$	Result	Limit
CH00	2~4	4	2.512	5	2.402	0.779
CH39	2~4	4	2.512	5	2.441	0.785
CH78	2~4	4	2.512	5	2.480	0.791

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.