

RF Exposure Evaluation Report

Product : Wireless Speaker
Trade mark : MINISO
Model/Type reference : M15
Serial Number : N/A
Report Number : EED32L00362202
FCC ID : 2AFJVM15
Date of Issue : Dec. 30, 2019
Test Standards : 47 CFR Part 1.1307(2015)
47 CFR Part 1.1310(2015)
KDB447498D01v06
Test result : PASS

Prepared for:

Shenzhen HuaZeng Technology Co., Ltd
8F, 6 Building, the 3rd Industrial Zone, TangWei Community,
GongMing Street, GuangMing New District, Shenzhen, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested By:

mark.chen.

Compiled by:

Sunlight Sun

Mark Chen

Sunlight Sun

Reviewed by:

Ware Xin

Approved by:

Kevin Yang

Ware Xin

Kevin Yang

Date:

Dec. 30, 2019

Check No.: 3096342601



2 Version

Version No.	Date	Description
00	Dec. 30, 2019	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	5
4.4 TEST LOCATION.....	6
4.5 DEVIATION FROM STANDARDS.....	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION.....	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	8
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	9

4 General Information

4.1 Client Information

Applicant:	Shenzhen HuaZeng Technology Co., Ltd
Address of Applicant:	8F, 6 Building, the 3rd Industrial Zone, TangWei Community, GongMing Street, GuangMing New District, Shenzhen, China
Manufacturer:	Shenzhen HuaZeng Technology Co., Ltd
Address of Manufacturer:	8F, 6 Building, the 3rd Industrial Zone, TangWei Community, GongMing Street, GuangMing New District, Shenzhen, China
Factory:	Shenzhen HuaZeng Technology Co., Ltd
Address of Factory:	8F, 6 Building, the 3rd Industrial Zone, TangWei Community, GongMing Street, GuangMing New District, Shenzhen, China

4.2 General Description of EUT

Product Name:	Wireless Speaker
Model No.(EUT):	M15
Trade Mark:	MINISO
EUT Supports Radios application	BT 5.0+EDR Single mode, 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz to 2480MHz		
Modulation Type:	GFSK, $\pi/4$ DQPSK		
Number of Channels:	79		
Test Power Grade:	GFSK:10; $\pi/4$ DQPSK:7		
Test Software of EUT:	FCCAssist2.4		
Antenna Type:	PCB antenna		
Antenna Specification	Bluetooth :	Antenna Gain :	-0.58 dBi (Numeric gain: 0.87)
Maximum tune up power	Bluetooth:	-1.00 dBm	(0.794 mW)
Power Supply:	Battery	18650 Li-ion Battery: DC 3.7V 1200mAh, Charge: DC 5V/500mA	
Sample Received Date:	Nov. 29, 2019		
Sample tested Date:	Nov. 29, 2019 to Dec. 18, 2019		
The tested sample(s) and the sample information are provided by the client.			

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
0	2402	0.928	0.87	20	0.0002	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No.EED32L00362201 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.