

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a BLUETOOTH SPEAKER with Bluetooth function. The EUT was powered by DC 3.7V lithium battery and charged by DC 5V USB port. It has one passive NFC. For more detail information pls. refer to the user manual.

Modulation Type: GFSK,  $\pi/4$ DQPSK, 8DPSK.

Bluetooth Version: 4.1+EDR.

Antenna Type: Integral antenna.

Antenna Gain: 1dBi.

The nominal conducted output power specified: 5.2dBm (+/-3dB).

The nominal radiated output power (e.i.r.p) specified: 6.2dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 104.4dB $\mu$ V/m at 3m in the frequency 2480MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = 9.17dBm  
which is within the production variation.

The minimum peak radiated emission for the EUT is 101.3dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = 6.07dBm  
which is within the production variation.

The maximum conducted output power specified is 8.2dBm = 6.6 mW

The source- based time-averaging conducted output power  
= 6.6 \* Duty Cycle mW (where Duty Cycle < 100%) < 6.6mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.480) mW  
= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.