

Human Exposure Report


Application No.: SZEM1903011626CR
Applicant: Spigen Korea Co., Ltd.
Address of Applicant: Spigen HQ-A, 446, Bongeunsa-ro, Gangnam-gu, Seoul, 06153, South Korea.
Manufacturer: Shenzhen Wireless Technology Co., Ltd.
Address of Manufacturer: Floor 2, 3 building A4, Fangxing Science and Technology park, NO.13 Baonan Road, Longgang street, Longgang District
Factory: SHENZHEN POWERQI TECHNOLOGY CO., LTD
Address of Factory: Floor 2, 3 building A4, Fangxing Science and Technology park, NO.13 Baonan Road, Longgang street, Longgang District

Equipment Under Test (EUT):

EUT Name: Fast Wireless Charger
Model No.: F301W
Trade Mark: Spigen
FCC ID: 2AFKNF301WR1
Standards: 47 CFR PART 1, Subpart I, Section 1.1310
Date of Receipt: 2019-03-12
Date of Test: 2019-03-13 to 2019-04-04
Date of Issue: 2019-04-08

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above



Keny Xu
 EMC Laboratory Manager



2 Contents

1	COVER PAGE	1
2	CONTENTS	2
3	GENERAL INFORMATION	3
3.1	DETAILS OF E.U.T.	3
3.2	DESCRIPTION OF SUPPORT UNITS	3
3.3	TEST LOCATION.....	4
3.4	TEST FACILITY.....	4
3.5	DEVIATION FROM STANDARDS	4
3.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	4
4	EQUIPMENTS USED DURING TEST	5
5	TEST RESULTS	6
5.1	RF EXPOSURE TEST	6
5.1.1	<i>E.U.T. Operation</i>	6
5.1.2	<i>Measurement Data</i>	7
6	PHOTOGRAPHS	8
6.1	TEST SETUP PHOTOS	8



3 General Information

3.1 Details of E.U.T.

Power supply:	Input: DC 9V, 1.67A, Output: 5W, 7.5W, 10W
Cable:	USB Cable: 150cm, Unshielded
Antenna Type:	Loop Antenna
Modulation Type:	Load Modulation
Operation Frequency:	112kHz to 205kHz
Remark:	This device has been tested the worst status of full load and the device has been tested with load at zero charge, intermediate charge, and full charge.

3.2 Description of Support Units

The EUT has been tested as an independent unit.



3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.



4 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Due date
1	Shielding Room	SAEMC	MSR733	SEM001-09	2020-05-09
2	Electric and Magnetic Field Analyzer	Narda	EHP-50F	EMC092	2019-05-06



5 Test Results

5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C Humidity: 52% RH Atmospheric Pressure: 1015 mbar

EUT Operation:

This device has been tested the worst status of full load and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



5.1.2 Measurement Data

Output Voltage=DC 5V; The max output power =10W;Calculation of resistor value=5Ω

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
147.2 kHz	15	Side 1	0.0231	0.815
		Side 2	0.0257	0.815
		Side 3	0.0245	0.815
		Side 4	0.0285	0.815
		Top	0.0274	0.815

Mobile phone has been charge at zero charge, intermediate charge, and full charge.

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	15	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
147.2 kHz	15	Side 1	0.0674	0.0435	0.0297	0.815
		Side 2	0.0757	0.0484	0.0144	0.815
		Side 3	0.0658	0.0361	0.0115	0.815
		Side 4	0.0629	0.0402	0.0238	0.815
		Top	0.0728	0.0412	0.0198	0.815





6 Photographs

6.1 Test setup photos

Please refer to RF exposure setup.

- End of the Report -

