SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

FCC REPORT

Application No:	SZEM1606004987CR
Applicant:	Embest Technology Co.,Ltd
Manufacturer:	Embest Technology Co.,Ltd
Factory:	Embest Technology Co.,Ltd
Product Name:	SBC-EC8800
Model No.(EUT):	SBC-EC8800
FCC ID:	2AFLY-SBC-EC8800
Standards:	47 CFR Part 15, Subpart C (2015)
Date of Receipt:	2016-06-30
Date of Test:	2016-07-11 to 2016-07-22
Date of Issue:	2016-08-04
Test Result:	**PASS ***

. * In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

2 Version

Revision Record				
Version	**Chapter**	**Date**	**Modifier**	**Remark**
00		2016-08-04		Original

Authorized for issue by:				
Tested By		Hank yan.		2016-07-22
		(Hank Yan) /Project Engineer		**Date**
Checked By		Eric Fu		2016-08-04
		(Eric Fu) /Reviewer		**Date**

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

4 Contents

Page

5 General Information

5.1 Client Information

Applicant:	Embest Technology Co.,Ltd
Address of Applicant:	Tower B 4/F, Shanshui Building, Nanshan Yungu Innovation Industry Park, Liuxian Ave. No.1183, Nanshan District, Shenzhen, Guangdong, China
Manufacturer:	Embest Technology Co.,Ltd
Address of Manufacturer:	Tower B 4/F, Shanshui Building, Nanshan Yungu Innovation Industry Park, Liuxian Ave. No.1183, Nanshan District, Shenzhen, Guangdong, China
Factory:	Embest Technology Co.,Ltd
Address of Factory:	Tower B 4/F, Shanshui Building, Nanshan Yungu Innovation Industry Park, Liuxian Ave. No.1183, Nanshan District, Shenzhen, Guangdong, China

5.2 General Description of EUT

Product Name:	SBC-EC8800
Model No.:	SBC-EC8800
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Mobile Product
Antenna Type:	Integral
Antenna Gain:	0dBi
Power Supply:	DC 5V
Test Voltage:	DC 5V

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422MHz	6	2437MHz	9	2452MHz
4	2427MHz	7	2442MHz		
5	2432MHz	8	2447MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

5.3 Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal. date (yyyy-mm-dd)**	**Cal.Due date (yyyy-mm-dd)**
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2015-10-09	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2015-08-30	2016-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2015-08-30	2016-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2015-08-30	2016-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09

RF connected test						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal. date (yyyy-mm-dd)**	**Cal.Due date (yyyy-mm-dd)**
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2015-10-17	2016-10-17
3	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
4	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2015-10-09	2016-10-09

RE in Chamber						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal. date (yyyy-mm-dd)**	**Cal.Due date (yyyy-mm-dd)**
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2015-09-16	2016-09-16
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2016-04-25	2017-04-25
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13

RE in Chamber						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal. date (yyyy-mm-dd)**	**Cal.Due date (yyyy-mm-dd)**
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2015-10-09	2016-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2015-10-09	2016-10-09
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The product uses a dedicated antenna connector (RP-SMA). The best case gain of the antenna is 0dBi.	

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	150kHz to 30MHz
Limit:	Frequency range (MHz) / Limit (dBuV): Quasi-peak / Average 0.15-0.5: 66 to 56* / 56 to 46* 0.5-5: 56 / 46 5-30: 60 / 50 * Decreases with the logarithm of the frequency.
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.

Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:



Site : Shielding Room
Condition : CE LINE
Job No. : 4987CR
Test Mode : TX mode

		Freq	Cable Loss	LISN Factor	Read Level	Level	Over Limit	Remark
		MHz	dB	dB	dBuV	dBuV	dB	
1		0.18056	0.02	9.60	41.33	50.95	-13.51	QP
2		0.18056	0.02	9.60	30.47	40.09	-14.37	AVERAGE
3		0.22083	0.02	9.60	37.44	47.06	-15.73	QP
4		0.22083	0.02	9.60	26.81	36.43	-16.35	AVERAGE
5		0.25078	0.02	9.60	34.47	44.09	-17.64	QP
6		0.25078	0.02	9.60	24.13	33.75	-17.98	AVERAGE
7		0.28478	0.02	9.59	32.62	42.24	-18.44	QP
8		0.28478	0.02	9.59	20.84	30.45	-20.22	AVERAGE
9		0.33740	0.02	9.59	31.58	41.19	-18.08	QP
10		0.33740	0.02	9.59	22.83	32.44	-16.82	AVERAGE
11	@	0.62383	0.02	9.61	38.39	48.03	-7.97	QP
12		0.62383	0.02	9.61	27.84	37.48	-8.52	AVERAGE

Neutral Line:



Site : Shielding Room
Condition : CE NEUTRAL
Job No. : 4987CR
Test Mode : TX mode

	Freq	Cable Loss	LISN Factor	Read Level	Level	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.15160	0.02	9.62	44.38	54.02	-11.90	QP
2	0.15160	0.02	9.62	31.17	40.80	-15.11	AVERAGE
3	0.18443	0.02	9.61	40.39	50.02	-14.26	QP
4	0.18443	0.02	9.61	28.35	37.98	-16.31	AVERAGE
5	0.21851	0.02	9.62	36.99	46.63	-16.25	QP
6	0.21851	0.02	9.62	25.97	35.61	-17.27	AVERAGE
7	0.25345	0.02	9.61	34.01	43.64	-18.00	QP
8	0.25345	0.02	9.61	23.33	32.96	-18.68	AVERAGE
9	0.29711	0.02	9.62	32.71	42.35	-17.97	QP
10	0.29711	0.02	9.62	22.52	32.16	-18.16	AVERAGE
11 @	0.63048	0.02	9.63	38.58	48.23	-7.77	QP
12 @	0.63048	0.02	9.63	28.88	38.53	-7.47	AVERAGE

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:

2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 :2013 Section 11.9.1
Test Setup:	 *Remark:* *Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.*
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40)
Limit:	30dBm
Test Results:	Pass

Pre-scan under all rate at lowest channel 1

Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	14.62	14.49	14.39	14.25				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	19.96	19.81	19.73	19.64	19.55	19.49	19.44	19.31
Mode	802.11n(HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	20.03	19.98	19.84	19.71	19.63	19.55	19.40	19.25
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power (dBm)	17.50	17.36	17.24	17.12	17.00	16.95	16.86	16.77

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).

Measurement Data

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	14.62	30.00	Pass
Middle	15.66	30.00	Pass
Highest	15.91	30.00	Pass
802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	19.96	30.00	Pass
Middle	20.50	30.00	Pass
Highest	20.79	30.00	Pass
802.11n(HT20)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	20.03	30.00	Pass
Middle	20.56	30.00	Pass
Highest	20.87	30.00	Pass
802.11n(HT40)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	17.50	30.00	Pass
Middle	17.67	30.00	Pass
Highest	17.85	30.00	Pass

Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest



Test mode:	802.11b	Test channel:	Middle



Test mode:	802.11b	Test channel:	Highest



Test mode:	802.11g	Test channel:	Lowest



Test mode:	802.11g	Test channel:	Middle



Test mode:	802.11g	Test channel:	Highest



Test mode:	802.11n(HT20)	Test channel:	Lowest



Test mode:	802.11n(HT20)	Test channel:	Middle



Test mode:	802.11n(HT20)	Test channel:	Highest



Test mode:	802.11n(HT40)	Test channel:	Lowest



Test mode:	802.11n(HT40)	Test channel:	Middle



Test mode:	802.11n(HT40)	Test channel:	Highest



6.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40)
Limit:	≥ 500 kHz
Test Results:	Pass

Measurement Data

802.11b mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.11	≥500	Pass
Middle	10.11	≥500	Pass
Highest	10.08	≥500	Pass
802.11g mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	15.21	≥500	Pass
Middle	15.15	≥500	Pass
Highest	15.15	≥500	Pass
802.11n(HT20) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	15.18	≥500	Pass
Middle	15.18	≥500	Pass
Highest	15.15	≥500	Pass
802.11n(HT40)mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	35.16	≥500	Pass
Middle	35.16	≥500	Pass
Highest	33.96	≥500	Pass

Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest



Test mode:	802.11b	Test channel:	Middle



Test mode:	802.11b	Test channel:	Highest



Test mode:	802.11g	Test channel:	Lowest



Test mode:	802.11g	Test channel:	Middle



Test mode:	802.11g	Test channel:	Highest



Test mode:	802.11n(HT20)	Test channel:	Lowest



Test mode:	802.11n(HT20)	Test channel:	Middle



Test mode:	802.11n(HT20)	Test channel:	Highest



Test mode:	802.11n(HT40)	Test channel:	Lowest



Test mode:	802.11n(HT40)	Test channel:	Middle



Test mode:	802.11n(HT40)	Test channel:	Highest



6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	 *Remark:* *Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.*
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40)
Limit:	≤8.00dBm/3kHz
Test Results:	Pass

Measurement Data

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-11.81	≤8.00	Pass
Middle	-9.37	≤8.00	Pass
Highest	-11.03	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-13.39	≤8.00	Pass
Middle	-11.57	≤8.00	Pass
Highest	-12.94	≤8.00	Pass
802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-12.20	≤8.00	Pass
Middle	-12.18	≤8.00	Pass
Highest	-12.32	≤8.00	Pass
802.11n(HT40) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-18.00	≤8.00	Pass
Middle	-19.14	≤8.00	Pass
Highest	-18.04	≤8.00	Pass

Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest



Test mode:	802.11b	Test channel:	Middle



Test mode:	802.11b	Test channel:	Highest



Test mode:	802.11g	Test channel:	Lowest



Test mode:	802.11g	Test channel:	Middle



Test mode:	802.11g	Test channel:	Highest



Test mode:	802.11n(HT20)	Test channel:	Lowest



Test mode:	802.11n(HT20)	Test channel:	Middle



Test mode:	802.11n(HT20)	Test channel:	Highest



Test mode:	802.11n(HT40)	Test channel:	Lowest



Test mode:	802.11n(HT40)	Test channel:	Middle



Test mode:	802.11n(HT40)	Test channel:	Highest



6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13
Test Setup:	 *Remark:* *Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.*
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest



Test mode:	802.11b	Test channel:	Highest



Test mode:	802.11g	Test channel:	Lowest



Test mode:	802.11g	Test channel:	Highest



Test mode:	802.11n(HT20)	Test channel:	Lowest



Test mode:	802.11n(HT20)	Test channel:	Highest



Test mode:	802.11n(HT40)	Test channel:	Lowest



Test mode:	802.11n(HT40)	Test channel:	Highest



6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	 *Remark:* *Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.*
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest







Test mode:	802.11b	Test channel:	Middle







Test mode:	802.11b	Test channel:	Highest







Test mode:	802.11g	Test channel:	Lowest







Test mode:	802.11g	Test channel:	Middle







Test mode:	802.11g	Test channel:	Highest







Test mode:	802.11n(HT20)	Test channel:	Lowest







Test mode:	802.11n(HT20)	Test channel:	Middle







Test mode:	802.11n(HT20)	Test channel:	Highest







Test mode:	802.11n(HT40)	Test channel:	Lowest







Test mode:	802.11n(HT40)	Test channel:	Middle







Test mode:	802.11n(HT40)	Test channel:	Highest







Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.

6.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10 :2013 Section 11.12
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

6.8.1 Radiated emission below 1GHz

30MHz~1GHz（QP）		
Test mode:	Transmitting	Vertical



Condition: 10m HORIZONTAL
Job No. : 4987CR
Test mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	250.30	7.85	11.25	32.64	32.61	19.07	35.60	-16.53
2	275.16	7.98	12.01	32.62	38.84	26.21	35.60	-9.39
3	325.60	8.13	13.38	32.60	37.07	25.98	35.60	-9.62
4	350.48	8.25	13.85	32.60	36.92	26.42	35.60	-9.18
5	451.14	8.43	16.19	32.60	32.62	24.64	35.60	-10.96
6 pp	734.49	9.20	20.58	32.60	29.49	26.67	35.60	-8.93

Test mode:	Transmitting	Horizontal



Condition: 10m HORIZONTAL
Job No. : 4987CR
Test mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	38.08	6.76	13.07	32.98	29.02	15.87	29.50	-13.63
2	275.16	7.98	12.01	32.62	37.47	24.84	35.60	-10.76
3	325.60	8.13	13.38	32.60	36.86	25.77	35.60	-9.83
4	350.48	8.25	13.85	32.60	36.38	25.88	35.60	-9.72
5	451.14	8.43	16.19	32.60	32.05	24.07	35.60	-11.53
6 pp	916.07	9.50	22.44	32.50	29.14	28.58	35.60	-7.02

6.8.2 Transmitter emission above 1GHz

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3615.625	32.54	7.67	38.52	40.99	42.68	74.00	-31.32	Vertical
4824.000	34.19	8.90	39.04	43.20	47.25	74.00	-26.75	Vertical
6283.882	34.93	10.20	38.82	41.51	47.82	74.00	-26.18	Vertical
7236.000	36.40	10.69	38.15	42.13	51.07	74.00	-22.93	Vertical
9648.000	37.53	12.52	36.97	38.02	51.10	74.00	-22.90	Vertical
11791.720	38.39	14.34	38.10	35.79	50.42	74.00	-23.58	Vertical
3368.157	31.98	7.60	38.40	42.32	43.50	74.00	-30.50	Horizontal
4824.000	34.19	8.90	39.04	44.88	48.93	74.00	-25.07	Horizontal
6131.199	34.81	10.39	38.92	43.50	49.78	74.00	-24.22	Horizontal
7236.000	36.40	10.69	38.15	42.15	51.09	74.00	-22.91	Horizontal
9648.000	37.53	12.52	36.97	38.56	51.64	74.00	-22.36	Horizontal
11877.340	38.48	14.43	38.18	36.46	51.19	74.00	-22.81	Horizontal

Test mode:	802.11b	Test channel:	Middle	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3467.050	32.14	7.62	38.45	43.08	44.39	74.00	-29.61	Vertical
4874.000	34.28	8.97	39.05	44.52	48.72	74.00	-25.28	Vertical
5828.433	34.60	10.08	39.02	43.98	49.64	74.00	-24.36	Vertical
7311.000	36.37	10.72	38.07	43.21	52.23	74.00	-21.77	Vertical
9748.000	37.55	12.58	36.92	38.51	51.72	74.00	-22.28	Vertical
11791.720	38.39	14.34	38.10	35.79	50.42	74.00	-23.58	Vertical
3417.246	32.06	7.61	38.43	41.80	43.04	74.00	-30.96	Horizontal
4874.000	34.28	8.97	39.05	44.20	48.40	74.00	-25.60	Horizontal
6016.949	34.71	10.54	38.99	42.45	48.71	74.00	-25.29	Horizontal
7311.000	36.37	10.72	38.07	42.51	51.53	74.00	-22.47	Horizontal
9748.000	37.55	12.58	36.92	38.60	51.81	74.00	-22.19	Horizontal
12015.620	38.61	14.55	38.32	35.72	50.56	74.00	-23.44	Horizontal

Test mode:	802.11b	Test channel:	Highest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3522.674	32.27	7.64	38.48	44.45	45.88	74.00	-28.12	Vertical
4924.000	34.37	9.04	39.07	45.12	49.46	74.00	-24.54	Vertical
6060.637	34.75	10.48	38.96	42.38	48.65	74.00	-25.35	Vertical
7386.000	36.34	10.75	38.00	43.21	52.30	74.00	-21.70	Vertical
9848.000	37.57	12.63	36.87	38.56	51.89	74.00	-22.11	Vertical
12085.370	38.65	14.49	38.39	36.54	51.29	74.00	-22.71	Vertical
3599.965	32.50	7.67	38.52	42.74	44.39	74.00	-29.61	Horizontal
4924.000	34.37	9.04	39.07	45.62	49.96	74.00	-24.04	Horizontal
6283.882	34.93	10.20	38.82	42.72	49.03	74.00	-24.97	Horizontal
7386.000	36.34	10.75	38.00	43.21	52.30	74.00	-21.70	Horizontal
9848.000	37.57	12.63	36.87	38.11	51.44	74.00	-22.56	Horizontal
11860.170	38.46	14.41	38.17	36.83	51.53	74.00	-22.47	Horizontal

Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3387.708	32.01	7.60	38.41	41.39	42.59	74.00	-31.41	Vertical
4824.000	34.19	8.90	39.04	43.57	47.62	74.00	-26.38	Vertical
5820.005	34.59	10.06	39.02	42.32	47.95	74.00	-26.05	Vertical
7236.000	36.40	10.69	38.15	42.56	51.50	74.00	-22.50	Vertical
9648.000	37.53	12.52	36.97	37.51	50.59	74.00	-23.41	Vertical
12243.770	38.75	14.36	38.55	35.33	49.89	74.00	-24.11	Vertical
3262.630	31.79	7.58	38.35	44.46	45.48	74.00	-28.52	Horizontal
4824.000	34.19	8.90	39.04	43.11	47.16	74.00	-26.84	Horizontal
5973.576	34.68	10.49	39.00	42.82	48.99	74.00	-25.01	Horizontal
7236.000	36.40	10.69	38.15	41.10	50.04	74.00	-23.96	Horizontal
9648.000	37.53	12.52	36.97	38.05	51.13	74.00	-22.87	Horizontal
12085.370	38.65	14.49	38.39	36.05	50.80	74.00	-23.20	Horizontal

Test mode:	802.11g	Test channel:	Middle	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3765.116	32.97	7.73	38.59	42.46	44.57	74.00	-29.43	Vertical
4874.000	34.28	8.97	39.05	43.49	47.69	74.00	-26.31	Vertical
6008.249	34.71	10.55	38.99	42.12	48.39	74.00	-25.61	Vertical
7311.000	36.37	10.72	38.07	41.21	50.23	74.00	-23.77	Vertical
9748.000	37.55	12.58	36.92	37.58	50.79	74.00	-23.21	Vertical
11455.380	38.07	13.97	37.77	36.24	50.51	74.00	-23.49	Vertical
3477.098	32.16	7.62	38.46	41.68	43.00	74.00	-31.00	Horizontal
4874.000	34.28	8.97	39.05	44.50	48.70	74.00	-25.30	Horizontal
6202.582	34.87	10.30	38.87	41.69	47.99	74.00	-26.01	Horizontal
7311.000	36.37	10.72	38.07	42.88	51.90	74.00	-22.10	Horizontal
9748.000	37.55	12.58	36.92	37.43	50.64	74.00	-23.36	Horizontal
12243.770	38.75	14.36	38.55	35.29	49.85	74.00	-24.15	Horizontal

Test mode:	802.11g	Test channel:	Highest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3392.613	32.02	7.61	38.41	41.26	42.48	74.00	-31.52	Vertical
4924.000	34.37	9.04	39.07	44.69	49.03	74.00	-24.97	Vertical
5964.939	34.68	10.46	39.00	41.93	48.07	74.00	-25.93	Vertical
7386.000	36.34	10.75	38.00	43.09	52.18	74.00	-21.82	Vertical
9848.000	37.57	12.63	36.87	37.42	50.75	74.00	-23.25	Vertical
12208.390	38.73	14.39	38.52	34.47	49.07	74.00	-24.93	Vertical
3776.027	33.00	7.73	38.60	42.08	44.21	74.00	-29.79	Horizontal
4924.000	34.37	9.04	39.07	44.10	48.44	74.00	-25.56	Horizontal
6008.249	34.71	10.55	38.99	42.37	48.64	74.00	-25.36	Horizontal
7386.000	36.34	10.75	38.00	42.80	51.89	74.00	-22.11	Horizontal
9848.000	37.57	12.63	36.87	38.01	51.34	74.00	-22.66	Horizontal
12085.370	38.65	14.49	38.39	37.16	51.91	74.00	-22.09	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3776.027	33.00	7.73	38.60	42.97	45.10	74.00	-28.90	Vertical
4824.000	34.19	8.90	39.04	46.11	50.16	74.00	-23.84	Vertical
5956.314	34.67	10.44	39.00	43.04	49.15	74.00	-24.85	Vertical
7236.000	36.40	10.69	38.15	42.51	51.45	74.00	-22.55	Vertical
9648.000	37.53	12.52	36.97	36.91	49.99	74.00	-24.01	Vertical
12530.530	38.89	14.24	38.84	36.65	50.94	74.00	-23.06	Vertical
3770.567	32.98	7.73	38.60	42.75	44.86	74.00	-29.14	Horizontal
4824.000	34.19	8.90	39.04	44.74	48.79	74.00	-25.21	Horizontal
6087.002	34.77	10.45	38.94	43.34	49.62	74.00	-24.38	Horizontal
7236.000	36.40	10.69	38.15	42.11	51.05	74.00	-22.95	Horizontal
9648.000	37.53	12.52	36.97	37.66	50.74	74.00	-23.26	Horizontal
12033.020	38.62	14.53	38.33	36.13	50.95	74.00	-23.05	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3339.043	31.93	7.59	38.39	40.32	41.45	74.00	-32.55	Vertical
4874.000	34.28	8.97	39.05	44.01	48.21	74.00	-25.79	Vertical
5982.226	34.69	10.51	39.00	40.79	46.99	74.00	-27.01	Vertical
7311.000	36.37	10.72	38.07	42.08	51.10	74.00	-22.90	Vertical
9748.000	37.55	12.58	36.92	37.91	51.12	74.00	-22.88	Vertical
12033.020	38.62	14.53	38.33	36.38	51.20	74.00	-22.80	Vertical
3447.042	32.11	7.62	38.44	42.99	44.28	74.00	-29.72	Horizontal
4874.000	34.28	8.97	39.05	44.74	48.94	74.00	-25.06	Horizontal
6034.386	34.73	10.52	38.98	43.56	49.83	74.00	-24.17	Horizontal
7311.000	36.37	10.72	38.07	41.56	50.58	74.00	-23.42	Horizontal
9748.000	37.55	12.58	36.92	38.58	51.79	74.00	-22.21	Horizontal
11672.890	38.28	14.21	37.98	35.71	50.22	74.00	-23.78	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3497.281	32.20	7.63	38.47	42.96	44.32	74.00	-29.68	Vertical
4924.000	34.37	9.04	39.07	44.09	48.43	74.00	-25.57	Vertical
6113.481	34.79	10.41	38.93	42.21	48.48	74.00	-25.52	Vertical
7386.000	36.34	10.75	38.00	43.20	52.29	74.00	-21.71	Vertical
9848.000	37.57	12.63	36.87	38.51	51.84	74.00	-22.16	Vertical
11808.790	38.41	14.36	38.12	35.51	50.16	74.00	-23.84	Vertical
3477.098	32.16	7.62	38.46	42.72	44.04	74.00	-29.96	Horizontal
4924.000	34.37	9.04	39.07	44.73	49.07	74.00	-24.93	Horizontal
6202.582	34.87	10.30	38.87	42.56	48.86	74.00	-25.14	Horizontal
7386.000	36.34	10.75	38.00	42.52	51.61	74.00	-22.39	Horizontal
9848.000	37.57	12.63	36.87	38.65	51.98	74.00	-22.02	Horizontal
11588.750	38.19	14.12	37.90	36.96	51.37	74.00	-22.63	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3462.037	32.14	7.62	38.45	43.33	44.64	74.00	-29.36	Vertical
4844.000	34.23	8.92	39.04	44.61	48.72	74.00	-25.28	Vertical
5947.702	34.67	10.42	39.00	42.08	48.17	74.00	-25.83	Vertical
7266.000	36.39	10.70	38.12	41.61	50.58	74.00	-23.42	Vertical
9688.000	37.54	12.54	36.95	37.52	50.65	74.00	-23.35	Vertical
12137.940	38.68	14.45	38.44	37.29	51.98	74.00	-22.02	Vertical
3737.975	32.89	7.72	38.58	43.09	45.12	74.00	-28.88	Horizontal
4844.000	34.23	8.92	39.04	44.13	48.24	74.00	-25.76	Horizontal
5879.252	34.63	10.22	39.01	41.46	47.30	74.00	-26.70	Horizontal
7266.000	36.39	10.70	38.12	42.11	51.08	74.00	-22.92	Horizontal
9688.000	37.54	12.54	36.95	37.54	50.67	74.00	-23.33	Horizontal
12458.220	38.88	14.18	38.77	35.77	50.06	74.00	-23.94	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Middle	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3537.998	32.31	7.64	38.49	41.76	43.22	74.00	-30.78	Vertical
4874.000	34.28	8.97	39.05	45.10	49.30	74.00	-24.70	Vertical
7311.000	36.37	10.72	38.07	41.11	50.13	74.00	-23.87	Vertical
8841.537	36.41	11.81	37.32	40.45	51.35	74.00	-22.65	Vertical
9748.000	37.55	12.58	36.92	37.46	50.67	74.00	-23.33	Vertical
12512.420	38.90	14.19	38.82	37.64	51.91	74.00	-22.09	Vertical
3492.224	32.19	7.63	38.46	42.47	43.83	74.00	-30.17	Horizontal
4874.000	34.28	8.97	39.05	44.26	48.46	74.00	-25.54	Horizontal
6025.661	34.72	10.53	38.98	42.16	48.43	74.00	-25.57	Horizontal
7311.000	36.37	10.72	38.07	42.65	51.67	74.00	-22.33	Horizontal
9748.000	37.55	12.58	36.92	38.50	51.71	74.00	-22.29	Horizontal
11929.010	38.53	14.48	38.23	36.50	51.28	74.00	-22.72	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Polarization
3467.050	32.14	7.62	38.45	41.81	43.12	74.00	-30.88	Vertical
4904.000	34.33	9.01	39.07	44.02	48.29	74.00	-25.71	Vertical
6184.658	34.85	10.32	38.88	41.04	47.33	74.00	-26.67	Vertical
7356.000	36.36	10.74	38.03	41.76	50.83	74.00	-23.17	Vertical
9808.000	37.56	12.61	36.89	38.51	51.79	74.00	-22.21	Vertical
11877.340	38.48	14.43	38.18	36.98	51.71	74.00	-22.29	Vertical
3492.224	32.19	7.63	38.46	40.95	42.31	74.00	-31.69	Horizontal
4904.000	34.33	9.01	39.07	44.21	48.48	74.00	-25.52	Horizontal
6184.658	34.85	10.32	38.88	42.61	48.90	74.00	-25.10	Horizontal
7356.000	36.36	10.74	38.03	42.17	51.24	74.00	-22.76	Horizontal
9808.000	37.56	12.61	36.89	37.59	50.87	74.00	-23.13	Horizontal
12102.870	38.66	14.47	38.41	36.19	50.91	74.00	-23.09	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013 Section 11.12
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Test Setup:



Figure 1. 30MHz to 1GHz



Figure 2. Above 1 GHz

Test Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel h. Test the EUT in the lowest channel , the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2412 Band edge
: B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	38.14	50.60	46.88	74.00	-27.12
2 pp	2413.186	5.36	29.15	38.15	95.54	91.90	74.00	17.90

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal



Condition: 3m Horizontal
Job No: : 4987CR
Mode: : 2412 Band edge
: B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2386.372	5.33	29.07	38.14	54.37	50.63	74.00	-23.37
2	2390.000	5.34	29.08	38.14	54.19	50.47	74.00	-23.53
3 pp	2413.072	5.35	29.15	38.15	106.14	102.49	74.00	28.49

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2462 Band edge
: B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.001	5.39	29.29	38.15	96.61	93.14	74.00	19.14
2	2483.500	5.41	29.35	38.15	50.48	47.09	74.00	-26.91

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2462 Band edge
: B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2460.953	5.39	29.29	38.15	105.00	101.53	74.00	27.53
2	2483.500	5.41	29.35	38.15	51.89	48.50	74.00	-25.50
3	2489.263	5.41	29.37	38.15	55.12	51.75	74.00	-22.25

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2412 Band edge
: G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	38.14	59.13	55.41	74.00	-18.59
2 av	2390.000	5.34	29.08	38.14	36.99	33.27	54.00	-20.73
3 pp	2414.558	5.36	29.15	38.15	98.75	95.11	74.00	21.11

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2412 Band edge
: G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	38.14	73.11	69.39	74.00	-4.61
2 av	2390.000	5.34	29.08	38.14	50.99	47.27	54.00	-6.73
3 pp	2411.016	5.35	29.14	38.15	109.01	105.35	74.00	31.35

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2462 Band edge
: G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2460.906	5.39	29.29	38.15	98.94	95.47	74.00	21.47
2	2483.500	5.41	29.35	38.15	62.01	58.62	74.00	-15.38
3 av	2483.500	5.41	29.35	38.15	41.10	37.71	54.00	-16.29

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2462 Band edge
: G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2459.570	5.39	29.28	38.15	108.32	104.84	74.00	30.84
2	2483.500	5.41	29.35	38.15	74.06	70.67	74.00	-3.33
3 av	2483.500	5.41	29.35	38.15	50.20	46.81	54.00	-7.19

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2412 Band edge
: N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	38.14	63.33	59.61	74.00	-14.39
2 av	2390.000	5.34	29.08	38.14	43.55	39.83	54.00	-14.17
3 pp	2411.245	5.35	29.14	38.15	97.15	93.49	74.00	19.49

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2412 Band edge
: N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	38.14	72.95	69.23	74.00	-4.77
2 av	2390.000	5.34	29.08	38.14	51.79	48.07	54.00	-5.93
3 pp	2413.643	5.36	29.15	38.15	109.52	105.88	74.00	31.88

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2462 Band edge
: N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.003	5.39	29.29	38.15	98.93	95.46	74.00	21.46
2	2483.500	5.41	29.35	38.15	62.76	59.37	74.00	-14.63
3 av	2483.500	5.41	29.35	38.15	41.11	37.72	54.00	-16.28

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2462 Band edge
: N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2459.999	5.39	29.28	38.15	108.00	104.52	74.00	30.52
2	2483.500	5.41	29.35	38.15	71.69	68.30	74.00	-5.70
3 av	2483.500	5.41	29.35	38.15	51.54	48.15	54.00	-5.85

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2422 Band edge
: N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2385.930	5.33	29.07	38.14	59.32	55.58	74.00	-18.42
2 av	2385.930	5.33	29.07	38.14	38.54	34.80	54.00	-19.20
3	2390.000	5.34	29.08	38.14	55.87	52.15	74.00	-21.85
4 pp	2419.980	5.36	29.17	38.15	91.71	88.09	74.00	14.09

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2422 Band edge
: N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2383.413	5.33	29.06	38.14	73.85	70.10	74.00	-3.90
2	2383.413	5.33	29.06	38.14	46.00	42.25	54.00	-11.75
3	2390.000	5.34	29.08	38.14	69.87	66.15	74.00	-7.85
4 av	2390.000	5.34	29.08	38.14	48.20	44.48	54.00	-9.52
5 pp	2414.071	5.36	29.15	38.15	102.99	99.35	74.00	25.35

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical



Condition: 3m VERTICAL
Job No: : 4987CR
Mode: : 2452 Band edge
: N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 2448.689	5.38	29.25	38.15	92.64	89.12	74.00	15.12
2	2483.500	5.41	29.35	38.15	55.00	51.61	74.00	-22.39
3	2483.782	5.41	29.35	38.15	57.89	54.50	74.00	-19.50
4	av 2483.782	5.41	29.35	38.15	45.21	41.82	54.00	-12.18

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal



Condition: 3m HORIZONTAL
Job No: : 4987CR
Mode: : 2452 Band edge
: N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2449.027	5.38	29.25	38.15	103.13	99.61	74.00	25.61
2	2483.500	5.41	29.35	38.15	69.33	65.94	74.00	-8.06
3 av	2483.500	5.41	29.35	38.15	48.51	45.12	54.00	-8.88
4	2485.701	5.41	29.36	38.15	70.74	67.36	74.00	-6.64
5	2485.701	5.41	29.36	38.15	46.69	43.31	54.00	-10.69

Note:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

7 Photographs - EUT Test Setup

Test model No.: SBC-EC8800

7.1 Conducted Emission

7.2 Radiated Emission

7.3 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1606004987CR.