

**KP-8IN-1REL**

**External Sticker 1**

**Caution: Disconnect supply before servicing**  
**Attention: Couper l'alimentation avant service**

**MODEL: KP-8IN-1REL**

**MANUFACTURER BY: GSI Electronics Inc.**  
5200, Armand-Frappier, St-Hubert (Qc), Canada

**AMBIENT TEMPERATURE: -40 to 40°C**

**ENCLOSURE IP/NEMA RATINGS: IP66, 4X**

**RELATIVE HUMIDITY: 95% MAX non-condensing**

**SUPPLY INPUTS: 24/28V $\overline{\text{DC}}$ , 5.62W**

**RELAY OUTPUT - Motor/inductive Load:**

**50/60Hz, 120V $\sim$ , 1/6HP (124W), 5A MAX**

**External Sticker 2**

**RELAY OUTPUT - Resistive Load at 150V $\sim$  Max. 50/60Hz**  
**and at 24/28V $\overline{\text{DC}}$ : 5A MAX.**

**RELAY OUTPUT - Tungsten load: 120 VAC, 2A max.**

**FCC ID: 2AFLZEDGERFID IC ID: 11680A-EDGERFID**

**CAUTION - The use of rigid conduits is allowed up to 1 inch**

**ATTENTION - L'utilisation de conduits rigides est permit jusqu'à 1 po**



**2016/04/06 - S/N: 0469269 -**



Labels on the product KP-8IN-1REL: The labels are stuck on the external faces of the plastic enclosure.



TR-2IN-1REL

External Sticker 1

**Caution: Disconnect supply before servicing**  
**Attention: Couper l'alimentation avant service**

**MODEL: TR-2IN-1REL**

---

MANUFACTURER BY: GSI Electronics Inc.  
5200, Armand-Frappier, St-Hubert (Qc), Canada  
AMBIENT TEMPERATURE: -40 to 40°C  
ENCLOSURE IP/NEMA RATINGS: IP66, 4X  
RELATIVE HUMIDITY: 95% MAX non-condensing  
SUPPLY INPUTS: 24/28V $\overline{\sim}$ : 4.3W  
RELAY OUTPUT - Motor/inductive Load:  
50/60Hz, 120V $\overline{\sim}$ , 1/8HP(124W), 5A MAX

External Sticker 2

RELAY OUTPUT - Resistive Load at 150V $\overline{\sim}$  Max. 50/60Hz  
and at 24/28V $\overline{\sim}$ : 5A MAX.

RELAY OUTPUT - Tungsten load: 120 V $\overline{\sim}$ , 2A max.

FCC ID: 2AFLZEDGERFID IC ID: 11880A-EDGERFID

CAUTION - The use of rigid conduits is allowed up to 1 inch

ATTENTION - L'utilisation de conduits rigides est permit jusqu'à 1 po



2016/04/06 - S/N: 0469270 -



Labels on the product TR-2IN-1REL: The labels are stuck on the external faces of the plastic enclosure.

