Product Title

Font: Arial, Regular, 12pt Top-align with Top Label Margin Left-align with Left Label Margin

Serial Number, Part Number, IMEI Number

Heading Font: Arial Narrow, Bold, 6pt Barcode Format: Code 128 Barcode Line Height: 2.5mm Barcode Text Font: OCR-B 10 BT, Regular, 11pt / Arial, Regular, 9pt Left-align with Left Label Margin

Bluetooth MAC Address

Heading Font: Arial Narrow, Regular, 6pt
Paragraph Alignment: Justify
MAC Address Font: Arial, Regular, 8pt
Left-align with Left Label Margin

Product Version, Supplier Code, Date Of Manufacture

Font: Arial, Regular, 8pt Paragraph alignment: Left Left-align with Left Label Margin

MiX Telematics Logo

Width: 29.91mm
Height: 5.36mm
Bottom-align with Bottom Label Margin
Left-align with Left Label Margin



M/X | TELEMATICS

FCC Compliance Notice Text

Font: Arial Narrow, Bold, 4.5pt Paragraph alignment: Justify Right-align with Right Label Margin Top-align with Top Label Margin

RCM Logo

Width: 6.78mm
Height: 5mm
Right-align with Right Label Margin
Bottom-align 1mm above CE Logo

Wheelie Bin Logo

Width: 5.44mm Height: 7.0mm

Right-align with Right Label Margin Bottom-align with IMEI Barcode Text

CE Logo

Width: 9.1mm Height: 6.5mm

Right-align 1.5mm from Wheelie Bin Logo Bottom-align with IMEI Barcode Text

FCC Text

Font: Arial Narrow, Bold, 6pt
Paragraph alignment: Right
Right-align with Right Label Margin
Bottom-align with Bluetooth MAC Addess Heading

Power Rating Text

Font: Arial Narrow, Bold, 8pt Right-align with Right Label Margin Bottom-align with Date of Manufacture Text

Line

Height: 0.5pt

Width: (Area between Left and Right Label Margins)

Origin Text,

MiX Telematics Website

Font: Arial. Bold. 6pt

Paragraph alignment: Justify Right-align with Right Label Margin

Centre vertically with MiX Telematics Logo

REF	DESCRIPTION	PART NUMBER
1	LABEL HG DURAFLEX OD:77 ID:25MM 74x49MM	CON0153
2	RIBBON THER TRANS 110MMx70M NOTCHES B325	CON0154



1. Use 2mm margin on all sides of label

2. Do not scale logos. Use only logo artwork provided

Apply label symmetrically to indentation on bottom surface of the OBC's housing.Orientate label so that bottom edge of label is closest to the OBC's connectors.

NOTES

SPECIFICATION					REV	DATE	ECN	CHANGES
DOCUMENT TITLE		MiX 44MC-3G-B: Housing Label			1A	18 Sep 2019	721	Field Trial 1
DOCUMENT NUMBER		SLU0034A			1B	4 Nov 2019	736	First release
SHEET		1 OF 1	SHEET SIZE	A4				
SCALE		1:1 Except where shown otherwise						
FORM	7.11.	5-22	FORM REVISION	5				

Made in South Africa

www.mixtelematics.com