Product Title Font: Arial. Regular. 12pt

Top-align with Top Label Margin Left-align with Left Label Margin

Serial Number. Part Number,

IMEI Number Heading Font: Arial Narrow, Bold, 6pt Barcode Format: Code 128 Barcode Line Height: 2.5mm Barcode Text Font: OCR-B 10 BT, Regular, 11pt / Arial, Regular, 9pt Left-align with Left Label Margin

Bluetooth MAC Address

Heading Font: Arial Narrow, Regular, 6pt Paragraph Alignment: Justify MAC Address Font: Arial. Regular. 8pt Left-align with Left Label Margin

Product Version,

Supplier Code, **Date Of Manufacture** Font: Arial, Regular, 8pt Paragraph alignment: Left Left-align with Left Label Margin

MiX Telematics Logo Width: 29.91mm Height: 5.36mm Bottom-align with Bottom Label Margin Left-align with Left Label Margin

NOTES

- 1. Use 2mm margin on all sides of label
- 2. Do not scale logos. Use only logo artwork provided
- 3. Serial number has format 45xxxxxx, where
 - XXXXXX is a 6-digit number as in the artwork above
- 4. Product Version has format Vn, where n=1,2,... (e.g. V1). Use the version number as indicated in the artwork above. This is not to be confused with the Document Specification Version as in the title block below
- 5. Supplier Code has format MM (e.g. AB). Use Supplier Code as specified by MiX Telematics

6. Date of Manufacture Code has format WW/YYYY, where WW is the week number, and YYYY the year of manufacture (e.g. 32/2011)

- 7. Apply label symmetrically to indentation on bottom surface of the OBC's housing.
- Orientate label so that bottom edge of label is closest to the OBC's connectors.

	12			
MiX 45MC-4G-B Serial NUMBER II IIII III III IIIIII 45123456	This device complex with Part 15 of the FFC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.			
PART NUMBER 111 11 11 11 11 11 11 11 11 11 11 11 11				
INEI NUMBER IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII				
BLUETOOTH MAC ADDRESS 00-01-02-1A-2 V1 MM WW/YYYY	B-3C Contains FCC ID: XPY2AGQN4NNN Contains ISED: 8595A-2AGQN4NNN 10.5 – 32VDC; 4.5A (max)			

WX |TELEMATICS

N4NNN (max) Made in South Africa

www.mixtelematics.com

FCC Compliance Notice Text

Font: Arial Narrow, Bold, 4.5pt Paragraph alignment: Justify Right-align with Right Label Margin Top-align with Top Label Margin

Wheelie Bin Logo

Width: 6.61mm Height: 8.5mm Right-align with Right Label Margin Bottom-align 1.5mm above Certification Text

Certification Text

Font: Arial Narrow, Bold, 6pt Paragraph alignment: Right Right-align with Right Label Margin Bottom-align with Bluetooth MAC Addess Heading

Power Rating Text

Font: Arial Narrow, Bold, 8pt Right-align with Right Label Margin Bottom-align with Date of Manufacture Text

Line

Height: 0.5pt Width: (Area between Left and Right Label Margins)

Origin Text.

MiX Telematics Website Font: Arial. Bold. 6pt Paragraph alignment: Justify Right-align with Right Label Margin Centre vertically with MiX Telematics Logo

REF	DESCRIPTION	PART NUMBER
1	LABEL HG DURAFLEX OD:77 ID:25MM 74x49MM	CON0153
2	RIBBON THER TRANS 110MMx70M NOTCHES B325	CON0154

	SPECIFICATION			REV	DATE	ECN	CHANGES	
	DOCUMENT TITLE	MiX 45MC-4	MiX 45MC-4G-B: Housing Label			16 Jul 2018	N/A	Field Trial 1
MA	DOCUMENT NUMBER 440SL0191A		1A	13 Sep 2018	642	Field Trial 2		
•	SHEET	1 OF 1	SHEET SIZE	A4	1B	5 Nov 2018	656	Added Certification details; Removed "Field Trial Unit" text
TELEMATICS MOBILE INFORMATION EXCHANGE	SCALE	1:1 Except v	1:1 Except where shown otherwise					
	FORM	7.11.5-22	FORM REVISION	5				