

# RF EXPOSURE REPORT

Applicant	SZ Telstar CO., LTD
Address	Telstar Technology Park No. 12-14, Gangbei Industrial Zone, Ailian, Longgang Dist, Shenzhen Guangdong 518172 China

Manufacturer or Supplier	SZ Telstar CO.,LTD		
Address	Telstar Technology Park No. 12-14, Gangbei Industrial Zone, Ailian, Longgang Dist, Shenzhen Guangdong 518172 China		
Product Projector			
Brand Name	miroir		
Model MP150W			
Additional Model & Model Difference	N/A		
Date of tests	Oct. 01, 2015 ~ Oct. 09, 2015		

- **☐** FCC Part 2 (Section 2.1091)
- **⊠ KDB 447498 D01**
- **⊠** IEEE C95.1

#### CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Date: Oct. 09, 2015

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **Table of Contents**

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED	
FS150904N002	Original release	Oct. 09, 2015	

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Fax: +86 769 8593 1080

Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Report Version 1

Page 3 of 6

Tel: +86 769 8593 5656



#### 1. CERTIFICATION

**PRODUCT:** Projector

**BRAND NAME:** miroir

MODEL NO.: MP150W

**ADDITIONAL MODEL:** N/A

FCC ID: 2AFOW-150WMIROIR

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: SZ Telstar CO., LTD

**STANDARDS:** FCC Part 2 (Section 2.1091)

KDB 447498 D01

**IEEE C95.1** 

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Page 4 of 6

#### RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

• • • • • • • • • • • • • • • • • • • •		MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)	
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

#### 2. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

## 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 6 Report Version 1



#### 4. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	1.0	Wire Antenna	

## 5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2412-2462	54.702	1.0	20	0.0137	1.0

--- END ---

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Page 6 of 6