

RF EXPOSURE REPORT

Applicant	SZ Telstar CO.,LTD
Address	Telstar Technology Park No.12~14,Gangbei Industrial Zone, Ailian, Longgang District, ShenZhen

Manufacturer or Supplier	SZ Telstar CO.,LTD
Address	Telstar Technology Park No.12~14, Gangbei Industrial Zone, Ailian, Longgang District, ShenZhen
Product	Projector
Brand Name	miroir, Brookstone
Model	U5
Additional Model & Model Difference	M400A, M400, 318490, see item 3.1
Date of tests	Oct. 15, 2016 ~ Nov. 08, 2016

- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Tom Chen Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department
Tom	Data: Nav. 20, 2016

Date: Nov. 30, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



Table of Contents

RELE	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
	CLASSIFICATION	
	ANTENNA GAIN	
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS160928N001	Original release	Nov. 30, 2016

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



1. CERTIFICATION

FCC ID:	2AFOW-UST520U5		
PRODUCT:	Projector		
BRAND NAME:	miroir, Brookstone		
MODEL NO.:	U5		
ADDITIONAL NO.:	M400A, M400, 318490		
APPLICANT:	SZ Telstar CO.,LTD		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

NOTE:

1. Additional models M400A, M400, 318490 are identical with the test model U5, except the model number and trade name for marketing purpose.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)							
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE							
300-1500 F/1500 30							
1500-100,000			1.0	30			

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 7



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Module 1

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2 dBi For BT, BT-BLE, WIFI 2.4GHz, WIFI 5GHz	Integral FPCB Antenna
Chain 1	2 dBi For WIFI 2.4GHz(802.11n), WIFI 5GHz	Integral FPCB Antenna

For wifi: $2+10\log(n)=2+10\log2=2+3.01=5.01dBi$

Module 2

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2 dBi For BT-BLE	Integral FPCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For Module 1

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm²)
2402-2480(BT)	3.443	2	20	0.00109	1.0
2402-2480(BT-BLE)	7.228	2	20	0.00228	1.0
2412-2462(WLAN)	212.385	5.01	20	0.13392	1.0
5180-5240 (WIFI 5GHz)	40.926	5.01	20	0.02581	1.0
5745-5825 (WIFI 5GHz)	25.763	5.01	20	0.01625	1.0

For Module 2

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm²)
2402-2480(BT-BLE)	6.779	2	20	0.00214	1.0

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 6 of 7

Report Version 1



CONCLUSION:

The module 1 and module 2 can transmit simultaneously, but WIFI 2.4GHz and WIFI 5GHz can not transmit simultaneously, the formula of calculated the MPE is:

CPD₁ / LPD₁ + CPD₂ / LPD₂ +etc. < 1 CPD = Calculation power density LPD = Limit of power density

Therefore, the worst-case situation is 0.00228 / 1 + 0.13392 / 1 + 0.00214 / 1 = 0.13834, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080