

## RF Exposure evaluation

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

FCC ID: 2AFOZF3501

### 1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

### 2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 4. Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna is 2dBi, the RF power density can be obtained.

#### BLE

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/c m <sup>2</sup> )	Result
GFSK								
2402	1.983	2±1.0	3	1.995	2	0.00063	1	Pass
2440	1.821	2±1.0	3	1.995	2	0.00063	1	Pass
2480	1.561	2±1.0	3	1.995	2	0.00063	1	Pass

#### RF ID Sub 1G

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/c m <sup>2</sup> )	Result
2-GFSK								
906.5	1.820	2±1.0	3	1.995	2	0.00063	1	Pass
914.5	1.767	2±1.0	3	1.995	2	0.00063	1	Pass
922.5	1.990	2±1.0	3	1.995	2	0.00063	1	Pass

### 2.4G WIFI

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b								
2412	14.33	14±1.0	15	31.6228	2	0.0100	1	Pass
2437	13.57	14±1.0	15	31.6228	2	0.0100	1	Pass
2462	13.78	14±1.0	15	31.6228	2	0.0100	1	Pass
802.11g								
2412	13.18	14±1.0	15	31.6228	2	0.0100	1	Pass
2437	13.55	14±1.0	15	31.6228	2	0.0100	1	Pass
2462	13.70	14±1.0	15	31.6228	2	0.0100	1	Pass
802.11n20								
2422	13.44	14±1.0	15	31.6228	2	0.0100	1	Pass
2437	13.51	14±1.0	15	31.6228	2	0.0100	1	Pass
2452	13.98	14±1.0	15	31.6228	2	0.0100	1	Pass

## 5. Simultaneously MPE

MPE Ratio BLE (mW/cm <sup>2</sup> )	MPE Ratio RF ID (mW/cm <sup>2</sup> )	MPE Ratio 2.4GWLAN (mW/cm <sup>2</sup> )	ΣMPE ratios	Limit	Results
0.01	0.01	0.01	0.03	1.0	PASS

## 6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.