




TEST REPORT


Test Report No. : UL-RPT-RP10935572JD06A


Manufacturer : ROLI Ltd
Model No. : Seaboard RISE 25
FCC ID : 2AFT3SBR025
Technology : *Bluetooth* – Low Energy
Test Standard(s) : FCC Parts 15.207, 15.209(a) & 15.247

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 1.0

Date of Issue: 16 November 2015

Checked by: 
Sarah Williams
Engineer, Radio Laboratory

Issued by : 
pp
Phil Davies
Regional Operations Manager,
UL VS LTD



This laboratory is accredited by UKAS.
The tests reported herein have been
performed in accordance with its terms
of accreditation.

The *Bluetooth*[®] word mark and logos are owned by the *Bluetooth* SIG, Inc. and any use of such marks by UL VS LTD is under licence. Other trademarks and trade names are those of their respective owners.

UL VS LTD

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire, RG23 8BG, UK
Telephone: +44 (0)1256 312000
Facsimile: +44 (0)1256 312001

This page has been left intentionally blank.

Table of Contents

1. Customer Information.....	4
2. Summary of Testing.....	5
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
3. Equipment Under Test (EUT)	6
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	6
3.3. Modifications Incorporated in the EUT	6
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	8
4. Operation and Monitoring of the EUT during Testing	9
4.1. Operating Modes	9
4.2. Configuration and Peripherals	9
5. Measurements, Examinations and Derived Results.....	10
5.1. General Comments	10
5.2. Test Results	11
5.2.1. Transmitter AC Conducted Spurious Emissions	11
5.2.2. Transmitter Minimum 6 dB Bandwidth	15
5.2.3. Transmitter Maximum Peak Output Power	17
5.2.4. Transmitter Radiated Emissions	20
5.2.5. Transmitter Band Edge Radiated Emissions	28
6. Measurement Uncertainty	30
7. Report Revision History	31

1. Customer Information








Company Name:	ROLI Ltd
Address:	2 Glebe Road Dalston LONDON E8 4BD United Kingdom

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.247
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Section 15.247
Specification Reference:	47CFR15.207 and 47CFR15.209
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Sections 15.207 and 15.209
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	02 November 2015 to 11 November 2015

2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 15.207	Transmitter AC Conducted Emissions	
Part 15.247(a)(2)	Transmitter Minimum 6 dB Bandwidth	
Part 15.247(e)	Transmitter Power Spectral Density	Note 1
Part 15.247(b)(3)	Transmitter Maximum Peak Output Power	
Part 15.247(d)/15.209(a)	Transmitter Radiated Emissions	
Part 15.247(d)/15.209(a)	Transmitter Band Edge Radiated Emissions	
Key to Results		
 = Complied  = Did not comply		

Note(s):

1. In accordance with FCC KDB 558074 Section 10.1, PSD is not required if the maximum conducted output power is less than the PSD limit of 8 dBm / 3 kHz. The PSD level is therefore deemed to be equal to the measured total output power.

2.3. Methods and Procedures

Reference:	ANSI C63.10-2013
Title:	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Reference:	KDB 558074 D01 v03r03 June 9, 2015
Title:	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	ROLI
Model Name or Number:	Seaboard RISE 25
Test Sample Serial Number:	R25111112271 (<i>Radiated sample</i>)
Hardware Version:	Rev D
Software Version:	Firmware 1.0.7 BT 0.0.4
FCC ID:	2AFT3SBR025

Brand Name:	ROLI
Model Name or Number:	Seaboard RISE 25
Test Sample Serial Number:	F1536P251021 (<i>Conducted sample with RF port</i>)
Hardware Version:	Rev D
Software Version:	Firmware 1.0.7 BT 0.0.4
FCC ID:	2AFT3SBR025

3.2. Description of EUT

The equipment under test was a musical MIDI keyboard with USB and *Bluetooth*® Low Energy connectivity. The *Bluetooth*® antenna was integral to the unit and could not be accessed by the user.

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

Technology Tested:	<i>Bluetooth</i> Low Energy (Digital Transmission System)		
Type of Unit:	Transceiver		
Channel Spacing:	2 MHz		
Modulation:	GFSK		
Data Rate:	1 Mbps		
Power Supply Requirement(s):	Nominal	120 VAC via external AC to DC adaptor, 5 VDC via USB	
Maximum Conducted Output Power:	-1.0 dBm		
Antenna Gain:	-5.5 dBi		
Transmit Frequency Range:	2402 MHz to 2480 MHz		
Transmit Channels Tested:	Channel ID	RF Channel	Channel Frequency (MHz)
	Bottom	0	2402
	Middle	19	2440
	Top	39	2480

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	Laptop
Brand Name:	Lenovo
Model Name or Number:	L440
Serial Number:	R9-019EA4 14/04

Description:	AC to DC adaptor
Brand Name:	XP Power
Model Name or Number:	VEP24US12
Serial Number:	1441-0012

Description:	Foot Pedal Switch
Brand Name:	M-Audio
Model Name or Number:	SP2
Serial Number:	CD1504501002500

Description:	Laptop
Brand Name:	Apple
Model Name or Number:	Macbook Air A1466
Serial Number:	C02L21GSF5V7

Description:	USB hub
Brand Name:	BELKIN
Model Name or Number:	F5U404
Serial Number:	Not stated

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

- Transmitting at maximum power in *Bluetooth* LE mode with modulation, maximum possible data length available (37 bytes) and Pseudorandom Bit Sequence 9.

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Controlled using a *BlueNRG_updater.exe v1.0.0.0* software application supplied by the customer, and run on a test laptop. The application was controlled via a Windows Command Prompt to enable continuous transmission. The customer supplied instructions in a read me note pad documenting how to place it into test mode, how to select the test channels, packet length and data configuration as required.
- The EUT command list for the *BlueNRG_updater* application was obtained by running the program from a Command Prompt window, with no EUT connected. All valid command arguments are shown in the window.
- The transmitter was configured using a power level setting of 12.
- For conducted tests, the EUT was powered by a 5 V USB connection from a test laptop.
- For radiated tests, the EUT was powered by an external 120 VAC to 12 VDC adaptor whilst charging an internal battery.
- The customer supplied an EUT with an SMA connector in order to perform conducted measurements.
- The EUT conducted sample was used for 6 dB bandwidth and maximum peak output power.
- The EUT radiated sample was used for AC conducted emissions and radiated spurious emissions tests.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

5.2. Test Results

5.2.1. Transmitter AC Conducted Spurious Emissions

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	06 November 2015
Test Sample Serial Number:	R25111112271		

FCC Reference:	Part 15.207
Test Method Used:	ANSI C63.10 Section 6.2


Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	57

Note(s):

1. The EUT was connected to the power supply input which was connected to a 120 VAC 60 Hz single phase supply via a LISN.
2. Pre-scans were performed and markers placed on the highest live and neutral measured levels. Final measurements were performed on the marker frequencies and the results entered into the tables below.
3. A pulse limiter was fitted between the LISN and the test receiver.

Test setup:



Transmitter AC Conducted Spurious Emissions (continued)**Results: Live / Quasi Peak**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.150	Live	39.3	66.0	26.7	Complied
0.168	Live	38.9	65.1	26.2	Complied
0.213	Live	40.0	63.1	23.1	Complied
0.384	Live	39.2	58.2	19.0	Complied
0.479	Live	31.1	56.4	25.3	Complied
1.001	Live	28.7	56.0	27.3	Complied

Results: Live / Average

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.236	Live	31.2	52.3	21.1	Complied
0.236	Live	31.1	52.3	21.2	Complied
0.393	Live	32.3	48.0	15.7	Complied
0.501	Live	23.6	46.0	22.4	Complied
0.623	Live	23.3	46.0	22.7	Complied
1.001	Live	23.9	46.0	22.1	Complied


Transmitter AC Conducted Spurious Emissions (continued)**Results: Neutral / Quasi Peak**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.155	Neutral	37.1	65.8	28.7	Complied
0.389	Neutral	36.5	58.1	21.6	Complied
0.465	Neutral	28.7	56.6	27.9	Complied
1.001	Neutral	28.0	56.0	28.0	Complied
1.500	Neutral	21.8	56.0	34.2	Complied
2.000	Neutral	19.8	56.0	36.2	Complied


Results: Neutral / Average

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.150	Neutral	30.0	56.0	26.0	Complied
0.393	Neutral	29.1	48.0	18.9	Complied
0.501	Neutral	27.0	46.0	19.0	Complied
1.001	Neutral	23.9	46.0	22.1	Complied
1.500	Neutral	17.7	46.0	28.3	Complied
2.000	Neutral	15.7	46.0	30.3	Complied

Transmitter AC Conducted Spurious Emissions (continued)



Live



Neutral

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1625	Thermohygrometer	JM Handelpunkt	30.5015.06	None stated	07 Jan 2016	12
A067	LISN	Rohde & Schwarz	ESH3-Z5	890603/002	27 Aug 2016	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	02 Mar 2016	12
M1379	Test Receiver	Rohde & Schwarz	ESIB7	100330	08 Dec 2015	12

5.2.2. Transmitter Minimum 6 dB Bandwidth**Test Summary:**

Test Engineer:	Kiren Mistry	Test Date:	10 November 2015
Test Sample Serial Number:	F1536P251021		


FCC Reference:	Part 15.247(a)(2)
Test Method Used:	FCC KDB 558074 Section 8.1 Option 1

Environmental Conditions:

Temperature (°C):	25
Relative Humidity (%):	47

Note(s):


- 6 dB DTS bandwidth tests were performed using a signal analyser in accordance with KDB 558074 Section 8.1 Option 1 measurement procedure. The signal analyser resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and the trace mode was Max Hold. The DTS bandwidth was measured at 6 dB down from the peak of the signal.
- The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable.

Test setup:**Results:**


Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)	Result
Bottom	693.000	≥500	193.000	Complied
Middle	690.000	≥500	190.000	Complied
Top	723.600	≥500	223.600	Complied

Transmitter Minimum 6 dB Bandwidth (continued)


Results:



Bottom Channel



Middle Channel



Top Channel

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1783	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
A2521	Attenuator	AtlanTecRF	AN18-20	832797#2	Calibrated before use	-
M1883	Signal Analyser	Rohde & Schwarz	FSV30	103084	23 Jul 2016	12
G0614	Signal Generator	Rohde & Schwarz	SMB100A	177687	01 May 2017	36

5.2.3. Transmitter Maximum Peak Output Power**Test Summary:**

Test Engineer:	Kiren Mistry	Test Date:	11 November 2015
Test Sample Serial Number:	F1536P251021		


FCC Reference:	Part 15.247(b)(3)
Test Method Used:	FCC KDB 558074 Section 9.1.1

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	50

Note(s):

1. Conducted power tests were performed using a signal analyser in accordance with KDB 558074 Section 9.1.1 with the RBW > *DTS bandwidth* procedure. The resolution bandwidth was set to 2 MHz and video bandwidth to 10 MHz. A peak detector was used, sweep time set to auto and trace mode was Max Hold. The span was set to 3 times the resolution bandwidth (6 MHz). A marker was placed at the peak of the signal and the results recorded in the table below.
2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable. An RF level offset was entered on the signal analyser to compensate for the loss of the attenuator and RF cable.
3. The conducted power was added to the declared antenna gain to obtain the EIRP.


Test setup:

Transmitter Maximum Peak Output Power (continued)**Results:**


Channel	Conducted Peak Power (dBm)	Conducted Peak Power Limit (dBm)	Margin (dB)	Result
Bottom	-1.0	30.0	31.0	Complied
Middle	-1.1	30.0	31.1	Complied
Top	-1.2	30.0	31.2	Complied

Channel	Conducted Peak Power (dBm)	Declared Antenna Gain (dBi)	EIRP (dBm)	De Facto EIRP Limit (dBm)	Margin (dB)	Result
Bottom	-1.0	-5.5	-6.5	36.0	42.5	Complied
Middle	-1.1	-5.5	-6.6	36.0	42.6	Complied
Top	-1.2	-5.5	-6.7	36.0	42.7	Complied


Transmitter Maximum Peak Output Power (continued)



Bottom Channel



Middle Channel



Top Channel

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1783	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
A2521	Attenuator	AtlanTecRF	AN18-20	832797#2	Calibrated before use	-
M1883	Signal Analyser	Rohde & Schwarz	FSV30	103084	23 Jul 2016	12
G0614	Signal Generator	Rohde & Schwarz	SMB100A	177687	01 May 2017	36

5.2.4. Transmitter Radiated Emissions**Test Summary:**

Test Engineer:	Nick Steele	Test Date:	11 November 2015
Test Sample Serial Number:	R25111112271		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Sections 6.3 and 6.5
Frequency Range	30 MHz to 1000 MHz

Environmental Conditions:



Temperature (°C):	24
Relative Humidity (%):	45

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. The preliminary scans showed similar emission levels below 1 GHz, for each channel of operation. Therefore final radiated emissions measurements were performed with the EUT set to the middle channel only.
3. All other emissions shown on the pre-scans were investigated and found to be ambient, or > 20 dB below the appropriate limit or below the noise floor of the measurement system.
4. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
5. Pre-scans were performed and markers placed on the highest measured levels. The test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold.
6. Final measurements were performed on the marker frequencies and the results entered into the table below. The test receiver resolution bandwidth was set to 120 kHz, using a CISPR quasi-peak detector and span big enough to see the whole emission.


Transmitter Radiated Emissions (continued)

Test setup for radiated measurements:



Transmitter Radiated Emissions (continued)**Results: Middle Channel**

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
120.054	Horizontal	23.8	43.5	19.7	Complied
168.453	Horizontal	27.9	43.5	15.6	Complied
240.128	Horizontal	26.3	46.0	19.7	Complied
264.464	Horizontal	28.3	46.0	17.7	Complied
408.352	Vertical	40.0	46.0	6.0	Complied



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1945	Thermohygrometer	JM Handlungspunkt	30.5015.01	0112	23 Apr 2016	12
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	19 Mar 2016	12
M1273	Test Receiver	Rohde & Schwarz	ESIB26	100275	19 Mar 2016	12
A490	Antenna	Chase	CBL6111A	1590	30 Apr 2016	12
G0543	Amplifier	Sonoma	310N	230801	10 Feb 2016	3
A1834	Attenuator	Hewlett Packard	8491B	10444	05 Mar 2016	12

Transmitter Radiated Emissions (continued)**Test Summary:**

Test Engineer:	Andrew Edwards	Test Dates:	02 November 2015 to 04 November 2015
Test Sample Serial Number:	R25111112271		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	FCC KDB 558074 Sections 11 & 12 referencing ANSI C63.10 Sections 6.3 and 6.6
Frequency Range	1 GHz to 25 GHz

Environmental Conditions:

Temperature (°C):	22 to 24
Relative Humidity (%):	41 to 51

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
3. The emission shown on the 1 GHz to 4 GHz plot is the EUT fundamental.
4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 1.5 m above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
5. Pre-scans were performed and a marker placed on the highest measured level of the appropriate plot. The test receiver resolution bandwidth was set to 1 MHz and video bandwidth 3 MHz. The sweep time was set to auto.
6. * In accordance with ANSI C63.10 Section 6.6.4.3, Note 1, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.
7. The reference level for the emission in the non-restricted band was established by following KDB 558074 Section 11.2 procedure.
8. ** -20 dBc limit applies in non-restricted bands, in accordance with KDB 558074 Section 11.1(a), as the conducted output power measurements were performed using a peak detector.

Transmitter Radiated Emissions (continued)**Results: Bottom Channel**

Frequency (MHz)	Antenna Polarity	Peak Level (dB μ V/m)	Average Limit* (dB μ V/m)	Margin (dB)	Result
4704.134	Vertical	44.8	54.0	9.2	Complied
4718.684	Vertical	45.9	54.0	8.1	Complied
4790.641	Vertical	47.8	54.0	6.2	Complied
4804.663	Horizontal	50.5	54.0	3.5	Complied
4815.801	Vertical	46.7	54.0	7.3	Complied
4823.574	Vertical	48.2	54.0	5.8	Complied
7205.412	Horizontal	51.0	63.2**	12.2	Complied
12011.298	Horizontal	47.8	54.0	6.2	Complied
14413.747	Horizontal	45.5	63.2**	17.7	Complied
16812.573	Horizontal	50.7	63.2**	12.5	Complied

Results: Middle Channel

Frequency (MHz)	Antenna Polarity	Peak Level (dB μ V/m)	Average Limit* (dB μ V/m)	Margin (dB)	Result
4704.487	Vertical	45.7	54.0	8.3	Complied
4718.942	Vertical	45.7	54.0	8.3	Complied
4866.603	Vertical	44.4	54.0	9.6	Complied
4879.744	Horizontal	47.4	54.0	6.6	Complied
4892.260	Vertical	44.0	54.0	10.0	Complied
4899.872	Vertical	44.5	54.0	9.5	Complied
7319.263	Vertical	53.2	54.0	0.8	Complied
12201.651	Horizontal	50.3	54.0	3.7	Complied
14641.715	Horizontal	47.9	63.6**	15.7	Complied
17078.542	Horizontal	48.8	63.6**	14.8	Complied





Transmitter Radiated Emissions (continued)**Results: Peak / Top Channel**

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4704.248	Vertical	47.3	54.0*	6.7	Complied
4718.356	Vertical	46.7	54.0*	7.3	Complied
4944.006	Vertical	45.0	54.0*	9.0	Complied
4959.551	Horizontal	48.4	54.0*	5.6	Complied
4970.208	Vertical	44.6	54.0*	9.4	Complied
4978.141	Vertical	44.8	54.0*	9.2	Complied
7440.978	Horizontal	51.9	54.0*	2.1	Complied
9921.778	Horizontal	42.8	61.1**	18.3	Complied
12401.538	Horizontal	54.9	74.0	19.1	Complied
14881.746	Horizontal	46.0	61.1**	15.1	Complied
17362.003	Horizontal	45.1	61.1**	16.0	Complied



Results: Average / Top Channel

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
12399.054	Horizontal	50.8	54.0	3.2	Complied

Transmitter Radiated Emissions (continued)



Transmitter Radiated Emissions (continued)



Note: The above plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 May 2016	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	12 Jun 2016	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	21 Dec 2015	12
A1818	Antenna	EMCO	3118	00075692	20 Dec 2015	12
A253	Antenna	Flann Microwave	12240-20	128	20 Dec 2015	12
A254	Antenna	Flann Microwave	14240-20	139	20 Dec 2015	12
A255	Antenna	Flann Microwave	16240-20	519	20 Dec 2015	12
A256	Antenna	Flann Microwave	18240-20	400	20 Dec 2015	12
A436	Antenna	Flann Microwave	20240-20	330	20 Dec 2015	12
A1975	High Pass Filter	AtlanTecRF	AFH-03000	090424010	17 Apr 2016	12
A2176	High Pass Filter	AtlanTecRF	AFH-07000	800980	17 Apr 2016	12

5.2.5. Transmitter Band Edge Radiated Emissions**Test Summary:**

Test Engineer:	Andrew Edwards	Test Date:	04 November 2015
Test Sample Serial Number:	R25111112271		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Section 6.10.4, 6.10.5 & FCC KDB 558074 Section 11

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	45

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. The maximum peak conducted output power was previously measured. In accordance with FCC KDB 558074 Section 11.1(a), the lower band edge measurement was performed with a peak detector and the -20 dBc limit applied.
3. There is a restricted band 10 MHz below the lower band edge. The test receiver was set up as follows: the RBW set to 1 MHz, the VBW set to 3 MHz, with the sweep time set to auto couple. Peak and average measurements were performed with their respective detectors. Markers were placed on the highest point on each trace.
4. * -20 dBc limit.



Results: Peak

Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2386.154	43.2	74.0	30.8	Complied
2399.760	43.9	63.2*	19.3	Complied
2400.0	40.7	63.2*	22.5	Complied
2483.5	54.5	74.0	19.5	Complied

Results: Average



Frequency (MHz)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2342.949	32.4	54.0	21.6	Complied
2483.5	41.1	54.0	12.9	Complied

Transmitter Band Edge Radiated Emissions (continued)



Lower Band Edge Peak Measurement

Upper Band Edge Peak Measurement



2310 MHz to 2390 MHz Restricted Band Plot

Upper Band Edge Average Measurement

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohyrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 May 2016	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	12 Jun 2016	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	21 Dec 2015	12
A1818	Antenna	EMCO	3115	00075692	20 Dec 2015	12

6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value measured (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±4.69 dB
Conducted Maximum Peak Output Power	2.4 GHz to 2.4835 GHz	95%	±1.13 dB
Minimum 6 dB Bandwidth	2.4 GHz to 2.4835 GHz	95%	±3.92 %
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 26.5 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

7. Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version

--- END OF REPORT ---