



BUREAU
VERITAS

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Test Report

Report No	EP2928-1
Client	ecoVent Robert Kim
Address	24 Cambridge St, Suite 6 Charlestown, MA 02129
Phone	857-204-4466
Items tested	WALL SENSOR
FCC ID	2AFTLSS1
FRN	0024870743
Equipment Type	Part 15.247 Digitally Modulated
Equipment Code	DTS
FCC/IC Rule Parts	47 CFR 15.247, RSS-247 Issue 1
Test Dates	October 15 – 16, 21 and 28-29, 2015
Results	As detailed within this report
Prepared by	 Tuyen A. Truong – Test Engineer
Authorized by	 Christopher Reynolds – EMC Supervisor
Issue Date	12/11/15
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 28 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Contents

Contents.....	2
Summary.....	3
Test Methodology.....	4
Product Tested - Configuration Documentation	5
Statement of Conformity.....	6
Modifications Required for Compliance	7
Test Results.....	8
<i>Bandwidth</i>	8
Fundamental Emission Output Power	11
<i>Radiated Spurious Emissions</i>	14
Power Spectral Density.....	22
Occupied Bandwidth	25
Measurement Uncertainty	28
Conditions Of Testing	29

Form Final Report REV 7-20-07 (DW)



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

Summary

This test report details the partial testing of the WALL SENSOR (with existing FCC ID: 2AFTLSS1) with the following modifications:

The channel plan was changed to operate on all channels (see channel plan exhibit) from 904 to 926 MHz range (formerly only 1 channel (915 MHz) used for operation). Per client, this is only a software change of the frequency. Also power setting was reduced to 10.6 dBm.

The following tests were performed to evaluate the above modifications: 6 dB Bandwidth, 99% Occupied Bandwidth, Fundamental Emissions Output power, Power Spectral Density, and Radiated Spurious Emissions. We found that the product met the above requirements with modification (see Modification Required for Compliance section on page 7 for details). Testing of the original channel plan was previously performed under report EP2231-1.

Robert Kim from ecoVent was present during the testing. The test sample was received in good condition.

Issue No.	Reason for change	Date Issued
1	Original Release	December 14, 2015

page 3 of 30



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Test Methodology

Radiated emission testing were performed according to DTS guidance document 558074D01 v03r03 specified in FCC Guidance for performing compliance measurement on DTS operating under section 15.247, April 19, 2013 and ANSI C63.10 (2013). Radiated Emissions were maximized by rotating the device around its axes as well as varying the test antenna's height and polarity. The device antenna was not maximized separately.

Operating channel frequency = 904 MHz

Operating channel frequency = 915 MHz

Operating channel frequency = 926 MHz

The following bandwidths were used during radiated spurious emissions.

Frequency	RBW	VBW
0.15-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz
1-10GHz	1MHz	3MHz



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 4 of 30

Product Tested - Configuration Documentation

EUT Configuration																			
Work Order:	P2928																		
Company:	ecoVent																		
Company Address:	24 Cambridge St, Suite 6 Charlestown, MA 02129																		
Contact:	Robert Kim																		
	MN			PN			SN												
EUT:	SS1			901-00002			Sample 1												
EUT Description:	Wall Sensor																		
EUT TX Frequency:	904 - 926 MHz																		
Support Equipment	MN			SN															
None																			
Port Label	Port Type	# ports	# populated	cable type	shielded	ferrite s	length (m)	max length (m)	in/out	under test	comment								
AC prongs	Power AC	1	1	Other	No	No	0.05		in	yes									
AC Output	Power AC	2	2	3-wire	No	No	1		In	yes									
USB	USB	2	2	USB	Yes	Yes	1	5	in	yes									
Software Operating Mode Description:																			
EUT is set to transmit with 10.6 dBm of power on 904 MHz, 915 MHz and 926 MHz respectively. Modulation type used is FSK2 with constant transmission (100% duty cycle). Maximum antenna gain is -2 dBi.																			



Statement of Conformity

The WALL SENSOR has been found to conform to the following parts of 47 CFR and as detailed below:

RSS-GEN	RSS 247	Part 15	Comments
5.3		15.15(b)	There are no controls accessible to the user that varies the output power above specified limits.
5.2		15.19	The label is shown in the label exhibit.
8.4		15.21	Information to the user is shown in the instruction manual exhibit.
		15.27	No special accessories are required for compliance.
		15.31	The EUT was tested in accordance with the measurement standards in this section.
		15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
		15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
6.7		15.203	EUT employs a permanently connected antenna with -2dBi gain.
	5.5	15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209.
8.8		15.207	Evaluation Not Requested. EUT AC Mains was tested under report EP2231-1
		15.247	The unit complies with the requirements of FCC Part 15.247
	RSS-247		The unit complies with the requirements of RSS-247
6.6		15.247	Occupied Bandwidth measurements were made.



Modifications Required for Compliance

The EUT transmit power was set to 10.6 dBm. The power setting in the original application was 11.6dBm. This power setting is fixed in firmware and therefore the user cannot change the power settings. Ecovent is taking care of the firmware and sets fixed power settings at the factory.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

page 7 of 30



Test Results

Bandwidth

LIMIT

The minimum 6 dB bandwidth shall be at least 500 kHz. [15.247(a) (2)]

MEASUREMENTS / RESULTS

6dB BANDWIDTH															
Date: 15-Oct-15	Company: ecoVent					Work Order: P2928									
Engineer: Tuyen Truong	EUT Desc: Wall Sensor					EUT Operating Voltage/Frequency: 120Vac/60Hz									
Temp: 22°C	Humidity: 33%	Pressure: 1006mBar													
Frequency Range: 904 - 926 MHz				Measurement Distance: 3 m											
Notes: FSK2 modulation with 100% duty cycle															
Antenna Polarization (H / V)	Frequency (MHz)	Reading (KHz)					6dB BW								
		704.953	705.464	695.323			Limit (KHz)	Margin (KHz)	Result (Pass/Fail)						
V	904						≥500	+204.953	Pass						
V	915						≥500	+205.464	Pass						
V	926						≥500	+195.323	Pass						
Test Site: EMI Chamber 1		Cable 1: Asset #2051		Cable 2: Asset #2053		Cable 3: ---									
Analyzer: Gold		Preamp: none		Antenna: Red-Brown		Preselector: ---									
CSsoft Radiated Emissions Calculator v 1.017.148															
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor															
Copyright Curtis-Straus LLC 2000															

Rev.10/8/2015

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range		Cat	Calibration Due	Calibrated on
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz		II	3/21/2017	3/21/2015
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown BiLog	30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables	Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
TH A#2080	HTC-1	HDE		2080	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 8 of 30

Testing Cert. No. 1627-01

PLOT(s)

* Agilent 10:49:43 Oct 15, 2015

R T



Transmit Freq Error 146.135 kHz
x dB Bandwidth 704.953 kHz

C:\temp.gif file saved

904 MHz - 6dB Bandwidth

* Agilent 11:37:44 Oct 15, 2015

R T



Transmit Freq Error 131.946 kHz
x dB Bandwidth 705.464 kHz

C:\temp.gif file saved

915 MHz - 6dB Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 9 of 30

* Agilent 09:49:10 Oct 15, 2015

R T



Transmit Freq Error 109.875 kHz
x dB Bandwidth 695.323 kHz

C:\temp.gif file saved

926 MHz - 6dB Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 10 of 30

Testing Cert. No. 1627-01

Fundamental Emission Output Power

LIMIT

Conducted Output Power

1 Watt

[15.247(b) (3)]

Per 558074 D01 DTS Measurement Guidance v0303 Section 9.2.2.2 (AVGSA-1 - Average Conducted Output Power)

MEASUREMENTS / RESULTS

Fundamental Emission Output Power																				
Date: 15-Oct-15		Company: ecoVent		Work Order: P2928																
Engineer: Tuyen Truong		EUT Desc: Wall Sensor		EUT Operating Voltage/Frequency: 120Vac/60Hz																
Temp: 22°C		Humidity: 33%		Pressure: 1006mBar																
Frequency Range: 904 - 926 MHz											Measurement Distance: 3 m									
Notes: FSK2 modulation with 100% duty cycle AVGSA-1																				
Antenna Polarization (H/V)	Frequency (MHz)	Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBuV/m)	Adjusted ERP Reading (dBm)	Final Conducted Reading (dBm)	FCC 15.247											
									Limit (dBm)	Margin (dB)	Result (Pass/Fail)									
V	904.0	73.8	0.0	22.5	1.7	98.0	2.77	4.77	30.0	-25.23	Pass									
V	915.0	72.1	0.0	22.4	1.7	96.2	0.97	2.97	30.0	-27.03	Pass									
V	926.0	71.4	0.0	22.5	1.7	95.6	0.37	2.37	30.0	-27.63	Pass									
Table Result: Pass by -25.23 dB				Worst Freq: 904.0 MHz																
Test Site: EMI Chamber 1			Cable 1: Asset #2051			Cable 2: Asset #2053			Cable 3: ---											
Analyzer: Gold			Preamp: none			Antenna: Red-Brown			Preselector: ---											
CSsoft Radiated Emissions Calculator v1.017.148 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																				
Copyright Curtis-Straus LLC 2000																				

Rev.10/8/2015		Spectrum Analyzers / Receivers/Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold		100Hz-26.5 GHz		E4407B		Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites		EMI Chamber 1		FCC Code	IC Code	VCCI Code	Range		Cat	Calibration Due	Calibrated on
				719150	2762A-6	A-0015	30-1000MHz		II	3/21/2017	3/21/2015
Antennas		Red-Brown Biolog		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
				30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables		Asset #2051		Range	Mfr				Cat	Calibration Due	Calibrated on
		Asset #2053		9kHz - 18GHz	Florida RF				II	3/8/2016	3/8/2015
		9kHz - 18GHz			Florida RF				II	3/8/2016	3/8/2015
Meteorological Meters		Weather Clock (Pressure Only)		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
		TH A#2080		BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
		HTC-1			HDE		2080	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 11 of 30

Testing Cert. No. 1627-01

PLOTS

* Agilent 10:33:26 Oct 15, 2015


R T

**Channel Power**73.79 dB μ V/789.4099 kHz**Power Spectral Density**14.82 dB μ V/Hz**C:\temp.gif file saved**

904 MHz - Channel Power

* Agilent 11:53:20 Oct 15, 2015

R T

**Channel Power**72.14 dB μ V/781.9808 kHz**Power Spectral Density**13.20 dB μ V/Hz**C:\temp.gif file saved**

915 MHz - Channel Power




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 12 of 30

* Agilent 10:09:10 Oct 15, 2015

R T



Channel Power

71.37 dB μ V/751.9024 kHz

Power Spectral Density

12.61 dB μ V/Hz

C:\temp.gif file saved

926 MHz - Channel Power



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 13 of 30

Radiated Spurious Emissions

LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth that contains the highest level of desired power based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB ...

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

[15.247(d)]

MEASUREMENTS / RESULTS

Radiated Band Edge (902 – 928 MHz)

Radiated Emissions Table - Band Edge Readings													
Date: 15-Oct-15	Company: ecoVent					Work Order: P2928							
Engineer: Tuyen Truong	EUT Desc: Wall Sensor					EUT Operating Voltage/Frequency: 120VAC, 60Hz							
Temp: 22°C	Humidity: 33%					Pressure: 1006mBar							
Frequency Range: BandEdge					Measurement Distance: 3 m								
Notes: The Limit here is set to -30dB from the max in-band peak PSD level in 100kHz rbw (this corresponds to 67.5dB _{uV/m})													
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB _{uV})	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB _{uV/m})	---						
							Limit (dB _{uV/m})	Margin (dB)	Result (Pass/Fail)				
V	902.0	38.5	0.0	22.5	1.7	62.7	---	---	---				
V	928.0	37.4	0.0	22.5	1.6	61.5	---	---	---				
Table Result: Pass				Worst Freq: 902.0 MHz									
Test Site: EMI Chamber 1	Cable 1: Asset #2051			Cable 2: Asset #2053			Cable 3: ---						
Analyzer: Gold	Preamp: none			Antenna: Red-Brown			Preselector: ---						
CSsoft Radiated Emissions Calculator	v 1.017.148						Copyright Curtis-Straus LLC 2000						
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor													

Radiated Emissions - maximum in-band peak PSD level in 100kHz													
Date: 15-Oct-15	Company: ecoVent					Work Order: P2928							
Engineer: Tuyen Truong	EUT Desc: Wall Sensor					EUT Operating Voltage/Frequency: 120VAC, 60Hz							
Temp: 22°C	Humidity: 33%					Pressure: 1006mBar							
Frequency Range: Fundamental Reading					Measurement Distance: 3 m								
Notes:													
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB _{uV})	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB _{uV/m})	---						
							Limit (dB _{uV/m})	Margin (dB)	Result (Pass/Fail)				
MAX Peak PSD in 100kHz BW	904.2	73.3	0.0	22.5	1.7	97.5	---	---	---				
Test Site: EMI Chamber 1	Cable 1: Asset #2051			Cable 2: Asset #2053			Cable 3: ---						
Analyzer: Gold	Preamp: none			Antenna: Red-Brown			Preselector: ---						
CSsoft Radiated Emissions Calculator	v 1.017.148						Copyright Curtis-Straus LLC 2000						
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor													



Rev.10/8/2015

Spectrum Analyzers / Receivers /Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold		100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites		FCC Code	IC Code	VCCI Code	Range		Cat	Calibration Due	Calibrated on
EMI Chamber 1		719150	2762A-6	A-0015	30-1000MHz		II	3/21/2017	3/21/2015
Antennas		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown Bilog		30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables		Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
TH A#2080		HTC-1	HDE		2080	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 15 of 30

Radiated Spurious EMI (30 to 10000 MHz)

Radiated Emissions Table

Date: 16-Oct-15	Company: ecoVent	Work Order: P2928											
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz											
Oct 16 -Temp: 22°C	Humidity: 0.31	Pressure: 1003mBar											
Oct 21 - Temp: 22.4°C	Humidity: 32%	Pressure: 1018mBar											
Frequency Range: 30 - 1000MHz		Measurement Distance: 3 m											
Notes: TX on 904 MHz Power setting: 10.6 dBm Spectrum Analyzer setting: RBW = 120KHz , VBW = 1MHz, span = 0 Hz, 401 points, sweep rate = auto, Detector: QuasiPeak.		EUT TX Freq: 904 - 926 MHz											
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)	--			FCC 15.209			
							Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	
v	38.0	32.8	25.3	15.4	0.4	23.3	---	---	---	40.0	-16.7	Pass	
v	73.0	29.8	25.4	8.2	0.5	13.1	---	---	---	40.0	-26.9	Pass	
v	108.0	35.5	25.3	12.2	0.5	22.9	---	---	---	43.5	-20.6	Pass	
h	108.0	35.5	25.3	12.2	0.5	22.9	---	---	---	43.5	-20.6	Pass	
v	149.9	38.8	25.1	12.5	0.7	26.9	---	---	---	43.5	-16.6	Pass	
v	608.0	37.2	25.2	18.9	1.4	32.3	---	---	---	46.0	-13.7	Pass	
h	608.0	36.1	25.2	18.9	1.4	31.2	---	---	---	46.0	-14.8	Pass	
v	614.0	33.9	25.3	19.2	1.5	29.3	---	---	---	46.0	-16.7	Pass	
h	614.0	31.9	25.3	19.2	1.5	27.3	---	---	---	46.0	-18.7	Pass	
v	961.6	30.8	24.4	22.9	1.7	31.0	---	---	---	54.0	-23.0	Pass	
Table Result: Pass		by	-13.7 dB		Worst Freq: 608.0 MHz								
Test Site: EMI Chamber 1 Analyzer: Gold	Cable 1: Asset #2051 Preamp: Blue-Blk		Cable 2: Asset #2053 Antenna: Red-Brown		Cable 3: --- Preselector: ---								
CSsoft Radiated Emissions Calculator v 1.017.148											Copyright Curtis-Straus LLC 2000		
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor													

Rev.10/8/2015

Spectrum Analyzers / Receivers /Preselectors Gold	Range 100Hz-26.5 GHz	MN E4407B	Mfr Agilent	SN MY45113816	Asset 1284	Cat I	Calibration Due 4/22/2016	Calibrated on 4/22/2015
Radiated Emissions Sites EMI Chamber 1	FCC Code 719150	IC Code 2762A-6	VCCI Code A-0015	Range 30-1000MHz		Cat II	Calibration Due 3/21/2017	Calibrated on 3/21/2015
Preamps /Couplers Attenuators / Filters Blue-Black	Range 0.009-2000MHz	MN ZFL-1000-LN	Mfr CS	SN N/A	Asset 800	Cat II	Calibration Due 12/26/2015	Calibrated on 12/26/2014
Antennas Red-Brown Bilog	Range 30-2000MHz	MN JB1	Mfr Sunol	SN A0032406	Asset 1218	Cat I	Calibration Due 12/4/2016	Calibrated on 12/4/2014
Cables Asset #2051 Asset #2053	Range 9KHz - 18GHz 9KHz - 18GHz		Mfr Florida RF Florida RF			Cat II	Calibration Due 3/8/2016 3/8/2016	Calibrated on 3/8/2015 3/8/2015
Meteorological Meters Weather Clock (Pressure Only) TH A#2080	MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2080	Cat I II	Calibration Due 3/19/2016 4/2/2016		Calibrated on 3/19/2014 4/2/2015

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 16 of 30

Testing Cert. No. 1627-01

Radiated Emissions Table

Date: 28-Oct-15	Company: ecoVent	Work Order: P2928													
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz													
Temp: 21°C	Humidity: 26%	Pressure: 1013 mBar													
Frequency Range: 1 - 6 GHz		Measurement Distance: 3 m													
Notes: 10.6 dBm power setting TX on 904 MHz Spectrum Analyzer setting: RBW = 1MHz , VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904-926 MHz													
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB _µ V)	Average Reading (dB _µ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB _µ V/m)	Adjusted Avg Reading (dB _µ V/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average			
h	1808.0	38.84	28.1	18.8	30.6	3.2	53.8	43.1	74.0	-20.2	Pass	54.0	-10.9	Pass	
	1808.0	38.61	26.9	18.8	30.6	3.2	53.6	41.9	74.0	-20.4	Pass	54.0	-12.1	Pass	
	2712.0	39.66	27.8	18.9	32.9	4.0	57.7	45.8	74.0	-16.3	Pass	54.0	-8.2	Pass	
	2712.0	37.5	24.7	18.9	32.9	4.0	55.5	42.7	74.0	-18.5	Pass	54.0	-11.3	Pass	
	3616.0	39.08	27.4	18.5	33.3	4.6	58.5	46.8	74.0	-15.5	Pass	54.0	-7.2	Pass	
	3616.0	36.57	21.8	18.5	33.3	4.6	56.0	41.2	74.0	-18.0	Pass	54.0	-12.8	Pass	
	4520.0	39.62	30.9	17.1	34.2	5.0	61.7	53.0	74.0	-12.3	Pass	54.0	-1.0	Pass	
	5424.0	37.08	23.6	16.4	34.8	5.6	61.1	47.6	74.0	-12.9	Pass	54.0	-6.4	Pass	
	5424.0	37.09	23.9	16.4	34.8	5.6	61.1	47.9	74.0	-12.9	Pass	54.0	-6.1	Pass	
Table Result: Pass		by	-1.0 dB							Worst Freq: 4520.0 MHz					
Test Site: EMI Chamber 2	Cable 1: Asset #2052				Cable 2: Asset #1787				Cable 3: ---						
Analyzer: Asset #1327	Preamp: Brown				Antenna: Blue Horn				Preselector: ---						
CSSoft Radiated Emissions Calculator	v 1.017.148											Copyright Curtis-Straus LLC 2000			
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor															

Radiated Emissions Table

Date: 28-Oct-15	Company: ecoVent	Work Order: P2928														
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz														
Temp: 21°C	Humidity: 26%	Pressure: 1013 mBar														
Frequency Range: 6 - 10 GHz		Measurement Distance: 1 m														
Notes: 10.6 dBm power setting TX on 904 MHz Spectrum Analyzer setting: RBW = 1MHz , VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904-926 MHz														
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB _µ V)	Average Reading (dB _µ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB _µ V/m)	Adjusted Avg Reading (dB _µ V/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average				
v	9040.0	39.23	31.3	15.7	36.6	7.4	67.5	59.6	83.5	-16.0	Pass	63.5	-3.9	Pass		
	Table Result: Pass						by -3.9 dB						Worst Freq: 9040.0 MHz			
Test Site: EMI Chamber 2	Cable 1: Asset #2052				Cable 2: Asset #1787				Cable 3: ---							
Analyzer: Asset #1327	Preamp: Brown				Antenna: Blue Horn				Preselector: ---							
CSSoft Radiated Emissions Calculator	v 1.017.148								Copyright Curtis-Straus LLC 2000							
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																

Rev.10/19/2015

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
SA EMI Chamber (1327)	9kHz-13.2 GHz	E4405B	Agilent	MY45103416	1327	I	7/10/2016	7/10/2015
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range	Cat	Calibration Due	Calibrated on	
EMI Chamber 2	719150	2762A-7	A-0015	30-1000MHz	II	3/22/2017	3/22/2015	
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Brown	1-10GHz	CS	CS	N/A	1523	II	4/9/2016	10/8/2015
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Blue Horn	1-18Ghz	3117	ETS	157647	1861	I	2/8/2017	2/8/2015
Cables	Range	Mfr			Cat	Calibration Due	Calibrated on	
Asset #2052	9kHz - 18GHz	Florida RF			II	3/8/2016	3/8/2015	
Asset #1787	9kHz - 18GHz	Florida RF			II	3/21/2016	3/21/2015	
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
TH A#2081	HTC-1	HDE		2081	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Emissions Table

Date: 21-Oct-15	Company: ecoVent	Work Order: P2928										
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz										
Temp: 22.4°C	Humidity: 32%	Pressure: 1018mBar										
Frequency Range: 30 to 1000 MHz		Measurement Distance: 3 m										
Notes: TX on 915 MHz Power setting : 10.6 dBm Spectrum Analyzer setting: RBW = 120KHz , VBW = 1MHz, span = 0 Hz, 401 points, sweep rate = auto, Detector: QuasiPeak.		EUT TX Freq: 904 - 926 MHz										
Antenna Polarization (H/V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)	---			FCC 15.209		
							Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)

v	38.25	34.9	25.3	15.2	0.4	25.2	---	---	---	40.0	-14.8	Pass
v	73.0	29.0	25.4	8.2	0.5	12.3	---	---	---	40.0	-27.7	Pass
v	108.75	29.7	25.3	12.3	0.6	17.3	---	---	---	43.5	-26.2	Pass
v	149.9	34.2	25.1	12.5	0.7	22.3	---	---	---	43.5	-21.2	Pass
h	608.0	38.6	25.2	18.9	1.4	33.7	---	---	---	46.0	-12.3	Pass
v	608.0	37.9	25.2	18.9	1.4	33.0	---	---	---	46.0	-13.0	Pass
h	614.0	34.1	25.3	19.2	1.5	29.5	---	---	---	46.0	-16.5	Pass
v	614.0	33.4	25.3	19.2	1.5	28.8	---	---	---	46.0	-17.2	Pass
v	962.7	32.0	24.4	22.9	1.7	32.2	---	---	---	54.0	-21.8	Pass

Table Result:	Pass	by	-12.3 dB	Worst Freq:	608.0 MHz
Test Site: EMI Chamber 1	Cable 1: Asset #2051		Cable 2: Asset #2053		
Analyzer: Gold	Preamp: Blue-Blk		Antenna: Red-Brown		
CSsoft Radiated Emissions Calculator	v 1.017.148		Copyright Curtis-Straus LLC 2000		
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor					

Rev.10/8/2015

Spectrum Analyzers / Receivers / Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range		Cat	Calibration Due	Calibrated on
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz		II	3/21/2017	3/21/2015
Preamps / Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Blue-Black	0.009-2000MHz	ZFL-1000-LN	CS	N/A	800	II	12/26/2015	12/26/2014
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown BiLog	30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables	Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014
TH A#2080		HTC-1	HDE		2080	II	4/2/2016	4/2/2015

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Radiated Emissions Table

Date: 28-Oct-15	Company: ecoVent	Work Order: P2928												
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz												
Temp: 21°C	Humidity: 26%	Pressure: 1013 mBar												
Frequency Range: 1 - 6 GHz		Measurement Distance: 3 m												
Notes: 10.6 dBm power setting TX on 915 MHz Spectrum Analyzer setting: RBW = 1MHz , VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904-926 MHz												
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average		
									Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)

h	1830.0	37.79	26.5	18.9	30.7	3.3	52.9	41.6	74.0	-21.1	Pass	54.0	-12.4	Pass
v	1830.0	37.44	26.8	18.9	30.7	3.3	52.5	41.9	74.0	-21.5	Pass	54.0	-12.1	Pass
h	2745.0	39.54	29.5	18.9	33.0	4.0	57.6	47.6	74.0	-16.4	Pass	54.0	-6.4	Pass
v	2745.0	38.6	27.7	18.9	33.0	4.0	56.7	45.8	74.0	-17.3	Pass	54.0	-8.2	Pass
h	3660.0	40.19	31.4	18.5	33.4	4.7	59.8	51.0	74.0	-14.2	Pass	54.0	-3.0	Pass
v	3660.0	37.3	26.7	18.5	33.4	4.7	56.9	46.3	74.0	-17.1	Pass	54.0	-7.7	Pass
h	4575.0	39.52	30.6	17.2	34.3	4.8	61.4	52.5	74.0	-12.6	Pass	54.0	-1.5	Pass
v	4575.0	37.86	28.3	17.2	34.3	4.8	59.8	50.2	74.0	-14.2	Pass	54.0	-3.8	Pass
h	5490.0	37.01	24.4	16.4	34.8	5.5	60.9	48.3	74.0	-13.1	Pass	54.0	-5.7	Pass
v	5490.0	37.14	25.9	16.4	34.8	5.5	61.0	49.8	74.0	-13.0	Pass	54.0	-4.2	Pass

Table Result:	Pass	by	-1.5 dB	Worst Freq:	4575.0 MHz
Test Site: EMI Chamber 2	Cable 1: Asset #2052		Cable 2: Asset #1787		Cable 3: ---
Analyzer: Asset #1327	Preamp: Brown		Antenna: Blue Horn		Preselector: ---
CSsoft Radiated Emissions Calculator	v 1.017.148		Copyright Curtis-Straus LLC 2000		
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor					



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Emissions Table

Date: 28-Oct-15	Company: ecoVent	Work Order: P2928												
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz												
Temp: 21°C	Humidity: 26%	Pressure: 1013 mBar												
Frequency Range: 6 - 10 GHz		Measurement Distance: 1 m												
Notes: TX on 915 MHz, Power setting: 10.6dBm Spectrum Analyzer setting: RBW = 1MHz, VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904-926 MHz												
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dBuV)	Average Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dBuV/m)	Adjusted Avg Reading (dBuV/m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average		
									Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)
v	9150.0	39.84	32.2	15.7	36.7	7.6	68.4	60.8	83.5	-15.1	Pass	63.5	-2.7	Pass

Table Result: Pass by -2.7 dB**Worst Freq:** 9150.0 MHz

Test Site: EMI Chamber 2 Analyzer: Asset #1327	Cable 1: Asset #2052 Preamp: Brown	Cable 2: Asset #1787 Antenna: Blue Horn	Cable 3: --- Preselector: ---
CCsoft Radiated Emissions Calculator v 1.017.148 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor			

Copyright Curtis-Straus LLC 2000

Rev.10/19/2015

Spectrum Analyzers / Receivers /Preselectors SA EMI Chamber (1327)	Range 9kHz-13.2 GHz	MN E4405B	Mfr Agilent	SN MY45103416	Asset 1327	Cat I	Calibration Due 7/10/2016	Calibrated on 7/10/2015
Radiated Emissions Sites EMI Chamber 2	FCC Code 719150	IC Code 2762A-7	VCCI Code A-0015	Range 30-1000MHz		Cat II	Calibration Due 3/22/2017	Calibrated on 3/22/2015
Preamps /Couplers Attenuators / Filters Brown	Range 1-10GHz	MN CS	Mfr CS	SN N/A	Asset 1523	Cat II	Calibration Due 4/9/2016	Calibrated on 10/8/2015
Antennas Blue Horn	Range 1-18Ghz	MN 3117	Mfr ETS	SN 157647	Asset 1861	Cat I	Calibration Due 2/8/2017	Calibrated on 2/8/2015
Cables Asset #2052 Asset #1787	Range 9kHz - 18GHz 9kHz - 18GHz		Mfr Florida RF Florida RF			Cat II II	Calibration Due 3/8/2016 3/21/2016	Calibrated on 3/8/2015 3/21/2015
Meteorological Meters Weather Clock (Pressure Only) TH A#2081	MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2081	Cat I II	Calibration Due 3/19/2016 4/2/2016	Calibrated on 3/19/2014 4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Radiated Emissions Table

Date: 21-Oct-15	Company: ecoVent	Work Order: P2928										
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz										
Temp: 22.4°C	Humidity: 32%	Pressure: 1018mBar										
Frequency Range: 30 to 1000 MHz		Measurement Distance: 3 m										
Notes: TX on 926 MHz Power setting: 10.6 dBm Spectrum Analyzer setting: RBW = 120KHz, VBW = 1MHz, span = 0 Hz, 401 points, sweep rate = auto, Detector: QuasiPeak.		EUT TX Freq: 904 - 926 MHz										
Antenna Polarization (H/V)	Frequency (MHz)	Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBuV/m)	---			FCC 15.209		
							Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)
v	38.25	24.7	25.3	15.2	0.4	15.0	---	---	---	40.0	-25.0	Pass
v	73.0	30.3	25.4	8.2	0.5	13.6	---	---	---	40.0	-26.4	Pass
v	108.75	27.2	25.3	12.3	0.6	14.8	---	---	---	43.5	-28.7	Pass
v	149.9	33.0	25.1	12.5	0.7	21.1	---	---	---	43.5	-22.4	Pass
v	608.0	39.9	25.2	18.9	1.4	35.0	---	---	---	46.0	-11.0	Pass
h	608.0	39.5	25.2	18.9	1.4	34.6	---	---	---	46.0	-11.4	Pass
h	614.0	34.6	25.3	19.2	1.5	30.0	---	---	---	46.0	-16.0	Pass
v	614.0	34.8	25.3	19.2	1.5	30.2	---	---	---	46.0	-15.8	Pass
v	962.7	29.6	24.4	22.9	1.7	29.8	---	---	---	54.0	-24.2	Pass

Table Result: Pass by -11.0 dB**Worst Freq:** 608.0 MHz

Test Site: EMI Chamber 1 Analyzer: Gold	Cable 1: Asset #2051 Preamp: Blue-Blk	Cable 2: Asset #2053 Antenna: Red-Brown	Cable 3: --- Preselector: ---
CCsoft Radiated Emissions Calculator v 1.017.148 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor			

Copyright Curtis-Straus LLC 2000



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 19 of 30

Rev.10/8/2015

Spectrum Analyzers / Receivers / Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold		100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	EMI Chamber 1	FCC Code	IC Code	VCCI Code	Range				
		719150	2762A-6	A-0015	30-1000MHz		II	Calibration Due	Calibrated on
Preamps / Couplers Attenuators / Filters	Blue-Black	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		0.009-2000MHz	ZFL-1000-LN	CS	N/A	800	II	12/26/2015	12/26/2014
Antennas	Red-Brown BiLog	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables		Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters			MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)			BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014
TH A#2080			HTC-1	HDE		2080	II	4/2/2016	4/2/2015

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Radiated Emissions Table

Date: 21-Oct-15	Company: ecoVent	Work Order: P2928													
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz													
Temp: 22.4°C	Humidity: 32%	Pressure: 1018mBar													
Frequency Range: 1 - 6 GHz		Measurement Distance: 3 m													
Notes: TX on High channel Power setting: 10.6 dBm Spectrum Analyzer setting: RBW = 1MHz , VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904 - 926 MHz													
Antenna Polarization (H / V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC 15.209 High Frequency - Peak	FCC 15.209 High Frequency - Average					
									Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	
v	1852.0	39.59	30.8	18.9	30.9	2.7	54.3	45.5	74.0	-19.7	Pass	54.0	-8.5	Pass	
v	2778.0	40.04	28.8	18.9	33.0	3.5	57.6	46.4	74.0	-16.4	Pass	54.0	-7.6	Pass	
h	2778.0	41.87	30.3	18.9	33.0	3.5	59.5	47.9	74.0	-14.5	Pass	54.0	-6.1	Pass	
v	3704.0	41.01	29.5	18.5	33.4	4.2	60.1	48.6	74.0	-13.9	Pass	54.0	-5.4	Pass	
h	3704.0	43.56	31.7	18.5	33.4	4.2	62.7	50.8	74.0	-11.3	Pass	54.0	-3.2	Pass	
v	4630.0	41.58	30.4	17.1	34.3	4.6	63.4	52.2	74.0	-10.6	Pass	54.0	-1.8	Pass	
h	4630.0	43.5	32.0	17.1	34.3	4.6	65.3	53.8	74.0	-8.7	Pass	54.0	-0.2	Pass	
v	5556.0	38.33	25.4	16.4	34.9	5.2	62.0	49.1	74.0	-12.0	Pass	54.0	-4.9	Pass	
h	5556.0	37.7	23.2	16.4	34.9	5.2	61.4	46.9	74.0	-12.6	Pass	54.0	-7.1	Pass	
Table Result: Pass by -0.2 dB		Worst Freq: 4630.0 MHz													
Test Site: EMI Chamber 1		Cable 1: Asset #2051		Cable 2: Asset #2053		Cable 3: ---									
Analyzer: Gold		Preamp: Brown		Antenna: Blue Horn		Preselector: ---								Copyright Curtis-Straus LLC 2000	
CSsoft Radiated Emissions Calculator v 1.017.148															
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor															

Rev.10/19/2015

Spectrum Analyzers / Receivers / Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold		100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	EMI Chamber 1	FCC Code	IC Code	VCCI Code	Range				
		719150	2762A-6	A-0015	30-1000MHz		II	Calibration Due	Calibrated on
Preamps / Couplers Attenuators / Filters	Brown	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		1-10GHz	CS	CS	N/A	1523	II	4/9/2016	10/8/2015
Antennas	Blue Horn	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
		1-18Ghz	3117	ETS	157647	1861	I	2/8/2017	2/8/2015
Cables		Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053		9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters			MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)			BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014
TH A#2080			HTC-1	HDE		2080	II	4/2/2016	4/2/2015

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Radiated Emissions Table

Date: 29-Oct-15	Company: ecoVent	Work Order: P2928												
Engineer: Tuyen Truong	EUT Desc: Wall Sensor	EUT Operating Voltage/Frequency: 120Vac/60Hz												
Temp: 22°C	Humidity: 51%	Pressure: 998mBar												
Frequency Range: 6 to 10 GHz		Measurement Distance: 1 m												
Notes: TX on 926 MHz Power setting: 10.6 dBm Spectrum Analyzer setting: RBW = 1MHz , VBW = 3MHz (Peak reading) & VBW = 10 Hz (Avg reading), span ≤ 10 MHz, 401 points, sweep rate = auto, Detector: Peak.		EUT Tx Freq: 904 - 926 MHz												
Antenna Polarization (H / V)	Frequency (MHz)	Peak Reading (dB _{UV})	Average Reading (dB _{UV})	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB _{UV} /m)	Adjusted Avg Reading (dB _{UV} /m)	FCC 15.209 High Frequency - Peak			FCC 15.209 High Frequency - Average		
									Limit (dB _{UV} /m)	Margin (dB)	Result (Pass/Fail)	Limit (dB _{UV} /m)	Margin (dB)	Result (Pass/Fail)
v	9260.0	39.93	31.4	15.7	36.8	7.6	68.6	60.1	83.5	-14.9	Pass	63.5	-3.4	Pass

Table Result: Pass by -3.4 dB**Worst Freq:** 9260.0 MHz

Test Site: EMI Chamber 2 Analyzer: Asset #1327 CSsoft Radiated Emissions Calculator v 1.017.148	Cable 1: Asset #2052 Preamp: Brown	Cable 2: Asset #1787 Antenna: Blue Horn	Cable 3: --- Preselector: ---
Copyright Curtis-Straus LLC 2000 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor			

Rev.10/19/2015

Spectrum Analyzers / Receivers /Preselectors SA EMI Chamber (1327)	Range 9kHz-13.2 GHz	MN E4405B	Mfr Agilent	SN MY45103416	Asset 1327	Cat I	Calibration Due 7/10/2016	Calibrated on 7/10/2015
Radiated Emissions Sites EMI Chamber 2	FCC Code 719150	IC Code 2762A-7	VCCI Code A-0015	Range 30-1000MHz		Cat II	Calibration Due 3/22/2017	Calibrated on 3/22/2015
Preamps /Couplers Attenuators / Filters Brown	Range 1-10GHz	MN CS	Mfr CS	SN N/A	Asset 1523	Cat II	Calibration Due 4/9/2016	Calibrated on 10/8/2015
Antennas Blue Horn	Range 1-18Ghz	MN 3117	Mfr ETS	SN 157647	Asset 1861	Cat I	Calibration Due 2/8/2017	Calibrated on 2/8/2015
Cables Asset #2052 Asset #1787	Range 9kHz - 18GHz 9kHz - 18GHz		Mfr Florida RF Florida RF			Cat II II	Calibration Due 3/8/2016 3/21/2016	Calibrated on 3/8/2015 3/21/2015
Meteorological Meters Weather Clock (Pressure Only) TH A#2081		MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2081	Cat I II	Calibration Due 3/19/2016 4/2/2016	Calibrated on 3/19/2014 4/2/2015

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

BUREAU
VERITAS



page 21 of 30

Testing Cert. No. 1627-01

Power Spectral Density

LIMIT

...the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.
[15.247(e)]

Per 558074 D01 DTS Measurement Guidance v0303 Section 10.3 (AVG PSD-1)

MEASUREMENTS / RESULTS

Power Spectral Density											Work Order: P2928													
Date: 15-Oct-15		Company: ecoVent																						
Engineer: Tuyen Truong		EUT Desc: Wall Sensor											EUT Operating Voltage/Frequency: 120Vac/60Hz											
Temp: 22°C		Humidity: 33%											Pressure: 1006mBar											
Frequency Range: 904 - 926 MHz													Measurement Distance: 3 m											
Notes: FSK2 modulation with 100% duty cycle AVG PSD-1																								
FCC 15.247																								
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB μ V/m)	Adjusted ERP Reading (dBm)	Final Conducted Reading (dBm)		Limit (dBm)			Margin (dB)	Result (Pass/Fail)										
V	904.0	64.7	0.0	22.5	1.7	88.9	-6.33	-4.33		8.0			-12.33	Pass										
V	915.0	63.3	0.0	22.4	1.7	87.4	-7.83	-5.83		8.0			-13.83	Pass										
V	926.0	61.4	0.0	22.5	1.7	85.6	-9.63	-7.63		8.0			-15.63	Pass										
Table Result: Pass by -12.33 dB											Worst Freq: 904.0 MHz													
Test Site: EMI Chamber 1		Cable 1: Asset #2051			Cable 2: Asset #2053			Cable 3: ---			Preselector: ---													
Analyzer: Gold		Preamp: none			Antenna: Red-Brown						Copyright Curtis-Straus LLC 2000													
CSsoft Radiated Emissions Calculator v 1.017.148 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																								

Rev.10/8/2015

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range		Cat	Calibration Due	Calibrated on
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz		II	3/21/2017	3/21/2015
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown BiLog	30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables	Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
TH A#2080	HTC-1	HDE		2080	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 22 of 30

Testing Cert. No. 1627-01

PLOTS


* Agilent 10:55:00 Oct 15, 2015

R T

Mkr1 903.7867 MHz
64.72 dB μ V

* Agilent 11:58:38 Oct 15, 2015

R T

Mkr1 914.7806 MHz
63.29 dB μ V

915 MHz - PSD




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 23 of 30

* Agilent 11:17:56 Oct 15, 2015

R T

Mkr1 925.7767 MHz
61.35 dB μ V

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 24 of 30

Testing Cert. No. 1627-01

Occupied Bandwidth

REQUIREMENT

When an occupied bandwidth is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured. [RSS-GEN 6.6]

MEASUREMENTS / RESULTS

99% OCCUPIED BANDWIDTH																
Date: 15-Oct-15	Company: ecoVent							Work Order: P2928								
Engineer: Tuyen Truong	EUT Desc: Wall Sensor							EUT Operating Voltage/Frequency: 120Vac/60Hz								
Temp: 22°C	Humidity: 33%							Pressure: 1006mBar								
Frequency Range: 904 - 926 MHz					Measurement Distance: 3 m											
Notes: FSK2 modulation with 100% duty cycle																
Antenna Polarization (H / V)	Frequency (MHz)	Occupied Bandwidth Reading (KHz)														
V	904	789.4099														
V	915	781.9808														
V	926	751.9024														
Test Site: EMI Chamber 1	Cable 1: Asset #2051	Cable 2: Asset #2053			Cable 3: ---											
Analyzer: Gold	Preamp: none	Antenna: Red-Brown			Preselector: ---											
CSsoft Radiated Emissions Calculator	v 1.017.148	Copyright Curtis-Straus LLC 2000														
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																

Rev.10/8/2015

Spectrum Analyzers / Receivers/Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Gold	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	4/22/2016	4/22/2015
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range				
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz				
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Brown BiLog	30-2000MHz	JB1	Sunol	A0032406	1218	I	12/4/2016	12/4/2014
Cables	Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2051	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Asset #2053	9kHz - 18GHz		Florida RF			II	3/8/2016	3/8/2015
Meteorological Meters	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on	
Weather Clock (Pressure Only)	BA928	Oregon Scientific	C3166-1	831	I	3/19/2016	3/19/2014	
TH A#2080	HTC-1	HDE		2080	II	4/2/2016	4/2/2015	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




page 25 of 30

Testing Cert. No. 1627-01

Plot(s)

* Agilent 10:28:18 Oct 15, 2015

R T




Transmit Freq Error 44.412 kHz
x dB Bandwidth 498.857 kHz

C:\temp.gif file saved

904 MHz - Occupied Bandwidth

* Agilent 11:49:03 Oct 15, 2015

R T



Transmit Freq Error 34.526 kHz
Occupied Bandwidth 498.191 kHz

C:\temp.gif file saved

915 MHz - Occupied Bandwidth




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 26 of 30

Agilent 10:04:38 Oct 15, 2015

R T



Transmit Freq Error 18.531 kHz
x dB Bandwidth 497.846 kHz

C:\temp.gif file saved

926 MHz - Occupied Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 27 of 30

Testing Cert. No. 1627-01

Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz) NIST CISPR	5.6dB 4.6dB	N/A 5.2dB (Ucispr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions NIST CISPR	3.9dB 3.6dB	N/A 3.6dB (Ucispr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB
Conducted emission of receivers	1.3dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB
Humidity	2.37%	5%
Temperature	0.7°C	1.0°C
Time	4.1%	10%
RF Power Density, Conducted	0.4dB	3dB
DC and low frequency voltages	1.3%	3%
Voltage (AC, <10kHz)	1.3%	2%
Voltage (DC)	0.62%	1%
The above reflects a 95% confidence level		



Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "**BUREAU VERITAS**," "**BUREAU VERITAS CONSUMER PRODUCTS SERVICES**," "**BVCPs**," "**MTL**," "**ACTS**," "**MTL-ACTS**" and **CURTIS-STRAUS** (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.
14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 29 of 30

Testing Cert. No. 1627-01

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request. Rev.160009121(2)_#684340 v14CS



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 30 of 30