

TEST REPORT

Product Name : Wireless Headphones
Brand Mark : SOUNDPEATS
Model No. : Life
Extension Model : Life Pro, Life2, Life2 Pro, Wings2, Wings2 Pro, Life3, Life4, Life5, Life6
FCC ID : 2AFTU-DD031
Report Number : BLA-EMC-202206-A2303
Date of Sample Receipt : 2022/6/8
Date of Test : 2022/6/8 to 2022/6/20
Date of Issue : 2022/6/20
Test Standard : 47 CFR Part 15, Part1.1307
47 CFR Part 15, Part2.1093
KDB447498D01 General RF Exposure Guidance v06
Test Result : Pass

Prepared for:

Shenzhen Soundsoul Information Technology Co.,Ltd
Room 1308-1309,Building B,Huihai Square,Chuangye Road, Longhua
District,Shenzhen,Guangdong,China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: *Charlie*

Review by: *Sueels*

Approved by: *Blue Zheng*

Date: 2022/6/20



REPORT REVISE RECORD

| Version No. | Date | Description |
|-------------|-----------|-------------|
| 00 | 2022/6/20 | Original |

BlueAsia

TABLE OF CONTENTS

| | | |
|-----|--|---|
| 1 | TEST SUMMARY | 4 |
| 2 | GENERAL INFORMATION | 5 |
| 3 | GENERAL DESCRIPTION OF E.U.T. | 5 |
| 4 | LABORATORY LOCATION | 5 |
| 5 | RF EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5.1 | STANDARD REQUIREMENT | 6 |
| 5.2 | LIMITS | 6 |
| 5.3 | EUT RF EXPOSURE | 6 |

BlueAsia

1 TEST SUMMARY

| Test item | Test Requirement | Test Method | Class/Severity | Result |
|-------------|---|-----------------------|--------------------|--------|
| RF Exposure | 47 CFR Part 1.1307, Part 2.1093, KDB 447498 | CFR 47 Part 2.1093 | CFR 47 Part 2.1093 | Pass |

BlueAsia

2 GENERAL INFORMATION

| | |
|------------------------|---|
| Applicant | Shenzhen Soundsoul Information Technology Co.,Ltd |
| Address | Room 1308-1309, Building B, Huihai Square, Chuangye Road, Longhua District, Shenzhen, Guangdong China |
| Manufacturer | Shenzhen Soundsoul Information Technology Co.,Ltd |
| Address | Room 1308-1309, Building B, Huihai Square, Chuangye Road, Longhua District, Shenzhen, Guangdong China |
| Factory | Shenzhen Soundsoul Information Technology Co.,Ltd |
| Address | Room 1308-1309, Building B, Huihai Square, Chuangye Road, Longhua District, Shenzhen, Guangdong China |
| Product Name | Wireless Headphones |
| Test Model No. | Life |
| Extension Model | Life Pro、Life2、Life2 Pro、Wings2、Wings2 Pro、Life3、Life4、Life5、Life6 |
| Remark | All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose. |

3 GENERAL DESCRIPTION OF E.U.T.

| | |
|-------------------------|-----|
| Hardware Version | N/A |
| Software Version | N/A |

| | |
|-----------------------------|-----------------------------------|
| Operation Frequency: | 2402MHz-2480MHz |
| Modulation Type: | GFSK, pi/4DQPSK, 8DPSK |
| Channel Spacing: | 1MHz |
| Number of Channels: | 79 |
| Antenna Type: | Chip Antenna |
| Antenna Gain: | 2.7dBi (Provided by the customer) |

4 LABORATORY LOCATION

All tests were performed at:
 BlueAsia of Technical Services(Shenzhen) Co., Ltd.
 Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
 Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
 No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

| Operational Mode: EDR (8DPSK worst case) | | | | | | |
|--|---|------------------------|-----------------------|-------|------------------|---------------------|
| Channel | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dB) | Maximum tune-up Power | | Calculated value | Exclusion threshold |
| | | | (dBm) | (mW) | | |
| 2402 MHz | 0.707 | ± 1 | 1.707 | 1.481 | 0.46 | 3.0 |
| 2441 MHz | 0.196 | ± 1 | 1.196 | 1.317 | 0.41 | |
| 2480 MHz | -0.906 | ± 1 | 0.094 | 1.022 | 0.32 | |
| Conclusion: the calculated value ≤ 3.0 , SAR is exempted. | | | | | | |

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.