

# FCC Test Report

## Part 15 subpart C

### Client Information:

Applicant: Guangzhou Maipai Electronics Co.,Ltd.  
Applicant add.: Room 202, No.94, Shinan Road, Xianchong Village, Qiaonan Street,  
Panyu District of Guangzhou.

### Product Information:

Product Name: wireless keyboard  
Model No.: KM-224W  
Derivative model No.: N/A  
Brand Name: N/A

Standards: CFR 47 FCC PART 15 SUBPART C:2013 section 249

### Prepared By:

**Dongguan Yaxu (AiT) Technology Limited**

Add. : No. 22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan,  
Guangdong, China.

Date of Receipt: Aug. 24, 2015

Date of Test: Aug. 24~ 28, 2015

Date of Issue: Aug. 28, 2015

Test Result: Pass


This device described above has been tested by Dongguan Yaxu (AiT) Technology Limited, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

ATT SZ commissioned AiT(Dongguan) to test the device described above, and then AiT(Dongguan) use the UTL(Dongguan)'s test site do this case.

This test report must not be used by the client to claim product endorsement by any agency of the U.S. government.



Reviewed by: \_\_\_\_\_



Approved by: \_\_\_\_\_

# 1 Contents

	Page
<b>COVER PAGE</b>	
<b>1 CONTENTS</b> .....	<b>2</b>
<b>2 TEST SUMMARY</b> .....	<b>3</b>
2.1 COMPLIANCE WITH FCC PART 15 SUBPART C .....	3
2.2 MEASUREMENT UNCERTAINTY .....	4
<b>3 TEST FACILITY</b> .....	<b>5</b>
3.1 DEVIATION FROM STANDARD .....	5
3.2 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
<b>4 GENERAL INFORMATION</b> .....	<b>5</b>
4.1 GENERAL DESCRIPTION OF EUT .....	5
4.2 TEST LOCATION .....	6
<b>5 DESCRIPTION OF TEST CONDITIONS</b> .....	<b>8</b>
5.1 E.U.T. OPERATION.....	8
5.2 EUT PERIPHERAL LIST .....	9
5.3 TEST PERIPHERAL LIST .....	9
<b>6 EQUIPMENTS LIST FOR ALL TEST ITEMS</b> .....	<b>10</b>
<b>7 TEST RESULT</b> .....	<b>11</b>
7.1 ANTENNA REQUIREMENT .....	11
7.2 FIELD STRENGTH OF FUNDAMENTAL& FIELD STRENGTH OF UNWANTED EMISSIONS& BAND EDGE .....	12
7.2.1 Duty cycle measurement:.....	17
7.2.2 Fundamental field strength measurement:.....	17
7.2.3 Radiated Emissions Test Data .....	18
7.2.4 Band Edge Measurement:.....	22
7.2.5 Restricted Bands Measurement:.....	23
7.3 OCCUPIED BANDWIDTH.....	24
7.4 CONDUCTED EMISSIONS AT MAINS TERMINALS 150 KHZ TO 30 MHZ .....	26
<b>8 PHOTOGRAPHS</b> .....	<b>27</b>
8.1 RADIATED EMISSION TEST SETUP .....	27
<b>9 EUT CONSTRUCTIONAL DETAILS</b> .....	<b>28</b>

## 2 Test Summary

### 2.1 Compliance with FCC Part 15 subpart C

Test	Test Requirement	Standard Paragraph	Result
Field Strength of Fundamental	FCC PART 15 C section 15.249 (a)	ANSI C63.10: Clause 6.6	PASS
Field Strength of Unwanted Emissions	FCC PART 15 C section 15.249 (a) section 15.249 (d)	ANSI C63.10: Clause 6.4, 6.6 and 6.7	PASS
Band Edges	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.9.2	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9.1	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	N/A

**Remark:**

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

## 2.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, the maximum value of the uncertainty as below:

No.	Item	Uncertainty
1	Conducted Emission Test	1.20dB
2	Radiated Emission Test	3.30dB
3	RF power,conducted	0.16dB
4	RF power density,conducted	0.24dB
5	Spurious emissions,conducted	0.21dB
6	All emissions,radiated(<1G)	4.68dB
7	All emissions,radiated(>1G)	4.89dB

### 3 Test Facility

The test facility is recognized, certified or accredited by the following organizations:

**.FCC- Registration No: 713614**

DONGGUAN UTL ELECTRONIC TECHNOLOGY CO., LTD.

1F,Hengzheng Bldg, North Road of Station, Nancheng District, Dongguan, Guangdong, China.

#### 3.1 Deviation from standard

None

#### 3.2 Abnormalities from standard conditions

None

## 4 General Information

### 4.1 General Description of EUT

Manufacturer:	Guangzhou Maipai Electronics Co.,Ltd.
Manufacturer Address:	Room 202,No.94,Shinan Road,Xianchong Village,Qiaonan Street, Panyu District of Guangzhou.
EUT Name:	wireless keyboard
FCC ID	2AFVEKM-224
Model No.:	KM-224W
Operation frequency:	2402 MHz to 2480 MHz
Number of channel:	40 channels
Modulation Type :	MSK
Antenna Type	PCB
Antenna Gain:	0 dBi
HW:	ASY_MA1386102_V1.0
SW:	V1.1
Brand Name:	N/A
Serial No:	N/A
Derivative model No.:	N/A



Power Supply Range:	DC 1.5V(1*1.5V AA battery)
Power Supply:	DC 1.5V from battery
Power Cord:	N/A
Signal Cable:	N/A

## 4.2 Test Location

All tests were performed at:

DONGGUAN UTL ELECTRONIC TECHNOLOGY CO., LTD.  
1F,Hengzheng Bldg, North Road of Station, Nancheng District, Dongguan, Guangdong, China.



<b>Description of Channel:</b>			
<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Channel</b>	<b>Frequency (MHz)</b>
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

## 5 Description of Test conditions

### 5.1 E.U.T. Operation

**Test Voltage:** DC 1.5V from battery(Use new batteries)

**Temperature:** 20.0 -25.0 °C

**Humidity:** 38-50 % RH

**Atmospheric Pressure:** 1000 -1010 mbar

**Test frequencies and frequency range:** According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

#### Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

#### Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified



## 5.2 EUT Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

## 5.3 Test Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

## 6 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.29	2016.06.28
2	EMI Measuring Receiver	R&S	ESR	101660	2014.12.12	2015.12.11
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.29	2016.06.28
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2014.12.02	2015.12.01
5	TRILOG Super Broadband test Antenna	SCHWARZBEC K	VULB9160	9160-3206	2014.12.03	2015.12.02
6	Broadband Horn Antenna	SCHWARZBEC K	BBHA9120D	452	2014.12.03	2015.12.02
7	SHF-EHF Horn	SCHWARZBEC K	BBHA9170	BBHA917036 7	2014.12.03	2015.12.02
8	Loop Antenna	ARA	PLA-1030/B	1029	2015.03.20	2016.03.19
9	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2015.01.04	2016.01.03
10	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2014.12.25	2015.12.24
11	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2015.01.04	2016.01.03
12	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A

Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.


## 7 Test Result

### 7.1 Antenna Requirement

#### Standard requirement

#### EUT Antenna

The antenna is PCB antenna and no consideration of replacement. The maximum gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.

## 7.2 Field Strength of Fundamental & Field Strength of Unwanted Emissions &

### Band Edge

Test Requirement: FCC Part 15 C section 15.249

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dB $\mu$ V/m @ 3m)	Field Strength of Harmonics (dB $\mu$ V/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Limits: The fundamental frequency range is in the frequency band of the EUT is 2402 MHz ~ 2480 MHz.

The limit for AVG field strength dB $\mu$ V/m for the fundamental frequency = 94.0 dB $\mu$ V/m.

The limit for Peak field strength dB $\mu$ V/m for the fundamental frequency = 114.0 dB $\mu$ V/m.

No fundamental is allowed in the restricted bands.

The limit for AVG field strength dB $\mu$ V/m for the harmonics and other above 1G frequencies = 54.0 dB $\mu$ V/m.

The limit for Peak field strength dB $\mu$ V/m for the harmonics and other above 1G frequencies = 74.0 dB $\mu$ V/m.

Test Method: ANSI C63.10: Clause 6.4, 6.6 and 6.7 for Field Strength of Fundamental & Field Strength of Unwanted Emissions

ANSI C63.10: Clause 6.9.2 for Band Edge

Status: Pre-test the EUT in continuous transmitting mode with setup as stand-alone in X, Y, Z three axes, found the worst case is X axes and report the data.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Frequency range: 9 kHz – 25 GHz for transmitting mode.

Test instrumentation resolution bandwidth

9 kHz (9 kHz - 30 MHz), 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 MHz – 25 GHz)

Detector:

For PK and QP value:

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for  $f \geq 1$  GHz,

VBW = 10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

**Test Procedure:**

1)9 kHz to 30 MHz emissions:

For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT, During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2)30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3)1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.


For testing performed with the horn antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scan between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

For the radiated emission test above 1GHz:


Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

**Test Configuration:**


- 1) 9 kHz to 30 MHz emissions:



- 2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 10 GHz emissions:




The field strength is calculated by adding the Antenna Factor, Cable Loss & Pre-amplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Preamplifier Factor}$$



### 7.2.1 Duty cycle measurement:



### 7.2.2 Fundamental field strength measurement:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Antenna polarization
2402.000	96.58	-5.68	90.90	114.00	-23.10	Peak	V
2402.000	82.74	-5.68	77.06	94.00	-16.94	AVG	V
2402.000	96.81	-5.68	91.13	114.00	-22.87	Peak	H
2402.000	80.66	-5.68	74.98	94.00	-19.02	AVG	H
2440.000	98.52	-5.36	93.16	114.00	-20.84	Peak	V
2440.000	82.10	-5.36	76.74	94.00	-17.26	AVG	V
2440.000	97.76	-5.36	92.40	114.00	-21.60	Peak	H
2440.000	82.69	-5.36	77.33	94.00	-16.67	AVG	H
2480.000	94.61	-5.01	89.60	114.00	-24.40	Peak	V
2480.000	79.70	-5.01	74.69	94.00	-19.31	AVG	V
2480.000	95.16	-5.01	90.15	114.00	-23.85	Peak	H
2480.000	82.37	-5.01	77.36	94.00	-16.64	AVG	H

Note: Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

### 7.2.3 Radiated Emissions Test Data

#### 9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

#### 30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

EUT:	wireless keyboard	Model Name :	KM-224W
Temperature:	25 °C	Test Data	2015-08-25
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX 2402 mode(worse-case)	Test Voltage :	DC 1.5V from battery
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
37.1550	38.58	-26.70	11.88	40.00	-28.12	QUASI-PEAK
107.5101	43.95	-23.70	20.25	43.50	-23.25	QUASI-PEAK
138.3873	40.26	-24.99	15.27	43.50	-28.23	QUASI-PEAK
434.0651	41.68	-15.70	25.98	46.00	-20.02	QUASI-PEAK
520.8882	42.35	-14.92	27.43	46.00	-18.57	QUASI-PEAK
726.8052	41.24	-10.16	31.08	46.00	-14.92	QUASI-PEAK

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
35.8746	39.75	-24.86	14.89	40.00	-25.11	QUASI-PEAK
107.5101	43.94	-25.70	18.24	43.50	-25.26	QUASI-PEAK
183.2005	39.41	-20.94	18.47	43.50	-25.03	QUASI-PEAK
238.3102	42.52	-22.11	20.41	46.00	-25.59	QUASI-PEAK
434.0651	43.02	-15.70	27.32	46.00	-18.68	QUASI-PEAK
948.7610	40.90	-6.20	34.70	46.00	-11.30	QUASI-PEAK

Note:

Measurement Level = Reading Level + Factor  
Factor=Ant Factor + Cable Loss– Pre-amplifier.

**Above 1GHz Field Strength of Unwanted Emissions Measurement**

EUT:	wireless keyboard	Model Name :	KM-224W
Temperature:	25 °C	Test Data	2015-08-25
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX mode	Test Voltage :	DC 1.5V from battery
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	1MHz/1MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	53.26	5.06	58.32	74.00	-15.68	PEAK
4804.000	41.31	5.06	46.37	54.00	-7.63	AVERAGE
7206.000	43.50	7.03	50.53	74.00	-23.47	PEAK
7206.000	30.66	7.03	37.69	54.00	-16.31	AVERAGE
9608.000	35.68	10.63	46.31	74.00	-27.69	PEAK
9608.000	23.65	10.63	34.28	54.00	-19.72	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	51.23	5.06	56.29	74.00	-17.71	PEAK
4804.000	37.56	5.06	42.62	54.00	-11.38	AVERAGE
7206.000	43.12	7.03	50.15	74.00	-23.85	PEAK
7206.000	31.66	7.03	38.69	54.00	-15.31	AVERAGE
9608.000	35.57	10.63	46.20	74.00	-27.80	PEAK
9608.000	23.90	10.63	34.53	54.00	-19.47	AVERAGE

Note:

**10~25GHz at least have 20dB margin. No recording in the test report.**

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

Low Channel: 2402 MHz

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4880.000	50.00	5.14	55.14	74.00	-18.86	PEAK
4880.000	36.11	5.14	41.25	54.00	-12.75	AVERAGE
7320.000	41.78	7.52	49.30	74.00	-24.70	PEAK
7320.000	28.15	7.52	35.67	54.00	-18.33	AVERAGE
9760.000	35.77	11.36	47.13	74.00	-26.87	PEAK
9760.000	21.22	11.36	32.58	54.00	-21.42	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4880.000	49.93	5.14	55.07	74.00	-18.93	PEAK
4880.000	37.51	5.14	42.65	54.00	-11.35	AVERAGE
7320.000	40.67	7.52	48.19	74.00	-25.81	PEAK
7320.000	26.20	7.52	33.72	54.00	-20.28	AVERAGE
9760.000	33.79	11.36	45.15	74.00	-28.85	PEAK
9760.000	21.42	11.36	32.78	54.00	-21.22	AVERAGE

Note:

**10~25GHz at least have 20dB margin. No recording in the test report.**

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

Middle Channel: 2440 MHz

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	49.34	5.22	54.56	74.00	-19.44	PEAK
4960.000	36.59	5.22	41.81	54.00	-12.19	AVERAGE
7440.000	40.21	8.06	48.27	74.00	-25.73	PEAK
7440.000	26.26	8.06	34.32	54.00	-19.68	AVERAGE
9920.000	36.77	12.10	48.87	74.00	-25.13	PEAK
9920.000	22.58	12.10	34.68	54.00	-19.32	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	50.10	5.22	55.32	74.00	-18.68	PEAK
4960.000	37.42	5.22	42.64	54.00	-11.36	AVERAGE
7440.000	39.87	8.06	47.93	74.00	-26.07	PEAK
7440.000	26.13	8.06	34.19	54.00	-19.81	AVERAGE
9920.000	33.50	12.10	45.60	74.00	-28.40	PEAK
9920.000	21.26	12.10	33.36	54.00	-20.64	AVERAGE

Note:

**10~25GHz at least have 20dB margin. No recording in the test report.**

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

High Channel: 2480 MHz

### 7.2.4 Band Edge Measurement:

Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
Lowest 2402 MHz								
V	2400.00	44.27	33.24	-5.72	38.55	27.52	74.00	54.00
H	2400.00	43.65	32.89	-5.72	37.93	27.17	74.00	54.00
Highest 2480 MHz								
V	2483.50	43.50	32.92	-4.98	38.52	27.94	74.00	54.00
H	2483.50	44.15	31.27	-4.98	39.17	26.29	74.00	54.00

Remark:

1). The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Preamplifier Factor.

**Test result: The unit does meet the FCC requirements.**

## 7.2.5 Restricted Bands Measurement:

EUT:	wireless keyboard	Model Name :	KM-224W
Temperature:	25 °C	Test Data	2015-08-25
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX mode	Test Voltage :	DC 1.5V from battery
Note:	<p>1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz.</p> <p>2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz.</p> <p>3. The data of 2390MHz and 2483.5MHz was the worst.</p>		

Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
V	2390.00	45.28	34.76	-5.79	39.49	28.97	74.00	54.00
H	2390.00	44.25	32.74	-5.79	38.46	26.95	74.00	54.00
V	2483.50	43.17	30.58	-4.98	38.19	25.60	74.00	54.00
H	2483.50	42.60	31.45	-4.98	37.62	26.47	74.00	54.00

### Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode.
- (2) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (3) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

### 7.3 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.215


(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Method: ANSI C63.10: Clause 6.9.1

Operation within the band 2402 MHz to 2480 MHz


Method of measurement: A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken.

#### Test in the frequency 2402 MHz (20 dB bandwidth)






**Test in the frequency 2440 MHz (20 dB bandwidth)**



**Test in the frequency 2480 MHz (20 dB bandwidth)**



## 7.4 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz


<b>Test Requirement:</b>	FCC Part 15 C section 15.207
<b>Test Method:</b>	ANSI C63.10: Clause 6.2
<b>Frequency Range:</b>	150 kHz to 30 MHz
<b>Detector:</b>	Peak for pre-scan (9 kHz Resolution Bandwidth)
<b>Test Result</b>	N/A (Please see the remark as below)

Remark: Because the EUT employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Measurements to demonstrate compliance with the conducted limits are not required for devices.

## 8 Photographs

### 8.1 Radiated Emission Test Setup

Below 1G





Above 1G





## 9 EUT Constructional Details









**\*\*End of report\*\***