

Android Connection Instructions:	Win 10 Connection Instructions:	• iOS Connection Instructions:		
Power Switch USB charging instanton	Power Swetch USB charging interface Power Swetch USB charging interface	Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the dot of the Y Passes time on the power loading of the Y Passes time on the power loading of the Y Passes time on the power loading of the Y Passes time on the Y Pass		
Image: Control of the second of the	2. Open settings. Line on Ulaston, dial Add Ulaston to the ferrors.	Argues as to be PC using "Armony" to search of any Series.		B022 Bluetooth eyboard
And Just - Vest Ind (1) The second s	Additional and the second of the Add Device to search	Article Art		User's manual
where the latter of the latter	Alter and being the set of the se	Autority to you have for the second s		
$ \begin{array}{ c } \hline \begin{array}{c c c } \hline \begin{array}{c} & A & A & A & A & A \\ \hline \begin{array}{c} & A & A & A & A \\ \hline \begin{array}{c} & A & A & A & A \\ \hline \begin{array}{c} & A & A & A & A \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \end{array} \end{array} \\ \hline \begin{array}{c} & A & A & A & A \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \hline \begin{array}{c} & A & A & A \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \\$	The second secon	The first of the second	Compatible System Win AOS /Android	Note: Please read the user manual carefully before you start using this product
*				
	FAQ 1.The tablet PC can't connect the BT keyboard ?	Troubleshooting Please contact the after-sales service.	Technical Specifications	Product features IOS/Android Windows Windows
Warranty Card	1) At first check the BT keyboard is into match code state, then open	Copyright	Keyboard size: 292 X 155 X 20 mm Weight: 463g Key working current: 0.6-2.2 mA flight off)	Corresponding En+ Corresponding Corresponding Leader
	the table PC Bluetooth searching. 2) Checking the BT keyboard Battery is enough, the battery low is also	It is forbidden to reproduce any part of this manual without the	Working distance : 8 m Standby current: 0.7~1.5 mA (light on)	function IIII [™] function Lactor O Eso Return to Desk O Eso Home Page O Eso Esc
User information	lead to can't connect, you need charge.	permission of seller.	Lithium battery capacity : 140mAh Sleep current: 0.03mA	Q F1 Search Q F1 Search Q F1 F1
Company or personage full name	2. The keyboard indication light always flashing when use?	Safety instructions Do not open or repair this device. Do not use the device in a damo	Working voltage : 3.7V Sleep time : ten minutes	E F2 Select E F2 Select E F2 F2
	Keyboard indication always flashing when use, is means the keyboard	Do not open or repair this device, Up not use the device in a damp environment. Clean the device with a dry cloth.	Keyboard layout: 78 Keys Awaken way : Press key	0 F3 Copy 0 F3 Copy 0 F3 F3
Contact address	will be no power please charge the power as soon as possible.	Warranty	Status Display LED	B F4 Stick B F4 Stick B F4 F4
TEL Zip	3 The table PC display BT keyboard is disconnect?	The device is provided with one-year limited hardware warranty from the purchase day.	 Code: Please turn on the power switch on the side of the keyboard, the areen light turn up, select the channel, press the Fn+C Bluetooth code 	¾ FS Cut ¾ FS Cut ¾ FS FS ••• F6 Pre-Track ••• F6 Pre-Track ••
	The BT keyboard will into dormant to save the battery after some time	Keyboard Maintenance	key, and the blue light flickers to code mode.	+4 F6 Pre-Track +4 F6 Pre-Track +4 F6 +11 F7 Play/Pause +11 F7 F7 -11 F7
The purchased product name and model NO.	later no use; press any key the BT keyboard will be awaken and working.	1 Please keen the keyboard away from liquid or humid environment	 Charging : Indicator light will be on Orange, after fully charging, the light off. 	Image: state Image: state<
		saunas, swimming pool, steam room and don't let the keyboard get wet	 Low Voltage Indication : When the voltage is below 3.2 V, green light twinkles. 	4 F9 Mute 4 F9 Mute 4 F9 F9
Purchased date		in the rain.	Multi-channel connection • When connecting the first device, first press Fn+ (\$1 and then press	• F10 Volume- • F10 Volume- • F10 F10
		 Please don't expose the keyboard at too high or too low temperature condition. 	Fn+C to start the connection.	40 _{F11} Volume+ 40 _{F11} Volume+ 40 _{F11} F11
The search as its topologic better and design is not in data or the seconds.		3.Please don't put keyboard under sun for a long time.	 Before connecting the second device, press Fn+ B12 once, then press Fn+C to start the connection. 	P12 Lock P12 Lock P12 F12
consense and a second sec		4.Please don't put keyboard close to the flame, such as cooking stoves,	 Before connecting the third device, press Fn+ B3 once, then press En+C to start the connection. 	Three system switching languages Windows: Alt-Shift switch language
(1) Or an experiment as such as speen tothering that are not provided to the sempary but applicable laws Enorgh other southouseholders are published.		candles or fireplace. 5. Avoid sharp objects scratching products, timely to recharge products to	 To use multiple devices at the same time, press Fn + iβt / iβ2 / iβ3 	IOS: Ctrl+Space key switch language
۱ ۲	К.	 Avoid sharp objects scharching products, unary to recharge products to ensure the normal use. 	to switch to freely switch to connected devices.	Android : Shift+Space key switch language
CE Susannot Hedgi,Shenchen DDH Industrial Co., Ltd declares But His Buekooth Keybourt, 1922 bit nonpliance with the essential requirements and Andreh KUD and Andreh 1900, Bue product allowed to be used in all EU menter attaine. Use the Buekooth Acploand in the environment with the temperature between 0 C and Andreh 90 C. Risk of explosion it battery is registered by an incorrect type. Dispose of used between accounting to be instruction. The product allow 2003 bit for the Andreh Ministry Andreh Ministry 2003 bit 2003 bit forteflice of version to prevent for Segure 2003 bits - 2003 bits forteflice of version Operation Frequency 2003 bits - 2003 bits Mathieute of version Operation Frequency 2003 bits - 2003 bits - 2003 bits Manufacture : Boenchen DDH Industria Co, Ltd Madess: In Frequency 2003 bits Figure - 480-073 bits Forty Figure - 480-073 bits Forty E- mail: analgebray usion	FCC Statement Collarge or molecular to expressly approved by the party responsible for compliance could of the sard's authority to sporate the explanence. This explanence has been testid and found to comply with the limits for a clusis fight indexiste installation. The explanence is a standard to the Coll Nass. These times are designed to provide reasonable protection against thandl interference in a reader standard to the sard's authority to sporate the standard to the sard to th			