

	TEST REPOR	Т			
FCC ID:	2AFW2G2104				
Test Report No::	TCT220926E022	(C^{\bullet})	(C)		
Date of issue::	Oct. 21, 2022				
Testing laboratory:	SHENZHEN TONGCE TESTING	S LAB			
Testing location/ address:	2101 & 2201, Zhenchang Factory Subdistrict, Bao'an District, Shen People's Republic of China				
Applicant's name::	Shenzhen DZH Industrial Co., Lt	d (C)			
Address:	3th Floor, YiTuo Mike Industrial Azone, ShaJing, Shenzhen, China	O ,	ng Industrial D		
Manufacturer's name:	Shenzhen DZH Industrial Co., Ltd	d			
Address::	3th Floor, YiTuo Mike Industrial Azone, ShaJing, Shenzhen, China	O ,	ng Industrial D		
Standard(s):	FCC CFR Title 47 Part 1.1307				
Product Name::	Bluetooth Keyboard				
Trade Mark:	N/A				
Model/Type reference:	G2104				
Rating(s)::	Rechargeable Li-ion Battery DC 3.7V				
Date of receipt of test item:	Sep. 26, 2022	(C)	(c ¹)		
Date (s) of performance of test:	Sep. 26, 2022 - Oct. 21, 2022				
Tested by (+signature) :	Onnado YE	Onnado Kon	IGCETA		
Check by (+signature):	Beryl ZHAO	Boyl 26 T	CT		
Approved by (+signature):	Tomsin	Tomsm "	**		

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.







Table of Contents

1.1. 1.2. 2. Gei 2.1. 2.2. 3. Fac 3.1. 3.2.	EUT desc Model(s) neral Info Test envi Descripti cilities au Facilities Location	cription listormation ironment a ion of Sup nd Accre	and mode. port Units ditations	ent Data		
4. Tes	st Result	s and Me	easureme	ent Data .	 (c)	 0



Report No.: TCT220926E023

1. General Product Information

1.1. EUT description

Product Name:	Bluetooth Keyboard	(C)		(3)
Model/Type reference:	G2104			
Sample Number:	TCT220926E022-0101			
Operation Frequency:	2402MHz~2480MHz		(6)	
Modulation Type:	GFSK			
Antenna Type:	PCB Antenna			(C)
Antenna Gain:	1.87dBi			
Rating(s):	Rechargeable Li-ion Battery DC	3.7V		

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. N	arameter. lodel(s) l one.		, , , , , , , ,	,	



Report No.: TCT220926E023

2. General Information

2.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	DC 3.7V
Humidity	56%
Atmospheric Pressure:	1008 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Equipment Model No.		FCC ID	Trade Name	
1			1	1	

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.





TESTING CENTRE TECHNOLOGY Report No.: TCT220926E023

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





Report No.: TCT220926E023

4. Test Results and Measurement Data

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- · The result is rounded to one decimal place for comparison
- BT:

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 00	2.402	-2.13	-3±1	-2	0.63	5	0.20	3.0

Result:

Base on the calculation value, No SAR measurement is required.

*****END OF REPORT****

Page 6 of 6