

FCC Test Report

Report No.: RF161107C06

FCC ID: 2AFXU8001UX36LDRZ24

Test Model: UPLYNX-M-RCZ24

Received Date: Nov. 07, 2016

Test Date: Nov. 25, 2016 to Feb. 17, 2017

Issued Date: Apr. 07, 2017

Applicant: M2Communication Inc.

Address: 15F-1, No.32, Gaotie 2nd Rd., Zhubei City, Hsinchu County 302, Taiwan (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Description of Support Units	11
3.3.1 Configuration of System under Test	11
3.4 General Description of Applied Standards	12
4 Test Types and Results	13
4.1 Radiated Emission and Bandedge Measurement	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement	13
4.1.2 Test Instruments	14
4.1.3 Test Procedures	16
4.1.4 Deviation from Test Standard	16
4.1.5 Test Setup	17
4.1.6 EUT Operating Conditions	18
4.1.7 Test Results (Mode 1)	19
4.1.8 Test Results (Mode 2)	23
4.2 Conducted Emission Measurement	27
4.2.1 Limits of Conducted Emission Measurement	27
4.2.2 Test Instruments	27
4.2.3 Test Procedures	28
4.2.4 Deviation From Test Standard	28
4.2.5 Test Setup	28
4.2.6 EUT Operating Condition	28
4.2.7 Test Results	29
4.3 Number of Hopping Frequency Used	31
4.3.1 Limits of Hopping Frequency Used Measurement	31
4.3.2 Test Setup	31
4.3.3 Test Instruments	31
4.3.4 Test Procedure	31
4.3.5 Deviation from Test Standard	31
4.3.6 Test Results	32
4.4 Dwell Time on Each Channel	34
4.4.1 Limits of Dwell Time on Each Channel Measurement	34
4.4.2 Test Setup	34
4.4.3 Test Instruments	34
4.4.4 Test Procedures	34
4.4.5 Deviation from Test Standard	34
4.4.6 Test Results	35
4.5 Channel Bandwidth	36
4.5.1 Limits of Channel Bandwidth Measurement	36
4.5.2 Test Setup	36
4.5.3 Test Instruments	36
4.5.4 Test Procedure	36
4.5.5 Deviation from Test Standard	36
4.5.6 EUT Operating Condition	36
4.5.7 Test Results	37
4.6 Hopping Channel Separation	38

4.6.1	Limits of Hopping Channel Separation Measurement.....	38
4.6.2	Test Setup.....	38
4.6.3	Test Instruments	38
4.6.4	Test Procedure	38
4.6.5	Deviation from Test Standard	38
4.6.6	Test Results	39
4.7	Maximum Output Power.....	40
4.7.1	Limits of Maximum Output Power Measurement	40
4.7.2	Test Setup.....	40
4.7.3	Test Instruments	40
4.7.4	Test Procedure	40
4.7.5	Deviation from Test Standard	40
4.7.6	EUT Operating Condition	40
4.7.7	Test Results	41
4.8	Conducted Out of Band Emission Measurement.....	42
4.8.1	Limits of Conducted Out of Band Emission Measurement.....	42
4.8.2	Test Instruments	42
4.8.3	Test Procedure	42
4.8.4	Deviation from Test Standard	42
4.8.5	EUT Operating Condition	42
4.8.6	Test Results	42
5	Pictures of Test Arrangements.....	43
	Appendix – Information on the Testing Laboratories	44

Release Control Record

Issue No.	Description	Date Issued
RF161107C06	Original release.	Apr. 07, 2017

1 Certificate of Conformity

Product: Sigfox Verified Uplynx RCZ24 Module

Brand: M2Comm

Test Model: UPLYNX-M-RCZ24

Sample Status: ENGINEERING SAMPLE

Applicant: M2Communication Inc.

Test Date: Nov. 25, 2016 to Feb. 17, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Midoli Peng , **Date:** Apr. 07, 2017
Midoli Peng / Specialist

Approved by : May Chen , **Date:** Apr. 07, 2017
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.38dB at 21.16797MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 4523.31MHz & 4510.69MHz
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is Reverse SMA or IPEX not a standard connector.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.32 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	4.82 dB
	6GHz ~ 18GHz	4.58 dB
	18GHz ~ 40GHz	5.03 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Sigfox Verified Uplynx RCZ24 Module
Brand	M2Comm
Test Model	UPLYNX-M-RCZ24
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 3.3V from host equipment
Modulation Type	D-BPSK
Modulation Technology	FHSS
Transfer Rate	600bps
Operating Frequency	902.1375MHz – 904.6625MHz
Number of Channel	Refer to 3.2
Output Power	208.449mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. The EUT antennas information:

No.	Antenna Type	Gain (dBi)	Connector Type
1	Dipole	4	Reverse SMA
2	PCB	1.9	IPEX

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Description of Test Modes

Channel frequencies are distributed into 9 groups of 6 channels.

Groups	Micro Channel 1 (MHz)	Micro Channel 2 (MHz)	Micro Channel 3 (MHz)	Micro Channel 4 (MHz)	Micro Channel 5 (MHz)	Micro Channel 6 (MHz)
1	902.1375	902.1625	902.1875	902.2125	902.2375	902.2625
2	902.4375	902.4625	902.4875	902.5125	902.5375	902.5625
3	902.7375	902.7625	902.7875	902.8125	902.8375	902.8625
4	903.0375	903.0625	903.0875	903.1125	903.1375	903.1625
5	903.3375	903.3625	903.3875	903.4125	903.4375	903.4625
6	903.6375	903.6625	903.6875	903.7125	903.7375	903.7625
7	903.9375	903.9625	903.9875	904.0125	904.0375	904.0625
8	904.2375	904.2625	904.2875	904.3125	904.3375	904.3625
9	904.5375	904.5625	904.5875	904.6125	904.6375	904.6625

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
1	√	√	√	√	With Dipole antenna
2	√	√	-	-	With PCB antenna

Where **RE \geq 1G**: Radiated Emission above 1GHz **RE $<$ 1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:

- The EUT' PCB antenna had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (MHz ~ MHz)	Tested Frequency	Modulation Technology	Modulation Technology
902.1375 ~ 904.6625	902.1375, 904.6625	FHSS	D-BPSK

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (MHz ~ MHz)	Tested Frequency	Modulation Technology	Modulation Technology
902.1375 ~ 904.6625	902.1375, 904.6625	FHSS	D-BPSK

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (MHz ~ MHz)	Tested Frequency	Modulation Technology	Modulation Technology
902.1375 ~ 904.6625	904.6625	FHSS	D-BPSK

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Operating Frequency (MHz ~ MHz)	Tested Frequency	Modulation Technology	Modulation Technology
902.1375 ~ 904.6625	902.1375, 904.6625	FHSS	D-BPSK

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE \geq 1G	23deg. C, 66%RH	120Vac, 60Hz	Robert Cheng
RE $<$ 1G	23deg. C, 66%RH	120Vac, 60Hz	Robert Cheng
PLC	25deg. C, 75%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Robert Cheng

3.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	4YV4VY1	FCC DoC	Provided by Lab
B.	Test Tool	M2Communication	NA	NA	NA	Supplied by client

Note:

1. All power cords of the above support units are non-shielded (1.8m).

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Below 1GHz test

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna ^(*) Electro-Metrics	EM-6879	264	Dec. 16, 2014	Dec. 15, 2016
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-05	May 07, 2016	May 06, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-156	Jan. 04, 2016	Jan. 03, 2017
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 02, 2016	Apr. 01, 2017
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Oct. 05, 2016	Oct. 04, 2017
Software	ADT_Radiated _V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The FCC Site Registration No. is 147459
6. The CANADA Site Registration No. is 20331-1
- 7 Loop antenna was used for all emissions below 30 MHz.
8. Tested Date: Nov. 25 to 29, 2016

For above 1GHz test

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Dec. 28, 2016	Dec. 27, 2017
Pre-Amplifier EMCI	EMC12630SE	980384	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160922 150317 150322	Feb. 02, 2017 Mar. 30, 2016 Mar. 30, 2016	Feb. 01, 2018 Mar. 29, 2017 Mar. 29, 2017
Spectrum Analyzer Keysight	N9030A	MY54490520	July 29, 2016	July 28, 2017
Pre-Amplifier EMCI	EMC184045S E	980386	Feb. 02, 2017	Feb. 01, 2018
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 15, 2016	Dec. 14, 2017
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 15, 2017	Jan. 14, 2018
Software	ADT_Radiated _V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. The FCC Site Registration No. is 147459
4. The CANADA Site Registration No. is 20331-1
5. Tested Date: Feb. 17, 2017

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Connected the EUT with the Support Unit A (Laptop) which is placed on test table.
- b. Controlling software (TeraTerm paste "AT_command for BV" command) has been activated to set the EUT on specific status.

4.1.7 Test Results (Mode 1)

Above 1GHz Data:

TESTED FREQUENCY	902.1375 MHz	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2706.41	47.4 PK	74.0	-26.6	2.63 H	37	48.7	-1.3
2	2706.41	39.4 AV	54.0	-14.6	2.63 H	37	40.7	-1.3
3	3608.55	43.4 PK	74.0	-30.6	1.45 H	214	43.1	0.3
4	3608.55	31.6 AV	54.0	-22.4	1.45 H	214	31.3	0.3
5	4510.69	53.6 PK	74.0	-20.4	1.26 H	87	51.8	1.8
6	4510.69	49.1 AV	54.0	-4.9	1.26 H	87	47.3	1.8
7	5412.82	49.2 PK	74.0	-24.8	1.09 H	84	45.9	3.3
8	5412.82	39.2 AV	54.0	-14.8	1.09 H	84	35.9	3.3
9	8119.24	53.1 PK	74.0	-20.9	1.65 H	174	43.7	9.4
10	8119.24	40.3 AV	54.0	-13.7	1.65 H	174	30.9	9.4
11	9021.37	54.1 PK	74.0	-19.9	2.11 H	302	44.7	9.4
12	9021.37	40.3 AV	54.0	-13.7	2.11 H	302	30.9	9.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2706.41	47.6 PK	74.0	-26.4	1.00 V	151	48.9	-1.3
2	2706.41	40.1 AV	54.0	-13.9	1.00 V	151	41.4	-1.3
3	3608.55	44.2 PK	74.0	-29.8	2.00 V	134	43.9	0.3
4	3608.55	31.2 AV	54.0	-22.8	2.00 V	134	30.9	0.3
5	4510.69	57.3 PK	74.0	-16.7	2.14 V	246	55.5	1.8
6	4510.69	53.7 AV	54.0	-0.3	2.14 V	246	51.9	1.8
7	5412.82	49.2 PK	74.0	-24.8	3.48 V	151	45.9	3.3
8	5412.82	40.1 AV	54.0	-13.9	3.48 V	151	36.8	3.3
9	8119.24	52.9 PK	74.0	-21.1	1.70 V	178	43.5	9.4
10	8119.24	40.2 AV	54.0	-13.8	1.70 V	178	30.8	9.4
11	9021.37	51.7 PK	74.0	-22.3	1.61 V	223	42.3	9.4
12	9021.37	39.6 AV	54.0	-14.4	1.61 V	223	30.2	9.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

TESTED FREQUENCY	904.6625 MHz	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2713.99	47.6 PK	74.0	-26.4	2.68 H	51	48.9	-1.3
2	2713.99	39.6 AV	54.0	-14.4	2.68 H	51	40.9	-1.3
3	3618.65	43.6 PK	74.0	-30.4	1.43 H	216	43.3	0.3
4	3618.65	31.8 AV	54.0	-22.2	1.43 H	216	31.5	0.3
5	4523.31	53.5 PK	74.0	-20.5	1.26 H	76	51.7	1.8
6	4523.31	49.3 AV	54.0	-4.7	1.26 H	76	47.5	1.8
7	5427.98	49.5 PK	74.0	-24.5	1.08 H	96	46.1	3.4
8	5427.98	39.3 AV	54.0	-14.7	1.08 H	96	35.9	3.4
9	8141.96	53.3 PK	74.0	-20.7	1.66 H	163	43.9	9.4
10	8141.96	40.2 AV	54.0	-13.8	1.66 H	163	30.8	9.4
11	9046.62	53.6 PK	74.0	-20.4	2.14 H	299	44.2	9.4
12	9046.62	40.0 AV	54.0	-14.0	2.14 H	299	30.6	9.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2713.99	48.0 PK	74.0	-26.0	1.00 V	137	49.3	-1.3
2	2713.99	40.6 AV	54.0	-13.4	1.00 V	137	41.9	-1.3
3	3618.65	44.1 PK	74.0	-29.9	2.05 V	118	43.8	0.3
4	3618.65	31.2 AV	54.0	-22.8	2.05 V	118	30.9	0.3
5	4523.31	57.4 PK	74.0	-16.6	2.12 V	259	55.6	1.8
6	4523.31	53.9 AV	54.0	-0.1	2.12 V	259	52.1	1.8
7	5427.98	49.3 PK	74.0	-24.7	3.51 V	160	45.9	3.4
8	5427.98	40.1 AV	54.0	-13.9	3.51 V	160	36.7	3.4
9	8141.96	53.0 PK	74.0	-21.0	1.69 V	172	43.6	9.4
10	8141.96	40.3 AV	54.0	-13.7	1.69 V	172	30.9	9.4
11	9046.62	51.6 PK	74.0	-22.4	1.60 V	230	42.2	9.4
12	9046.62	39.8 AV	54.0	-14.2	1.60 V	230	30.4	9.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Below 1GHz Data:

TESTED FREQUENCY	902.1375 MHz	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	384.01	39.8 QP	46.0	-6.2	1.34 H	142	45.1	-5.3
2	395.61	40.4 QP	46.0	-5.6	1.74 H	301	45.5	-5.1
3	456.01	40.0 QP	46.0	-6.0	1.24 H	244	43.2	-3.2
4	536.12	42.1 QP	46.0	-3.9	1.64 H	300	43.9	-1.8
5	739.45	41.7 QP	46.0	-4.3	1.24 H	241	39.3	2.4
6	993.41	50.2 QP	54.0	-3.8	1.64 H	255	45.1	5.1
7	902.00	72.8 QP	90.1	-17.3	1.13 H	219	41.4	31.4
8	*902.1375	110.1 QP			1.13 H	219	78.7	31.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	335.12	38.1 QP	46.0	-7.9	2.44 V	145	44.6	-6.5
2	359.75	36.3 QP	46.0	-9.7	1.42 V	241	42.4	-6.1
3	407.64	38.1 QP	46.0	-7.9	1.88 V	54	42.9	-4.8
4	431.65	39.1 QP	46.0	-6.9	1.24 V	241	42.9	-3.8
5	533.14	37.2 QP	46.0	-8.8	1.98 V	241	39.1	-1.9
6	971.41	45.2 QP	54.0	-8.8	3.24 V	145	40.0	5.2
7	902.00	83.5 QP	102.0	-18.5	1.08 V	24	52.1	31.4
8	*902.1375	122.0 QP			1.08 V	24	90.6	31.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

TESTED FREQUENCY	904.6625 MHz	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	383.71	39.7 QP	46.0	-6.3	1.64 H	244	45.0	-5.3
2	395.42	40.1 QP	46.0	-5.9	3.01 H	145	45.2	-5.1
3	455.79	40.1 QP	46.0	-5.9	1.35 H	304	43.3	-3.2
4	536.02	42.0 QP	46.0	-4.0	1.74 H	247	43.8	-1.8
5	739.31	41.6 QP	46.0	-4.4	1.54 H	301	39.3	2.3
6	993.31	50.1 QP	54.0	-3.9	1.74 H	304	45.0	5.1
7	*904.6625	110.2 QP			1.09 H	218	78.7	31.5
8	928.00	42.1 QP	90.2	-48.1	1.09 H	218	10.2	31.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	335.01	38.0 QP	46.0	-8.0	1.25 V	241	44.5	-6.5
2	359.62	36.2 QP	46.0	-9.8	1.24 V	342	42.3	-6.1
3	407.42	38.2 QP	46.0	-7.8	1.64 V	301	43.1	-4.9
4	431.51	39.0 QP	46.0	-7.0	1.74 V	304	42.8	-3.8
5	533.01	37.6 QP	46.0	-8.4	2.40 V	300	39.5	-1.9
6	971.31	45.5 QP	54.0	-8.5	1.00 V	244	40.3	5.2
7	*904.6625	122.2 QP			1.08 V	20	90.7	31.5
8	928.00	46.6 QP	102.2	-55.6	1.08 V	20	14.7	31.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

4.1.8 Test Results (Mode 2)

Above 1GHz Data:

TESTED FREQUENCY	902.1375 MHz	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2706.41	48.7 PK	74.0	-25.3	2.01 H	38	50.0	-1.3
2	2706.41	41.6 AV	54.0	-12.4	2.01 H	38	42.9	-1.3
3	3608.55	47.1 PK	74.0	-26.9	1.51 H	192	46.8	0.3
4	3608.55	37.3 AV	54.0	-16.7	1.51 H	192	37.0	0.3
5	4510.69	57.2 PK	74.0	-16.8	1.00 H	117	55.4	1.8
6	4510.69	53.9 AV	54.0	-0.1	1.00 H	117	52.1	1.8
7	5412.82	49.8 PK	74.0	-24.2	1.06 H	91	46.5	3.3
8	5412.82	42.2 AV	54.0	-11.8	1.06 H	91	38.9	3.3
9	8119.24	52.3 PK	74.0	-21.7	1.65 H	214	42.9	9.4
10	8119.24	39.5 AV	54.0	-14.5	1.65 H	214	30.1	9.4
11	9021.37	52.5 PK	74.0	-21.5	2.17 H	305	43.1	9.4
12	9021.37	40.1 AV	54.0	-13.9	2.17 H	305	30.7	9.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2706.41	43.1 PK	74.0	-30.9	3.66 V	131	44.4	-1.3
2	2706.41	37.6 AV	54.0	-16.4	3.66 V	131	38.9	-1.3
3	3608.55	42.3 PK	74.0	-31.7	2.65 V	108	42.0	0.3
4	3608.55	32.7 AV	54.0	-21.3	2.65 V	108	32.4	0.3
5	4510.69	56.8 PK	74.0	-17.2	1.21 V	100	55.0	1.8
6	4510.69	53.6 AV	54.0	-0.4	1.21 V	100	51.8	1.8
7	5412.82	49.9 PK	74.0	-24.1	3.31 V	152	46.6	3.3
8	5412.82	41.3 AV	54.0	-12.7	3.31 V	152	38.0	3.3
9	8119.24	53.2 PK	74.0	-20.8	1.65 V	177	43.8	9.4
10	8119.24	40.5 AV	54.0	-13.5	1.65 V	177	31.1	9.4
11	9021.37	52.3 PK	74.0	-21.7	1.65 V	214	42.9	9.4
12	9021.37	39.9 AV	54.0	-14.1	1.65 V	214	30.5	9.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

TESTED FREQUENCY	904.6625 MHz	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2713.99	49.0 PK	74.0	-25.0	2.02 H	32	50.3	-1.3
2	2713.99	42.0 AV	54.0	-12.0	2.02 H	32	43.3	-1.3
3	3618.65	47.4 PK	74.0	-26.6	1.53 H	184	47.1	0.3
4	3618.65	37.4 AV	54.0	-16.6	1.53 H	184	37.1	0.3
5	4523.31	57.2 PK	74.0	-16.8	1.05 H	125	55.4	1.8
6	4523.31	53.8 AV	54.0	-0.2	1.05 H	125	52.0	1.8
7	5427.98	49.7 PK	74.0	-24.3	1.06 H	100	46.3	3.4
8	5427.98	42.0 AV	54.0	-12.0	1.06 H	100	38.6	3.4
9	8141.96	52.7 PK	74.0	-21.3	1.66 H	216	43.3	9.4
10	8141.96	39.9 AV	54.0	-14.1	1.66 H	216	30.5	9.4
11	9046.62	52.2 PK	74.0	-21.8	2.14 H	296	42.8	9.4
12	9046.62	39.6 AV	54.0	-14.4	2.14 H	296	30.2	9.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2713.99	43.6 PK	74.0	-30.4	3.62 V	145	44.9	-1.3
2	2713.99	38.1 AV	54.0	-15.9	3.62 V	145	39.4	-1.3
3	3618.65	42.3 PK	74.0	-31.7	2.65 V	113	42.0	0.3
4	3618.65	32.7 AV	54.0	-21.3	2.65 V	113	32.4	0.3
5	4523.31	56.9 PK	74.0	-17.1	1.27 V	110	55.1	1.8
6	4523.31	53.7 AV	54.0	-0.3	1.27 V	110	51.9	1.8
7	5427.98	50.4 PK	74.0	-23.6	3.32 V	167	47.0	3.4
8	5427.98	41.6 AV	54.0	-12.4	3.32 V	167	38.2	3.4
9	8141.96	52.7 PK	74.0	-21.3	1.68 V	186	43.3	9.4
10	8141.96	40.2 AV	54.0	-13.8	1.68 V	186	30.8	9.4
11	9046.62	52.5 PK	74.0	-21.5	1.67 V	218	43.1	9.4
12	9046.62	39.9 AV	54.0	-14.1	1.67 V	218	30.5	9.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Below 1GHz Data:

TESTED FREQUENCY	902.1375 MHz	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	384.00	40.2 QP	46.0	-5.8	1.00 H	187	45.5	-5.3
2	395.98	40.8 QP	46.0	-5.2	1.00 H	183	45.9	-5.1
3	456.00	40.8 QP	46.0	-5.2	2.00 H	214	44.0	-3.2
4	536.19	42.4 QP	46.0	-3.6	1.50 H	360	44.2	-1.8
5	739.75	41.9 QP	46.0	-4.1	1.00 H	211	39.5	2.4
6	993.70	50.1 QP	54.0	-3.9	1.50 H	99	45.0	5.1
7	902.00	84.5 QP	101.7	-17.2	1.54 H	285	53.1	31.4
8	*902.1375	121.7 QP			1.54 H	285	90.3	31.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	335.99	38.5 QP	46.0	-7.5	1.00 V	275	45.0	-6.5
2	359.99	36.6 QP	46.0	-9.4	1.00 V	277	42.7	-6.1
3	407.98	38.4 QP	46.0	-7.6	2.00 V	290	43.2	-4.8
4	431.97	39.4 QP	46.0	-6.6	2.00 V	245	43.2	-3.8
5	533.14	37.6 QP	46.0	-8.4	1.50 V	272	39.5	-1.9
6	971.85	45.3 QP	54.0	-8.7	1.50 V	242	40.1	5.2
7	902.00	80.3 QP	97.3	-17.0	1.53 V	212	48.9	31.4
8	*902.1375	117.3 QP			1.53 V	212	85.9	31.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

TESTED FREQUENCY	904.6625 MHz	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	384.12	40.1 QP	46.0	-5.9	1.45 H	241	45.4	-5.3
2	395.75	40.6 QP	46.0	-5.4	1.42 H	241	45.7	-5.1
3	456.12	40.6 QP	46.0	-5.4	1.64 H	301	43.8	-3.2
4	536.01	42.2 QP	46.0	-3.8	1.24 H	245	44.0	-1.8
5	739.61	41.8 QP	46.0	-4.2	1.42 H	301	39.4	2.4
6	993.62	50.3 QP	54.0	-3.7	1.24 H	241	45.2	5.1
7	*904.6625	121.8 QP			1.54 H	285	90.3	31.5
8	928.00	46.3 QP	101.8	-55.5	1.54 H	285	14.4	31.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	335.78	38.3 QP	46.0	-7.7	1.42 V	301	44.8	-6.5
2	359.84	36.4 QP	46.0	-9.6	1.64 V	341	42.5	-6.1
3	407.81	38.2 QP	46.0	-7.8	1.64 V	301	43.0	-4.8
4	431.81	39.2 QP	46.0	-6.8	1.64 V	301	43.0	-3.8
5	533.01	37.1 QP	46.0	-8.9	1.64 V	301	39.0	-1.9
6	971.74	45.2 QP	54.0	-8.8	1.68 V	274	40.0	5.2
7	*904.6625	117.5 QP			1.53 V	212	86.0	31.5
8	928.00	44.2 QP	97.5	-53.3	1.52 V	212	12.3	31.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
- 5." * ": Fundamental frequency.

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2016	Oct. 23, 2017
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 26, 2016	Oct. 25, 2017
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 13, 2016	June 12, 2017
50 ohms Terminator	N/A	EMC-02	Sep. 29, 2016	Sep. 28, 2017
RF Cable	5D-FB	COCCAB-001	Sep. 30, 2016	Sep. 29, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 20, 2016	June 19, 2017
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
- 3 Tested Date: Nov. 29, 2016

4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor (dB)	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.15781	10.19	40.97	24.46	51.16	34.65	65.58	55.58	-14.42	-20.93
2	0.17406	10.19	43.20	32.73	53.39	42.92	64.76	54.76	-11.37	-11.84
3	0.74375	10.24	10.82	1.16	21.06	11.40	56.00	46.00	-34.94	-34.60
4	3.93359	10.24	24.26	7.17	34.50	17.41	56.00	46.00	-21.50	-28.59
5	16.46484	11.15	30.48	30.22	41.63	41.37	60.00	50.00	-18.37	-8.63
6	21.16797	11.39	32.46	31.84	43.85	43.23	60.00	50.00	-16.15	-6.77

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	10.17	43.22	30.70	53.39	40.87	64.98	54.98	-11.59	-14.11
2	0.23203	10.17	33.64	20.21	43.81	30.38	62.38	52.38	-18.57	-22.00
3	0.28281	10.18	26.79	15.09	36.97	25.27	60.73	50.73	-23.76	-25.46
4	3.48047	10.19	15.43	6.05	25.62	16.24	56.00	46.00	-30.38	-29.76
5	16.46484	10.94	30.69	30.52	41.63	41.46	60.00	50.00	-18.37	-8.54
6	21.16797	11.09	33.26	32.53	44.35	43.62	60.00	50.00	-15.65	-6.38

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

CONDITION	HOPPING FREQUENCY USED	APPLICATION
20dB Bandwidth <250kHz	hopping channels ≥ 50	v
20dB Bandwidth >250kHz	hopping channels ≥ 25	x

4.3.2 Test Setup



4.3.3 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	June 28, 2016	June 27, 2017

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Feb. 17, 2017

4.3.4 Test Procedure

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 54 hopping frequencies in the hopping mode. Please refer to the test result. On the plots, it shows that the hopping frequencies are equally spaced.






4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

CONDITION	DWELL TIME	APPLICATION
20dB Bandwidth <250kHz (hopping channels ≥ 50)	0.4 seconds within a 20 second period	v
20dB Bandwidth >250kHz (hopping channels ≥ 25)	0.4 seconds within a 10 second period	x

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.3.3 to get information of above instrument.

4.4.4 Test Procedures


- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

Number of transmission in a 20 s	Length of transmission time (msec)	Result (msec)	Limit (msec)
1 time	0.304	0.304	400




4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

CONDITION	APPLICATION
20dB Bandwidth <250kHz (hopping channels ≥ 50)	v
20dB Bandwidth >250kHz (hopping channels ≥ 25)	x

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.3.3 to get information of above instrument.

4.5.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard


No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Frequency (MHz)	20dB Bandwidth (MHz)
902.1375	0.0227
904.6625	0.0226




4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation from Test Standard


No deviation.

4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

CONDITION	OUTPUT POWER	APPLICATION
hopping channels ≥ 50	1 W	v
hopping channels ≥ 25 & ≤ 50	0.25W	x

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.3.3 to get information of above instrument.

4.7.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 30kHz RBW and 100 kHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard


No deviation.

4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---