

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Hatch Baby Rest with BT 4.1 BLE function operating in 2402-2480MHz. The EUT is powered by DC 5V/1A from adapter with 120V/60Hz input. For more detail information pls. refer to the user manual.

Modulation Type: GFSK.

Bluetooth Version: BT 4.1 BLE(single mode)

Antenna Type: Integral antenna.

Antenna Gain: 1.6dBi.

The nominal conducted output power specified: -1.6dBm (+/-3dB).

The nominal radiated output power (e.i.r.p) specified: 0dBm (+/- 3dB).

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 97.9dB μ V/m at 3m in the frequency 2402MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 2.7dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 97.5dB μ V/m at 3m in the frequency 2480MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 2.3dBm
which is within the production variation.

The maximum conducted output power specified is 1.4dBm = 1.4mW

The source- based time-averaging conducted output power

= 1.4 * Duty factor mW (where Duty Factor \leq 1)

= 1.4 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.480) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.