



RF EXPOSURE EVALUATION REPORT

APPLICANT : HATCH BABY, INC.
PRODUCT NAME : Restore - Sound Machine & Night Light
MODEL NAME : RESTORE02
BRAND NAME : Hatch
FCC ID : 2AFYZ-RESTORE02
STANDARD(S) : 47 CFR§2.1091, KDB 447498 D01v06
RECEIPT DATE : 2020-08-31
TEST DATE : 2020-09-01 to 2020-09-16
ISSUE DATE : 2020-10-30

Edited by : Stefan Sun.
Stefan Sun (Test engineer)
Review by: Peng fuwei
Peng fuwei(Auditor)
Approved by: Anne Liu
Anne Liu (Supervisor)

NOTE: 1.The report is invalid when there is no the approver signature and the special stamp for test report. 2.The test report shall not be reproduced except in full without prior written permission of the company. 3.The report copy is invalid when there is no the special stamp for test repor. 4.The altered report is invalid. 5.The entrust test is responsibility for the received sample only.



DIRECTORY

- 1. Technical Information..... 3
- 1.1. Applicant and Manufacturer Information..... 3
- 1.2. Equipment Under Test (EUT) Description..... 3
- 1.3. Applied Reference Documents..... 3
- 2. Device category and RF exposure limit..... 4
- 3. RF Exposure Evaluation..... 5
- Annex A General Information..... 6

| Change History | | |
|----------------|------------|-------------------|
| Issue | Date | Reason for change |
| 1.0 | 2020-10-30 | First edition |



1. Technical Information

Note: Provide by manufacturer.

1.1. Applicant and Manufacturer Information

| | |
|---------------------------|--|
| Applicant: | HATCH BABY, INC. |
| Applicant Address: | 3525 Alameda de las Pulgas, Suite D, Menlo Park CA 94025 |

1.2. Equipment Under Test (EUT) Description

| | |
|--------------------------|---|
| EUT Type: | Restore - Sound Machine & Night Light |
| Hardware Version: | 5.3.1 |
| Software Version: | 5.0.939 |
| Frequency Bands: | 802.11b/g/n20:2.412GHz-2.462GHz 802.11 n40: 2.422GHz - 2.452GHz Bluetooth: 2402MHz – 2480MHz |
| Modulation Mode: | Wi-Fi:OFDM,DSSS Bluetooth: FHSS GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps) Bluetooth 4.2 LE: GFSK |
| Antenna type: | PCB Antenna |

1.3. Applied Reference Documents

Leading reference documents for testing:

| No. | Identity | Document Title |
|-----|--------------------------|--|
| 1 | 47 CFR§2.1091 | Radiofrequency Radiation Exposure Evaluation: mobile devices |
| 2 | KDB 447498 D01v06 | General RF Exposure Guidance |



2. Device category and RF exposure limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | f/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

3. RF Exposure Evaluation

Standalone transmission MPE evaluation

| Mode | Frequency | Antenna Gain | Output Power | | Power density(S) | Limit for MPE |
|--------------|-----------|--------------|--------------|--------|-----------------------|-----------------------|
| | (MHz) | (dBi) | (dBm) | (mW) | (mW/cm ²) | (mW/cm ²) |
| Wi-Fi(Esp32) | 2437 | 2.0 | 14.18 | 52.240 | 0.010 | 1.0 |
| BLE(Esp32) | 2480 | 2.0 | 2.648 | 3.671 | 0.001 | 1.0 |

According to KDB447498 D01 General RF Exposure Guidance v06, simultaneous transmission is evaluated:

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 .

Calculation method:

$$S = P \cdot G / 4\pi R^2$$

Where:

S = power density(in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = antenna gain

R = Separation distance (20cm)



Annex A General Information

1. Identification of the Responsible Testing Laboratory

| | |
|-------------------------------|--|
| Company Name: | Kehu-Morlab Test Laboratory |
| Department: | Kehu-Morlab Test Laboratory |
| Address: | Unit 101, No.1732 Gangzhong Road, Xiamen Area, Pilot Free Trade Zone (Fujian), P. R. China |
| Responsible Test Lab Manager: | Mr. Di Dehai |
| Telephone: | +86-592-5612050 |
| Facsimile: | +86-592-5612095 |

2. Identification of the Responsible Testing Location

| | |
|----------|--|
| Name: | Kehu-Morlab Test Laboratory |
| Address: | Unit 101, No.1732 Gangzhong Road, Xiamen Area, Pilot Free Trade Zone (Fujian), P. R. China |

————— END OF REPORT —————