

FCC 47 CFR MPE REPORT

Avi-on Labs, Inc.

Avi-on Remote Access Bridge

Model Number: 2001RAB

FCC ID: 2AFZI-2001RAB

Prepared for : Avi-on Labs, Inc.

2750 Rasmussen, Suite 206, Park City, Utah, United States.

Prepared By : EST Technology Co., Ltd.

San Tun Management Zone, Houjie District, Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1607044

Date of Test : June 27 ~ July 16, 2016

Date of Report : July 20, 2016

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3. Calculated Result and Limit

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
					(dBi)	(Linear)			
IEEE 802.11b	2412	8.72	7.44732	8±2	1	1.2589	0.00250	1	Compiles
	2442	9.27	8.45279	9±2	1	1.2589	0.00315	1	Compiles
	2472	10.17	10.39920	10±2	1	1.2589	0.00397	1	Compiles
IEEE 802.11g	2412	4.48	2.80543	4±2	1	1.2589	0.00100	1	Compiles
	2442	5.01	3.16957	5±2	1	1.2589	0.00126	1	Compiles
	2472	6.39	4.35512	6±2	1	1.2589	0.00158	1	Compiles
IEEE 802.11n HT20	2412	7.94	6.22300	7±2	1	1.2589	0.00199	1	Compiles
	2442	8.74	7.48170	8±2	1	1.2589	0.00250	1	Compiles
	2472	9.71	9.35406	9±2	1	1.2589	0.00315	1	Compiles
IEEE 802.11n HT40	2422	7.96	6.25173	7±2	1	1.2589	0.00199	1	Compiles
	2442	8.55	7.16143	8±2	1	1.2589	0.00250	1	Compiles
	2462	9.58	9.07821	9±2	1	1.2589	0.00315	1	Compiles
BLE	2402	2.75	1.88365	2±2	1	1.2589	0.00063	1	Compiles
	2440	4.15	2.60016	4±2	1	1.2589	0.00100	1	Compiles
	2480	3.57	2.27510	3±2	1	1.2589	0.00079	1	Compiles
GFSK	2402	3.87	2.43781	3±2	1	1.2589	0.00079	1	Compiles
	2441	6.59	4.56037	6±2	1	1.2589	0.00158	1	Compiles
	2480	7.78	5.99791	7±2	1	1.2589	0.00199	1	Compiles
8-DPSK	2402	1.89	1.54525	1±2	1	1.2589	0.00050	1	Compiles
	2441	5.01	3.16957	5±2	1	1.2589	0.00126	1	Compiles
	2480	6.55	4.51856	6±2	1	1.2589	0.00158	1	Compiles
Max Target Power Density of the total from BT and Wi-Fi									
BT Max Target Power (dBm)	Wi-Fi Max Target Power (dBm)	Total Max Target Power (W)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result		
			(dBi)	(Linear)					
7.78	10.17	0.07852	1	1.2589	0.01562	1	Compiles		