



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Avi-on Labs, Inc.

Address: 2700 Rasmussen, Suite L-10, Park City, Utah, United States

FCC ID: 2AFZI-AVIBG21

Product Name: Avi-on Low Voltage Fixture Adapter / Avi-on Network Time Manager

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230850844-00A1

Date Of Issue: 2023/11/01

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 MINIMUM 6 DB BANDWIDTH.....	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 MAXIMUM CONDUCTED OUTPUT POWER.....	18
3.4.1 Applicable Standard.....	18
3.4.2 EUT Setup.....	18
3.4.3 Test Procedure	18
3.5 MAXIMUM POWER SPECTRAL DENSITY.....	19
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	20
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure	20
3.7 DUTY CYCLE	21
3.7.1 EUT Setup.....	21
3.7.2 Test Procedure	21

3.8 ANTENNA REQUIREMENT.....22
 3.8.1 Applicable Standard.....22
 3.8.2 Judgment.....22

4. Test DATA AND RESULTS 23
 4.1 AC LINE CONDUCTED EMISSIONS.....23
 4.2 RADIATION SPURIOUS EMISSIONS26
 4.3 MAXIMUM CONDUCTED OUTPUT POWER.....39

5. RF EXPOSURE EVALUATION 40
 5.1 APPLICABLE STANDARD.....40
 5.1.2 MEASUREMENT RESULT.....40

6. EUT PHOTOGRAPHS 41

7. TEST SETUP PHOTOGRAPHS 42

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230850844-00A1	Original Report	2023/11/01

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Avi-on Low Voltage Fixture Adapter / Avi-on Network Time Manager
Trade Name:	Avi-on
EUT Model:	AVI-B-LVFA-12-24VDC-1CH
Multiple Model(s):	AVI-B-LVFA-12-24VDC-2CH, AVI-B-NTM-12-24VDC
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	9.82 dBm
Modulation Type:	GFSK
Rated Input Voltage:	AC 120V
Serial Number:	CE&RE: 2BR6-1 RF: 2BR6-2
EUT Received Date:	2023/8/31
EUT Received Status:	Good
Test Purpose:	
Note1: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	
Note2: This is Class II permissive change application for FCC ID: 2AFZI-AVIBG21, the below changes was made based on the device certified on 10/12/2023, which was provided by the manufacturer▲: 1): Changing the Product Type to “Avi-on Low Voltage Fixture Adapter, Avi-on Network Time Manager”. 2): Changing the product test model to “AVI-B-LVFA-12-24VDC-1CH”. 3): Changing the series model to “AVI-B-LVFA-12-24VDC-1CH, AVI-B-NTM-12-24VDC”. 4): Changing the trade name to “Avi-on”. 5): Changing the antenna. 6): The module was limited to a platform board.	

Operation Frequency Detail: For BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2402	
Middle		2440	
Highest		2480	

Antenna Information Detail▲:

Antenna Model	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
/	Integral	50	2.4~2.5GHz	1.42dBi

The Method of §15.203 Compliance:

- Antenna was permanently attached to the unit.
- Antenna use a unique type of connector to attach to the EUT.
- Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For BLE:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:	No		
EUT Exercise Software:	BGTool		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
1Mbps	200	200	200
2Mbps	200	200	200

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Load	Unknown	Unknown
Unknown	sensor	E520218	02024173807F

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Unshielded DC cable	/	/	0.3	load	EUT
Unshielded DC cable	/	/	0.3	load	EUT
Flat Cable	/	/	0.5	Sensor	EUT

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Note*
§15.247(b)(3)	Maximum Conducted Output Power	Report only
§15.247(e)	Power Spectral Density	Note*
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Note*
§15.203	Antenna Requirement	Compliant
FCC§15.247 (i) & §1.1307	RF Exposure Evaluation	Compliant

Note*: per spot check with the output power, the RF parameters identical with the original device, the result please refer to the original report: CR230850531-00, China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided in the original report.

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum Conducted Output Power

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

For Peak Power

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.


3.5 Maximum power spectral density

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2BR6-1	Test Date:	2023/09/30
Test Site:	CE	Test Mode:	Transmitting maximum output power mode BLE 2M low channel
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2	Relative Humidity: (%)	56	ATM Pressure: (kPa)	101.2
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2023/03/31	2024/03/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/08/06	2024/08/05
Audix	Test Software	E3	190306 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Project No.: CR230850844-RFA1
 Tester: David Huang
 Port: Line
 Note:


Date: 2023-09-30



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.162	18.31	9.61	27.92	55.35	27.43	Average
2	0.162	30.62	9.61	40.23	65.35	25.12	QP
3	0.188	15.37	9.61	24.98	54.11	29.13	Average
4	0.188	27.26	9.61	36.87	64.11	27.24	QP
5	0.314	28.52	9.61	38.13	49.85	11.72	Average
6	0.314	36.48	9.61	46.09	59.85	13.76	QP
7	0.604	17.02	9.62	26.64	46.00	19.36	Average
8	0.604	23.52	9.62	33.14	56.00	22.86	QP
9	1.106	18.66	9.62	28.28	46.00	17.72	Average
10	1.106	25.88	9.62	35.50	56.00	20.50	QP
11	1.602	13.44	9.63	23.07	46.00	22.93	Average
12	1.602	24.97	9.63	34.60	56.00	21.40	QP

Project No.: CR230850844-RFA1
 Tester: David Huang
 Port: neutral
 Note:

Date: 2023-09-30



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.162	17.37	9.61	26.98	55.38	28.40	Average
2	0.162	30.36	9.61	39.97	65.38	25.41	QP
3	0.316	28.00	9.61	37.61	49.82	12.21	Average
4	0.316	36.21	9.61	45.82	59.82	14.00	QP
5	0.578	16.71	9.62	26.33	46.00	19.67	Average
6	0.578	23.39	9.62	33.01	56.00	22.99	QP
7	1.127	17.27	9.62	26.89	46.00	19.11	Average
8	1.127	24.20	9.62	33.82	56.00	22.18	QP
9	1.637	15.75	9.63	25.38	46.00	20.62	Average
10	1.637	24.74	9.63	34.37	56.00	21.63	QP
11	3.845	14.47	9.65	24.12	46.00	21.88	Average
12	3.845	22.73	9.65	32.38	56.00	23.62	QP

4.2 Radiation Spurious Emissions

Serial Number:	2BR6-1	Test Date:	2023/10/20 for below 1GHz 2023/9/30 for above 1GHz
Test Site:	966-2, 966-1	Test Mode:	Transmitting
Tester:	Vic Du, Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6~ 26.7	Relative Humidity: (%)	53~59	ATM Pressure: (kPa)	100.6 ~100.8
----------------------	------------	------------------------------	-------	------------------------	--------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
30MHz-1GHz					
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
1GHz -25GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test data:


After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.

1) 30MHz-1GHz: (maximum output power mode BLE 2M)

Low channel

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: horizontal
 Note:


Date: 2023-10-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	28.51	-4.45	24.06	40.00	15.94	Peak
2	73.103	28.52	-16.82	11.70	40.00	28.30	Peak
3	126.329	28.11	-11.32	16.79	43.50	26.71	Peak
4	204.955	27.79	-12.37	15.42	43.50	28.08	Peak
5	504.706	28.61	-5.93	22.68	46.00	23.32	Peak
6	952.094	28.27	-0.22	28.05	46.00	17.95	Peak

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: vertical
 Note:

Date: 2023-10-20




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	27.74	-4.20	23.54	40.00	16.46	Peak
2	38.212	37.74	-10.02	27.72	40.00	12.28	Peak
3	39.715	38.59	-11.19	27.40	40.00	12.60	Peak
4	43.812	38.43	-13.58	24.85	40.00	15.15	Peak
5	71.832	35.72	-16.74	18.98	40.00	21.02	Peak
6	945.440	27.85	-0.36	27.49	46.00	18.51	Peak

Middle channel

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: horizontal
 Note:


Date: 2023-10-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.64	-4.20	24.44	40.00	15.56	Peak
2	67.202	28.72	-16.80	11.92	40.00	28.08	Peak
3	121.549	28.43	-11.43	17.00	43.50	26.50	Peak
4	163.755	28.14	-12.28	15.86	43.50	27.64	Peak
5	731.920	29.05	-3.04	26.01	46.00	19.99	Peak
6	916.069	27.62	-0.64	26.98	46.00	19.02	Peak

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: vertical
 Note:

Date: 2023-10-20




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	27.96	-4.20	23.76	40.00	16.24	Peak
2	36.895	34.79	-9.06	25.73	40.00	14.27	Peak
3	42.900	38.18	-13.05	25.13	40.00	14.87	Peak
4	71.832	37.06	-16.74	20.32	40.00	19.68	Peak
5	130.379	28.10	-11.31	16.79	43.50	26.71	Peak
6	929.008	27.56	-0.59	26.97	46.00	19.03	Peak

High channel

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: horizontal
 Note:


Date: 2023-10-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.12	-4.20	23.92	40.00	16.08	Peak
2	74.919	29.09	-16.97	12.12	40.00	27.88	Peak
3	121.976	28.32	-11.42	16.90	43.50	26.60	Peak
4	153.739	28.72	-11.91	16.81	43.50	26.69	Peak
5	444.851	29.07	-7.14	21.93	46.00	24.07	Peak
6	903.309	28.26	-0.80	27.46	46.00	18.54	Peak

Project No.: CR230850844-RFA
 Tester: Vic Du
 Polarization: vertical
 Note:

Date: 2023-10-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	39.715	38.03	-11.19	26.84	40.00	13.16	Peak
2	43.202	38.41	-13.22	25.19	40.00	14.81	Peak
3	71.832	36.72	-16.74	19.98	40.00	20.02	Peak
4	125.886	28.18	-11.30	16.88	43.50	26.62	Peak
5	508.258	28.24	-5.85	22.39	46.00	23.61	Peak
6	903.309	28.64	-0.80	27.84	46.00	18.16	Peak


2) 1-25GHz:**BLE 1Mbps:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	26.36	PK	H	31.46	57.82	74.00	16.18
2390.000	13.69	AV	H	31.46	45.15	54.00	8.85
4804.000	40.79	PK	H	10.91	51.70	74.00	22.30
4804.000	27.36	AV	H	10.91	38.27	54.00	15.73
2390.000	26.43	PK	V	31.46	57.89	74.00	16.11
2390.000	13.94	AV	V	31.46	45.40	54.00	8.60
4804.000	39.46	PK	V	10.91	50.37	74.00	23.63
4804.000	26.74	AV	V	10.91	37.65	54.00	16.35
Middle Channel: 2440 MHz							
4880.000	38.43	PK	H	11.07	49.50	74.00	24.50
4880.000	25.98	AV	H	11.07	37.05	54.00	16.95
4880.000	36.92	PK	V	11.07	47.99	74.00	26.01
4880.000	24.90	AV	V	11.07	35.97	54.00	18.03
High Channel: 2480 MHz							
2483.500	26.78	PK	H	31.64	58.42	74.00	15.58
2483.500	13.76	AV	H	31.64	45.40	54.00	8.60
4960.000	40.21	PK	H	11.23	51.44	74.00	22.56
4960.000	27.88	AV	H	11.23	39.11	54.00	14.89
2483.500	26.51	PK	V	31.64	58.15	74.00	15.85
2483.500	13.71	AV	V	31.64	45.35	54.00	8.65
4960.000	39.12	PK	V	11.23	50.35	74.00	23.65
4960.000	26.59	AV	V	11.23	37.82	54.00	16.18

BLE 2Mbps:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2402 MHz							
2390.000	26.88	PK	H	31.46	58.34	74.00	15.66
2390.000	13.47	AV	H	31.46	44.93	54.00	9.07
4804.000	41.36	PK	H	10.91	52.27	74.00	21.73
4804.000	28.36	AV	H	10.91	39.27	54.00	14.73
2390.000	26.74	PK	V	31.46	58.20	74.00	15.80
2390.000	13.41	AV	V	31.46	44.87	54.00	9.13
4804.000	40.00	PK	V	10.91	50.91	74.00	23.09
4804.000	26.95	AV	V	10.91	37.86	54.00	16.14
Middle Channel: 2440 MHz							
4880.000	39.67	PK	H	11.07	50.74	74.00	23.26
4880.000	26.44	AV	H	11.07	37.51	54.00	16.49
4880.000	38.02	PK	V	11.07	49.09	74.00	24.91
4880.000	24.93	AV	V	11.07	36.00	54.00	18.00
High Channel: 2480 MHz							
2483.500	26.38	PK	H	31.64	58.02	74.00	15.98
2483.500	13.67	AV	H	31.64	45.31	54.00	8.69
4960.000	40.74	PK	H	11.23	51.97	74.00	22.03
4960.000	27.12	AV	H	11.23	38.35	54.00	15.65
2483.500	26.30	PK	V	31.64	57.94	74.00	16.06
2483.500	13.57	AV	V	31.64	45.21	54.00	8.79
4960.000	39.10	PK	V	11.23	50.33	74.00	23.67
4960.000	25.81	AV	V	11.23	37.04	54.00	16.96


Worst Test plots for Harmonic Margin (BLE 2M Low channel was the worst)



Horizontal

Project No.: CR230850844-RFA1
Tester: Mack Huang
Polarization: Horizontal
Note:

Date: 2023-09-30




18-25GHz

Vertical

Project No.: CR230850844-RFA1
Tester: Mack Huang
Polarization: Vertical
Note:

Date: 2023-09-30




1-18GHz

Vertical

Project No.: CR230850844-RFA1
Tester: Mack Huang
Polarization: Vertical
Note:

Date: 2023-09-30



18-25GHz

4.3 Maximum Conducted Output Power

Serial Number:	2BR6-2	Test Date:	2023/9/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rou Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.8	Relative Humidity: (%)	51.2	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	------	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1Mbps	2402	9.35	≤30
	2440	9.07	≤30
	2480	8.99	≤30
BLE 2Mbps	2402	9.82	≤30
	2440	9.16	≤30
	2480	9.11	≤30
Max.EIRP:	11.24	dBm	
EIRP Limit for RSS-247:36 dBm			

5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

5.1.2 Measurement Result

Operation Modes	Frequency (MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Exemption ERP		Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP (dBm)	MPE-Based Exemption
				(mW)	(dBm)				
BLE	2402-2480	19.88	200	768	28.85	10.5	1.42	9.77	Compliant

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Result: The device compliant the MPE-Based Exemption at 20cm distances.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR230850844-EXP EUT EXTERNAL PHOTOGRAPHS and CR230850844-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230850844-00A1-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====