



## Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse Wang and James Chiu	Temperature :	21~23°C
		Relative Humidity :	41~42%

15E Band 2 - 5250~5350MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11a CH 52 5260MHz		5126.15	57.04	-16.96	74	44.77	34.59	11.5	33.82	100	340	P	H
		5149.1	42.81	-11.19	54	30.47	34.61	11.55	33.82	100	340	A	H
	*	5260	113.97	-	-	101.4	34.77	11.62	33.82	100	340	P	H
	*	5260	102.27	-	-	89.7	34.77	11.62	33.82	100	340	A	H
		5382.56	58.86	-15.14	74	45.99	34.94	11.74	33.81	100	340	P	H
		5413.47	44.28	-9.72	54	31.37	34.98	11.74	33.81	100	340	A	H
		5130.8	57.14	-16.86	74	44.87	34.59	11.5	33.82	246	328	P	V
		5144.75	42.93	-11.07	54	30.59	34.61	11.55	33.82	246	328	A	V
	*	5260	120.83	-	-	108.26	34.77	11.62	33.82	246	328	P	V
	*	5260	109.9	-	-	97.33	34.77	11.62	33.82	246	328	A	V
		5351.21	59.25	-14.75	74	46.47	34.89	11.71	33.82	246	328	P	V
		5440.09	44.64	-9.36	54	31.64	35.01	11.8	33.81	246	328	A	V
802.11a CH 60 5300MHz		5147.3	56.62	-17.38	74	44.28	34.61	11.55	33.82	100	349	P	H
		5146.25	42.6	-11.4	54	30.26	34.61	11.55	33.82	100	349	A	H
	*	5300	114.83	-	-	102.18	34.82	11.65	33.82	100	349	P	H
	*	5300	102.85	-	-	90.2	34.82	11.65	33.82	100	349	A	H
		5380.69	58.47	-15.53	74	45.6	34.94	11.74	33.81	100	349	P	H
		5350.22	44.51	-9.49	54	31.73	34.89	11.71	33.82	100	349	A	H
		5076.2	56.71	-17.29	74	44.56	34.52	11.46	33.83	258	343	P	V
		5120	42.97	-11.03	54	30.73	34.56	11.5	33.82	258	343	A	V
	*	5300	120.47	-	-	107.82	34.82	11.65	33.82	258	343	P	V
	*	5300	108.82	-	-	96.17	34.82	11.65	33.82	258	343	A	V
		5378.16	58.3	-15.7	74	45.46	34.94	11.71	33.81	258	343	P	V
		5375.74	44.91	-9.09	54	32.1	34.91	11.71	33.81	258	343	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11a CH 64 5320MHz	*	5320	114.47	-	-	101.77	34.84	11.68	33.82	103	349	P	H
	*	5320	102.14	-	-	89.44	34.84	11.68	33.82	103	349	A	H
		5350.44	60.77	-13.23	74	47.99	34.89	11.71	33.82	103	349	P	H
		5350	46.44	-7.56	54	33.66	34.89	11.71	33.82	103	349	A	H
													H
													H
	*	5320	121.06	-	-	108.36	34.84	11.68	33.82	242	331	P	V
	*	5320	109.61	-	-	96.91	34.84	11.68	33.82	242	331	A	V
		5352.1	60.16	-13.84	74	47.38	34.89	11.71	33.82	242	331	P	V
		5350	46.93	-7.07	54	34.15	34.89	11.71	33.82	242	331	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz  
WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11a CH 52 5260MHz		10525	54.99	-19.01	74	60.96	37.32	16.49	59.78	370	185	P	H
		10525	43.59	-10.41	54	49.56	37.32	16.49	59.78	370	185	A	H
		15780	49.15	-24.85	74	45.79	40.63	20.46	57.73	100	0	P	H
													H
		10525	57.73	-16.27	74	63.7	37.32	16.49	59.78	380	287	P	V
		10525	45.37	-8.63	54	51.34	37.32	16.49	59.78	380	287	A	V
		15780	51.29	-22.71	74	47.93	40.63	20.46	57.73	214	98	P	V
		15780	42.01	-11.99	54	38.65	40.63	20.46	57.73	214	98	A	V
802.11a CH 60 5300MHz		10600	58.84	-15.16	74	64.52	37.42	16.56	59.66	395	0	P	H
		10600	46.95	-7.05	54	52.63	37.42	16.56	59.66	395	0	A	H
		15900	48.29	-25.71	74	44.65	40.78	20.52	57.66	100	0	P	H
													H
		10600	59.59	-14.41	74	65.27	37.42	16.56	59.66	349	121	P	V
		10600	48.89	-5.11	54	54.57	37.42	16.56	59.66	349	121	A	V
		15900	50.74	-23.26	74	47.1	40.78	20.52	57.66	100	0	P	V
													V
802.11a CH 64 5320MHz		10645	58.16	-15.84	74	63.7	37.47	16.6	59.61	354	117	P	H
		10645	46.34	-7.66	54	51.88	37.47	16.6	59.61	354	117	A	H
		15960	47.46	-26.54	74	43.67	40.86	20.55	57.62	100	0	P	H
													H
		10640	58	-16	74	63.54	37.47	16.6	59.61	302	118	P	V
		10640	46.73	-7.27	54	52.27	37.47	16.6	59.61	302	118	A	V
		15960	49.17	-24.83	74	45.38	40.86	20.55	57.62	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz  
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT20 CH 52 5260MHz		5132.75	56.49	-17.51	74	44.22	34.59	11.5	33.82	100	348	P	H
		5148.65	42.11	-11.89	54	29.77	34.61	11.55	33.82	100	348	A	H
	*	5259	114.27	-	-	101.7	34.77	11.62	33.82	100	348	P	H
	*	5259	101.64	-	-	89.07	34.77	11.62	33.82	100	348	A	H
		5376.4	57.13	-16.87	74	44.32	34.91	11.71	33.81	100	348	P	H
		5413.25	43.53	-10.47	54	30.62	34.98	11.74	33.81	100	348	A	H
		5127.8	57.03	-16.97	74	44.76	34.59	11.5	33.82	246	342	P	V
		5120	42.85	-11.15	54	30.61	34.56	11.5	33.82	246	342	A	V
	*	5260	120.71	-	-	108.14	34.77	11.62	33.82	246	342	P	V
	*	5260	108.63	-	-	96.06	34.77	11.62	33.82	246	342	A	V
		5363.64	57.49	-16.51	74	44.69	34.91	11.71	33.82	246	342	P	V
	5353.3	44.13	-9.87	54	31.35	34.89	11.71	33.82	246	342	A	V	
802.11ac VHT20 CH 60 5300MHz		5148.95	56	-18	74	43.66	34.61	11.55	33.82	100	349	P	H
		5147.45	42.17	-11.83	54	29.83	34.61	11.55	33.82	100	349	A	H
	*	5300	115.22	-	-	102.57	34.82	11.65	33.82	100	349	P	H
	*	5300	102.33	-	-	89.68	34.82	11.65	33.82	100	349	A	H
		5374.53	57.55	-16.45	74	44.74	34.91	11.71	33.81	100	349	P	H
		5386.52	43.71	-10.29	54	30.84	34.94	11.74	33.81	100	349	A	H
		5147.9	56.96	-17.04	74	44.62	34.61	11.55	33.82	229	26	P	V
		5148.05	42.37	-11.63	54	30.03	34.61	11.55	33.82	229	26	A	V
	*	5300	120.35	-	-	107.7	34.82	11.65	33.82	229	26	P	V
	*	5300	108.15	-	-	95.5	34.82	11.65	33.82	229	26	A	V
		5375.41	59.54	-14.46	74	46.73	34.91	11.71	33.81	229	26	P	V
	5353.19	44.95	-9.05	54	32.17	34.89	11.71	33.82	229	26	A	V	



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11ac VHT20 CH 64 5320MHz	*	5320	114.03	-	-	101.33	34.84	11.68	33.82	100	349	P	H
	*	5320	101.6	-	-	88.9	34.84	11.68	33.82	100	349	A	H
		5350.66	59.66	-14.34	74	46.88	34.89	11.71	33.82	100	349	P	H
		5350	45.97	-8.03	54	33.19	34.89	11.71	33.82	100	349	A	H
													H
													H
	*	5320	120.02	-	-	107.32	34.84	11.68	33.82	241	22	P	V
	*	5320	107.95	-	-	95.25	34.84	11.68	33.82	241	22	A	V
		5350.11	59.41	-14.59	74	46.63	34.89	11.71	33.82	241	22	P	V
		5350	45.77	-8.23	54	32.99	34.89	11.71	33.82	241	22	A	V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz  
WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT20 CH 52 5260MHz		10520	51.01	-22.99	74	56.98	37.32	16.49	59.78	100	0	P	H
		15780	50.4	-23.6	74	47.04	40.63	20.46	57.73	100	0	P	H
													H
													H
		10520	52.65	-21.35	74	58.62	37.32	16.49	59.78	100	0	P	V
		15780	51.77	-22.23	74	48.41	40.63	20.46	57.73	100	0	P	V
													V
802.11ac VHT20 CH 60 5300MHz		10600	51.7	-22.3	74	57.38	37.42	16.56	59.66	100	0	P	H
		15900	49.06	-24.94	74	45.42	40.78	20.52	57.66	100	0	P	H
													H
													H
		10600	53.53	-20.47	74	59.21	37.42	16.56	59.66	100	0	P	V
		15900	51.99	-22.01	74	48.35	40.78	20.52	57.66	100	0	P	V
													V
802.11ac VHT20 CH 64 5320MHz		10640	51.63	-22.37	74	57.17	37.47	16.6	59.61			P	H
		15960	47.81	-26.19	74	44.02	40.86	20.55	57.62	100	0	P	H
													H
													H
		10640	56.99	-17.01	74	62.53	37.47	16.6	59.61	395	61	P	V
		10640	43.62	-10.38	54	49.16	37.47	16.6	59.61	395	61	A	V
		15960	49.47	-24.53	74	45.68	40.86	20.55	57.62	100	0	P	V
												V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT40 CH 54 5270MHz		5142.65	55.88	-18.12	74	43.54	34.61	11.55	33.82	100	349	HORIZONTAL	H
		5145.65	42.69	-11.31	54	30.35	34.61	11.55	33.82	100	349	HORIZONTAL	H
	*	5270	106.73	-	-	94.13	34.77	11.65	33.82	100	349	HORIZONTAL	H
	*	5270	96.19	-	-	83.59	34.77	11.65	33.82	100	349	HORIZONTAL	H
		5376.29	57.49	-16.51	74	44.68	34.91	11.71	33.81	100	349	HORIZONTAL	H
		5399.17	44.09	-9.91	54	31.2	34.96	11.74	33.81	100	349	HORIZONTAL	H
		5150	56.35	-17.65	74	44.01	34.61	11.55	33.82	231	25	VERTICAL	V
		5146.1	43.34	-10.66	54	31	34.61	11.55	33.82	231	25	VERTICAL	V
	*	5270	116.82	-	-	104.22	34.77	11.65	33.82	231	25	VERTICAL	V
	*	5270	105.83	-	-	93.23	34.77	11.65	33.82	231	25	VERTICAL	V
802.11ac VHT40 CH 62 5310MHz		5143.85	55.76	-18.24	74	43.42	34.61	11.55	33.82	100	349	P	H
		5148.05	42.77	-11.23	54	30.43	34.61	11.55	33.82	100	349	A	H
	*	5310	104.96	-	-	92.26	34.84	11.68	33.82	100	349	P	H
	*	5310	95.03	-	-	82.33	34.84	11.68	33.82	100	349	A	H
		5350.22	62.06	-11.94	74	49.28	34.89	11.71	33.82	100	349	P	H
		5350	49.45	-4.55	54	36.67	34.89	11.71	33.82	100	349	A	H
		5131.7	56.46	-17.54	74	44.19	34.59	11.5	33.82	230	26	P	V
		5145.5	43.02	-10.98	54	30.68	34.61	11.55	33.82	230	26	A	V
	*	5310	114.85	-	-	102.15	34.84	11.68	33.82	230	26	P	V
	*	5310	103.87	-	-	91.17	34.84	11.68	33.82	230	26	A	V
	5354.95	67.56	-6.44	74	54.78	34.89	11.71	33.82	230	26	P	V	
	5353.85	53.21	-0.79	54	40.43	34.89	11.71	33.82	230	26	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz  
WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT40 CH 54 5270MHz		10540	42.1	-31.9	74	48.02	37.34	16.49	59.75	100	0	P	H
		15810	48.27	-25.73	74	44.83	40.67	20.48	57.71	100	0	P	H
													H
													H
802.11ac VHT40 CH 62 5310MHz		10620	42.97	-31.03	74	48.6	37.44	16.56	59.63	100	0	P	H
		15930	47.64	-26.36	74	43.93	40.82	20.53	57.64	100	0	P	H
													H
													H
802.11ac VHT40 CH 62 5310MHz		10620	44.12	-29.88	74	49.75	37.44	16.56	59.63	100	0	P	V
		15930	48.13	-25.87	74	44.42	40.82	20.53	57.64	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





15E band 2 5250~5350MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11ac VHT80 CH 58 5290MHz		5144.9	56.09	-17.91	74	43.75	34.61	11.55	33.82	105	9	P	H
		5141.9	42.45	-11.55	54	30.11	34.61	11.55	33.82	105	9	A	H
	*	5290	97.12	-	-	84.49	34.8	11.65	33.82	105	9	P	H
	*	5290	86.99	-	-	74.36	34.8	11.65	33.82	105	9	A	H
		5351.1	67.4	-6.6	74	54.62	34.89	11.71	33.82	105	9	P	H
		5351.43	52.95	-1.05	54	40.17	34.89	11.71	33.82	105	9	A	H
		5000	55.49	-18.51	74	43.55	34.4	11.37	33.83	294	360	P	V
		5000	43.31	-10.69	54	31.37	34.4	11.37	33.83	294	360	A	V
	*	5316	96.75	-	-	84.05	34.84	11.68	33.82	294	360	P	V
	*	5316	86.31	-	-	73.61	34.84	11.68	33.82	294	360	A	V
	5350.66	65.42	-8.58	74	52.64	34.89	11.71	33.82	294	360	P	V	
	5350	51.39	-2.61	54	38.61	34.89	11.71	33.82	294	360	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 2 5250~5350MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT80		10580	42.48	-31.52	74	48.24	37.4	16.52	59.68	100	0	P	H
		15870	47.63	-26.37	74	44.02	40.76	20.52	57.67	100	0	P	H
													H
													H
CH 58 5290MHz		10580	42.68	-31.32	74	48.44	37.4	16.52	59.68	100	0	P	V
		15870	47.23	-26.77	74	43.62	40.76	20.52	57.67	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 3 - 5470~5725MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
802.11a CH 100 5500MHz		5466.8	58.46	-15.54	74	45.36	35.05	11.86	33.81	100	352	P	H	
		5470	45.34	-8.66	54	32.24	35.05	11.86	33.81	100	352	A	H	
	*	5500	111.83	-	-	98.68	35.1	11.86	33.81	100	352	P	H	
	*	5500	100.54	-	-	87.39	35.1	11.86	33.81	100	352	A	H	
													H	
													H	
			5463.44	59.25	-14.75	74	46.15	35.05	11.86	33.81	251	346	P	V
			5469.84	45.59	-8.41	54	32.49	35.05	11.86	33.81	251	346	A	V
	*		5500	118.41	-	-	105.26	35.1	11.86	33.81	251	346	P	V
	*		5500	107.24	-	-	94.09	35.1	11.86	33.81	251	346	A	V
													V	
													V	
802.11a CH 116 5580MHz		5376.4	57.09	-16.91	74	44.28	34.91	11.71	33.81	100	349	P	H	
		5420.1	43.58	-10.42	54	30.61	34.98	11.8	33.81	100	349	A	H	
	*	5580	112.74	-	-	99.43	35.14	11.98	33.81	100	349	P	H	
	*	5580	100.42	-	-	87.11	35.14	11.98	33.81	100	349	A	H	
			5732.84	58.1	-15.9	74	44.43	35.23	12.26	33.82	100	349	P	H
			5746.2	43.86	-10.14	54	30.11	35.24	12.33	33.82	100	349	A	H
			5388.88	57.57	-16.43	74	44.7	34.94	11.74	33.81	250	332	P	V
			5440.1	44.69	-9.31	54	31.69	35.01	11.8	33.81	250	332	A	V
	*		5580	118.29	-	-	104.98	35.14	11.98	33.81	250	332	P	V
	*		5580	105.66	-	-	92.35	35.14	11.98	33.81	250	332	A	V
			5742.28	58.01	-15.99	74	44.26	35.24	12.33	33.82	250	332	P	V
			5760.12	43.93	-10.07	54	30.16	35.26	12.33	33.82	250	332	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11a CH 140 5700MHz	*	5700	111.83	-	-	98.26	35.21	12.18	33.82	102	350	P	H
	*	5700	99.85	-	-	86.28	35.21	12.18	33.82	102	350	A	H
		5725.08	67.48	-6.52	74	53.81	35.23	12.26	33.82	102	350	P	H
		5725	50.97	-3.03	54	37.3	35.23	12.26	33.82	102	350	A	H
													H
													H
	*	5700	116.17	-	-	102.6	35.21	12.18	33.82	247	334	P	V
	*	5700	105.09	-	-	91.52	35.21	12.18	33.82	247	334	A	V
		5725	66.11	-7.89	74	52.44	35.23	12.26	33.82	247	334	P	V
		5725	50.41	-3.59	54	36.74	35.23	12.26	33.82	247	334	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 - 5470~5725MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11a CH 100 5500MHz		11000	59.08	-14.92	74	63.34	37.9	16.94	59.1	395	4	P	H
		11000	48.78	-5.22	54	53.04	37.9	16.94	59.1	395	4	A	H
		16500	48.57	-25.43	74	43.09	41.4	20.88	56.8	100	0	P	H
													H
		11000	61.82	-12.18	74	66.08	37.9	16.94	59.1	391	119	P	V
		11000	49.44	-4.56	54	53.7	37.9	16.94	59.1	391	119	A	V
		16500	51.42	-22.58	74	45.94	41.4	20.88	56.8	395	120	P	V
		16500	42.5	-11.5	54	37.02	41.4	20.88	56.8	395	120	A	V
802.11a CH 116 5580MHz		11150	56.32	-17.68	74	59.96	37.99	17.08	58.71	395	13	P	H
		11150	46.2	-7.8	54	49.84	37.99	17.08	58.71	395	13	A	H
		16740	50.18	-23.82	74	43.87	41.88	21.04	56.61	100	0	P	H
													H
		11165	58.03	-15.97	74	61.62	38	17.08	58.67	393	120	P	V
		11165	47.8	-6.2	54	51.39	38	17.08	58.67	393	120	A	V
		16734	56.48	-17.52	74	50.17	41.88	21.04	56.61	395	166	P	V
		16734	47.33	-6.67	54	41.02	41.88	21.04	56.61	395	166	A	V
802.11a CH 140 5700MHz		11395	59.37	-14.63	74	62.03	38.13	17.31	58.1	395	355	P	H
		11395	49.47	-4.53	54	52.13	38.13	17.31	58.1	395	355	A	H
		17100	50.69	-23.31	74	43.56	42.32	21.27	56.46	100	0	P	H
													H
		11395	62.25	-11.75	74	64.91	38.13	17.31	58.1	352	110	P	V
		11395	52.55	-1.45	54	55.21	38.13	17.31	58.1	352	110	A	V
		17088	58.73	-15.27	74	51.58	42.33	21.27	56.45	302	110	P	V
		17088	43.2	-10.8	54	36.05	42.33	21.27	56.45	302	110	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 - 5470~5725MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
802.11ac VHT20 CH 100 5500MHz		5469.84	57.57	-16.43	74	44.47	35.05	11.86	33.81	100	350	P	H	
		5470	44.38	-9.62	54	31.28	35.05	11.86	33.81	100	350	A	H	
	*	5500	112.33	-	-	99.18	35.1	11.86	33.81	100	350	P	H	
	*	5500	99.32	-	-	86.17	35.1	11.86	33.81	100	350	A	H	
													H	
													H	
			5467.12	59.08	-14.92	74	45.98	35.05	11.86	33.81	215	24	P	V
			5466.32	45.53	-8.47	54	32.43	35.05	11.86	33.81	215	24	A	V
	*		5500	117.65	-	-	104.5	35.1	11.86	33.81	215	24	P	V
	*		5500	105.47	-	-	92.32	35.1	11.86	33.81	215	24	A	V
													V	
													V	
802.11ac VHT20 CH 116 5580MHz		5370.96	57.52	-16.48	74	44.72	34.91	11.71	33.82	100	349	P	H	
		5420.24	43.62	-10.38	54	30.65	34.98	11.8	33.81	100	349	A	H	
	*	5580	113.48	-	-	100.17	35.14	11.98	33.81	100	349	P	H	
	*	5580	100.49	-	-	87.18	35.14	11.98	33.81	100	349	A	H	
			5730.92	58.2	-15.8	74	44.53	35.23	12.26	33.82	100	349	P	H
			5746.44	43.88	-10.12	54	30.13	35.24	12.33	33.82	100	349	A	H
			5457.04	57.59	-16.41	74	44.57	35.03	11.8	33.81	220	22	P	V
			5439.92	44.81	-9.19	54	31.81	35.01	11.8	33.81	220	22	A	V
	*		5580	118.34	-	-	105.03	35.14	11.98	33.81	220	22	P	V
	*		5580	106	-	-	92.69	35.14	11.98	33.81	220	22	A	V
		5736.52	57.74	-16.26	74	44.06	35.24	12.26	33.82	220	22	P	V	
		5760.04	44.04	-9.96	54	30.27	35.26	12.33	33.82	220	22	A	V	



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11ac VHT20 CH 140 5700MHz	*	5700	111.02	-	-	97.45	35.21	12.18	33.82	100	350	P	H
	*	5700	99.44	-	-	85.87	35.21	12.18	33.82	100	350	A	H
		5725.16	71.72	-2.28	74	58.05	35.23	12.26	33.82	100	350	P	H
		5725	53.77	-0.23	54	40.1	35.23	12.26	33.82	100	350	A	H
													H
													H
	*	5700	116.96	-	-	103.39	35.21	12.18	33.82	233	334	P	V
	*	5700	105.55	-	-	91.98	35.21	12.18	33.82	233	334	A	V
		5725	69.66	-4.34	74	55.99	35.23	12.26	33.82	233	334	P	V
		5725	53.64	-0.36	54	39.97	35.23	12.26	33.82	233	334	A	V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 - 5470~5725MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT20 CH 100 5500MHz		11000	58.33	-15.67	74	62.59	37.9	16.94	59.1	395	0	P	H
		11000	45.23	-8.77	54	49.49	37.9	16.94	59.1	395	0	A	H
		16500	48.87	-25.13	74	43.39	41.4	20.88	56.8	100	0	P	H
													H
		11000	63.17	-10.83	74	67.43	37.9	16.94	59.1	395	66	P	V
		11000	49.09	-4.91	54	53.35	37.9	16.94	59.1	395	66	A	V
		16500	48.4	-25.6	74	42.92	41.4	20.88	56.8	100	0	P	V
													V
802.11ac VHT20 CH 116 5580MHz		11160	58.38	-15.62	74	61.97	38	17.08	58.67	370	0	P	H
		11160	44.57	-9.43	54	48.16	38	17.08	58.67	370	0	A	H
		16740	51.25	-22.75	74	44.94	41.88	21.04	56.61	100	0	P	H
													H
		11160	61.9	-12.1	74	65.49	38	17.08	58.67	395	68	P	V
		11160	48.9	-5.1	54	52.49	38	17.08	58.67	395	68	A	V
		16740	52.83	-21.17	74	46.52	41.88	21.04	56.61	100	0	P	V
													V
802.11ac VHT20 CH 140 5700MHz		11395	56.39	-17.61	74	59.05	38.13	17.31	58.1	372	0	P	H
		11395	43.1	-10.9	54	45.76	38.13	17.31	58.1	372	0	A	H
		17100	51.34	-22.66	74	44.21	42.32	21.27	56.46	100	0	P	H
													H
		11400	61.44	-12.56	74	64.05	38.14	17.31	58.06	390	48	P	V
		11400	47	-7	54	49.61	38.14	17.31	58.06	390	48	A	V
		17100	52.52	-21.48	74	45.39	42.32	21.27	56.46	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





15E band 3 - 5470~5725MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11ac VHT40 CH 102 5510MHz		5464.88	63.68	-10.32	74	50.58	35.05	11.86	33.81	100	225	P	H
		5469.84	48.77	-5.23	54	35.67	35.05	11.86	33.81	100	225	A	H
	*	5510	105.42	-	-	92.21	35.1	11.92	33.81	100	225	P	H
	*	5510	95.05	-	-	81.84	35.1	11.92	33.81	100	225	A	H
		5761.88	57.69	-16.31	74	43.92	35.26	12.33	33.82	100	225	P	H
		5763.56	44.53	-9.47	54	30.76	35.26	12.33	33.82	100	225	A	H
		5469.84	63.74	-10.26	74	50.64	35.05	11.86	33.81	319	155	P	V
		5470	51.3	-2.7	54	38.2	35.05	11.86	33.81	319	155	A	V
	*	5510	114.61	-	-	101.4	35.1	11.92	33.81	319	155	P	V
	*	5510	103.65	-	-	90.44	35.1	11.92	33.81	319	155	A	V
802.11ac VHT40 CH 110 5550MHz		5356.08	57.41	-16.59	74	44.63	34.89	11.71	33.82	236	224	P	H
		5404.4	44.06	-9.94	54	31.17	34.96	11.74	33.81	236	224	A	H
	*	5550	104.82	-	-	91.52	35.13	11.98	33.81	236	224	P	H
	*	5550	94.48	-	-	81.18	35.13	11.98	33.81	236	224	A	H
		5750.44	57.38	-16.62	74	43.63	35.24	12.33	33.82	236	224	P	H
		5762.2	44.5	-9.5	54	30.73	35.26	12.33	33.82	236	224	A	H
		5440.56	58.42	-15.58	74	45.42	35.01	11.8	33.81	332	156	P	V
		5440.08	45.35	-8.65	54	32.35	35.01	11.8	33.81	332	156	A	V
	*	5550	114.56	-	-	101.26	35.13	11.98	33.81	332	156	P	V
	*	5550	103.83	-	-	90.53	35.13	11.98	33.81	332	156	A	V
	5749.48	57.89	-16.11	74	44.14	35.24	12.33	33.82	332	156	P	V	
	5750.12	44.62	-9.38	54	30.87	35.24	12.33	33.82	332	156	A	V	



WIFI Ant.	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 134 5670MHz		5414.96	56.56	-17.44	74	43.65	34.98	11.74	33.81	236	243	P	H
		5410.64	43.6	-10.4	54	30.71	34.96	11.74	33.81	236	243	A	H
	*	5670	102.13	-	-	88.57	35.2	12.18	33.82	236	243	P	H
	*	5670	93.11	-	-	79.55	35.2	12.18	33.82	236	243	A	H
		5756.52	57.81	-16.19	74	44.04	35.26	12.33	33.82	236	243	P	H
		5755.4	44.09	-9.91	54	30.32	35.26	12.33	33.82	236	243	A	H
		5462.48	56.63	-17.37	74	43.55	35.03	11.86	33.81	332	196	P	V
		5409.84	43.75	-10.25	54	30.86	34.96	11.74	33.81	332	196	A	V
	*	5670	112.8	-	-	99.24	35.2	12.18	33.82	332	196	P	V
	*	5670	102.48	-	-	88.92	35.2	12.18	33.82	332	196	A	V
	5727.72	58.97	-15.03	74	45.3	35.23	12.26	33.82	332	196	P	V	
	5725.8	45.86	-8.14	54	32.19	35.23	12.26	33.82	332	196	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 - 5470~5725MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBµV/m )	( dB )	( dBµV/m )	( dBµV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11ac VHT40 CH 102 5510MHz		11020	46.8	-27.2	74	51.01	37.91	16.94	59.06	100	0	P	H
		16530	47.92	-26.08	74	42.31	41.47	20.91	56.77	100	0	P	H
													H
													H
		11025	49.88	-24.12	74	54	37.92	16.97	59.01	100	0	P	V
		16530	49.18	-24.82	74	43.57	41.47	20.91	56.77	100	0	P	V
802.11ac VHT40 CH 110 5550MHz		11100	44.66	-29.34	74	48.53	37.96	17.01	58.84	100	0	P	H
		16650	48.7	-25.3	74	42.68	41.71	20.99	56.68	100	0	P	H
													H
													H
		11100	46.01	-27.99	74	49.88	37.96	17.01	58.84	100	0	P	V
		16650	48.78	-25.22	74	42.76	41.71	20.99	56.68	100	0	P	V
802.11ac VHT40 CH 134 5670MHz		11340	45.8	-28.2	74	48.7	38.1	17.23	58.23	100	0	P	H
		17010	49.84	-24.16	74	42.64	42.39	21.22	56.41	100	0	P	H
													H
													H
		11345	50.33	-23.67	74	53.14	38.11	17.27	58.19	100	0	P	V
		17010	49.79	-24.21	74	42.59	42.39	21.22	56.41	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 5470~5725MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT80 CH 106 5530MHz		5470	66.55	-7.45	74	53.45	35.05	11.86	33.81	250	54	P	H
		5470	53.28	-0.72	54	40.18	35.05	11.86	33.81	250	54	A	H
	*	5530	99.08	-	-	85.86	35.11	11.92	33.81	250	54	P	H
	*	5530	87.69	-	-	74.47	35.11	11.92	33.81	250	54	A	H
		5749.08	57.73	-16.27	74	43.98	35.24	12.33	33.82	250	54	P	H
		5747.56	44.21	-9.79	54	30.46	35.24	12.33	33.82	250	54	A	H
		5468.08	63.12	-10.88	74	50.02	35.05	11.86	33.81	134	291	P	V
		5470	50.27	-3.73	54	37.17	35.05	11.86	33.81	134	291	A	V
	*	5530	96.63	-	-	83.41	35.11	11.92	33.81	134	291	P	V
	*	5530	85.02	-	-	71.8	35.11	11.92	33.81	134	291	A	V
802.11ac VHT80 CH 122 5610MHz		5760.04	57.36	-16.64	74	43.59	35.26	12.33	33.82	134	291	P	V
		5730.04	44.11	-9.89	54	30.44	35.23	12.26	33.82	134	291	A	V
		5461.36	57.56	-16.44	74	44.48	35.03	11.86	33.81	103	43	P	H
		5468.24	45.5	-8.5	54	32.4	35.05	11.86	33.81	103	43	A	H
	*	5610	105.62	-	-	92.24	35.16	12.04	33.82	103	43	P	H
	*	5610	93.58	-	-	80.2	35.16	12.04	33.82	103	43	A	H
		5727.72	61.08	-12.92	74	47.41	35.23	12.26	33.82	103	43	P	H
		5725.56	48.06	-5.94	54	34.39	35.23	12.26	33.82	103	43	A	H
		5468.24	57.16	-16.84	74	44.06	35.05	11.86	33.81	117	292	P	V
		5467.12	44.72	-9.28	54	31.62	35.05	11.86	33.81	117	292	A	V
*	5610	104.28	-	-	90.9	35.16	12.04	33.82	117	292	P	V	
*	5610	92.88	-	-	79.5	35.16	12.04	33.82	117	292	A	V	
	5726.52	63.26	-10.74	74	49.59	35.23	12.26	33.82	117	292	P	V	
	5725.88	48.26	-5.74	54	34.59	35.23	12.26	33.82	117	292	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E band 3 5470~5725MHz  
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11ac VHT80 CH 106 5530MHz		11060	43.54	-30.46	74	47.56	37.94	16.97	58.93	100	0	P	H
		16590	48.59	-25.41	74	42.79	41.57	20.96	56.73	100	0	P	H
													H
													H
802.11ac VHT80 CH 122 5610MHz		11220	45.27	-28.73	74	48.66	38.03	17.12	58.54	100	0	P	H
		16830	49.68	-24.32	74	43.04	42.06	21.12	56.54	100	0	P	H
													H
													H
802.11ac VHT80 CH 122 5610MHz		11205	49.03	-24.97	74	52.47	38.02	17.12	58.58	100	0	P	V
		16830	49.62	-24.38	74	42.98	42.06	21.12	56.54	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





15E Emission below 1GHz

WIFI 802.11ac VHT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
802.11ac VHT20 LF		30.27	24.94	-15.06	40	34.77	19.9	1.77	31.5			P	H	
		166.89	32.8	-10.7	43.5	50.87	10.45	2.61	31.13			P	H	
		260.85	38.02	-7.98	46	51.81	14.05	3.16	31			P	H	
		562.5	37.99	-8.01	46	45.85	18.88	4.01	30.75			P	H	
		650	40.53	-5.47	46	47.11	19.7	4.22	30.5	100	66	P	H	
		687.8	38.27	-7.73	46	44.64	19.7	4.35	30.42			P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			30	34.93	-5.07	40	44.76	19.9	1.77	31.5	100	84	P	V
			183.9	31.45	-12.05	43.5	49.98	9.76	2.69	30.98			P	V
			257.07	35.07	-10.93	46	49.31	13.8	2.96	31			P	V
			325.2	29.28	-16.72	46	42.4	14.6	3.28	31			P	V
			650	38.67	-7.33	46	45.25	19.7	4.22	30.5			P	V
			687.8	33.24	-12.76	46	39.61	19.7	4.35	30.42			P	V
													V	
												V		
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



15E Emission below 1GHz

WIFI 802.11ac VHT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
802.11ac VHT40 LF		30	25.14	-14.86	40	34.97	19.9	1.77	31.5			P	H	
		168.24	33.96	-9.54	43.5	52.12	10.35	2.61	31.12			P	H	
		259.77	38.23	-7.77	46	52.17	14.1	2.96	31			P	H	
		562.5	36.78	-9.22	46	44.64	18.88	4.01	30.75			P	H	
		650	40.61	-5.39	46	47.19	19.7	4.22	30.5	100	17	P	H	
		687.8	37.74	-8.26	46	44.11	19.7	4.35	30.42			P	H	
													H	
													H	
													H	
													H	
													H	
													H	
			30.27	34.75	-5.25	40	44.58	19.9	1.77	31.5	100	78	P	V
			182.82	31.22	-12.28	43.5	49.72	9.77	2.69	30.96			P	V
			260.85	36.09	-9.91	46	49.88	14.05	3.16	31			P	V
			562.5	33.32	-12.68	46	41.18	18.88	4.01	30.75			P	V
			650	39.15	-6.85	46	45.73	19.7	4.22	30.5			P	V
			687.8	32.52	-13.48	46	38.89	19.7	4.35	30.42			P	V
													V	
													V	
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													





15E Emission below 1GHz

WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
5TX		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
802.11ac VHT80 LF		30.27	24.97	-15.03	40	34.8	19.9	1.77	31.5			P	H	
		168.24	34.97	-8.53	43.5	53.13	10.35	2.61	31.12			P	H	
		263.55	38.07	-7.93	46	52.01	13.9	3.16	31			P	H	
		562.5	37.53	-8.47	46	45.39	18.88	4.01	30.75			P	H	
		650	40.22	-5.78	46	46.8	19.7	4.22	30.5	100	17	P	H	
		687.8	38.29	-7.71	46	44.66	19.7	4.35	30.42			P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			30.54	35.33	-4.67	40	45.68	19.34	1.77	31.46	100	63	P	V
			168.24	32.04	-11.46	43.5	50.2	10.35	2.61	31.12			P	V
			263.28	35.48	-10.52	46	49.37	13.95	3.16	31			P	V
			562.5	33.69	-12.31	46	41.55	18.88	4.01	30.75			P	V
			650	39.1	-6.9	46	45.68	19.7	4.22	30.5			P	V
			687.8	32.82	-13.18	46	39.19	19.7	4.35	30.42			P	V
													V	
												V		
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2412MHz													

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**