






5.6.3 LTE Band 38




















5.7 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Test Requirement: FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)(b)

Test Method: ANSI/TIA/EIA-603-D 2010 & KDB 971168 D01v02r02

Limit:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm

Test Procedure:

The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range. b. Measuring frequency range is from 30 MHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


Test Setup: Refer to section 4.2.2 for details.


Instruments Used: Refer to section 3 for details


Test Mode: Link mode


Test Results: Pass


5.7.1 LTE Band 4


















5.7.2 LTE Band 7













5.7.3 LTE Band 38









5.8 FIELD STRENGTH OF SPURIOUS RADIATION

Test Requirement: FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 24.238(a)(b)

Test Method: ANSI/TIA/EIA-603-D 2010 & KDB 971168 D01v02r02

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009 MHz-30 MHz	Peak	10 kHz	30 KHz	Peak
30 MHz-1 GHz	Quasi-peak	100 kHz	300 KHz	Peak
Above 1 GHz	Peak	1 MHz	3 MHz	Peak

Limits:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm

Test Setup: Refer to section 4.2.1 for details.

Test Procedures:

1. Scan up to 10th harmonic, find the maximum radiation frequency to measure.
2. The technique used to find the Spurious Emissions of the transmitter was the antenna substitution method. Substitution method was performed to determine the actual ERP/EIRP emission levels of the EUT.

Test procedure as below:

- 1) The EUT was powered ON and placed on a 0.8/1.5m high table at a 3 meter semi/fully Anechoic Chamber. The antenna of the transmitter was extended to its maximum length. Modulation mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 4) Steps 1) to 3) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 5) The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 6) A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 3) is obtained for this set of conditions.
- 7) The output power into the substitution antenna was then measured.
- 8) Steps 6) and 7) were repeated with both antennas polarized.
- 9) Calculate power in dBm by the following formula:

$$\text{ERP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP} = \text{ERP} + 2.15\text{dB}$$

where:

Pg is the generator output power into the substitution antenna.

- 10) Test the EUT in the lowest channel, the middle channel the Highest channel

11) The radiation measurements are performed in X, Y, Z axis positioning for EUT operation mode, and found the 错误!未找到引用源。 positioning which it is worse case.


- 12) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass


The measurement data as follows:

5.8.1 Radiated Emission Test Data (30 MHz to 1 GHz)




LTE Band 4 / 3 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 4 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 4 / 10 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 4 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 4 / 20 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 10 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 20 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 10 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 20 MHz / QPSK_ Middle Channel


Horizontal



Vertical




5.8.2 Radiated Emission Test Data (Above 1GHz)




LTE Band 4 / 3 MHz / QPSK_ Middle Channel

Horizontal




Vertical





LTE Band 4 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical






LTE Band 4 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 4 / 20 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 10 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 7 / 20 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 5 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 10 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 15 MHz / QPSK_ Middle Channel

Horizontal




Vertical




LTE Band 38 / 20 MHz / QPSK_ Middle Channel

Horizontal



Vertical



5.9 FREQUENCY STABILITY

Test Requirement: FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 24.235

Test Method: ANSI/TIA/EIA-603-D 2010 & KDB 971168 D01v02r02

Limits: The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Setup: Refer to section 4.2.2 for details.

Test Procedures:

1) Use CMW 500 or CMU 200 with Frequency Error measurement capability.

a) Temp. = -30° to + 50°C

b) Voltage =low voltage, 3.6 Vdc, Normal, **错误!未找到引用源。** Vdc and High voltage, 4.4 Vdc.

2) Frequency Stability vs Temperature:

The EUT is place inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until +50°C is reached.

3) Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

Equipment Used: Refer to section 3 for details.

Test Result: Pass

Modulation	Channel/ Frequency (MHz)	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
		(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 4 / 20MHz / Full RB							
QPSK	20175 / 1732.5	VL	TN	24	0.0139	Note 1	Pass
		VN		22	0.0127		Pass
		VH		23	0.0133		Pass
		VN	50	27	0.0156		Pass
			40	25	0.0144		Pass
			30	23	0.0133		Pass
			20	22	0.0127		Pass
			10	22	0.0127		Pass
			0	20	0.0115		Pass
			-10	-10	-0.0058		Pass
			-20	-13	-0.0075		Pass
			-30	-23	-0.0133		Pass

Modulation	Channel/ Frequency (MHz)	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
		(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 7 / 20MHz / Full RB							
QPSK	21100 / 2535	VL	TN	-14	-0.0055	Note 1	Pass
		VN		-12	-0.0047		Pass
		VH		-14	-0.0055		Pass
		VN	50	-20	-0.0079		Pass
			40	-18	-0.0071		Pass
			30	-14	-0.0055		Pass
			20	-14	-0.0055		Pass
			10	-12	-0.0047		Pass
			0	3	0.0012		Pass
			-10	8	0.0032		Pass
			-20	10	0.0039		Pass
			-30	11	0.0043		Pass

Modulation	Channel/ Frequency (MHz)	Voltage	Temperature	Deviation	Deviation	Limit	Pass/ Fail
		(Vdc)	(°C)	(Hz)	(ppm)	(ppm)	
LTE Band 38 / 20MHz / Full RB							
QPSK	38000 / 2595	VL	TN	-12	-0.0046	Note 1	Pass
		VN		-10	-0.0039		Pass
		VH		-11	-0.0042		Pass
		VN	50	-15	-0.0058		Pass
			40	-13	-0.0050		Pass
			30	-10	-0.0039		Pass
			20	-10	-0.0039		Pass
			10	-6	-0.0023		Pass
			0	2	0.0008		Pass
			-10	8	0.0031		Pass
			-20	11	0.0042		Pass
			-30	13	0.0050		Pass

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
