



FCC Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Redmi
MODEL NAME : M1810F6LH
FCC ID : 2AFZZ-RMSF6LH
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Dec. 18, 2018 and testing was completed on Jan. 17, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 7

 1.7. Applicable Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system 10

 2.4. EUT Operation Test Setup 11

3. TEST RESULT 12

 3.1. Test of AC Conducted Emission Measurement 12

 3.2. Test of Radiated Emission Measurement 16

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC8D1803-01	Rev. 01	Initial issue of report	Jan. 31, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.59 dB at 0.150 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 5.36 dB at 46.490 MHz



1. General Description

1.1. Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China

1.2. Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	M1810F6LH
FCC ID	2AFZZ-RMSF6LH
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+(1 6QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE
IMEI Code	Conduction: Sample 1: 864466040013656/864466040013664 Radiation: Sample 2: 864466040005132/864466040005140 864466040011619/864466040011627
HW Version	P2.0
SW Version	MIUI 10
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two samples under test, the difference of two samples is for memory: the sample 1 is 3+32GB capacity and the sample 2 is 3+64GB capacity. According to the difference, sample 1 perform full test, and sample 2 verify the difference for Radiated Emission test item.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM: 88MHz~108MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN : Fixed Internal Antenna Bluetooth : Fixed Internal Antenna GNSS: Fixed Internal Antenna FM: External Handset Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (Uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

GNSS Rx = GPS Rx + Glonass Rx + Beidou Rx + Galileo Rx + SBAS Rx



1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN5013	630927

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Earphone + USB Cable 1 (Charging from Adapter 1)+ SIM 1 for Sample 1
	Mode 2: PCS1900 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + Earphone + USB Cable 2 (Charging from Adapter 1)+ SIM 2 for Sample 1
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + MGEP4 + Earphone + USB Cable 2 (Charging from Adapter 1)+ SIM 1 for Sample 1
	Mode 4: LTE Band 4 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(98MHz) + USB Cable 2(Charging from Adapter 1) + SIM 2 for Sample 1
	Mode 5: LTE Band 2 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + SIM 1 for Sample 1
	Mode 6: LTE Band 7 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS RX + USB Cable 2(Data Link with Notebook) + SIM 2 for Sample 1
	Mode 7: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + MGEP4 + Earphone + USB Cable 2 (Charging from Adapter 2)+ SIM 1 for Sample 1



Radiated Emissions	<p>Mode 1: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + SIM 1 for Sample 1</p> <p>Mode 2: PCS1900 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2 (Charging from Adapter 1) + SIM 2 for Sample 1</p> <p>Mode 3: WCDMA Band V Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + USB Cable 2(Charging from Adapter 1) + SIM 1 for Sample 1</p> <p>Mode 4: LTE Band 4 Idle + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(98MHz) + Earphone + USB Cable 2(Charging from Adapter 1)+ SIM 2 for Sample1</p> <p>Mode 5: LTE Band 2 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + SIM 1 for Sample 1</p> <p>Mode 6: LTE Band 7 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GPS RX + USB Cable 2(Data Link with Notebook) + SIM 2 for Sample 1</p> <p>Mode 7: LTE Band 2 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + SIM 1 for Sample 2</p> <p>Mode 8: WCDMA Band V Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + USB Cable 2(Charging from Adapter 2) + SIM 1 for Sample 1</p>
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 3; only the test data of this mode is reported. 2. The worst case of RE is mode 3; only the test data of this mode is reported. 	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Signal Generator	R&S	GSS7000	NA	NA	Unshielded, 1.8m
3.	WLAN AP	TP-LINK	TL-WDR5600	N/A	N/A	Unshielded, 1.8m
4.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
5.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
6.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	Notebook	Lenovo	Latitude 3480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
8.	SD Card	Kingston	8GB	N/A	N/A	N/A
9.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
10.	iPod	Apple	A1199	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.
5. Turn on FM receiver function to make the EUT receive continuous signals from FM station



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhao	Temperature :	22.3~23.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L-181013-060103 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.150	61.41	-4.59	66.00	50.70	0.23	10.48	QP
2	0.150	50.61	-5.39	56.00	39.90	0.23	10.48	Average
3	0.184	49.92	-14.36	64.28	39.30	0.22	10.40	QP
4	0.184	32.92	-21.36	54.28	22.30	0.22	10.40	Average
5	0.195	55.20	-8.60	63.80	44.61	0.22	10.37	QP
6	0.195	42.80	-11.00	53.80	32.21	0.22	10.37	Average
7	0.224	47.67	-14.99	62.66	37.10	0.22	10.35	QP
8	0.224	34.47	-18.19	52.66	23.90	0.22	10.35	Average
9	0.239	47.76	-14.37	62.13	37.20	0.22	10.34	QP
10	0.239	35.06	-17.07	52.13	24.50	0.22	10.34	Average
11	0.285	44.04	-16.64	60.68	33.51	0.22	10.31	QP
12	0.285	31.74	-18.94	50.68	21.21	0.22	10.31	Average
13	0.336	43.02	-16.29	59.31	32.50	0.23	10.29	QP
14	0.336	30.72	-18.59	49.31	20.20	0.23	10.29	Average



Test Engineer :	Amos Zhao	Temperature :	22.3~23.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-181013-060103 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.150	60.29	-5.71	66.00	49.60	0.21	10.48	QP
2 *	0.150	50.89	-5.11	56.00	40.20	0.21	10.48	Average
3	0.181	51.11	-13.35	64.46	40.51	0.20	10.40	QP
4	0.181	31.81	-22.65	54.46	21.21	0.20	10.40	Average
5	0.194	57.18	-6.66	63.84	46.61	0.20	10.37	QP
6	0.194	44.78	-9.06	53.84	34.21	0.20	10.37	Average
7	0.227	45.15	-17.42	62.57	34.60	0.20	10.35	QP
8	0.227	26.15	-26.42	52.57	15.60	0.20	10.35	Average
9	0.244	51.63	-10.32	61.95	41.09	0.20	10.34	QP
10	0.244	38.13	-13.82	51.95	27.59	0.20	10.34	Average
11	0.285	48.81	-11.87	60.68	38.30	0.20	10.31	QP
12	0.285	35.11	-15.57	50.68	24.60	0.20	10.31	Average
13	0.345	47.08	-12.01	59.09	36.60	0.19	10.29	QP
14	0.345	32.68	-16.41	49.09	22.20	0.19	10.29	Average
15	0.476	42.63	-13.78	56.41	32.20	0.19	10.24	QP
16	0.476	27.93	-18.48	46.41	17.50	0.19	10.24	Average



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Imp Li	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 23188-3M HORIZONTAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	72.68	21.29	-18.71	40.00	39.62	12.70	0.88	31.91	---	---	Peak
2	111.48	29.01	-14.49	43.50	42.22	17.64	1.08	31.93	100	0	Peak
3	192.96	27.15	-16.35	43.50	42.15	15.49	1.42	31.91	---	---	Peak
4	384.05	23.75	-22.25	46.00	32.55	21.31	1.99	32.10	---	---	Peak
5	578.05	22.89	-23.11	46.00	28.38	24.35	2.54	32.38	---	---	Peak
6	773.99	24.31	-21.69	46.00	27.91	25.79	2.80	32.19	---	---	Peak
7 *	880.69	47.16			49.34	26.42	2.99	31.59	---	---	Peak
8	1616.00	38.17	-35.83	74.00	42.21	29.00	4.16	37.20	---	---	Peak
9	3072.00	44.58	-29.42	74.00	42.77	32.78	6.10	37.07	---	---	Peak
10	4800.00	46.25	-27.75	74.00	39.26	35.66	8.09	36.76	---	---	Peak
11	7176.00	45.54	-28.46	74.00	37.48	35.80	9.13	36.87	---	---	Peak
12	11331.00	43.24	-30.76	74.00	30.08	39.18	11.54	37.56	---	---	Peak
13	16830.00	45.56	-28.44	74.00	26.90	41.08	13.89	36.31	---	---	Peak



Test Engineer :	Imp Li	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 23188-3M VERTICAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	46.49	34.64	-5.36	40.00	50.36	15.50	0.72	31.94	100	0 Peak	
2	113.42	24.45	-19.05	43.50	37.52	17.77	1.09	31.93	---	---	Peak
3	175.50	23.24	-20.26	43.50	38.40	15.42	1.34	31.92	---	---	Peak
4	272.50	20.07	-25.93	46.00	31.07	19.24	1.77	32.01	---	---	Peak
5	359.80	20.51	-25.49	46.00	29.98	20.70	1.92	32.09	---	---	Peak
6	630.43	23.29	-22.71	46.00	28.41	24.69	2.57	32.38	---	---	Peak
7 *	881.66	46.66			48.82	26.43	2.99	31.58	---	---	Peak
8	3400.00	42.73	-31.27	74.00	39.70	33.38	6.04	36.39	---	---	Peak
9	4768.00	44.31	-29.69	74.00	37.30	35.69	8.09	36.77	---	---	Peak
10	5304.00	44.22	-29.78	74.00	37.73	35.27	7.91	36.69	---	---	Peak
11	7856.00	43.31	-30.69	74.00	35.34	35.65	9.48	37.16	---	---	Peak
12	10674.00	43.71	-30.29	74.00	31.46	38.69	11.33	37.77	---	---	Peak
13	14544.00	44.84	-29.16	74.00	27.41	40.89	12.80	36.26	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 19, 2018	Jan. 17, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Jan. 17, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Jan. 17, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Jan. 17, 2019	Oct. 11, 2019	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 06, 2018	Jan. 17, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr. 17, 2018	Jan. 17, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Jan. 29, 2018	Jan. 17, 2019	Jan. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 21, 2018	Jan. 17, 2019	Jan. 20, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Jan. 17, 2019	Feb. 06, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18~40GHz	Feb. 08, 2018	Jan. 17, 2019	Feb. 07, 2019	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2018	Jan. 17, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5G Hz	Apr. 18, 2018	Jan. 17, 2019	Apr. 17, 2019	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Jan. 17, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 17, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 17, 2019	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------