



SAR TEST REPORT

Applicant Xiaomi Communications Co., Ltd.
FCC ID 2AFZZ-RMSG6S
Product Mobile Phone
Brand MI
Model MDG6S
Report No. RXA1708-0290SAR02R1
Issue Date September 27, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **IEEE 1528-2013, ANSI/IEEE C95.1-1992**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Jiang peng Lan

Kai Xu

Performed by: Jiangpeng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

| | | |
|---------|---|----|
| 1 | Test Laboratory..... | 4 |
| 1.1 | Notes of the Test Report..... | 4 |
| 1.2 | Test facility..... | 4 |
| 1.3 | Testing Location..... | 5 |
| 1.4 | Laboratory Environment..... | 5 |
| 2 | Statement of Compliance..... | 6 |
| 3 | Description of Equipment under Test..... | 7 |
| 4 | Test Specification, Methods and Procedures..... | 10 |
| 5 | Operational Conditions during Test..... | 11 |
| 5.1 | Test Positions..... | 11 |
| 5.1.1 | Against Phantom Head..... | 11 |
| 5.1.2 | Body Worn Configuration..... | 11 |
| 5.1.3 | Phablet SAR test considerations..... | 12 |
| 5.2 | Measurement Variability..... | 13 |
| 5.3 | Test Configuration..... | 13 |
| 5.3.1 | GSM Test Configuration..... | 13 |
| 5.3.2 | 3G Test Configuration..... | 14 |
| 5.3.2.1 | WCDMA Test Configuration..... | 14 |
| 5.3.3 | LTE Test Configuration..... | 18 |
| 5.3.4 | TDD LTE specification..... | 20 |
| 5.3.5 | Wi-Fi Test Configuration..... | 22 |
| 5.3.6 | BT Test Configuration..... | 23 |
| 5.3.7 | Downlink LTE CA specification..... | 24 |
| 6 | SAR Measurements System Configuration..... | 25 |
| 6.1 | SAR Measurement Set-up..... | 25 |
| 6.2 | DASY5 E-field Probe System..... | 26 |
| 6.3 | SAR Measurement Procedure..... | 27 |
| 7 | Main Test Equipment..... | 29 |
| 8 | Tissue Dielectric Parameter Measurements & System Verification..... | 30 |
| 8.1 | Tissue Verification..... | 30 |
| 8.2 | System Performance Check..... | 32 |
| 9 | Normal and Maximum Output Power..... | 34 |
| 9.1 | GSM Mode..... | 34 |
| 9.2 | WCDMA Mode..... | 36 |
| 9.3 | LTE Mode..... | 37 |
| 9.4 | WLAN Mode..... | 46 |
| 9.5 | Bluetooth Mode..... | 47 |
| 10 | Measured and Reported (Scaled) SAR Results..... | 48 |
| 10.1 | EUT Antenna Locations..... | 48 |
| 10.2 | Standalone SAR test exclusion considerations..... | 49 |
| 10.3 | Measured SAR Results..... | 50 |



| | |
|---|-----|
| 10.4 Simultaneous Transmission Analysis..... | 64 |
| 11 Measurement Uncertainty | 66 |
| ANNEX A: Test Layout..... | 67 |
| ANNEX B: System Check Results..... | 73 |
| ANNEX C: Highest Graph Results..... | 83 |
| ANNEX D: Probe Calibration Certificate..... | 107 |
| ANNEX E: D835V2 Dipole Calibration Certificate..... | 118 |
| ANNEX F: D1750V2 Dipole Calibration Certificate..... | 126 |
| ANNEX G: D1900V2 Dipole Calibration Certificate | 134 |
| ANNEX H: D2450V2 Dipole Calibration Certificate | 142 |
| ANNEX I: D2600V2 Dipole Calibration Certificate | 150 |
| ANNEX J: DAE4 Calibration Certificate..... | 158 |
| ANNEX K: The EUT Appearances and Test Configuration | 161 |

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2 Test facility

CNAS (accreditation number:L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

1.4 Laboratory Environment

| | |
|---|---------------------------|
| Temperature | Min. = 18°C, Max. = 25 °C |
| Relative humidity | Min. = 30%, Max. = 70% |
| Ground system resistance | < 0.5 Ω |
| Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards. | |

2 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Table 2.1: Highest Reported SAR

| Mode | Highest Reported SAR (W/kg) | | |
|---|------------------------------------|---------------------------------------|-------------------------------------|
| | 1g SAR Head | 1g SAR Body-worn (Separation 10mm) | 1g SAR Hotspot (Separation 10mm) |
| GSM 850 | 0.369 | 0.376 | 0.445 |
| DTM 850 | 0.400 | 0.447 | 0.447 |
| GSM 1900 | 0.077 | 0.297 | 0.386 |
| DTM 1900 | 0.068 | 0.415 | 0.547 |
| WCDMA Band II | 0.106 | 0.616 | 0.744 |
| WCDMA Band V | 0.390 | 0.376 | 0.376 |
| LTE FDD 4 | 0.073 | 0.788 | 0.985 |
| LTE FDD 5 | 0.352 | 0.610 | 0.610 |
| LTE FDD 7 | 0.135 | 0.742 | 0.742 |
| LTE TDD 38 | 0.185 | 1.159 | 1.167 |
| Wi-Fi (2.4G) | 1.059 | 0.248 | 0.248 |
| Date of Testing: | August 22, 2017~ September 5, 2017 | | |
| Note: The device is in compliance with SAR for Uncontrolled Environment /General Population exposure limits (1.6 W/kg and 4.0 W/kg) specified in ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013. | | | |

Table 2.2: Highest Simultaneous Transmission SAR

| Exposure Configuration | 1g SAR Head | 1g SAR Body-worn (Separation 10mm) | 1g SAR Hotspot (Separation 10mm) |
|---|-------------|---------------------------------------|-------------------------------------|
| Highest Simultaneous Transmission SAR (W/kg) | 1.459 | 1.365 | 1.365 |
| Note: 1. The detail for simultaneous transmission consideration is described in chapter 10.4. | | | |

3 Description of Equipment under Test

Client Information

| | |
|-----------------------------|---|
| Applicant | Xiaomi Communications Co., Ltd. |
| Applicant address | The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China |
| Manufacturer | Xiaomi Communications Co., Ltd. |
| Manufacturer address | The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China |

**General Technologies**

| | |
|----------------------|---|
| Application Purpose: | Original Grant |
| EUT Stage | Identical Prototype |
| Model: | MDG6S |
| IMEI: | SIM 1: 865396030035469 SIM 2: 865396030035477 |
| Hardware Version: | P2 |
| Software Version: | MIUI9 |
| Antenna Type: | Internal Antenna |
| Device Class: | A |
| Wi-Fi Hotspot | Wi-Fi 2.4G |
| Power Class: | GSM 850/ DTM 850:4 GSM 1900/ DTM 1900:1 UMTS Band II/V:3 LTE FDD 4/5/7:3 LTE TDD 38:3 |
| Power Level | GSM 850/ DTM 850:level 5 GSM 1900/ DTM 1900:level 0 UMTS Band II/V:all up bits LTE FDD 4/5/7:max power LTE TDD 38:max power |
| EUT Accessory | |
| Adapter 1 | Manufacturer: Jiangsu Chenyang Electron Co., Ltd. Model: MDY-08-EZ |
| Adapter 2 | Manufacturer: DONGGUAN AOHAI POWER TECHNOLOGY CO., LTD. Model: MDY-08-EZ |
| Battery 1 | Manufacturer:HARBIN COSLIGHT POWER CO LTD Model: BN31 |
| Battery 2 | Manufacturer:Sunwoda Electronic Co.,LTD Model: BN31 |
| USB Cable | Manufacturer:BOLUDE Model:A TO Micro-B Length: 1m |

Wireless Technology and Frequency Range

| Wireless Technology | | Modulation | Operating mode | Tx (MHz) |
|--|---|---|---|-------------|
| GSM | 850 | Voice(GMSK) GPRS(GMSK) EGPRS(GMSK,8PSK) | <input type="checkbox"/> Multi-slot Class:8-1UP <input checked="" type="checkbox"/> Multi-slot Class:10-2UP (DTM) <input checked="" type="checkbox"/> Multi-slot Class:12-4UP (GPRS/ EGPRS) <input type="checkbox"/> Multi-slot Class:33-4UP | 824 ~ 849 |
| | 1900 | | | 1850 ~ 1910 |
| | Does this device support DTM (Dual Transfer Mode)? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No | | | |
| UMTS | Band II | QPSK | HSDPA UE Category:24 HSUPA UE Category:6 | 1850 ~ 1910 |
| | Band V | | | 824 ~ 849 |
| LTE | FDD 4 | QPSK, 16QAM | Rel. 11 Category 4 | 1710 ~ 1755 |
| | FDD 5 | | | 824 ~ 849 |
| | FDD 7 | | | 2500 ~ 2570 |
| | TDD 38 | | | 2570 ~ 2620 |
| | Does this device support Carrier Aggregation (CA) <input checked="" type="checkbox"/> Yes downlink only <input type="checkbox"/> No | | | |
| Does this device support SV-LTE (1xRTT-LTE)? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | | | |
| BT | 2.4G | Version 4.2 LE | | 2402 ~ 2480 |
| Wi-Fi | 2.4G | DSSS,OFDM | 802.11b/g/n HT20 | 2412 ~ 2462 |
| | Does this device support MIMO <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | | |



4 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE 1528- 2013, ANSI/IEEE C95.1-1992, the following FCC Published RF exposure KDB procedures:

248227 D01 802.11 Wi-Fi SAR v02r02
447498 D01 General RF Exposure Guidance v06
648474 D04 Handset SAR v01r03
865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
865664 D02 RF Exposure Reporting v01r02
941225 D01 3G SAR Procedures v03r01
941225 D05 SAR for LTE Devices v02r05
941225 D06 Hotspot Mode v02r01
941225 D05A LTE Rel.10 KDB Inquiry Sheet v01r02

5 Operational Conditions during Test

5.1 Test Positions

5.1.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2013 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.1.2 Body Worn Configuration

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

5.1.3 Phablet SAR test considerations

For smart phones, with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, that can provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets and support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance.

- a) The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
- b) The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB Publication 865664 D01 to address interactive hand use exposure conditions. The 1-g SAR at 5 mm for UMPC mini-tablets is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold. The normal tablet procedures in KDB Publication 616217 are required when the overall diagonal dimension of the device is > 20.0 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Extremity 10-g SAR is also not required for the front (top) surface of larger form factor full size tablets. The more conservative normal tablet SAR results can be used to support phablet mode 10-g extremity SAR.
- c) The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless modes and exposure conditions.

5.2 Measurement Variability

Per FCC KDB Publication 865664 D01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

5.3 Test Configuration

5.3.1 GSM Test Configuration

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Output power of reductions:

Table 5.1: The allowed power reduction in the multi-slot configuration

| Number of timeslots in uplink assignment | Permissible nominal reduction of maximum output power,(dB) |
|--|--|
| 1 | 0 |
| 2 | 0 to 3,0 |
| 3 | 1,8 to 4,8 |
| 4 | 3,0 to 6,0 |

5.3.2 3G Test Configuration

3G SAR Test Reduction Procedure

In the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.³ This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

5.3.2.1 WCDMA Test Configuration

Output power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

Body-Worn Accessory SAR

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices” section of this document, for the highest reported SAR body-worn accessory exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

HSDPA should be configured according to the UE category of a test device. The number of HSDSCH/ HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors(β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Table 5.2: Subtests for UMTS Release 5 HSDPA

| Sub-set | β_c | β_d | β_d (SF) | β_c/β_d | β_{hs} (note 1, note 2) | CM(dB) (note 3) | MPR(dB) |
|---------|-------------------|-------------------|-------------------|-------------------|----------------------------------|--------------------|---------|
| 1 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 0.0 | 0.0 |
| 2 | 12/15 (note 4) | 15/15 (note 4) | 64 | 12/15 (note 4) | 24/15 | 1.0 | 0.0 |
| 3 | 15/15 | 8/15 | 64 | 15/8 | 30/15 | 1.5 | 0.5 |
| 4 | 15/15 | 4/15 | 64 | 15/4 | 30/15 | 1.5 | 0.5 |

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$
 Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$.
 Note3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1,TF1) to $\beta_c=11/15$ and $\beta_d=15/15$.

HSUPA Test Configuration

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices” section of this document, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn accessory measurements is tested for next to the ear head exposure.

Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in Table 2 and other applicable procedures described in the ‘WCDMA Handset’ and ‘Release 5 HSDPA Data Devices’ sections of this document

Table 5.3: Sub-Test 5 Setup for Release 6 HSUPA

| Sub-set | β_c | β_d | β_d (SF) | β_c/β_d | $\beta_{hs}^{(1)}$ | β_{ec} | β_{ed} | β_{ed} (SF) | β_{ed} (codes) | CM ⁽²⁾ (dB) | MPR (dB) | AG ⁽⁴⁾ Index | E-TFCI |
|---------|----------------------|----------------------|----------------|----------------------|--------------------|--------------|--|-------------------|----------------------|------------------------|----------|-------------------------|--------|
| 1 | 11/15 ⁽³⁾ | 15/15 ⁽³⁾ | 64 | 11/15 ⁽³⁾ | 22/15 | 209/225 | 1039/225 | 4 | 1 | 1.0 | 0.0 | 20 | 75 |
| 2 | 6/15 | 15/15 | 64 | 6/15 | 12/15 | 12/15 | 94/75 | 4 | 1 | 3.0 | 2.0 | 12 | 67 |
| 3 | 15/15 | 9/15 | 64 | 15/9 | 30/15 | 30/15 | β_{ed1} 47/15 β_{ed2} 47/15 | 4 | 2 | 2.0 | 1.0 | 15 | 92 |
| 4 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 2/15 | 56/75 | 4 | 1 | 3.0 | 2.0 | 17 | 71 |
| 5 | 15/15 ⁽⁴⁾ | 15/15 ⁽⁴⁾ | 64 | 15/15 ⁽⁴⁾ | 30/15 | 24/15 | 134/15 | 4 | 1 | 1.0 | 0.0 | 21 | 81 |

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Figure 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table 5.4: HSUPA UE category

| UE E-DCH Category | Maximum E-DCH Codes Transmitted | Number of HARQ Processes | E-DCH TTI (ms) | Minimum Spreading Factor | Maximum E-DCH Transport Block Bits | Max Rate (Mbps) |
|-------------------|---------------------------------|--------------------------|----------------|--------------------------|------------------------------------|-----------------|
| 1 | 1 | 4 | 10 | 4 | 7110 | 0.7296 |
| 2 | 2 | 8 | 2 | 4 | 2798 | 1.4592 |
| | 2 | 4 | 10 | 4 | 14484 | |
| 3 | 2 | 4 | 10 | 4 | 14484 | 1.4592 |
| 4 | 2 | 8 | 2 | 2 | 5772 | 2.9185 |
| | 2 | 4 | 10 | 2 | 20000 | 2.00 |
| 5 | 2 | 4 | 10 | 2 | 20000 | 2.00 |
| 6 (No DPDCH) | 4 | 8 | 2 | 2 SF2 & 2 SF4 | 11484 | 5.76 |
| | 4 | 4 | 10 | | 20000 | 2.00 |
| 7 (No DPDCH) | 4 | 8 | 2 | 2 SF2 & 2 SF4 | 22996 | ? |
| | 4 | 4 | 10 | | 20000 | ? |

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4.
 UE Categories 1 to 6 supports QPSK only. UE Category 7 supports QPSK and 16QAM. (TS25.306-7.3.0)

HSPA, HSPA+ and DC-HSDPA Test Configuration

Measurement is required for HSPA, HSPA+ or DC-HSDPA, a KDB inquiry is required to confirm that the wireless mode configurations in the test setup have remained stable throughout the SAR measurements.³⁵ Without prior KDB confirmation to determine the SAR results are acceptable, a PBA is required for TCB approval.

SAR test exclusion for HSPA, HSPA+ and DC-HSDPA is determined according to the following:

1) The HSPA procedures are applied to configure 3GPP Rel. 6 HSPA devices in the required sub-test mode(s) to determine SAR test exclusion.

2) SAR is required for Rel. 7 HSPA+ when SAR is required for Rel. 6 HSPA; otherwise, the 3G SAR test reduction procedure is applied to (uplink) HSPA+ with 12.2 kbps RMC as the primary mode.³⁶ Power is measured for HSPA+ that supports uplink 16 QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

3) SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

4) Regardless of whether a PBA is required, the following information must be verified and included in the SAR report for devices supporting HSPA, HSPA+ or DC-HSDPA: a) The output power measurement results and applicable release version(s) of 3GPP TS 34.121.

i) Power measurement difficulties due to test equipment setup or availability must be resolved between the grantee and its test lab.

b) The power measurement results are in agreement with the individual device implementation and specifications. When Enhanced MPR (E-MPR) applies, the normal MPR targets may be modified according to the Cubic Metric (CM) measured by the device, which must be taken into consideration.

c) The UE category, operating parameters, such as the β and Δ values used to configure the device for testing, power setback procedures described in 3GPP TS 34.121 for the power measurements, and HSPA/HSPA+ channel conditions (active and stable) for the entire duration of the measurement according to the required E-TFCl and AG index values.

5) When SAR measurement is required, the test configurations, procedures and power measurement results must be clearly described to confirm that the required test parameters are used, including E-TFCl and AG index stability and output power conditions.

Table 5.5: HS-DSCH UE category

Table 5.1a: FDD HS-DSCH physical layer categories

| HS-DSCH category | Maximum number of HS-DSCH codes received | Minimum inter-TTI interval | Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI NOTE 1 | Total number of soft channel bits | Supported modulations without MIMO operation or dual cell operation | Supported modulations with MIMO operation and without dual cell operation | Supported modulations with dual cell operation |
|-----------------------|--|----------------------------|---|-----------------------------------|---|---|--|
| Category 1 | 5 | 3 | 7298 | 19200 | QPSK, 16QAM | Not applicable (MIMO not supported) | Not applicable (dual cell operation not supported) |
| Category 2 | 5 | 3 | 7298 | 28800 | | | |
| Category 3 | 5 | 2 | 7298 | 28800 | | | |
| Category 4 | 5 | 2 | 7298 | 38400 | | | |
| Category 5 | 5 | 1 | 7298 | 57600 | | | |
| Category 6 | 5 | 1 | 7298 | 67200 | | | |
| Category 7 | 10 | 1 | 14411 | 115200 | | | |
| Category 8 | 10 | 1 | 14411 | 134400 | | | |
| Category 9 | 15 | 1 | 20251 | 172800 | | | |
| Category 10 | 15 | 1 | 27952 | 172800 | | | |
| Category 11 | 5 | 2 | 3630 | 14400 | QPSK | Not applicable (dual cell operation not supported) | |
| Category 12 | 5 | 1 | 3630 | 28800 | QPSK, 16QAM, 64QAM | | |
| Category 13 | 15 | 1 | 35280 | 259200 | | | |
| Category 14 | 15 | 1 | 42192 | 259200 | QPSK, 16QAM | | |
| Category 15 | 15 | 1 | 23370 | 345600 | | | |
| Category 16 | 15 | 1 | 27952 | 345600 | QPSK, 16QAM, 64QAM | | - |
| Category 17 NOTE 2 | 15 | 1 | 35280 | 259200 | | | |
| | | | 23370 | 345600 | - | | |
| Category 18 NOTE 3 | 15 | 1 | 42192 | 259200 | QPSK, 16QAM, 64QAM | | - |
| | | | 27952 | 345600 | - | | QPSK, 16QAM |
| Category 19 | 15 | 1 | 35280 | 518400 | QPSK, 16QAM, 64QAM | | |
| Category 20 | 15 | 1 | 42192 | 518400 | | | |
| Category 21 | 15 | 1 | 23370 | 345600 | - | - | QPSK, 16QAM |
| Category 22 | 15 | 1 | 27952 | 345600 | | | |
| Category 23 | 15 | 1 | 35280 | 518400 | | | |
| Category 24 | 15 | 1 | 42192 | 518400 | | | QPSK, 16QAM, 64QAM |

5.3.3 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

C) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the *reported* SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

5.3.4 TDD LTE specification

For Time-Division Duplex (TDD) systems, SAR must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP LTE TDD configurations.

TDD LTE Band supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Figure 4.2-1: Frame structure type 2




Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS)

| Special subframe configuration | Normal cyclic prefix in downlink | | | Extended cyclic prefix in downlink | | |
|--------------------------------|----------------------------------|--------------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|
| | DwPTS | UpPTS | | DwPTS | UpPTS | |
| | | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink | | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink |
| 0 | $6592 \cdot T_s$ | $2192 \cdot T_s$ | $2560 \cdot T_s$ | $7680 \cdot T_s$ | $2192 \cdot T_s$ | $2560 \cdot T_s$ |
| 1 | $19760 \cdot T_s$ | | | $20480 \cdot T_s$ | | |
| 2 | $21952 \cdot T_s$ | | | $23040 \cdot T_s$ | | |
| 3 | $24144 \cdot T_s$ | | | $25600 \cdot T_s$ | | |
| 4 | $26336 \cdot T_s$ | | | $7680 \cdot T_s$ | $4384 \cdot T_s$ | $5120 \cdot T_s$ |
| 5 | $6592 \cdot T_s$ | $20480 \cdot T_s$ | | | | |
| 6 | $19760 \cdot T_s$ | $23040 \cdot T_s$ | | | | |
| 7 | $21952 \cdot T_s$ | $4384 \cdot T_s$ | $5120 \cdot T_s$ | $12800 \cdot T_s$ | - | - |
| 8 | $24144 \cdot T_s$ | | | - | | |
| 9 | $13168 \cdot T_s$ | | | - | | |

Table 4.2-2: Uplink-downlink configurations

| Uplink-downlink configuration | Downlink-to-Uplink Switch-point periodicity | Subframe number | | | | | | | | | |
|-------------------------------|---|-----------------|---|---|---|---|---|---|---|---|---|
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | 5 ms | D | S | U | U | U | D | S | U | U | U |
| 1 | 5 ms | D | S | U | U | D | D | S | U | U | D |
| 2 | 5 ms | D | S | U | D | D | D | S | U | D | D |
| 3 | 10 ms | D | S | U | U | U | D | D | D | D | D |
| 4 | 10 ms | D | S | U | U | D | D | D | D | D | D |
| 5 | 10 ms | D | S | U | D | D | D | D | D | D | D |
| 6 | 5 ms | D | S | U | U | U | D | S | U | U | D |

According to Figure 4.2-1, one radio frame is configured by 10 subframes, which consist of Uplink-subframe, Downlink-subframe and Special subframe. For TDD-LTE, the Duty Cycle should be calculated on Uplink-subframes and Special subframes, due to Special subframe containing both Uplink transmissions. So for one radio frame, Duty Cycle can be calculated with formula as below. The count of Uplink subframes are according to Table 4.2-2:

$$\text{Duty cycle} = \frac{(30720Ts * \text{Ups} + \text{Uplink Component} * \text{Specials})}{(307200Ts)}$$

About the uplink component of Special subframes, we can figure out by Table 4.2-1:

$$\text{Uplink Component} = \text{UpPTS}$$


In conclusion, for the TDD LTE Band, Duty Cycle can be calculated with formula as below .all these sets are ok when we test, or we can set as below.

$$\text{Duty cycle} = \frac{[(30720Ts * \text{Ups}) + \text{UpPTS} * \text{Specials}]}{(307200Ts)}$$

And we can get different Duty cycles under different configurations:

| Uplink-downlink configuration | Subframe number | | | Configuration of special subframe | | | | | | | |
|-------------------------------|-----------------|---|---|-----------------------------------|-------------------|----------------------------------|-------------------|------------------------------------|-------------------|----------------------------------|-------------------|
| | | | | Normal cyclic prefix in downlink | | | | Extended cyclic prefix in downlink | | | |
| | D | S | U | Normal cyclic prefix in uplink | | Extended cyclic prefix in uplink | | Normal cyclic prefix in uplink | | Extended cyclic prefix in uplink | |
| | | | | configuration 0~4 | configuration 5~9 | configuration 0~4 | configuration 5~9 | configuration 0~3 | configuration 4~7 | configuration 0~3 | configuration 4~7 |
| 0 | 2 | 2 | 6 | 61.43% | 62.85% | 61.67% | 63.33% | 61.43% | 62.85% | 61.67% | 63.33% |
| 1 | 4 | 2 | 4 | 41.43% | 42.85% | 41.67% | 43.33% | 41.43% | 42.85% | 41.67% | 43.33% |
| 2 | 6 | 2 | 2 | 21.43% | 22.85% | 21.67% | 23.33% | 21.43% | 22.85% | 21.67% | 23.33% |
| 3 | 6 | 1 | 3 | 30.71% | 31.43% | 30.83% | 31.67% | 30.71% | 31.43% | 30.83% | 31.67% |
| 4 | 7 | 1 | 2 | 20.71% | 21.43% | 20.83% | 21.67% | 20.71% | 21.43% | 20.83% | 21.67% |
| 5 | 8 | 1 | 1 | 10.71% | 11.43% | 10.83% | 11.67% | 10.71% | 11.43% | 10.83% | 11.67% |
| 6 | 3 | 2 | 5 | 51.43% | 52.85% | 51.67% | 53.33% | 51.43% | 52.85% | 51.67% | 53.33% |

SAR test Plan: For TDD LTE, SAR should be tested with the highest transmission duty factor (63.33%) using Uplink-downlink configuration 0 and Special subframe configuration 7 for Frame structure type



5.3.5 Wi-Fi Test Configuration

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the *initial test position(s)* by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The *initial test position(s)* is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the *reported SAR* for the *initial test position* is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to

the required SAR procedures.

- 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the *initial test position* to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the *reported SAR* is ≤ 0.8 W/kg or all required test positions are tested.
 - ✧ For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - ✧ When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the *initial test position* and subsequent test positions, when the *reported SAR* is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the *reported SAR* is ≤ 1.2 W/kg or all required test channels are considered.
 - ✧ The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.

To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered the worst case position; thus used as the initial test position.

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

5.3.6 BT Test Configuration

For BT SAR testing, BT engineering testing software installed on the EUT can provide continuous transmitting RF signal with maximum output power. And the CBT control the EUT operating with hopping off and data rate set for 3DH5. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

5.3.7 Downlink LTE CA specification

The device supports downlink Release 10 LTE Carrier Aggregation (CA) only. It supports a maximum of 2 carriers in the downlink. Other Release 10 features are not supported, including Uplink Carrier Aggregation, Enhanced SC-FDMA and Uplink MIMO or other antenna diversity configurations etc. All uplink communications are identical to the Release 8 Specifications.

intra-band contiguous CA (per 3GPP TS 36.101 Table 5.6A.1-1)

| E-UTRA CA configuration / Bandwidth combination set | | | | |
|---|---|--------------------------------------|------------------------------------|---------------------------|
| E-UTRA CA configuration | Component carriers in order of increasing carrier frequency | | Maximum aggregated bandwidth [MHz] | Bandwidth combination set |
| | Channel bandwidths for carrier [MHz] | Channel bandwidths for carrier [MHz] | | |
| CA_7C | 15 | 15 | 40 | 0 |
| | 20 | 20 | | |
| | 10 | 20 | 40 | 1 |
| | 15 | 15, 20 | | |
| | 20 | 10, 15, 20 | | |
| | 15 | 10, 15 | 40 | 2 |
| | 20 | 15, 20 | | |
| CA_38C | 15 | 15 | 40 | 0 |
| | 20 | 20 | | |
| | 20 | 10, 15, 20 | | |

NOTE 1: The CA Configuration refers to a combination of an operating band and a CA bandwidth class specified in Table 5.6A-1. Absence of a CA bandwidth class for an operating band implies support of all classes.


NOTE 2: For each band combination, all combinations of indicated bandwidths belong to the set.

NOTE 3: The channel number and frequency refer to 3GPP TS 36.508.

6 SAR Measurements System Configuration

6.1 SAR Measurement Set-up

The DASY system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.2 DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

EX3DV4 Probe Specification

| | |
|---------------|--|
| Construction | Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| Calibration | ISO/IEC 17025 calibration service available |
| Frequency | 10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz) |
| Directivity | ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis) |
| Dynamic Range | 10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g) |
| Dimensions | Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm |
| Application | High precision dosimetric measurements in any exposure Scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |



E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than ± 0.25 dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based



temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \Delta T / \Delta t$$

Where: Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = |E|^2 \sigma / \rho$$

Where: σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

6.3 SAR Measurement Procedure

Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

| | ≤ 3 GHz | > 3 GHz |
|--|---|--|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | 5 ± 1 mm | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$ |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location | 30° ± 1° | 20° ± 1° |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$ | ≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm | 3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm |
| | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. | |

Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

| | | | ≤3GHz | > 3 GHz |
|---|------------------------------------|--|--------------------------------|---|
| Maximum zoom scan spatial resolution: Δx_{zoom} Δy_{zoom} | | | ≤2GHz: ≤8mm 2 – 3GHz: ≤5mm* | 3 – 4GHz: ≤5mm* 4 – 6GHz: ≤4mm* |
| Maximum zoom scan spatial resolution, normal to phantom surface | Uniform grid: $\Delta z_{zoom}(n)$ | | ≤5mm | 3 – 4GHz: ≤4mm 4 – 5GHz: ≤3mm 5 – 6GHz: ≤2mm |
| | Graded grid | $\Delta z_{zoom}(1)$: between 1 st two points closest to phantom surface | ≤4mm | 3 – 4GHz: ≤3mm 4 – 5GHz: ≤2.5mm 5 – 6GHz: ≤2mm |
| | | $\Delta z_{zoom}(n > 1)$: between subsequent points | ≤1.5• $\Delta z_{zoom}(n-1)$ | |
| Minimum zoom scan volume | X, y, z | | ≥30mm | 3 – 4GHz: ≥28mm 4 – 5GHz: ≥25mm 5 – 6GHz: ≥22mm |
| <p>Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4W/kg, ≤8mm, ≤7mm and ≤5mm zoom scan resolution may be applied, respectively, for 2GHz to 3GHz, 3GHz to 4GHz and 4GHz to 6GHz.</p> | | | | |

Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

7 Main Test Equipment

| Name of Equipment | Manufacturer | Type/Model | Serial Number | Last Cal. | Cal. Due Date |
|-------------------------------------|-----------------|------------|---------------|------------|---------------|
| Network analyzer | Agilent | E5071B | MY42404014 | 2017-05-20 | 2018-05-19 |
| Dielectric Probe Kit | HP | 85070E | US44020115 | 2017-05-20 | 2018-05-19 |
| Power meter | Agilent | E4417A | GB41291714 | 2017-05-21 | 2018-05-20 |
| Power sensor | Agilent | N8481H | MY50350004 | 2017-05-21 | 2018-05-20 |
| Power sensor | Agilent | E9327A | US40441622 | 2017-05-20 | 2018-05-19 |
| Dual directional coupler | Agilent | 778D-012 | 50519 | 2017-05-21 | 2018-05-20 |
| Dual directional coupler | Agilent | 777D | 50146 | 2017-05-20 | 2018-05-19 |
| Amplifier | INDEXSAR | IXA-020 | 0401 | 2017-05-20 | 2018-05-19 |
| Wideband radio communication tester | R&S | CMW 500 | 113645 | 2017-05-20 | 2018-05-19 |
| BT Base Station Simulator | R&S | CBT | 100271 | 2017-05-14 | 2018-05-13 |
| E-field Probe | SPEAG | EX3DV4 | 3677 | 2017-01-23 | 2018-01-22 |
| DAE | SPEAG | DAE4 | 1291 | 2017-01-19 | 2018-01-18 |
| Validation Kit 835MHz | SPEAG | D835V2 | 4d020 | 2017-08-28 | 2020-08-27 |
| Validation Kit 1750MHz | SPEAG | D1750V2 | 1033 | 2017-01-10 | 2020-01-09 |
| Validation Kit 1900MHz | SPEAG | D1900V2 | 5d060 | 2017-08-26 | 2020-08-25 |
| Validation Kit 2450MHz | SPEAG | D2450V2 | 786 | 2017-08-29 | 2020-08-28 |
| Validation Kit 2600MHz | SPEAG | D2600V2 | 1025 | 2014-12-08 | 2017-12-07 |
| Temperature Probe | Tianjin jinming | JM222 | AA1009129 | 2017-05-20 | 2018-05-19 |
| Hygrothermograph | Anymetr | NT-311 | 20150731 | 2017-05-17 | 2018-05-16 |

8 Tissue Dielectric Parameter Measurements & System Verification

8.1 Tissue Verification

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance.

Target values

| Frequency (MHz) | Water (%) | Salt (%) | Sugar (%) | Glycol (%) | Preventol (%) | Cellulose (%) | ϵ_r | σ (s/m) | |
|-----------------|-----------|----------|-----------|------------|---------------|---------------|--------------|----------------|------|
| Head | 835 | 41.45 | 1.45 | 56 | 0 | 0.1 | 1.0 | 41.5 | 0.90 |
| | 1750 | 55.24 | 0.31 | 0 | 44.45 | 0 | 0 | 40.1 | 1.37 |
| | 1900 | 55.242 | 0.306 | 0 | 44.452 | 0 | 0 | 40.0 | 1.40 |
| | 2450 | 62.7 | 0.5 | 0 | 36.8 | 0 | 0 | 39.2 | 1.80 |
| | 2600 | 55.242 | 0.306 | 0 | 44.452 | 0 | 0 | 39.0 | 1.96 |
| Body | 835 | 52.5 | 1.4 | 45 | 0 | 0.1 | 1.0 | 55.2 | 0.97 |
| | 1750 | 69.91 | 0.12 | 0 | 29.97 | 0 | 0 | 53.4 | 1.49 |
| | 1900 | 69.91 | 0.13 | 0 | 29.96 | 0 | 0 | 53.3 | 1.52 |
| | 2450 | 73.2 | 0.1 | 0 | 26.7 | 0 | 0 | 52.7 | 1.95 |
| | 2600 | 72.6 | 0.1 | 0 | 27.3 | 0 | 0 | 52.5 | 2.16 |

Measurements results


| Frequency (MHz) | | Test Date | Temp °C | Measured Dielectric Parameters | | Target Dielectric Parameters | | Limit (Within ±5%) | |
|-----------------|------|-----------|---------|--------------------------------|----------------|------------------------------|----------------|----------------------|------------------|
| | | | | ϵ_r | σ (s/m) | ϵ_r | σ (s/m) | Dev ϵ_r (%) | Dev σ (%) |
| 835 | Head | 8/29/2017 | 21.5 | 42.3 | 0.91 | 41.5 | 0.90 | 1.93 | 1.11 |
| | Body | 9/5/2017 | 21.5 | 55.4 | 1.01 | 55.2 | 0.97 | 0.36 | 4.12 |
| 1750 | Head | 8/30/2017 | 21.5 | 38.6 | 1.37 | 40.1 | 1.37 | -3.74 | 0.00 |
| | Body | 8/30/2017 | 21.5 | 51.8 | 1.43 | 53.4 | 1.49 | -3.00 | -4.03 |
| 1900 | Head | 8/29/2017 | 21.5 | 40.4 | 1.39 | 40.0 | 1.40 | 1.00 | -0.71 |
| | Body | 8/28/2017 | 21.5 | 51.2 | 1.51 | 53.3 | 1.52 | -3.94 | -0.66 |
| 2450 | Head | 8/30/2017 | 21.5 | 40.8 | 1.84 | 39.2 | 1.80 | 4.08 | 2.22 |
| | Body | 9/1/2017 | 21.5 | 51.4 | 1.91 | 52.7 | 1.95 | -2.47 | -2.05 |
| 2600 | Head | 8/31/2017 | 21.5 | 40.3 | 2.01 | 39.0 | 1.96 | 3.33 | 2.55 |
| | Body | 8/22/2017 | 21.5 | 51.1 | 2.08 | 52.5 | 2.16 | -2.67 | -3.70 |

Note: The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.

8.2 System Performance Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured using the dielectric probe kit and the network analyzer. A system check measurement for every day was made following the determination of the dielectric parameters of the Tissue simulates, using the dipole validation kit. The dipole antenna was placed under the flat section of the twin SAM phantom.

System check is performed regularly on all frequency bands where tests are performed with the DASYS system.



Picture 1 System Performance Check setup



Picture 2 Setup Photo

**Justification for Extended SAR Dipole Calibrations**

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (< - 20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB 865664 D01:

| Dipole | | Date of Measurement | Return Loss(dB) | Δ % | Impedance (Ω) | $\Delta\Omega$ |
|-------------------------------|----------------|---------------------|-----------------|------------|------------------------|----------------|
| Dipole D2600V2 SN: 1025 | Head Liquid | 12/8/2014 | -24.2 | / | 49.7 | / |
| | | 12/7/2015 | -23.9 | 1.2% | 50.4 | 0.7 Ω |
| | | 12/6/2016 | -23.3 | 2.6% | 50.7 | -0.3 Ω |
| | Body Liquid | 12/8/2014 | -23.6 | / | 46.6 | / |
| | | 12/7/2015 | -24.0 | 1.7% | 47.2 | 0.6 Ω |
| | | 12/6/2016 | -24.4 | -1.6% | 47.1 | 0.1 Ω |

System Check results

| Frequency (MHz) | | Test Date | Temp $^{\circ}\text{C}$ | 250mW Measured SAR _{1g} (W/kg) | 1W Normalized SAR _{1g} (W/kg) | 1W Target SAR _{1g} (W/kg) | Δ % (Limit $\pm 10\%$) | Plot No. |
|-----------------|------|-----------|-------------------------|---|--|------------------------------------|--------------------------------|----------|
| 835 | Head | 8/29/2017 | 21.5 | 2.44 | 9.76 | 9.45 | 3.28 | 1 |
| | Body | 9/5/2017 | 21.5 | 2.41 | 9.64 | 9.75 | -1.13 | 2 |
| 1750 | Head | 8/30/2017 | 21.5 | 8.95 | 35.80 | 37.20 | -3.76 | 3 |
| | Body | 8/30/2017 | 21.5 | 9.24 | 36.96 | 37.60 | -1.70 | 4 |
| 1900 | Head | 8/29/2017 | 21.5 | 9.88 | 39.52 | 40.10 | -1.45 | 5 |
| | Body | 8/28/2017 | 21.5 | 9.93 | 39.72 | 39.50 | 0.56 | 6 |
| 2450 | Head | 8/30/2017 | 21.5 | 13.70 | 54.80 | 52.60 | 4.18 | 7 |
| | Body | 9/1/2017 | 21.5 | 12.50 | 50.00 | 50.80 | -1.57 | 8 |
| 2600 | Head | 8/31/2017 | 21.5 | 13.90 | 55.60 | 56.90 | -2.28 | 9 |
| | Body | 8/22/2017 | 21.5 | 13.88 | 55.52 | 56.40 | -1.56 | 10 |

Note: Target Values used derive from the calibration certificate Data Storage and Evaluation.

9 Normal and Maximum Output Power

KDB 447498 D01 at the maximum rated output power and within the tune-up tolerance range specified for the product, but not more than 2 dB lower than the maximum tune-up tolerance limit.

9.1 GSM Mode

| GSM 850 | | Burst Average | | | Division Factors (dB) | Frame-Average | | | Burst Tune-up Limit (dBm) |
|----------------|----------|---------------|-------|--------|-----------------------|---------------|--------------|--------------|---------------------------|
| | | Power(dBm) | | | | Power(dBm) | | | |
| Tx Channel | | 128 | 190 | 251 | 9.03 | 128 | 190 | 251 | 33.50 |
| Frequency(MHz) | | 824.2 | 836.6 | 848.8 | | 824.2 | 836.6 | 848.8 | |
| GSM(GMSK) | | 32.14 | 32.24 | 32.46 | 9.03 | 23.11 | 23.21 | 23.43 | 33.50 |
| GPRS (GMSK) | 1Txslot | 32.14 | 32.22 | 32.44 | 9.03 | 23.11 | 23.19 | 23.41 | 33.00 |
| | 2Txslots | 29.87 | 29.82 | 30.03 | 6.02 | 23.85 | 23.80 | 24.01 | 31.00 |
| | 3Txslots | 27.88 | 27.62 | 27.85 | 4.26 | 23.62 | 23.36 | 23.59 | 29.00 |
| | 4Txslots | 26.12 | 26.01 | 26.20 | 3.01 | 23.11 | 23.00 | 23.19 | 27.50 |
| EGPRS (GMSK) | 1Txslot | 32.18 | 32.23 | 32.43 | 9.03 | 23.15 | 23.20 | 23.40 | 33.00 |
| | 2Txslots | 29.85 | 29.80 | 30.01 | 6.02 | 23.83 | 23.78 | 23.99 | 31.00 |
| | 3Txslots | 27.87 | 27.71 | 27.90 | 4.26 | 23.61 | 23.45 | 23.64 | 29.00 |
| | 4Txslots | 26.11 | 25.99 | 26.21 | 3.01 | 23.10 | 22.98 | 23.20 | 27.50 |
| EGPRS (8PSK) | 1Txslot | 26.19 | 25.98 | 26.02 | 9.03 | 17.16 | 16.95 | 16.99 | 27.00 |
| | 2Txslots | 25.64 | 25.03 | 25.10 | 6.02 | 19.62 | 19.01 | 19.08 | 26.00 |
| | 3Txslots | 24.52 | 24.05 | 24.01 | 4.26 | 20.26 | 19.79 | 19.75 | 25.00 |
| | 4Txslots | 23.07 | 22.81 | 22.49 | 3.01 | 20.06 | 19.80 | 19.48 | 24.00 |
| GSM 1900 | | Power(dBm) | | | Division Factors (dB) | Power(dBm) | | | Burst Tune-up Limit (dBm) |
| Tx Channel | | 512 | 661 | 810 | | 512 | 661 | 810 | |
| Frequency(MHz) | | 1850.2 | 1880 | 1909.8 | 9.03 | 1850.2 | 1880 | 1909.8 | 30.50 |
| GSM(GMSK) | | 29.64 | 29.68 | 29.45 | | 20.61 | 20.65 | 20.42 | |
| GPRS (GMSK) | 1Txslot | 29.76 | 29.80 | 29.54 | 9.03 | 20.73 | 20.77 | 20.51 | 30.00 |
| | 2Txslots | 28.03 | 28.18 | 28.02 | 6.02 | 22.01 | 22.16 | 22.00 | 28.50 |
| | 3Txslots | 26.30 | 26.55 | 26.41 | 4.26 | 22.04 | 22.29 | 22.15 | 27.00 |
| | 4Txslots | 25.20 | 25.51 | 25.31 | 3.01 | 22.19 | 22.50 | 22.30 | 26.00 |
| EGPRS (GMSK) | 1Txslot | 29.80 | 29.81 | 29.53 | 9.03 | 20.77 | 20.78 | 20.50 | 30.00 |
| | 2Txslots | 28.01 | 28.16 | 28.00 | 6.02 | 21.99 | 22.14 | 21.98 | 28.50 |
| | 3Txslots | 26.29 | 26.64 | 26.46 | 4.26 | 22.03 | 22.38 | 22.20 | 27.00 |
| | 4Txslots | 25.19 | 25.49 | 25.32 | 3.01 | 22.18 | 22.48 | 22.31 | 26.00 |
| EGPRS (8PSK) | 1Txslot | 25.32 | 25.33 | 25.38 | 9.03 | 16.29 | 16.30 | 16.35 | 26.00 |
| | 2Txslots | 24.56 | 24.66 | 24.58 | 6.02 | 18.54 | 18.64 | 18.56 | 25.50 |



| | | | | | | | | |
|----------|-------|-------|-------|------|-------|-------|-------|-------|
| 3Txslots | 23.83 | 23.82 | 23.92 | 4.26 | 19.57 | 19.56 | 19.66 | 25.00 |
| 4Txslots | 23.07 | 22.75 | 22.98 | 3.01 | 20.06 | 19.74 | 19.97 | 24.50 |

Notes: The worst-case configuration and mode for SAR testing is determined to be as follows:

1. Standalone: GSM 850 GMSK (GPRS) mode with 2 time slots for Max power, GSM 1900 GMSK (GPRS) mode with 4 time slots for Max power, based on the output power measurements above.
2. SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode.

| DTM 850 | | Burst Average | | | Division Factors (dB) | Frame-Average | | | Burst Tune-up Limit (dBm) |
|------------------|----------|---------------|-------|--------|-----------------------|---------------|--------------|--------------|---------------------------|
| | | Power(dBm) | | | | Power(dBm) | | | |
| Tx Channel | | 128 | 190 | 251 | Division Factors (dB) | 128 | 190 | 251 | Burst Tune-up Limit (dBm) |
| Frequency(MHz) | | 824.2 | 836.6 | 848.8 | | 824.2 | 836.6 | 848.8 | |
| GSM&GPRS (GMSK) | 2Txslots | 29.71 | 29.77 | 29.67 | 6.02 | 23.69 | 23.75 | 23.65 | 31.00 |
| | 3Txslots | 27.50 | 27.32 | 27.54 | 4.26 | 23.24 | 23.06 | 23.28 | 29.00 |
| GSM&EGPRS (GMSK) | 2Txslots | 29.68 | 29.45 | 29.65 | 6.02 | 23.66 | 23.43 | 23.63 | 31.00 |
| | 3Txslots | 27.46 | 27.29 | 27.52 | 4.26 | 23.20 | 23.03 | 23.26 | 29.00 |
| GSM&EGPRS (8PSK) | 2Txslots | 25.27 | 24.93 | 24.89 | 6.02 | 19.25 | 18.91 | 18.87 | 26.00 |
| | 3Txslots | 24.06 | 23.47 | 23.68 | 4.26 | 19.80 | 19.21 | 19.42 | 25.00 |
| DTM 1900 | | Power(dBm) | | | Division Factors (dB) | Power(dBm) | | | Burst Tune-up Limit (dBm) |
| Tx Channel | | 512 | 661 | 810 | | 512 | 661 | 810 | |
| Frequency(MHz) | | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 | | |
| GSM&GPRS (GMSK) | 2Txslots | 28.17 | 28.13 | 28.08 | 6.02 | 22.15 | 22.11 | 22.06 | 28.50 |
| | 3Txslots | 26.26 | 26.25 | 26.16 | 4.26 | 22.00 | 21.99 | 21.90 | 27.00 |
| GSM&EGPRS (GMSK) | 2Txslots | 28.04 | 28.01 | 27.95 | 6.02 | 22.02 | 21.99 | 21.93 | 28.50 |
| | 3Txslots | 26.33 | 26.33 | 26.34 | 4.26 | 22.07 | 22.07 | 22.08 | 27.00 |
| GSM&EGPRS (8PSK) | 2Txslots | 24.34 | 24.02 | 23.93 | 6.02 | 18.32 | 18.00 | 17.91 | 25.50 |
| | 3Txslots | 23.54 | 23.39 | 23.33 | 4.26 | 19.28 | 19.13 | 19.07 | 25.00 |

Notes: The worst-case configuration and mode for SAR testing is determined to be as follows:

1. Standalone: DTM 850 GMSK (GSM&GPRS) mode with 2 time slots for Max power, DTM 1900 GMSK (GSM&GPRS) mode with 2 time slots for Max power, based on the output power measurements above.
2. SAR is not required for GSM&EGPRS (8PSK) mode because its output power is less than that of GSM&GPRS Mode.

9.2 WCDMA Mode

The following tests were completed according to the test requirements outlined in the 3GPP TS34.121 specification.

| WCDMA | | Band II(dBm) | | | | Band V(dBm) | | | |
|----------------|----------|--------------|-------|--------|---------------------|-------------|-------|-------|---------------------|
| Tx Channel | | 9262 | 9400 | 9538 | Tune-up Limit (dBm) | 4132 | 4183 | 4233 | Tune-up Limit (dBm) |
| Frequency(MHz) | | 1852.4 | 1880 | 1907.6 | | 826.4 | 836.6 | 846.6 | |
| RMC | 12.2kbps | 22.93 | 22.85 | 22.74 | 23.50 | 22.94 | 22.97 | 23.17 | 24.00 |
| | 64kbps | 22.87 | 22.73 | 22.58 | 23.50 | 22.87 | 22.83 | 23.11 | 24.00 |
| | 144kbps | 22.78 | 22.68 | 22.57 | 23.50 | 22.86 | 22.82 | 23.01 | 24.00 |
| | 384kbps | 22.77 | 22.69 | 22.58 | 23.50 | 22.85 | 22.81 | 23.00 | 24.00 |
| HSDPA | Sub 1 | 21.54 | 21.50 | 21.43 | 22.50 | 21.80 | 21.85 | 22.07 | 23.00 |
| | Sub 2 | 21.58 | 21.51 | 21.37 | 22.50 | 20.13 | 20.14 | 20.26 | 22.00 |
| | Sub 3 | 21.05 | 21.01 | 20.98 | 22.50 | 21.29 | 21.31 | 21.57 | 22.00 |
| | Sub 4 | 21.08 | 21.02 | 20.91 | 22.50 | 21.29 | 21.35 | 21.63 | 22.00 |
| HSUPA | Sub 1 | 21.83 | 21.64 | 21.50 | 22.50 | 21.87 | 21.85 | 22.07 | 23.00 |
| | Sub 2 | 21.14 | 21.05 | 21.02 | 22.00 | 21.33 | 21.32 | 21.63 | 22.50 |
| | Sub 3 | 21.57 | 21.56 | 21.49 | 22.00 | 21.83 | 21.85 | 22.10 | 22.50 |
| | Sub 4 | 21.77 | 21.57 | 21.48 | 22.00 | 21.82 | 21.84 | 22.15 | 22.50 |
| | Sub 5 | 21.54 | 21.53 | 21.40 | 22.50 | 21.80 | 21.81 | 22.04 | 23.00 |
| DC-HSDPA | Sub 1 | 21.76 | 21.64 | 21.53 | 22.50 | 21.71 | 21.74 | 21.94 | 23.00 |
| | Sub 2 | 21.75 | 21.63 | 21.52 | 22.50 | 21.80 | 21.72 | 21.93 | 22.00 |
| | Sub 3 | 21.54 | 21.42 | 21.31 | 22.50 | 21.29 | 21.21 | 21.42 | 22.00 |
| | Sub 4 | 21.53 | 21.51 | 21.29 | 22.50 | 21.28 | 21.20 | 21.41 | 22.00 |

Note: 1.Per KDB 941225 D01, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps AMR with TPC bits configured to all "1's".

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

9.3 LTE Mode

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

| Modulation | Channel bandwidth / Transmission bandwidth (N _{RB}) | | | | | | MPR (dB) |
|------------|---|---------|-------|--------|--------|--------|----------|
| | 1.4 MHz | 3.0 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz | |
| QPSK | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | ≤ 1 |
| 16 QAM | ≤ 5 | ≤ 4 | ≤ 8 | ≤ 12 | ≤ 16 | ≤ 18 | ≤ 1 |
| 16 QAM | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | ≤ 2 |

| LTE FDD Band 4 | | | | Conducted Power(dBm) | | | Tune-up Limit (dBm) |
|----------------|------------|---------|-----------|-------------------------|--------------|--------------|---------------------|
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | |
| | | | | 19957/1710.7 | 20175/1732.5 | 20393/1754.3 | |
| 1.4MHz | QPSK | 1 | 0 | 23.24 | 23.72 | 23.74 | 24.00 |
| | | 1 | 2 | 23.33 | 23.63 | 23.48 | 24.00 |
| | | 1 | 5 | 23.16 | 23.33 | 23.26 | 24.00 |
| | | 3 | 0 | 23.00 | 23.46 | 23.48 | 24.00 |
| | | 3 | 2 | 23.01 | 23.35 | 23.14 | 24.00 |
| | | 3 | 3 | 23.12 | 23.54 | 23.07 | 24.00 |
| | 16QAM | 6 | 0 | 22.11 | 22.58 | 22.38 | 23.30 |
| | | 1 | 0 | 22.24 | 22.56 | 22.37 | 23.00 |
| | | 1 | 2 | 22.29 | 22.32 | 22.36 | 23.00 |
| | | 1 | 5 | 22.08 | 22.22 | 22.24 | 23.00 |
| | | 3 | 0 | 22.10 | 22.12 | 22.00 | 23.00 |
| | | 3 | 2 | 22.09 | 22.29 | 22.14 | 23.00 |
| | | 3 | 3 | 22.15 | 22.14 | 22.24 | 23.00 |
| | | 6 | 0 | 21.05 | 21.27 | 21.53 | 22.30 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 19965/1711.5 | 20175/1732.5 | 20385/1753.5 | |
| 3MHz | QPSK | 1 | 0 | 23.26 | 23.76 | 23.77 | 24.00 |
| | | 1 | 7 | 23.36 | 23.68 | 23.52 | 24.00 |
| | | 1 | 14 | 23.19 | 23.38 | 23.30 | 24.00 |
| | | 8 | 0 | 22.10 | 22.58 | 22.61 | 23.00 |
| | | 8 | 4 | 22.13 | 22.45 | 22.26 | 23.00 |
| | | 8 | 7 | 22.22 | 22.65 | 22.17 | 23.00 |
| | | 15 | 0 | 22.14 | 22.62 | 22.41 | 23.30 |
| | 16QAM | 1 | 0 | 22.27 | 22.58 | 22.40 | 23.00 |
| | | 1 | 7 | 22.32 | 22.37 | 22.40 | 23.00 |
| | | 1 | 14 | 22.10 | 22.26 | 22.27 | 23.00 |



| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
|-----------|------------|---------|-----------|-------------------------|--------------|--------------|---------------------|
| | | | | 19975/1712.5 | 20175/1732.5 | 20375/1752.5 | |
| | | 8 | 0 | 21.21 | 21.25 | 21.12 | 22.00 |
| | | 8 | 4 | 21.20 | 21.42 | 21.26 | 22.00 |
| | | 8 | 7 | 21.25 | 21.26 | 21.37 | 22.00 |
| | | 15 | 0 | 21.08 | 21.31 | 21.56 | 22.30 |
| 5MHz | QPSK | 1 | 0 | 23.23 | 23.74 | 23.73 | 24.00 |
| | | 1 | 13 | 23.34 | 23.64 | 23.49 | 24.00 |
| | | 1 | 24 | 23.16 | 23.33 | 23.26 | 24.00 |
| | | 12 | 0 | 22.07 | 22.53 | 22.57 | 23.00 |
| | | 12 | 6 | 22.11 | 22.41 | 22.21 | 23.00 |
| | | 12 | 13 | 22.20 | 22.63 | 22.13 | 23.00 |
| | | 25 | 0 | 22.12 | 22.61 | 22.39 | 23.30 |
| | 16QAM | 1 | 0 | 22.24 | 22.54 | 22.37 | 23.00 |
| | | 1 | 13 | 22.29 | 22.35 | 22.37 | 23.00 |
| | | 1 | 24 | 22.07 | 22.24 | 22.23 | 23.00 |
| | | 12 | 0 | 21.19 | 21.21 | 21.09 | 22.00 |
| | | 12 | 6 | 21.17 | 21.37 | 21.22 | 22.00 |
| | | 12 | 13 | 21.22 | 21.21 | 21.33 | 22.00 |
| | | 25 | 0 | 21.06 | 21.27 | 21.51 | 22.30 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20000/1715 | 20175/1732.5 | 20350/1750 | |
| 10MHz | QPSK | 1 | 0 | 23.25 | 23.75 | 23.76 | 24.00 |
| | | 1 | 25 | 23.37 | 23.69 | 23.53 | 24.00 |
| | | 1 | 49 | 23.18 | 23.37 | 23.29 | 24.00 |
| | | 25 | 0 | 22.10 | 22.58 | 22.61 | 23.00 |
| | | 25 | 13 | 22.14 | 22.46 | 22.25 | 23.00 |
| | | 25 | 25 | 22.22 | 22.67 | 22.18 | 23.00 |
| | | 50 | 0 | 22.20 | 22.63 | 22.43 | 23.30 |
| | 16QAM | 1 | 0 | 22.26 | 22.57 | 22.39 | 23.00 |
| | | 1 | 25 | 22.32 | 22.39 | 22.40 | 23.00 |
| | | 1 | 49 | 22.10 | 22.26 | 22.26 | 23.00 |
| | | 25 | 0 | 21.22 | 21.26 | 21.13 | 22.00 |
| | | 25 | 13 | 21.19 | 21.41 | 21.25 | 22.00 |
| | | 25 | 25 | 21.25 | 21.26 | 21.37 | 22.00 |
| | | 50 | 0 | 21.09 | 21.32 | 21.55 | 22.30 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20025/1717.5 | 20175/1732.5 | 20325/1747.5 | |
| 15MHz | QPSK | 1 | 0 | 23.24 | 23.71 | 23.74 | 24.00 |
| | | 1 | 38 | 23.35 | 23.68 | 23.50 | 24.00 |



| | | 1 | 74 | 23.15 | 23.32 | 23.25 | 24.00 | |
|-------|-----------|------------|---------|-----------|-------------------------|--------------|------------|---------------------|
| | | 36 | 0 | 22.08 | 22.54 | 22.58 | 23.00 | |
| | | 36 | 18 | 22.11 | 22.41 | 22.21 | 23.00 | |
| | | 36 | 39 | 22.19 | 22.64 | 22.14 | 23.00 | |
| | | 75 | 0 | 22.18 | 22.59 | 22.38 | 23.30 | |
| | 16QAM | 1 | 0 | 22.21 | 22.55 | 22.37 | 23.00 | |
| | | 1 | 38 | 22.30 | 22.36 | 22.38 | 23.00 | |
| | | 1 | 74 | 22.07 | 22.22 | 22.23 | 23.00 | |
| | | 36 | 0 | 21.19 | 21.24 | 21.10 | 22.00 | |
| | | 36 | 18 | 21.16 | 21.36 | 21.21 | 22.00 | |
| | | 36 | 39 | 21.23 | 21.22 | 21.34 | 22.00 | |
| | | 75 | 0 | 21.06 | 21.27 | 21.51 | 22.30 | |
| | Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | | 20050/1720 | 20175/1732.5 | 20300/1745 | |
| 20MHz | QPSK | 1 | 0 | 23.21 | 23.67 | 23.71 | 24.00 | |
| | | 1 | 50 | 23.34 | 23.64 | 23.48 | 24.00 | |
| | | 1 | 99 | 23.13 | 23.31 | 23.22 | 24.00 | |
| | | 50 | 0 | 22.05 | 22.49 | 22.54 | 23.00 | |
| | | 50 | 25 | 22.09 | 22.37 | 22.18 | 23.00 | |
| | | 50 | 50 | 22.16 | 22.59 | 22.10 | 23.00 | |
| | | 100 | 0 | 22.15 | 22.54 | 22.34 | 23.30 | |
| | 16QAM | 1 | 0 | 22.19 | 22.51 | 22.32 | 23.00 | |
| | | 1 | 50 | 22.26 | 22.34 | 22.34 | 23.00 | |
| | | 1 | 99 | 22.05 | 22.19 | 22.21 | 23.00 | |
| | | 50 | 0 | 21.16 | 21.20 | 21.07 | 22.00 | |
| | | 50 | 25 | 21.13 | 21.34 | 21.18 | 22.00 | |
| | | 50 | 50 | 21.20 | 21.17 | 21.30 | 22.00 | |
| | | 100 | 0 | 21.04 | 21.23 | 21.48 | 22.30 | |

| LTE FDD Band 5 | | | | Conducted Power(dBm) | | | Tune-up Limit (dBm) |
|----------------|------------|---------|-----------|-------------------------|-------------|-------------|---------------------|
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | |
| | | | | 20407/824.7 | 20525/836.5 | 20643/848.3 | |
| 1.4MHz | QPSK | 1 | 0 | 23.07 | 23.14 | 22.96 | 24.00 |
| | | 1 | 2 | 23.18 | 23.16 | 23.07 | 24.00 |
| | | 1 | 5 | 23.06 | 23.00 | 22.97 | 24.00 |
| | | 3 | 0 | 23.07 | 23.03 | 22.77 | 24.00 |
| | | 3 | 2 | 22.93 | 22.97 | 22.85 | 24.00 |
| | | 3 | 3 | 22.98 | 22.81 | 22.83 | 24.00 |
| | | 6 | 0 | 22.02 | 21.96 | 21.91 | 23.30 |
| | 16QAM | 1 | 0 | 21.93 | 22.02 | 21.85 | 23.00 |
| | | 1 | 2 | 21.94 | 21.82 | 21.77 | 23.00 |
| | | 1 | 5 | 21.81 | 21.78 | 21.71 | 23.00 |
| | | 3 | 0 | 22.02 | 21.96 | 21.72 | 23.00 |
| | | 3 | 2 | 21.97 | 22.06 | 21.84 | 23.00 |
| | | 3 | 3 | 21.95 | 21.92 | 21.73 | 23.00 |
| | | 6 | 0 | 20.88 | 20.95 | 20.93 | 22.30 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20415/825.5 | 20525/836.5 | 20635/847.5 | |
| 3MHz | QPSK | 1 | 0 | 23.09 | 23.18 | 22.99 | 24.00 |
| | | 1 | 7 | 23.21 | 23.21 | 23.11 | 24.00 |
| | | 1 | 14 | 23.09 | 23.05 | 23.01 | 24.00 |
| | | 8 | 0 | 22.17 | 22.15 | 21.90 | 23.00 |
| | | 8 | 4 | 22.05 | 22.07 | 21.97 | 23.00 |
| | | 8 | 7 | 22.08 | 21.92 | 21.93 | 23.00 |
| | | 15 | 0 | 22.05 | 22.00 | 21.94 | 23.30 |
| | 16QAM | 1 | 0 | 21.96 | 22.04 | 21.88 | 23.00 |
| | | 1 | 7 | 21.97 | 21.87 | 21.81 | 23.00 |
| | | 1 | 14 | 21.83 | 21.82 | 21.74 | 23.00 |
| | | 8 | 0 | 21.13 | 21.09 | 20.84 | 22.00 |
| | | 8 | 4 | 21.08 | 21.19 | 20.96 | 22.00 |
| | | 8 | 7 | 21.05 | 21.04 | 20.86 | 22.00 |
| | | 15 | 0 | 20.91 | 20.99 | 20.96 | 22.30 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20425/826.5 | 20525/836.5 | 20625/846.5 | |
| 5MHz | QPSK | 1 | 0 | 23.06 | 23.16 | 22.95 | 24.00 |
| | | 1 | 13 | 23.19 | 23.17 | 23.08 | 24.00 |
| | | 1 | 24 | 23.06 | 23.00 | 22.97 | 24.00 |
| | | 12 | 0 | 22.14 | 22.10 | 21.86 | 23.00 |
| | | 12 | 6 | 22.03 | 22.03 | 21.92 | 23.00 |



| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
|-----------|------------|---------|-----------|-------------------------|-------------|-----------|---------------------|
| | | | | 20450/829 | 20525/836.5 | 20600/844 | |
| 10MHz | 16QAM | 12 | 13 | 22.06 | 21.90 | 21.89 | 23.00 |
| | | 25 | 0 | 22.03 | 21.99 | 21.92 | 23.30 |
| | | 1 | 0 | 21.93 | 22.00 | 21.85 | 23.00 |
| | | 1 | 13 | 21.94 | 21.85 | 21.78 | 23.00 |
| | | 1 | 24 | 21.80 | 21.80 | 21.70 | 23.00 |
| | | 12 | 0 | 21.11 | 21.05 | 20.81 | 22.00 |
| | | 12 | 6 | 21.05 | 21.14 | 20.92 | 22.00 |
| | | 12 | 13 | 21.02 | 20.99 | 20.82 | 22.00 |
| | 25 | 0 | 20.89 | 20.95 | 20.91 | 22.30 | |
| | QPSK | 1 | 0 | 23.04 | 23.09 | 22.93 | 24.00 |
| | | 1 | 25 | 23.49 | 23.17 | 23.07 | 24.00 |
| | | 1 | 49 | 23.03 | 22.98 | 22.93 | 24.00 |
| | | 25 | 0 | 22.12 | 22.06 | 21.83 | 23.00 |
| | | 25 | 13 | 22.01 | 21.99 | 21.89 | 23.00 |
| | | 25 | 25 | 22.02 | 21.86 | 21.86 | 23.00 |
| | | 50 | 0 | 22.06 | 21.92 | 21.87 | 23.30 |
| 16QAM | | 1 | 0 | 21.88 | 21.97 | 21.80 | 23.00 |
| | 1 | 25 | 21.91 | 21.84 | 21.75 | 23.00 | |
| | 1 | 49 | 21.78 | 21.75 | 21.68 | 23.00 | |
| | 25 | 0 | 21.08 | 21.04 | 20.79 | 22.00 | |
| | 25 | 13 | 21.01 | 21.11 | 20.88 | 22.00 | |
| | 25 | 25 | 21.00 | 20.95 | 20.79 | 22.00 | |
| | 50 | 0 | 20.87 | 20.91 | 20.88 | 22.30 | |



| LTE FDD Band 7 | | | | Conducted Power(dBm) | | | Tune-up Limit (dBm) |
|----------------|------------|---------|-----------|-------------------------|------------|--------------|---------------------------|
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | |
| | | | | 20775/2502.5 | 21100/2535 | 21425/2567.5 | |
| 5MHz | QPSK | 1 | 0 | 22.56 | 22.79 | 22.64 | 24.00 |
| | | 1 | 13 | 22.63 | 22.76 | 22.99 | 24.00 |
| | | 1 | 24 | 22.54 | 22.56 | 22.83 | 24.00 |
| | | 12 | 0 | 20.54 | 21.00 | 20.92 | 23.00 |
| | | 12 | 6 | 20.73 | 21.02 | 21.09 | 23.00 |
| | | 12 | 13 | 20.80 | 20.99 | 21.11 | 23.00 |
| | | 25 | 0 | 20.65 | 20.99 | 21.05 | 23.00 |
| | 16QAM | 1 | 0 | 20.69 | 21.25 | 20.82 | 23.00 |
| | | 1 | 13 | 21.16 | 21.30 | 21.08 | 23.00 |
| | | 1 | 24 | 21.01 | 21.42 | 21.23 | 23.00 |
| | | 12 | 0 | 19.97 | 20.36 | 20.34 | 22.00 |
| | | 12 | 6 | 20.21 | 20.40 | 20.42 | 22.00 |
| | | 12 | 13 | 20.21 | 20.23 | 20.36 | 22.00 |
| | | 25 | 0 | 20.05 | 20.17 | 20.24 | 22.00 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20800/2505 | 21100/2535 | 21400/2565 | |
| 10MHz | QPSK | 1 | 0 | 22.58 | 22.80 | 22.67 | 24.00 |
| | | 1 | 25 | 22.66 | 22.81 | 23.03 | 24.00 |
| | | 1 | 49 | 22.56 | 22.60 | 22.86 | 24.00 |
| | | 25 | 0 | 20.57 | 21.05 | 20.96 | 23.00 |
| | | 25 | 13 | 20.76 | 21.07 | 21.13 | 23.00 |
| | | 25 | 25 | 20.82 | 21.03 | 21.16 | 23.00 |
| | | 50 | 0 | 20.73 | 21.01 | 21.09 | 23.00 |
| | 16QAM | 1 | 0 | 20.71 | 21.28 | 20.84 | 23.00 |
| | | 1 | 25 | 21.19 | 21.34 | 21.11 | 23.00 |
| | | 1 | 49 | 21.04 | 21.44 | 21.26 | 23.00 |
| | | 25 | 0 | 20.00 | 20.41 | 20.38 | 22.00 |
| | | 25 | 13 | 20.23 | 20.44 | 20.45 | 22.00 |
| | | 25 | 25 | 20.24 | 20.28 | 20.40 | 22.00 |
| | | 50 | 0 | 20.08 | 20.22 | 20.28 | 22.00 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 20825/2507.5 | 21100/2535 | 21375/2562.5 | |
| 15MHz | QPSK | 1 | 0 | 22.57 | 22.76 | 22.65 | 24.00 |
| | | 1 | 38 | 22.64 | 22.80 | 23.00 | 24.00 |
| | | 1 | 74 | 22.53 | 22.55 | 22.82 | 24.00 |
| | | 36 | 0 | 20.55 | 21.01 | 20.93 | 23.00 |
| | | 36 | 18 | 20.73 | 21.02 | 21.09 | 23.00 |



| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
|-----------|------------|---------|-----------|-------------------------|------------|------------|---------------------|
| | | | | 20850/2510 | 21100/2535 | 21350/2560 | |
| | | 36 | 39 | 20.79 | 21.00 | 21.12 | 23.00 |
| | | 75 | 0 | 20.71 | 20.97 | 21.04 | 23.00 |
| | 16QAM | 1 | 0 | 20.66 | 21.26 | 20.82 | 23.00 |
| | | 1 | 38 | 21.17 | 21.31 | 21.09 | 23.00 |
| | | 1 | 74 | 21.01 | 21.40 | 21.23 | 23.00 |
| | | 36 | 0 | 19.97 | 20.39 | 20.35 | 22.00 |
| | | 36 | 18 | 20.20 | 20.39 | 20.41 | 22.00 |
| | | 36 | 39 | 20.22 | 20.24 | 20.37 | 22.00 |
| | | 75 | 0 | 20.05 | 20.17 | 20.24 | 22.00 |
| 20MHz | QPSK | 1 | 0 | 22.54 | 22.72 | 22.62 | 24.00 |
| | | 1 | 50 | 22.63 | 22.76 | 22.98 | 24.00 |
| | | 1 | 99 | 22.51 | 22.54 | 22.79 | 24.00 |
| | | 50 | 0 | 21.21 | 21.26 | 21.19 | 23.00 |
| | | 50 | 25 | 21.01 | 21.28 | 21.36 | 23.00 |
| | | 50 | 50 | 21.06 | 21.25 | 21.38 | 23.00 |
| | | 100 | 0 | 21.36 | 21.32 | 21.33 | 23.00 |
| | 16QAM | 1 | 0 | 20.64 | 21.22 | 21.07 | 23.00 |
| | | 1 | 50 | 21.13 | 21.29 | 21.05 | 23.00 |
| | | 1 | 99 | 21.12 | 21.37 | 21.21 | 23.00 |
| | | 50 | 0 | 20.03 | 20.35 | 20.32 | 22.00 |
| | | 50 | 25 | 20.17 | 20.37 | 20.38 | 22.00 |
| | | 50 | 50 | 20.19 | 20.19 | 20.33 | 22.00 |
| | | 100 | 0 | 20.03 | 20.13 | 20.21 | 22.00 |

| LTE TDD Band 38 | | | | Conducted Power(dBm) | | | Tune-up Limit (dBm) |
|-----------------|------------|---------|-----------|-------------------------|------------|--------------|---------------------|
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | |
| | | | | 37775/2572.5 | 38000/2595 | 38225/2617.5 | |
| 5MHz | QPSK | 1 | 0 | 22.81 | 22.62 | 22.70 | 23.50 |
| | | 1 | 13 | 22.60 | 22.67 | 22.78 | 23.50 |
| | | 1 | 24 | 22.33 | 22.68 | 22.61 | 23.50 |
| | | 12 | 0 | 21.79 | 21.73 | 21.65 | 22.50 |
| | | 12 | 6 | 21.66 | 21.66 | 21.71 | 22.50 |
| | | 12 | 13 | 21.74 | 21.61 | 21.63 | 22.50 |
| | | 25 | 0 | 21.64 | 21.82 | 21.63 | 22.50 |
| | 16QAM | 1 | 0 | 21.37 | 21.21 | 21.12 | 22.50 |
| | | 1 | 13 | 21.53 | 21.32 | 21.14 | 22.50 |
| | | 1 | 24 | 21.24 | 21.28 | 21.29 | 22.50 |
| | | 12 | 0 | 20.80 | 20.56 | 20.67 | 21.50 |
| | | 12 | 6 | 20.79 | 20.66 | 20.64 | 21.50 |



| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
|-----------|------------|---------|-----------|-------------------------|------------|--------------|---------------------|
| | | | | 37800/2575 | 38000/2595 | 38200/2615 | |
| | | 12 | 13 | 20.86 | 20.75 | 20.67 | 21.50 |
| | | 25 | 0 | 20.67 | 20.77 | 20.73 | 21.50 |
| 10MHz | QPSK | 1 | 0 | 22.83 | 22.63 | 22.73 | 23.50 |
| | | 1 | 25 | 22.63 | 22.72 | 22.82 | 23.50 |
| | | 1 | 49 | 22.35 | 22.72 | 22.64 | 23.50 |
| | | 25 | 0 | 21.82 | 21.78 | 21.69 | 22.50 |
| | | 25 | 13 | 21.69 | 21.71 | 21.75 | 22.50 |
| | | 25 | 25 | 21.76 | 21.65 | 21.68 | 22.50 |
| | | 50 | 0 | 21.72 | 21.84 | 21.67 | 22.50 |
| | 16QAM | 1 | 0 | 21.39 | 21.24 | 21.14 | 22.50 |
| | | 1 | 25 | 21.56 | 21.36 | 21.17 | 22.50 |
| | | 1 | 49 | 21.27 | 21.30 | 21.32 | 22.50 |
| | | 25 | 0 | 20.83 | 20.61 | 20.71 | 21.50 |
| | | 25 | 13 | 20.81 | 20.70 | 20.67 | 21.50 |
| | | 25 | 25 | 20.89 | 20.80 | 20.71 | 21.50 |
| | | 50 | 0 | 20.70 | 20.82 | 20.77 | 21.50 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 37825/2577.5 | 38000/2595 | 38175/2612.5 | |
| 15MHz | QPSK | 1 | 0 | 22.82 | 22.59 | 22.71 | 23.50 |
| | | 1 | 38 | 22.61 | 22.71 | 22.79 | 23.50 |
| | | 1 | 74 | 22.32 | 22.67 | 22.60 | 23.50 |
| | | 36 | 0 | 21.80 | 21.74 | 21.66 | 22.50 |
| | | 36 | 18 | 21.66 | 21.66 | 21.71 | 22.50 |
| | | 36 | 39 | 21.73 | 21.62 | 21.64 | 22.50 |
| | | 75 | 0 | 21.70 | 21.80 | 21.62 | 22.50 |
| | 16QAM | 1 | 0 | 21.34 | 21.22 | 21.12 | 22.50 |
| | | 1 | 38 | 21.54 | 21.33 | 21.15 | 22.50 |
| | | 1 | 74 | 21.24 | 21.26 | 21.29 | 22.50 |
| | | 36 | 0 | 20.80 | 20.59 | 20.68 | 21.50 |
| | | 36 | 18 | 20.78 | 20.65 | 20.63 | 21.50 |
| | | 36 | 39 | 20.87 | 20.76 | 20.68 | 21.50 |
| | | 75 | 0 | 20.67 | 20.77 | 20.73 | 21.50 |
| Bandwidth | Modulation | RB size | RB offset | Channel/Frequency (MHz) | | | Tune-up Limit (dBm) |
| | | | | 37850/2580 | 38000/2595 | 38150/2610 | |
| 20MHz | QPSK | 1 | 0 | 22.79 | 22.55 | 22.68 | 23.50 |
| | | 1 | 50 | 22.60 | 22.67 | 22.77 | 23.50 |
| | | 1 | 99 | 22.30 | 22.66 | 22.57 | 23.50 |
| | | 50 | 0 | 21.77 | 21.69 | 21.62 | 22.50 |



| | | | | | | | |
|--|-------|-----|----|-------|-------|-------|-------|
| | | 50 | 25 | 21.64 | 21.62 | 21.68 | 22.50 |
| | | 50 | 50 | 21.70 | 21.57 | 21.60 | 22.50 |
| | | 100 | 0 | 21.67 | 21.75 | 21.58 | 22.50 |
| | 16QAM | 1 | 0 | 21.32 | 21.18 | 21.07 | 22.50 |
| | | 1 | 50 | 21.50 | 21.31 | 21.11 | 22.50 |
| | | 1 | 99 | 21.22 | 21.23 | 21.27 | 22.50 |
| | | 50 | 0 | 20.77 | 20.55 | 20.65 | 21.50 |
| | | 50 | 25 | 20.75 | 20.63 | 20.60 | 21.50 |
| | | 50 | 50 | 20.84 | 20.71 | 20.64 | 21.50 |
| | | 100 | 0 | 20.65 | 20.73 | 20.70 | 21.50 |

| DL LTE CA Class | PCC | | | | | | | | SCC | | | Power | | Tune-up Limit (dBm) |
|-----------------|----------|---------------------|----------------|------------------|----------------|------------------|----------------|----------------|----------|---------------------|----------------|--------------------------|---------------------------------|---------------------|
| | PCC Band | PCC Bandwidth (MHz) | PCC UL RB size | PCC UL RB offset | PCC DL RB size | PCC DL RB offset | PCC UL Channel | PCC DL Channel | SCC Band | SCC Bandwidth (MHz) | SCC DL Channel | Rel 8 LTE Tx Power (dBm) | Rel 10 DL LTE CA Tx Power (dBm) | |
| CA_7C | 7 | 15 | 1 | 38 | 75 | 0 | 21225 | 3225 | 7 | 15 | 3375 | 23.00 | 23.08 | 24.00 |
| | 7 | 20 | 1 | 50 | 100 | 0 | 21152 | 3152 | 7 | 20 | 3350 | 22.98 | 22.97 | 24.00 |
| CA_38C | 38 | 15 | 1 | 0 | 75 | 0 | 37825 | 37825 | 38 | 15 | 37975 | 22.82 | 22.92 | 23.50 |
| | 38 | 20 | 1 | 0 | 100 | 0 | 37850 | 37850 | 38 | 20 | 38075 | 22.79 | 22.79 | 23.50 |

Note: For downlink carrier aggregation, SAR is not required when downlink carrier aggregation in active uplink maximum output power not more than 1/4dB higher than the maximum output power measured when downlink carrier aggregation inactive.

9.4 WLAN Mode

| Wi-Fi 2.4G Mode | Channel | Frequency (MHz) | Average Conducted Power (dBm) for Data Rates (bps) | Tune-up Limit (dBm) | TX Power Setting level |
|-----------------|---------|-----------------|--|---------------------|------------------------|
| | | | 1M | | |
| 802.11b | 1 | 2412 | 13.76 | 14.50 | 15 |
| | 6 | 2437 | 13.61 | 14.50 | |
| | 11 | 2462 | 13.96 | 14.50 | |
| Mode | Channel | Frequency (MHz) | 6M | Tune-up Limit (dBm) | TX Power Setting level |
| 802.11g | 1 | 2412 | 11.75 | 13.00 | 14 |
| | 6 | 2437 | 12.37 | 13.00 | |
| | 11 | 2462 | 12.16 | 13.00 | |
| Mode | Channel | Frequency (MHz) | 6.5M | Tune-up Limit (dBm) | TX Power Setting level |
| 802.11n (HT20) | 1 | 2412 | 8.92 | 11.50 | 12 |
| | 6 | 2437 | 10.34 | 11.50 | |
| | 11 | 2462 | 9.38 | 11.50 | |


Note. 1. SAR is not required for OFDM when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

9.5 Bluetooth Mode

| BT | Conducted Power(dBm) | | | Tune-up Limit (dBm) |
|---------------|------------------------|-----------------------|-----------------------|----------------------------|
| | Channel/Frequency(MHz) | | | |
| | Ch 0/2402 MHz | Ch 39/2441 MHz | Ch 78/2480 MHz | |
| GFSK | 1.67 | 2.93 | 2.36 | 4.00 |
| $\pi/4$ DQPSK | 2.35 | 3.56 | 2.63 | 5.00 |
| 8DPSK | 2.94 | 4.03 | 3.10 | 5.00 |
| BLE | Ch 0/2402 MHz | Ch 19/2440 MHz | Ch 39/2480 MHz | Tune-up Limit (dBm) |
| GFSK | -4.18 | -3.62 | -3.69 | -1.00 |

10 Measured and Reported (Scaled) SAR Results

10.1 EUT Antenna Locations



| Overall (Length x Width): 150 mm x 74 mm | | | | | | |
|---|-----------|------------|-----------|------------|----------|-------------|
| Overall Diagonal: 161.5 mm/Display Diagonal: 139mm | | | | | | |
| Distance of the Antenna to the EUT surface/edge | | | | | | |
| Antenna | Back Side | Front side | Left Edge | Right Edge | Top Edge | Bottom Edge |
| Main-Antenna | 0 | 0 | 2.8 | 2.8 | 142 | 0.6 |
| BT/Wi-Fi Antenna | 0 | 0 | 58 | 0.4 | 0 | 140 |
| Hotspot mode, Positions for SAR tests | | | | | | |
| Mode | Back Side | Front side | Left Edge | Right Edge | Top Edge | Bottom Edge |
| GSM 850/1900/DTM 850/1900 | Yes | Yes | Yes | Yes | N/A | Yes |
| UMTS Band II/V | Yes | Yes | Yes | Yes | N/A | Yes |
| LTE 4/5/7/38 | Yes | Yes | Yes | Yes | N/A | Yes |
| 2.4GHz WLAN | Yes | Yes | N/A | Yes | Yes | N/A |
| <p>Note: 1. Per KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.</p> <p>2. For smart phones with an overall diagonal dimension is 161.5mm. Per KDB 648474 D04, for smart phones with a display diagonal dimension $> 15.0\text{ cm}$ or an overall diagonal dimension $> 16.0\text{ cm}$, 10-g extremity SAR must be tested as a phablet to determine SAR compliance.</p> | | | | | | |

10.2 Standalone SAR test exclusion considerations

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

| Bluetooth | Distance (mm) | MAX Power (dBm) | Frequency (MHz) | Ratio | Evaluation |
|-----------|---------------|-----------------|-----------------|-------|------------|
| Head | 5 | 5.00 | 2480 | 1.00 | No |
| Body-worn | 10 | 5.00 | 2480 | 0.50 | No |
| Extremity | 5 | 5.00 | 2480 | 1.00 | No |

10.3 Measured SAR Results

Table 1: GSM 850

| Test Position | Cover Type | Channel/Frequency (MHz) | Time slot | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|----------------------------------|------------|-------------------------|-----------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | -0.030 | 0.276 | 1.34 | 0.369 | 11 |
| Left Tilt | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | -0.060 | 0.154 | 1.34 | 0.206 | / |
| Right Cheek | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | -0.030 | 0.256 | 1.34 | 0.342 | / |
| Right Tilt | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | 0.150 | 0.246 | 1.34 | 0.329 | / |
| Left Cheek | SIM 2 | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | -0.080 | 0.262 | 1.34 | 0.350 | / |
| Left Cheek | Battery 2 | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | 0.018 | 0.254 | 1.34 | 0.339 | / |
| Body-worn (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | 0.080 | 0.281 | 1.34 | 0.376 | 12 |
| Front Side | standard | 190/836.6 | GSM | 1:8.3 | 33.50 | 32.24 | 0.150 | 0.225 | 1.34 | 0.301 | / |
| Hotspot (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.050 | 0.268 | 1.31 | 0.352 | / |
| Front Side | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.140 | 0.217 | 1.31 | 0.285 | / |
| Left Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.100 | 0.181 | 1.31 | 0.238 | / |
| Right Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.000 | 0.154 | 1.31 | 0.202 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.030 | 0.097 | 1.31 | 0.127 | / |
| Back Side | SIM 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | -0.100 | 0.339 | 1.31 | 0.445 | 13 |
| Back Side | Battery 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.82 | 0.007 | 0.318 | 1.31 | 0.417 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).

3. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.

4. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.

5. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.

Table 2: DTM 850

| Test Position | Cover Type | Channel/Frequency (MHz) | Time slot | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------|------------|-------------------------|-----------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | -0.010 | 0.301 | 1.33 | 0.400 | 14 |
| Left Tilt | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.020 | 0.146 | 1.33 | 0.194 | / |
| Right Cheek | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.041 | 0.272 | 1.33 | 0.361 | / |
| Right Tilt | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.080 | 0.158 | 1.33 | 0.210 | / |
| Left Cheek | SIM 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.030 | 0.294 | 1.33 | 0.390 | / |
| Left Cheek | Battery 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.008 | 0.287 | 1.33 | 0.381 | / |
| Body SAR (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.020 | 0.337 | 1.33 | 0.447 | 15 |
| Front Side | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.040 | 0.178 | 1.33 | 0.236 | / |
| Left Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | -0.040 | 0.196 | 1.33 | 0.260 | / |
| Right Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | -0.010 | 0.150 | 1.33 | 0.199 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | -0.080 | 0.098 | 1.33 | 0.130 | / |
| Back Side | SIM 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | -0.025 | 0.323 | 1.33 | 0.429 | / |
| Back Side | Battery 2 | 190/836.6 | 2Txslots | 1:4.15 | 31.00 | 29.77 | 0.046 | 0.306 | 1.33 | 0.406 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.
 2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
 3. When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
 4. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.
 5. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.



Table 3: GSM 1900

| Test Position | Cover Type | Channel/Frequency (MHz) | Time slot | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|----------------------------------|------------|-------------------------|-----------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.020 | 0.049 | 1.21 | 0.059 | / |
| Left Tilt | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.034 | 0.037 | 1.21 | 0.045 | / |
| Right Cheek | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.112 | 0.062 | 1.21 | 0.074 | / |
| Right Tilt | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.170 | 0.030 | 1.21 | 0.036 | / |
| Right Cheek | SIM 2 | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | -0.036 | 0.064 | 1.21 | 0.077 | 16 |
| Right Cheek | Battery 2 | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.028 | 0.057 | 1.21 | 0.069 | / |
| Body-worn (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.150 | 0.211 | 1.21 | 0.255 | / |
| Front Side | standard | 661/1880 | GSM | 1:8.3 | 30.50 | 29.68 | 0.038 | 0.246 | 1.21 | 0.297 | 17 |
| Hotspot (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | 0.040 | 0.253 | 1.12 | 0.283 | / |
| Front Side | standard | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | 0.024 | 0.288 | 1.12 | 0.322 | / |
| Left Edge | standard | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | -0.140 | 0.062 | 1.12 | 0.070 | / |
| Right Edge | standard | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | -0.064 | 0.034 | 1.12 | 0.038 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | -0.051 | 0.345 | 1.12 | 0.386 | 18 |
| Bottom Edge | SIM 2 | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | -0.046 | 0.241 | 1.12 | 0.270 | / |
| Bottom Edge | Battery 2 | 661/1880 | 4Txslots | 1:2.07 | 26.00 | 25.51 | 0.107 | 0.225 | 1.12 | 0.252 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.
- According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.



Table 4: DTM 1900

| Test Position | Cover Type | Channel/Frequency (MHz) | Time slot | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------|------------|-------------------------|-----------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.062 | 0.056 | 1.09 | 0.061 | / |
| Left Tilt | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.030 | 0.042 | 1.09 | 0.046 | / |
| Right Cheek | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.105 | 0.063 | 1.09 | 0.068 | 19 |
| Right Tilt | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.032 | 0.035 | 1.09 | 0.038 | / |
| Right Cheek | SIM 2 | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.010 | 0.059 | 1.09 | 0.064 | / |
| Right Cheek | Battery 2 | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.032 | 0.052 | 1.09 | 0.057 | / |
| Body SAR (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.140 | 0.381 | 1.09 | 0.415 | / |
| Front Side | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | -0.052 | 0.302 | 1.09 | 0.329 | / |
| Left Edge | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.090 | 0.045 | 1.09 | 0.049 | / |
| Right Edge | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.180 | 0.032 | 1.09 | 0.035 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.029 | 0.502 | 1.09 | 0.547 | 20 |
| Bottom Edge | SIM 2 | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.032 | 0.500 | 1.09 | 0.544 | / |
| Bottom Edge | Battery 2 | 661/1880 | 2Txslots | 1:4.15 | 28.50 | 28.13 | 0.044 | 0.491 | 1.09 | 0.535 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.
- According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.



Table 5: UMTS Band II

| Test Position | Cover Type | Channel/Frequency (MHz) | Channel Type | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------|------------|-------------------------|--------------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.160 | 0.084 | 1.16 | 0.098 | / |
| Left Tilt | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.090 | 0.056 | 1.16 | 0.065 | / |
| Right Cheek | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.124 | 0.073 | 1.16 | 0.085 | / |
| Right Tilt | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.110 | 0.050 | 1.16 | 0.057 | / |
| Left Cheek | SIM 2 | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.051 | 0.091 | 1.16 | 0.106 | 21 |
| Left Cheek | Battery 2 | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.010 | 0.084 | 1.16 | 0.098 | / |
| Body SAR (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | -0.140 | 0.530 | 1.16 | 0.616 | / |
| Front Side | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.120 | 0.390 | 1.16 | 0.453 | / |
| Left Edge | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | -0.020 | 0.099 | 1.16 | 0.115 | / |
| Right Edge | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | 0.051 | 0.038 | 1.16 | 0.044 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | -0.038 | 0.641 | 1.16 | 0.744 | 22 |
| Bottom Edge | SIM 2 | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | -0.120 | 0.605 | 1.16 | 0.703 | / |
| Bottom Edge | Battery 2 | 9400/1880 | RMC 12.2K | 1:1 | 23.50 | 22.85 | -0.032 | 0.583 | 1.16 | 0.677 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.
- According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.

Table 6: UMTS Band V

| Test Position | Cover Type | Channel/Frequency (MHz) | Channel Type | Duty Cycle | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------|------------|-------------------------|--------------|------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | |
| Left Cheek | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.059 | 0.308 | 1.27 | 0.390 | 23 |
| Left Tilt | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.130 | 0.155 | 1.27 | 0.196 | / |
| Right Cheek | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | -0.080 | 0.290 | 1.27 | 0.368 | / |
| Right Tilt | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.030 | 0.168 | 1.27 | 0.213 | / |
| Left Cheek | SIM 2 | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | -0.180 | 0.301 | 1.27 | 0.382 | / |
| Left Cheek | Battery 2 | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | -0.051 | 0.287 | 1.27 | 0.364 | / |
| Body SAR (Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.020 | 0.297 | 1.27 | 0.376 | 24 |
| Front Side | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.110 | 0.182 | 1.27 | 0.231 | / |
| Left Edge | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.120 | 0.226 | 1.27 | 0.286 | / |
| Right Edge | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | -0.040 | 0.159 | 1.27 | 0.202 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | -0.040 | 0.096 | 1.27 | 0.122 | / |
| Back Side | SIM 2 | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.080 | 0.297 | 1.27 | 0.376 | / |
| Back Side | Battery 2 | 4183/836.6 | RMC 12.2K | 1:1 | 24.00 | 22.97 | 0.012 | 0.280 | 1.27 | 0.355 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

- Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode
- Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was ≤ 1.2 W/kg, no additional SAR evaluations using a headset cable were required.
- According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.



Table 7: LTE Band 4 (20MHz)

| Test Position | Cover Type | RB size | RB offset | Channel/ Frequency (MHz) | Maximum Allowed Power(dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------------|------------|---------|-----------|--------------------------|----------------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR (QPSK) | | | | | | | | | | | |
| Left Cheek | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.047 | 0.030 | 1.07 | 0.032 | / |
| Left Tilt | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.080 | 0.025 | 1.07 | 0.027 | / |
| Right Cheek | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.030 | 0.068 | 1.07 | 0.073 | 25 |
| Right Tilt | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.087 | 0.034 | 1.07 | 0.036 | / |
| Left Cheek | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.179 | 0.027 | 1.10 | 0.029 | / |
| Left Tilt | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.052 | 0.023 | 1.10 | 0.025 | / |
| Right Cheek | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.131 | 0.063 | 1.10 | 0.069 | / |
| Right Tilt | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.061 | 0.033 | 1.10 | 0.036 | / |
| Right Cheek | SIM 2 | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.033 | 0.068 | 1.07 | 0.073 | / |
| Right Cheek | Battery 2 | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.019 | 0.061 | 1.07 | 0.065 | / |
| Body SAR (QPSK, Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.149 | 0.737 | 1.07 | 0.788 | / |
| Front Side | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.080 | 0.442 | 1.07 | 0.473 | / |
| Left Edge | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.170 | 0.026 | 1.07 | 0.028 | / |
| Right Edge | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.160 | 0.034 | 1.07 | 0.037 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 1RB | 0 | 20300/1745 | 24.00 | 23.71 | 0.024 | 0.814 | 1.07 | 0.870 | / |
| | | 1RB | 0 | 20175/1732.5 | 24.00 | 23.67 | 0.021 | 0.821 | 1.08 | 0.886 | / |
| | | 1RB | 50 | 20050/1720 | 24.00 | 23.34 | -0.120 | 0.846 | 1.16 | 0.985 | 26 |
| Back Side | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.037 | 0.690 | 1.10 | 0.758 | / |
| Front Side | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.022 | 0.407 | 1.10 | 0.447 | / |
| Left Edge | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.081 | 0.025 | 1.10 | 0.027 | / |
| Right Edge | standard | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.033 | 0.032 | 1.10 | 0.035 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 50%RB | 0 | 20300/1745 | 23.00 | 22.54 | 0.022 | 0.747 | 1.11 | 0.830 | / |
| | | 50%RB | 50 | 20175/1732.5 | 23.00 | 22.59 | 0.190 | 0.741 | 1.10 | 0.814 | / |
| | | 50%RB | 50 | 20050/1720 | 23.00 | 22.16 | 0.024 | 0.797 | 1.21 | 0.967 | / |
| Bottom Edge | standard | 100%RB | 0 | 20300/1745 | 23.00 | 22.34 | 0.020 | 0.710 | 1.16 | 0.827 | / |
| | | 100%RB | 0 | 20175/1732.5 | 23.00 | 22.54 | 0.022 | 0.775 | 1.11 | 0.862 | / |
| | | 100%RB | 0 | 20050/1720 | 23.00 | 22.15 | 0.110 | 0.800 | 1.22 | 0.973 | / |
| Bottom Edge | SIM 2 | 1RB | 50 | 20050/1720 | 24.00 | 23.34 | 0.028 | 0.832 | 1.16 | 0.969 | / |
| Bottom Edge | Battery 2 | 1RB | 50 | 20050/1720 | 24.00 | 23.34 | 0.091 | 0.829 | 1.16 | 0.965 | / |
| Bottom Edge | Repeated | 1RB | 50 | 20050/1720 | 24.00 | 23.34 | 0.033 | 0.845 | 1.16 | 0.984 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output



power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).

3. For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 0.8 W/kg.

4. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g *reported* SAR < 1.2 W/kg, 10-g extremity SAR is no required.

| Measurement Variability | | | | |
|-------------------------|----------------------------|--|--|-------|
| Test Position | Channel/ Frequency(MHz) | MAX Measured SAR _{1g} (W/kg) | 1 st Repeated SAR _{1g} (W/kg) | Ratio |
| Bottom Edge | 20050/1720 | 0.846 | 0.845 | 1.00 |

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
 2) A second repeated measurement was preformed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg



Table 8: LTE Band 5 (10MHz)

| Test Position | Cover Type | RB size | RB offset | Channel/Frequency (MHz) | Maximum Allowed Power (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------------|------------|---------|-----------|-------------------------|-----------------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR (QPSK) | | | | | | | | | | | |
| Left Cheek | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.150 | 0.313 | 1.12 | 0.352 | / |
| Left Tilt | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | -0.025 | 0.173 | 1.12 | 0.195 | / |
| Right Cheek | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | -0.130 | 0.313 | 1.12 | 0.352 | 27 |
| Right Tilt | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.150 | 0.212 | 1.12 | 0.238 | / |
| Left Cheek | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.110 | 0.216 | 1.22 | 0.265 | / |
| Left Tilt | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.077 | 0.141 | 1.22 | 0.173 | / |
| Right Cheek | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.170 | 0.229 | 1.22 | 0.280 | / |
| Right Tilt | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.060 | 0.158 | 1.22 | 0.193 | / |
| Right Cheek | SIM 2 | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.026 | 0.297 | 1.12 | 0.334 | / |
| Right Cheek | Battery 2 | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.009 | 0.284 | 1.12 | 0.319 | / |
| Body SAR (QPSK, Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | -0.020 | 0.376 | 1.12 | 0.423 | / |
| Front Side | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | -0.150 | 0.192 | 1.12 | 0.216 | / |
| Left Edge | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | -0.010 | 0.243 | 1.12 | 0.273 | / |
| Right Edge | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.000 | 0.188 | 1.12 | 0.211 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 1RB | 25 | 20450/829 | 24.00 | 23.49 | 0.090 | 0.096 | 1.12 | 0.108 | / |
| Back Side | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.000 | 0.304 | 1.22 | 0.372 | / |
| Front Side | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.040 | 0.157 | 1.22 | 0.192 | / |
| Left Edge | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.080 | 0.192 | 1.22 | 0.235 | / |
| Right Edge | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | 0.070 | 0.148 | 1.22 | 0.181 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 50%RB | 0 | 20450/829 | 23.00 | 22.12 | -0.060 | 0.076 | 1.22 | 0.093 | / |
| Back Side | SIM 2 | 1RB | 0 | 20450/829 | 24.00 | 23.49 | 0.080 | 0.542 | 1.12 | 0.610 | 28 |
| Back Side | Battery 2 | 1RB | 0 | 20450/829 | 24.00 | 23.49 | 0.042 | 0.518 | 1.12 | 0.583 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).

3. For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 0.8 W/kg.

4. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.

Table 9: LTE Band 7 (20MHz)

| Test Position | Cover Type | RB size | RB offset | Channel/Frequency (MHz) | Maximum Allowed Power (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---------------------------------------|------------|---------|-----------|-------------------------|-----------------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR (QPSK) | | | | | | | | | | | |
| Left Cheek | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.105 | 0.091 | 1.26 | 0.115 | / |
| Left Tilt | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.046 | 0.037 | 1.26 | 0.046 | / |
| Right Cheek | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.052 | 0.104 | 1.26 | 0.132 | 29 |
| Right Tilt | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.037 | 0.026 | 1.26 | 0.033 | / |
| Left Cheek | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.149 | 0.088 | 1.45 | 0.127 | / |
| Left Tilt | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.070 | 0.034 | 1.45 | 0.049 | / |
| Right Cheek | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.055 | 0.093 | 1.45 | 0.135 | / |
| Right Tilt | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.032 | 0.027 | 1.45 | 0.040 | / |
| Right Cheek | SIM 2 | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.032 | 0.096 | 1.26 | 0.122 | / |
| Right Cheek | Battery 2 | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.033 | 0.092 | 1.26 | 0.116 | / |
| Body SAR (QPSK, Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.060 | 0.523 | 1.26 | 0.661 | 30 |
| Front Side | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | -0.029 | 0.287 | 1.26 | 0.363 | / |
| Left Edge | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | -0.030 | 0.164 | 1.26 | 0.207 | / |
| Right Edge | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | -0.040 | 0.151 | 1.26 | 0.191 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | -0.021 | 0.522 | 1.26 | 0.660 | / |
| Back Side | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.039 | 0.511 | 1.45 | 0.742 | / |
| Front Side | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.026 | 0.279 | 1.45 | 0.405 | / |
| Left Edge | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | -0.060 | 0.110 | 1.45 | 0.160 | / |
| Right Edge | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | 0.030 | 0.102 | 1.45 | 0.148 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 50%RB | 50 | 21350/2560 | 23.00 | 21.38 | -0.010 | 0.499 | 1.45 | 0.725 | / |
| Back Side | SIM 2 | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.033 | 0.521 | 1.26 | 0.659 | / |
| Back Side | Battery 2 | 1RB | 50 | 21350/2560 | 24.00 | 22.98 | 0.084 | 0.507 | 1.26 | 0.641 | / |

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).

3. For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 0.8 W/kg.

4. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is no required.



Table 10: LTE Band 38 (20MHz)

| Test Position | Cover Type | RB size | RB offset | Channel/Frequency (MHz) | Maximum Allowed Power (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|--|------------|---------|-----------|-------------------------|-----------------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR (QPSK) | | | | | | | | | | | |
| Left Cheek | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.023 | 0.147 | 1.18 | 0.173 | / |
| Left Tilt | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.021 | 0.051 | 1.18 | 0.060 | / |
| Right Cheek | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.140 | 0.111 | 1.18 | 0.131 | / |
| Right Tilt | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.158 | 0.043 | 1.18 | 0.051 | / |
| Left Cheek | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.043 | 0.114 | 1.18 | 0.135 | / |
| Left Tilt | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.100 | 0.028 | 1.18 | 0.033 | / |
| Right Cheek | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | -0.023 | 0.087 | 1.18 | 0.103 | / |
| Right Tilt | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.086 | 0.033 | 1.18 | 0.039 | / |
| Left Cheek | SIM 2 | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.039 | 0.157 | 1.18 | 0.185 | 31 |
| Left Cheek | Battery 2 | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.032 | 0.144 | 1.18 | 0.170 | / |
| Body SAR (QPSK, Distance 10mm) | | | | | | | | | | | |
| Back Side | standard | 1RB | 50 | 38150/2610 | 23.50 | 22.77 | -0.120 | 0.712 | 1.18 | 0.842 | / |
| | | 1RB | 50 | 38000/2595 | 23.50 | 22.67 | 0.060 | 0.853 | 1.21 | 1.033 | / |
| | | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.084 | 0.984 | 1.18 | 1.159 | / |
| Front Side | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.140 | 0.428 | 1.18 | 0.504 | / |
| Left Edge | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.190 | 0.055 | 1.18 | 0.065 | / |
| Right Edge | standard | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.100 | 0.089 | 1.18 | 0.104 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 1RB | 50 | 38150/2610 | 23.50 | 22.77 | 0.026 | 0.610 | 1.18 | 0.722 | / |
| | | 1RB | 50 | 38000/2595 | 23.50 | 22.67 | 0.026 | 0.749 | 1.21 | 0.907 | / |
| | | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.026 | 0.991 | 1.18 | 1.167 | 32 |
| Back Side | standard | 50%RB | 25 | 38150/2610 | 22.50 | 21.68 | -0.030 | 0.542 | 1.21 | 0.655 | / |
| | | 50%RB | 0 | 38000/2595 | 22.50 | 21.69 | 0.044 | 0.645 | 1.21 | 0.777 | / |
| | | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | -0.021 | 0.729 | 1.18 | 0.862 | / |
| Front Side | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.052 | 0.328 | 1.18 | 0.388 | / |
| Left Edge | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | -0.150 | 0.030 | 1.18 | 0.036 | / |
| Right Edge | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.020 | 0.067 | 1.18 | 0.079 | / |
| Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Bottom Edge | standard | 50%RB | 0 | 37850/2580 | 22.50 | 21.77 | 0.033 | 0.650 | 1.18 | 0.769 | / |
| Back Side | standard | 100%RB | 0 | 38000/2595 | 22.50 | 21.75 | -0.130 | 0.619 | 1.19 | 0.736 | / |
| Bottom Edge | standard | 100%RB | 0 | 38000/2595 | 22.50 | 21.75 | 0.021 | 0.524 | 1.19 | 0.623 | / |
| Bottom Edge | SIM 2 | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.180 | 0.838 | 1.18 | 0.987 | / |
| Bottom Edge | Battery 2 | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.040 | 0.877 | 1.18 | 1.033 | / |
| Bottom Edge | Repeated | 1RB | 0 | 37850/2580 | 23.50 | 22.79 | 0.031 | 0.857 | 1.18 | 1.009 | / |
| <p>Note: 1. The value with blue color is the maximum SAR Value of each test band.</p> <p>2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test</p> | | | | | | | | | | | |



configuration(s).

3. For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 0.8 W/kg.

4. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g *reported* SAR < 1.2 W/kg, 10-g extremity SAR is no required.

| Measurement Variability | | | | |
|-------------------------|----------------------------|--|--|-------|
| Test Position | Channel/ Frequency(MHz) | MAX Measured SAR _{1g} (W/kg) | 1 st Repeated SAR _{1g} (W/kg) | Ratio |
| Bottom Edge | 37850/2580 | 0.991 | 0.857 | 1.16 |

Note: 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.

2) A second repeated measurement was preformed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg



Table 11: Wi-Fi (2.4G)

| Test Position | Cover Type | Channel/Frequency (MHz) | Mode 802.11b | Duty Cycle | Area Scan Max.SAR (W/Kg) | Tune-up limit (dBm) | Conducted Power (dBm) | Drift (dB) | Measured SAR _{1g} (W/kg) | Scaling Factor | Reported SAR _{1g} (W/kg) | Plot No. |
|---|------------|-------------------------|--------------|------------|--------------------------|---------------------|-----------------------|------------|-----------------------------------|----------------|-----------------------------------|----------|
| Head SAR | | | | | | | | | | | | |
| Left Cheek | standard | 11/2462 | DSSS | 97.7% | 0.856 | 14.50 | 13.96 | 0.059 | 0.880 | 1.16 | 1.020 | 33 |
| | | 6/2437 | DSSS | 97.7% | 0.818 | 14.50 | 13.61 | 0.010 | 0.843 | 1.26 | 1.059 | / |
| | | 1/2412 | DSSS | 97.7% | 0.719 | 14.50 | 13.76 | 0.024 | 0.789 | 1.21 | 0.958 | / |
| Left Tilt | standard | 11/2462 | DSSS | 97.7% | 0.615 | 14.50 | 13.96 | -0.020 | 0.700 | 1.16 | 0.811 | / |
| Right Cheek | standard | 11/2462 | DSSS | 97.7% | 0.162 | 14.50 | 13.96 | 0.060 | 0.294 | 1.16 | 0.341 | / |
| Right Tilt | standard | 11/2462 | DSSS | 97.7% | 0.301 | 14.50 | 13.96 | 0.030 | 0.335 | 1.16 | 0.388 | / |
| Left Cheek | Battery 2 | 6/2437 | DSSS | 97.7% | 0.806 | 14.50 | 13.61 | 0.014 | 0.805 | 1.26 | 1.011 | / |
| Left Cheek | Repeated | 6/2437 | DSSS | 97.7% | 0.811 | 14.50 | 13.61 | 0.070 | 0.816 | 1.26 | 1.025 | / |
| Body SAR (Distance 10mm) | | | | | | | | | | | | |
| Back Side | standard | 11/2462 | DSSS | 97.7% | 0.177 | 14.50 | 13.96 | 0.100 | 0.178 | 1.16 | 0.206 | / |
| Front Side | standard | 11/2462 | DSSS | 97.7% | 0.212 | 14.50 | 13.96 | 0.043 | 0.214 | 1.16 | 0.248 | 34 |
| Left Edge | standard | 11/2462 | DSSS | 97.7% | 0.0323 | 14.50 | 13.96 | -0.044 | 0.034 | 1.16 | 0.040 | / |
| Right Edge | standard | 11/2462 | DSSS | 97.7% | 0.139 | 14.50 | 13.96 | -0.120 | 0.147 | 1.16 | 0.170 | / |
| Top Edge | standard | 11/2462 | DSSS | 97.7% | 0.168 | 14.50 | 13.96 | -0.140 | 0.186 | 1.16 | 0.216 | / |
| Bottom Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Front Side | Battery 2 | 11/2462 | DSSS | 97.7% | 0.204 | 14.50 | 13.96 | 0.073 | 0.207 | 1.16 | 0.240 | / |
| Note: 1. The value with blue color is the maximum SAR Value of each test band. | | | | | | | | | | | | |
| 2. According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, 10-g extremity SAR is not required. | | | | | | | | | | | | |

| MAX Adjusted SAR | | | | | | | |
|---|---------------|------------------------|---------------------------------------|-----------------------------|---------------------|----------------|-----------------------------------|
| Mode | Test Position | Channel/Frequency(MHz) | MAX Measured SAR _{1g} (W/kg) | 802.11b Tune-up limit (dBm) | Tune-up limit (dBm) | Scaling Factor | Adjusted SAR _{1g} (W/kg) |
| 802.11g | Left Cheek | 11/2462 | 0.880 | 14.50 | 13.00 | 0.71 | 0.623 |
| 802.11n HT20 | Left Cheek | 11/2462 | 0.880 | 14.50 | 11.50 | 0.50 | 0.441 |
| Note: SAR is not required for OFDM when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. | | | | | | | |



Table 12: BT

| Band | Configuration | Frequency (MHz) | Maximum Power (dBm) | Separation Distance (mm) | Estimated SAR (W/kg) |
|-----------|---------------|-----------------|---------------------|--------------------------|----------------------|
| Bluetooth | Head | 2480 | 5.00 | 5 | 0.133 |
| | Body-worn | 2480 | 5.00 | 10 | 0.066 |

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below.

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}]^x \text{ W/kg}$
for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

10.4 Simultaneous Transmission Analysis

| Simultaneous Transmission Configurations | Head | Body-worn | Hotspot |
|--|------|-----------|---------|
| GSM(Voice) + Bluetooth(data) | Yes | Yes | Yes |
| GPRS/EDGE(Data) + Bluetooth(data) | N/A | Yes | Yes |
| WCDMA(Voice) + Bluetooth(data) | Yes | Yes | Yes |
| WCDMA(Data) + Bluetooth(data) | N/A | Yes | Yes |
| LTE(Data) + Bluetooth(data) | Yes | Yes | Yes |
| GSM(Voice) + Wi-Fi-2.4GHz(data) | Yes | Yes | Yes |
| GPRS/EDGE(Data) + Wi-Fi-2.4GHz(data) | N/A | Yes | Yes |
| WCDMA(Voice) + Wi-Fi-2.4GHz(data) | Yes | Yes | Yes |
| WCDMA(Data) + Wi-Fi-2.4GHz(data) | N/A | Yes | Yes |
| LTE(Data) + Wi-Fi-2.4GHz(data) | Yes | Yes | Yes |
| Wi-Fi-2.4GHz(data) + Bluetooth(data) | N/A | N/A | N/A |

General Note:

1. The Scaled SAR summation is calculated based on the same configuration and test position.
2. Per KDB 447498 D01, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg, simultaneously transmission SAR measurement is not necessary.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

The maximum SAR_{1g} Value for Main- Antenna

| Test Position | | SAR _{1g} (W/kg) | | | | | | | | | | |
|---------------|-------------|--------------------------|---------|----------|----------|---------------|--------------|-----------|-----------|-----------|------------|------------------------|
| | | GSM 850 | DTM 850 | GSM 1900 | DTM 1900 | WCDMA Band II | WCDMA Band V | LTE FDD 4 | LTE FDD 5 | LTE FDD 7 | LTE TDD 38 | MAX. SAR _{1g} |
| Left Cheek | | 0.369 | 0.400 | 0.059 | 0.061 | 0.106 | 0.390 | 0.032 | 0.352 | 0.127 | 0.185 | 0.400 |
| Left Tilt | | 0.206 | 0.194 | 0.045 | 0.046 | 0.065 | 0.196 | 0.027 | 0.195 | 0.049 | 0.060 | 0.206 |
| Right Cheek | | 0.342 | 0.361 | 0.077 | 0.068 | 0.085 | 0.368 | 0.073 | 0.352 | 0.135 | 0.131 | 0.368 |
| Right Tilt | | 0.329 | 0.210 | 0.036 | 0.038 | 0.057 | 0.213 | 0.036 | 0.238 | 0.040 | 0.051 | 0.329 |
| Body worn | Back Side | 0.376 | 0.447 | 0.255 | 0.415 | 0.616 | 0.376 | 0.788 | 0.610 | 0.742 | 1.159 | 1.159 |
| | Front Side | 0.301 | 0.236 | 0.297 | 0.329 | 0.453 | 0.231 | 0.473 | 0.216 | 0.405 | 0.504 | 0.504 |
| Hotspot | Back Side | 0.445 | 0.447 | 0.283 | 0.415 | 0.616 | 0.376 | 0.788 | 0.610 | 0.742 | 1.159 | 1.159 |
| | Front Side | 0.285 | 0.236 | 0.322 | 0.329 | 0.453 | 0.231 | 0.473 | 0.216 | 0.405 | 0.504 | 0.504 |
| | Left Edge | 0.238 | 0.260 | 0.070 | 0.049 | 0.115 | 0.286 | 0.028 | 0.273 | 0.207 | 0.065 | 0.286 |
| | Right Edge | 0.202 | 0.199 | 0.038 | 0.035 | 0.044 | 0.202 | 0.037 | 0.211 | 0.191 | 0.104 | 0.211 |
| | Top Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | 0 |
| | Bottom Edge | 0.127 | 0.130 | 0.386 | 0.547 | 0.744 | 0.122 | 0.985 | 0.108 | 0.725 | 1.167 | 1.167 |

About BT and Main- Antenna

| SAR _{1g} (W/kg) | | Main-antenna | BT | MAX. ΣSAR _{1g} |
|--------------------------|-------------|--------------|-------|-------------------------|
| Test Position | | | | |
| Left Cheek | | 0.400 | 0.133 | 0.533 |
| Left Tilt | | 0.206 | 0.133 | 0.339 |
| Right Cheek | | 0.368 | 0.133 | 0.501 |
| Right Tilt | | 0.329 | 0.133 | 0.462 |
| Body worn | Back Side | 1.159 | 0.066 | 1.225 |
| | Front Side | 0.504 | 0.066 | 0.570 |
| Hotspot | Back Side | 1.159 | 0.066 | 1.225 |
| | Front Side | 0.504 | 0.066 | 0.570 |
| | Left Edge | 0.286 | 0.066 | 0.352 |
| | Right Edge | 0.211 | 0.066 | 0.277 |
| | Top Edge | 0 | 0.066 | 0.066 |
| | Bottom Edge | 1.167 | 0.066 | 1.233 |

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.
 2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 1.233 W/kg <1.6 W/kg and, so the Simultaneous transimition SAR with volum scan are not required for BT and Main-Antenna.

About Wi-Fi and Main- Antenna

| SAR _{1g} (W/kg) | | Main-antenna | Wi-Fi 2.4G | MAX. ΣSAR _{1g} |
|--------------------------|-------------|--------------|------------|-------------------------|
| Test Position | | | | |
| Left, Cheek | | 0.400 | 1.059 | 1.459 |
| Left, Tilt | | 0.206 | 0.811 | 1.017 |
| Right, Cheek | | 0.368 | 0.341 | 0.709 |
| Right, Tilt | | 0.329 | 0.388 | 0.717 |
| Body worn | Back Side | 1.159 | 0.206 | 1.365 |
| | Front Side | 0.504 | 0.248 | 0.752 |
| Hotspot | Back Side | 1.159 | 0.206 | 1.365 |
| | Front Side | 0.504 | 0.248 | 0.752 |
| | Left Edge | 0.286 | 0.040 | 0.326 |
| | Right Edge | 0.211 | 0.170 | 0.381 |
| | Top Edge | 0 | 0.216 | 0.216 |
| | Bottom Edge | 1.167 | N/A | 1.167 |

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.
 2. MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. ΣSAR_{1g} = 1.459 W/kg <1.6 W/kg, so the Simultaneous transimition SAR with volum scan are not required for Wi-Fi and Main-Antenna.




11 Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528- 2013 is not required in SAR reports submitted for equipment approval.

ANNEX A: Test Layout






Picture 3: Liquid depth in the head Phantom (835MHz, 15.3cm depth)



Picture 4: Liquid depth in the flat Phantom (835MHz, 15.4cm depth)




Picture 5: liquid depth in the head Phantom (1750 MHz, 15.3cm depth)



Picture 6: Liquid depth in the flat Phantom (1750 MHz, 15.2cm depth)




Picture 7: liquid depth in the head Phantom (1900 MHz, 15.3cm depth)



Picture 8: Liquid depth in the flat Phantom (1900 MHz, 15.2cm depth)



Picture 9: Liquid depth in the head Phantom (2450 MHz, 15.4cm depth)



Picture 10: Liquid depth in the flat Phantom (2450 MHz, 15.3cm depth)



Picture 11: Liquid depth in the head Phantom (2600 MHz, 15.4cm depth)



Picture 12: Liquid depth in the flat Phantom (2600 MHz, 15.3cm depth)

ANNEX B: System Check Results

Plot 1 System Performance Check at 835 MHz Head TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 8/29/2017

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 42.3$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: $22.3 \text{ }^\circ\text{C}$ Liquid Temperature: $21.5 \text{ }^\circ\text{C}$

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.31, 9.31, 9.31); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.64 mW/g


d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.4 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.44 mW/g; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.64 mW/g



Plot 2 System Performance Check at 835 MHz Body TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d020

Date: 9/5/2017

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.01 \text{ mho/m}$; $\epsilon_r = 55.4$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: $22.3 \text{ }^\circ\text{C}$ Liquid Temperature: $21.5 \text{ }^\circ\text{C}$

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=15mm, Pin=250mW/Area Scan (41x121x1): Measurement grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 2.58 mW/g


d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.9 V/m ; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 3.5 W/kg

SAR(1 g) = 2.41 mW/g ; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.6 mW/g



Plot 3 System Performance Check at 1750 MHz Head TSL**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1033**

Date: 8/30/2017

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.60, 8.60, 8.60); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (51x81x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.78 mW/g

d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,


dz=5mm

Reference Value = 80 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 15.5 W/kg

SAR(1 g) = 8.95 mW/g; SAR(10 g) = 4.5 mW/g

Maximum value of SAR (measured) = 9.46 mW/g



Plot 4 System Performance Check at 1750 MHz Body TSL**DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1033**

Date: 8/30/2017

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.7 °C

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (51x81x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 10.6 mW/g


d=10mm, Pin=250mW/Area Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 77.7 V/m; Power Drift = 0.097 dB

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 9.24 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.3 mW/g



Plot 5 System Performance Check at 1900 MHz Head TSL**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060**

Date: 8/29/2017

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 11.3 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 85.5 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.88 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.7 mW/g



Plot 6 System Performance Check at 1900 MHz Body TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d060

Date: 8/28/2017

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.98, 7.98, 7.98); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 12.2 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 82.3 V/m; Power Drift = 0.068 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.93 mW/g; SAR(10 g) = 5.25 mW/g

Maximum value of SAR (measured) = 11.3 mW/g



Plot 7 System Performance Check at 2450 MHz Head TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 8/30/2017

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.84$ mho/m; $\epsilon_r = 40.8$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 18.2 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.8 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 30 W/kg

SAR(1 g) = 13.7 mW/g; SAR(10 g) = 6.22 mW/g

Maximum value of SAR (measured) = 15.9 mW/g



Plot 8 System Performance Check at 2450 MHz Body TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 786

Date: 9/1/2017

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 51.4$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.85, 7.85, 7.85); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 16 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 81.2 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 25.4 W/kg

SAR(1 g) = 12.5 mW/g; SAR(10 g) = 6.20 mW/g

Maximum value of SAR (measured) = 14.4 mW/g



Plot 9 System Performance Check at 2600 MHz Head TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1025

Date: 8/31/2017

Communication System: CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.01$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.64, 7.64, 7.64); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 17.439 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.998 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 31.858 W/kg

SAR(1 g) = 13.9 mW/g; SAR(10 g) = 6.07 mW/g

Maximum value of SAR (measured) = 15.617 mW/g



Plot 10 System Performance Check at 2600 MHz Body TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1025

Date: 8/22/2017

Communication System: CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.08$ mho/m; $\epsilon_r = 51.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

d=10mm, Pin=250mW/Area Scan (41x71x1): Measurement grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 17.59 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.998 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 31.858 W/kg

SAR(1 g) = 13.88 mW/g; SAR(10 g) = 6.09 mW/g

Maximum value of SAR (measured) = 15.66 mW/g



ANNEX C: Highest Graph Results

Plot 11 GSM 850 Left Cheek Middle

Date: 8/29/2017

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 42.425$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.31, 9.31, 9.31); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.290 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.329 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.344 W/kg

SAR(1 g) = 0.276 W/kg; SAR(10 g) = 0.208 W/kg

Maximum value of SAR (measured) = 0.290 W/kg



Plot 12 GSM 850 Back Side Middle (Distance 10mm)

Date: 9/5/2017

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 1.013$ S/m; $\epsilon_r = 55.395$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.322 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.59 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.488 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.176 W/kg

Maximum value of SAR (measured) = 0.304 W/kg



Plot 13 GSM 850 GPRS (2Txslots) Back Side Middle (SIM 2, Distance 10mm)

Date: 9/5/2017

Communication System: UID 0, 2 slot GPRS (0); Frequency: 836.6 MHz; Duty Cycle: 1:4.14954

Medium parameters used: $f = 837$ MHz; $\sigma = 1.013$ S/m; $\epsilon_r = 55.395$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.353 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.52 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.417 W/kg

SAR(1 g) = 0.339 W/kg; SAR(10 g) = 0.264 W/kg

Maximum value of SAR (measured) = 0.353 W/kg



Plot 14 DTM 850 Left Cheek Middle

Date: 8/29/2017

Communication System: UID 0, 2 slot GPRS (0); Frequency: 836.6 MHz; Duty Cycle: 1:4.14954

Medium parameters used: $f = 837$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 42.425$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.31, 9.31, 9.31); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.320 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.206 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.381 W/kg

SAR(1 g) = 0.301 W/kg; SAR(10 g) = 0.225 W/kg

Maximum value of SAR (measured) = 0.314 W/kg



Plot 15 DTM 850 GSM&GPRS (2Txslots) Back Side Middle (Distance 10mm)

Date: 9/5/2017

Communication System: UID 0, 2 slot GPRS (0); Frequency: 836.6 MHz; Duty Cycle: 1:4.14954

Medium parameters used: $f = 837$ MHz; $\sigma = 1.013$ S/m; $\epsilon_r = 55.395$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.352 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.82 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.414 W/kg

SAR(1 g) = 0.337 W/kg; SAR(10 g) = 0.261 W/kg

Maximum value of SAR (measured) = 0.352 W/kg



Plot 16 GSM 1900 Right Cheek Middle (SIM 2)

Date: 8/29/2017

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.364$ S/m; $\epsilon_r = 40.415$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0729 W/kg


Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.868 V/m; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 0.0930 W/kg

SAR(1 g) = 0.064 W/kg; SAR(10 g) = 0.040 W/kg

Maximum value of SAR (measured) = 0.0672 W/kg



Plot 17 GSM 1900 Back Side Middle (Distance 10mm)

Date: 8/28/2017

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 51.207$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.98, 7.98, 7.98); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.289 W/kg


Front Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.922 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.246 W/kg; SAR(10 g) = 0.143 W/kg

Maximum value of SAR (measured) = 0.269 W/kg



Plot 18 GSM 1900 GPRS (4Txslots) Bottom Edge Middle (Distance 10mm)

Date: 8/28/2017

Communication System: UID 0, 4 slot GPRS (0); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 51.207$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.98, 7.98, 7.98); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Middle/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.429 W/kg


Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.81 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.596 W/kg

SAR(1 g) = 0.345 W/kg; SAR(10 g) = 0.181 W/kg

Maximum value of SAR (measured) = 0.383 W/kg



Plot 19 DTM 1900 Right Cheek Middle

Date: 8/29/2017

Communication System: UID 0, 2 slot GPRS (0); Frequency: 1880 MHz; Duty Cycle: 1:4.14954

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.364$ S/m; $\epsilon_r = 40.415$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0671 W/kg


Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.584 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.0900 W/kg

SAR(1 g) = 0.063 W/kg; SAR(10 g) = 0.040 W/kg

Maximum value of SAR (measured) = 0.0656 W/kg



Plot 20 DTM 1900 GSM&GPRS (2Txslots) Bottom Edge Middle (Distance 10mm)

Date: 8/28/2017

Communication System: UID 0, 2 slot GPRS (0); Frequency: 1880 MHz; Duty Cycle: 1:4.14954

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 51.207$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.98, 7.98, 7.98); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Middle/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.620 W/kg


Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.52 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 0.852 W/kg

SAR(1 g) = 0.502 W/kg; SAR(10 g) = 0.270 W/kg

Maximum value of SAR (measured) = 0.551 W/kg



Plot 21 UMTS Band II Left Cheek Middle (SIM 2)

Date: 8/29/2017

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.364$ S/m; $\epsilon_r = 40.415$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0999 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.022 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 0.142 W/kg

SAR(1 g) = 0.091 W/kg; SAR(10 g) = 0.056 W/kg

Maximum value of SAR (measured) = 0.0971 W/kg



Plot 22 UMTS Band II Bottom Edge Middle (Distance 10mm)

Date: 8/28/2017

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.49$ S/m; $\epsilon_r = 51.207$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.98, 7.98, 7.98); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Low/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.787 W/kg


Bottom Edge Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.61 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.641 W/kg; SAR(10 g) = 0.334 W/kg

Maximum value of SAR (measured) = 0.723 W/kg



Plot 23 UMTS Band V Left Cheek Middle

Date: 8/29/2017

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 42.425$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.31, 9.31, 9.31); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.331 W/kg


Left Cheek Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.627 V/m; Power Drift = 0.059 dB

Peak SAR (extrapolated) = 0.379 W/kg

SAR(1 g) = 0.308 W/kg; SAR(10 g) = 0.234 W/kg

Maximum value of SAR (measured) = 0.324 W/kg



Plot 24 UMTS Band V Back Side Middle (Distance 10mm)

Date: 9/5/2017

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 1.013$ S/m; $\epsilon_r = 55.395$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Middle/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.312 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.24 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.363 W/kg

SAR(1 g) = 0.297 W/kg; SAR(10 g) = 0.231 W/kg

Maximum value of SAR (measured) = 0.309 W/kg



Plot 25 LTE Band 4 1RB Right Cheek High

Date: 8/30/2017

Communication System: UID 0, LTE_FDD (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.362$ S/m; $\epsilon_r = 38.706$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.60, 8.60, 8.60); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0720 W/kg


Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.686 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.103 W/kg

SAR(1 g) = 0.068 W/kg; SAR(10 g) = 0.042 W/kg

Maximum value of SAR (measured) = 0.0744 W/kg



Plot 26 LTE Band 4 1RB Bottom Edge Low (Distance 10mm)

Date: 8/30/2017

Communication System: UID 0, LTE_FDD (0); Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1720$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 51.959$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.39, 8.39, 8.39); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Low/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.13 W/kg


Bottom Edge Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.71 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.846 W/kg; SAR(10 g) = 0.467 W/kg

Maximum value of SAR (measured) = 0.920 W/kg



Plot 27 LTE Band 5 1RB Right Cheek Low

Date: 8/29/2017

Communication System: UID 0, LTE_FDD (0); Frequency: 829 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 829$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 42.527$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.31, 9.31, 9.31); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek Low/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.320 W/kg


Right Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.618 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.391 W/kg

SAR(1 g) = 0.313 W/kg; SAR(10 g) = 0.231 W/kg

Maximum value of SAR (measured) = 0.328 W/kg



Plot 28 LTE Band 5 1RB Back Side Low (SIM 2, Distance 10mm)

Date: 9/5/2017

Communication System: UID 0, LTE_FDD (0); Frequency: 829 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 829$ MHz; $\sigma = 1.005$ S/m; $\epsilon_r = 55.487$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.74, 9.74, 9.74); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side Low/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.570 W/kg


Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.68 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.658 W/kg

SAR(1 g) = 0.542 W/kg; SAR(10 g) = 0.421 W/kg

Maximum value of SAR (measured) = 0.568 W/kg



Plot 29 LTE Band 7 1RB Right Cheek High

Date: 8/31/2017

Communication System: UID 0, LTE_FDD (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.983$ S/m; $\epsilon_r = 38.678$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.64, 7.64, 7.64); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Right Cheek High/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.135 W/kg


Right Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.138 V/m; Power Drift = 0.052 dB

Peak SAR (extrapolated) = 0.201 W/kg

SAR(1 g) = 0.104 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.113 W/kg



Plot 30 LTE Band 7 1RB Back Side High (Distance 10mm)

Date: 8/22/2017

Communication System: UID 0, LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.033$ S/m; $\epsilon_r = 51.206$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Back Side High/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.557 W/kg


Back Side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.943 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.523 W/kg; SAR(10 g) = 0.241 W/kg

Maximum value of SAR (measured) = 0.578 W/kg



Plot 31 LTE Band 38 1RB Left Cheek Low (SIM 2)

Date: 8/31/2017

Communication System: UID 0, LTE (0); Frequency: 2580 MHz; Duty Cycle: 1:1.57979

Medium parameters used: $f = 2580$ MHz; $\sigma = 1.988$ S/m; $\epsilon_r = 40.388$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.64, 7.64, 7.64); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek Low/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.203 W/kg


Left Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.144 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.082 W/kg

Maximum value of SAR (measured) = 0.175 W/kg



Plot 32 LTE Band 38 1RB Bottom Edge Low (Distance 10mm)

Date: 8/22/2017

Communication System: UID 0, LTE (0); Frequency: 2580 MHz; Duty Cycle: 1:1.57979

Medium parameters used: $f = 2580$ MHz; $\sigma = 2.112$ S/m; $\epsilon_r = 51.264$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.63, 7.63, 7.63); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 2; Type: SAM;

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Bottom Edge Low/Area Scan (51x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.04 W/kg


Bottom Edge Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.99 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 1.97 W/kg

SAR(1 g) = 0.991 W/kg; SAR(10 g) = 0.472 W/kg

Maximum value of SAR (measured) = 1.15 W/kg



Plot 33 802.11b Left Cheek High

Date: 8/30/2017

Communication System: UID 0, WiFi (0); Frequency: 2462 MHz; Duty Cycle: 1:1.0235

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.874$ S/m; $\epsilon_r = 39.037$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Left Cheek High/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.21 W/kg


Left Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.98 V/m; Power Drift = 0.059 dB

Peak SAR (extrapolated) = 2.07 W/kg

SAR(1 g) = 0.880 W/kg; SAR(10 g) = 0.431 W/kg

Maximum value of SAR (measured) = 0.987 W/kg



Plot 34 802.11b Front Side High (Distance 10mm)

Date: 9/1/2017

Communication System: UID 0, WiFi (0); Frequency: 2462 MHz; Duty Cycle: 1:1.0235

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.918$ S/m; $\epsilon_r = 51.42$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.85, 7.85, 7.85); Calibrated: 1/23/2017;

Electronics: DAE4 Sn1291; Calibrated: 1/19/2017

Phantom: SAM 1; Type: QD000P40CD; Serial: TP:1666

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Front Side High/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.246 W/kg


Front Side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.978 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 0.427 W/kg

SAR(1 g) = 0.214 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.231 W/kg





ANNEX D: Probe Calibration Certificate



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Client **TA(Shanghai)**

Certificate No: **Z17-97012**

CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3677**

Calibration Procedure(s): **FD-Z11-004-01
Calibration Procedures for Dosimetric E-field Probes**

Calibration date: **January 23, 2017**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|-------------------------|-------------|--|-----------------------|
| Power Meter NRP2 | 101919 | 27-Jun-16 (CTTL, No.J16X04777) | Jun-17 |
| Power sensor NRP-Z91 | 101547 | 27-Jun-16 (CTTL, No.J16X04777) | Jun-17 |
| Power sensor NRP-Z91 | 101548 | 27-Jun-16 (CTTL, No.J16X04777) | Jun-17 |
| Reference10dBAttenuator | 18N50W-10dB | 13-Mar-16(CTTL,No.J16X01547) | Mar-18 |
| Reference20dBAttenuator | 18N50W-20dB | 13-Mar-16(CTTL, No.J16X01548) | Mar-18 |
| Reference Probe EX3DV4 | SN 7433 | 26-Sep-16(SPEAG,No.EX3-7433_Sep16) | Sep-17 |
| DAE4 | SN 549 | 13-Dec-16(SPEAG, No.DAE4-549_Dec16) | Dec -17 |
| Secondary Standards | ID # | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
| SignalGeneratorMG3700A | 6201052605 | 27-Jun-16 (CTTL, No.J16X04776) | Jun-17 |
| Network Analyzer E5071C | MY46110673 | 26-Jan-16 (CTTL, No.J16X00894) | Jan -17 |

| | Name | Function | Signature |
|----------------|-------------|-----------------------------------|-----------|
| Calibrated by: | Yu Zongying | SAR Test Engineer | |
| Reviewed by: | Qi Dianyuan | SAR Project Leader | |
| Approved by: | Lu Bingsong | Deputy Director of the laboratory | |

Issued: January 24, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.