



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Tablet Computer
BRAND NAME : XIAOMI
MODEL NAME : 21051182G
FCC ID : 2AFZZ1182G
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Jun. 18, 2021 ~ Jul. 06, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	12
3.2 Maximum Conducted Output Power Measurement	15
3.3 Power Spectral Density Measurement	16
3.4 Unwanted Emissions Measurement.....	19
3.5 AC Conducted Emission Measurement.....	24
3.6 Antenna Requirements.....	26
4 LIST OF MEASURING EQUIPMENT	27
5 UNCERTAINTY OF EVALUATION	28
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR160318F	Rev. 01	Initial issue of report	Jul. 12, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 8.02 dB at 5643.200 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.96 dB at 0.283 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet Computer
Brand Name	XIAOMI
Model Name	21051182G
FCC ID	2AFZZ1182G
HW Version	P2
SW Version	MIUI 12.5
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification				
Tx/Rx Channel Frequency Range		5745 MHz ~ 5825 MHz		
Maximum Output Power		802.11a : 11.43 dBm / 0.0139 W 802.11n HT20 : 12.32 dBm / 0.0171 W 802.11n HT40 : 12.36 dBm / 0.0172 W 802.11ac VHT20: 12.42 dBm / 0.0175 W 802.11ac VHT40: 12.54 dBm / 0.0179 W 802.11ac VHT80: 12.50 dBm / 0.0178 W		
99% Occupied Bandwidth		802.11a : 17.53 MHz 802.11ac VHT20 : 18.68 MHz 802.11ac VHT40 : 36.56 MHz 802.11ac VHT80 : 75.52 MHz		
Type of Modulation		802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)		
Antenna Type / Gain		<Ant. 1> : IFA Antenna with gain -1.70 dBi <Ant. 2> : IFA Antenna with gain -4.04 dBi		
Antenna Function Description				
		Ant. 1	Ant. 2	
		802.11 a SISO	V	V
		802.11 n/ac MIMO	V	

Note:

1. For WLAN SISO & MIMO mode for 802.11n/ac mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power.
2. For 802.11n HT20/ac VHT20 and 802.11n HT40/ac VHT40 mode, the whole testing have assessed only 802.11ac VHT20/VHT40 by referring to the higher output power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH06-KS	AUDIX	E3	6.2009-8-24a1
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

SISO Mode

Modulation	Data Rate
802.11a	6 Mbps

MIMO Mode


Modulation	Data Rate
802.11a	6 Mbps
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter) + Keyboard + EUT Charger to Stylus for Sample 1
Remark: For Radiated Test Cases, The tests were pre-scanned with Adaptor/Earphone and Keyboard mode, the worst Adapter mode is reported.	


Ch. #		U-NII-3 : 5725-5850 MHz			
		802.11a	802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System

For AC Conducted Emission:



For Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Earphone	Xiaomi	N/A	N/A	Unshielded,1.2m	N/A
5.	Keyboard	N/A	N/A	N/A	N/A	N/A
6.	Stylus	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 7.2 dB.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\
 &= 7.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(NANT/NSS=1) dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
	Ant. 1	Ant. 2	DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	-1.70	-4.04	-1.70	0.22	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	Jul. 05, 2021~ Jul. 06, 2021	Oct. 31, 2021	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 07, 2021	Jul. 05, 2021~ Jul. 06, 2021	Jan. 06, 2022	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 07, 2021	Jul. 05, 2021~ Jul. 06, 2021	Jan. 06, 2022	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 04	3Hz~8.5GHz; Max 30dBm	Oct. 17, 2020	Jul. 03, 2021	Oct. 16, 2021	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 08	10Hz~44GHz	Apr. 12, 2021	Jul. 03, 2021	Apr. 11, 2022	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 01, 2020	Jul. 03, 2021	Oct. 31, 2021	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	May 28, 2021	Jul. 03, 2021	May 27, 2022	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 25, 2021	Jul. 03, 2021	Apr. 24, 2022	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2020	Jul. 03, 2021	Nov. 09, 2021	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Apr. 12, 2021	Jul. 03, 2021	Apr. 11, 2022	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GG A	060728	18~40GHz	Jan. 06, 2021	Jul. 03, 2021	Jan. 05, 2022	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Jan. 06, 2021	Jul. 03, 2021	Jan. 05, 2022	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY532702 03	500MHz~26.5GHz	Apr. 13, 2021	Jul. 03, 2021	Apr. 12, 2022	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Jul. 03, 2021	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jul. 03, 2021	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jul. 03, 2021	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 21, 2021	Jun. 18, 2021	Apr. 20, 2022	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 17, 2020	Jun. 18, 2021	Oct. 16, 2021	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Oct. 17, 2020	Jun. 18, 2021	Oct. 16, 2021	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 17, 2020	Jun. 18, 2021	Oct. 16, 2021	Conduction (CO01-KS)

NCR: No Calibration Required.

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Rise Liu/Long Wu	Temperature:	21~25	°C
Test Date:	2021/07/05~2021/7/6	Relative Humidity:	51~54	%
Tool & Version		Test Site		

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	17.53	-	23.83	-	15.35	-	0.5	Pass
11a	6Mbps	1	157	5785	17.53	-	23.78	-	14.65	-	0.5	Pass
11a	6Mbps	1	165	5825	17.53	-	23.33	-	15.10	-	0.5	Pass

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
VHT20	MCS0	2	149	5745	18.68	18.68	24.83	24.58	16.15	16.55	0.5	Pass
VHT20	MCS0	2	157	5785	18.68	18.68	25.13	25.13	17.30	16.50	0.5	Pass
VHT20	MCS0	2	165	5825	18.68	18.63	24.58	24.33	15.95	15.15	0.5	Pass
VHT40	MCS0	2	151	5755	36.36	36.36	41.72	41.81	35.37	35.19	0.5	Pass
VHT40	MCS0	2	159	5795	36.46	36.56	41.81	41.90	35.10	35.28	0.5	Pass
VHT80	MCS0	2	155	5775	75.52	75.52	82.96	83.12	75.20	75.20	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	11.42	5.86		30.00	30.00	-1.70	-4.04	Pass
11a	6Mbps	1	157	5785	11.43	5.92		30.00	30.00	-1.70	-4.04	Pass
11a	6Mbps	1	165	5825	11.34	5.56		30.00	30.00	-1.70	-4.04	Pass

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HT20	MCS0	2	149	5745	11.10	5.60	12.18	30.00		-1.70		Pass
HT20	MCS0	2	157	5785	11.30	5.54	12.32	30.00		-1.70		Pass
HT20	MCS0	2	165	5825	11.17	5.27	12.16	30.00		-1.70		Pass
HT40	MCS0	2	151	5755	11.21	5.78	12.31	30.00		-1.70		Pass
HT40	MCS0	2	159	5795	11.27	5.81	12.36	30.00		-1.70		Pass
VHT20	MCS0	2	149	5745	11.23	5.73	12.31	30.00		-1.70		Pass
VHT20	MCS0	2	157	5785	11.39	5.66	12.42	30.00		-1.70		Pass
VHT20	MCS0	2	165	5825	11.29	5.37	12.28	30.00		-1.70		Pass
VHT40	MCS0	2	151	5755	11.32	5.89	12.42	30.00		-1.70		Pass
VHT40	MCS0	2	159	5795	11.47	5.94	12.54	30.00		-1.70		Pass
VHT80	MCS0	2	155	5775	11.43	5.89	12.50	30.00		-1.70		Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	2.22	-	-2.39	-		30.00	30.00	-1.70	-4.04	Pass
11a	6Mbps	1	157	5785	2.22	-	-2.22	-		30.00	30.00	-1.70	-4.04	Pass
11a	6Mbps	1	165	5825	2.22	-	-2.46	-		30.00	30.00	-1.70	-4.04	Pass


U-NII-3 MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
VHT20	MCS0	2	149	5745	2.22		-2.29	-8.42	0.72	30.00		0.22		Pass
VHT20	MCS0	2	157	5785	2.22		-2.70	-8.57	0.31	30.00		0.22		Pass
VHT20	MCS0	2	165	5825	2.22		-2.51	-8.45	0.50	30.00		0.22		Pass
VHT40	MCS0	2	151	5755	2.22		-5.83	-11.42	-2.82	30.00		0.22		Pass
VHT40	MCS0	2	159	5795	2.22		-5.68	-10.98	-2.67	30.00		0.22		Pass
VHT80	MCS0	2	155	5775	2.22		-8.35	-13.54	-5.34	30.00		0.22		Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : FCC PART 15E TWO-LISN-CN02-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.164	48.28	-16.97	65.25	28.20	9.64	10.44	QP
2	0.164	33.38	-21.87	55.25	13.30	9.64	10.44	Average
3	0.223	43.79	-18.91	62.70	23.80	9.64	10.35	QP
4	0.223	26.89	-25.81	52.70	6.90	9.64	10.35	Average
5 *	0.283	43.76	-16.96	60.72	23.80	9.64	10.32	QP
6	0.283	30.16	-20.56	50.72	10.20	9.64	10.32	Average
7	0.459	36.99	-19.72	56.71	17.09	9.65	10.25	QP
8	0.459	26.49	-20.22	46.71	6.59	9.65	10.25	Average
9	15.388	38.83	-21.17	60.00	17.51	10.92	10.40	QP
10	15.388	29.93	-20.07	50.00	8.61	10.92	10.40	Average
11	16.312	39.60	-20.40	60.00	18.21	10.97	10.42	QP
12	16.312	30.70	-19.30	50.00	9.31	10.97	10.42	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E TWO-LISN-CN02-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.165	44.77	-20.44	65.21	24.50	9.83	10.44	QP
2	0.165	30.57	-24.64	55.21	10.30	9.83	10.44	Average
3	0.223	41.41	-21.29	62.70	21.20	9.86	10.35	QP
4	0.223	25.81	-26.89	52.70	5.60	9.86	10.35	Average
5	0.345	35.66	-23.53	59.09	15.50	9.77	10.29	QP
6	0.345	22.66	-26.43	49.09	2.60	9.77	10.29	Average
7	2.854	32.49	-23.51	56.00	12.20	10.05	10.24	QP
8	2.854	23.49	-22.51	46.00	3.20	10.05	10.24	Average
9	14.828	35.93	-24.07	60.00	14.51	11.03	10.39	QP
10	14.828	28.53	-21.47	50.00	7.11	11.03	10.39	Average
11	16.398	34.90	-25.10	60.00	13.30	11.17	10.43	QP
12	16.398	27.80	-22.20	50.00	6.20	11.17	10.43	Average

Note:

1. Level(dBuV) = Read Level(dBuV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBuV) – Limit Line(dBuV)



Appendix C. Radiated Spurious Emission

SISO <Ant.1>

UNII 3 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5633.2	56.85	-11.45	68.3	41.38	35.59	12.54	32.66	100	217	P	H
		5698	56.31	-47.52	103.83	40.74	35.67	12.6	32.7	100	217	P	H
		5719.6	61.3	-49.49	110.79	45.67	35.7	12.65	32.72	100	217	P	H
		5724	63.51	-56.51	120.02	47.86	35.72	12.65	32.72	100	217	P	H
		5746	105.68	-	-	89.99	35.75	12.67	32.73	100	217	P	H
		5746	98.27	-	-	82.58	35.75	12.67	32.73	100	217	A	H
		5649.2	55.46	-12.84	68.3	40.19	35.4	12.54	32.67	286	105	P	V
		5678.8	56.47	-33.18	89.65	41.21	35.37	12.58	32.69	286	105	P	V
		5719.6	60.76	-50.03	110.79	45.51	35.32	12.65	32.72	286	105	P	V
		5724.8	64.68	-57.16	121.84	49.43	35.32	12.65	32.72	286	105	P	V
		5746	106.57	-	-	91.32	35.31	12.67	32.73	286	105	P	V
		5746	100.02	-	-	84.77	35.31	12.67	32.73	286	105	A	V



WIFI Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5850.8	57.44	-63.04	120.48	41.56	35.9	12.79	32.81	100	218	P	H
		5856	57.7	-52.92	110.62	41.8	35.9	12.81	32.81	100	218	P	H
		5875.6	57.38	-47.47	104.85	41.48	35.9	12.82	32.82	100	218	P	H
		5982.8	57.71	-10.59	68.3	41.79	35.88	12.92	32.88	100	218	P	H
		5824	103.8	-	-	87.97	35.85	12.77	32.79	100	218	P	H
		5824	96.72	-	-	80.89	35.85	12.77	32.79	100	218	A	H
		5850.8	58.83	-61.65	120.48	43.63	35.22	12.79	32.81	250	107	P	V
		5869.2	57.5	-49.42	106.92	42.3	35.2	12.81	32.81	250	107	P	V
		5921.6	56.8	-14.01	70.81	41.56	35.22	12.87	32.85	250	107	P	V
		5925.6	56.33	-11.97	68.3	41.09	35.22	12.87	32.85	250	107	P	V
		5824	108.08	-	-	92.87	35.23	12.77	32.79	250	107	P	V
		5824	100.25	-	-	85.04	35.23	12.77	32.79	250	107	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 3 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149		11489.48	45.97	-28.03	74	48.27	39.19	19	60.49	300	0	P	H
5745MHz		11489.48	47.12	-26.88	74	50.02	38.59	19	60.49	100	360	P	V
802.11a CH 157		11569.56	46.64	-27.36	74	48.68	39.42	19.07	60.53	300	0	P	H
5785MHz		11569.56	45.54	-28.46	74	48.32	38.68	19.07	60.53	100	360	P	V
802.11a CH 165		11649.64	46.19	-27.81	74	48	39.64	19.12	60.57	300	0	P	H
5825MHz		11649.64	46.24	-27.76	74	48.92	38.77	19.12	60.57	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 3 5725~5850MHz

Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
0		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a LF		31.94	20.41	-19.59	40	28.28	24.22	0.61	32.7	-	-	P	H
		157.07	20.85	-22.65	43.5	34.69	16.98	2.02	32.84	-	-	P	H
		270.56	17.87	-28.13	46	29.4	18.83	2.66	33.02	-	-	P	H
		595.51	23.68	-22.32	46	26.4	25.82	3.97	32.51	-	-	P	H
		873.9	27.4	-18.6	46	25.89	29.24	4.82	32.55	-	-	P	H
		935.98	28.85	-17.15	46	26.42	29.8	4.98	32.35	185	74	P	H
		46.49	31.44	-8.56	40	47.41	16.13	0.83	32.93	147	256	P	V
		87.23	21.65	-18.35	40	38.56	14.37	1.44	32.72	-	-	P	V
		192.96	16.8	-26.7	43.5	32.29	15.32	2.25	33.06	-	-	P	V
		309.36	24.03	-21.97	46	34.55	19.53	2.85	32.9	-	-	P	V
		421.88	22.63	-23.37	46	29.62	22.43	3.34	32.76	-	-	P	V
		771.08	26.53	-19.47	46	26.29	28.34	4.52	32.62	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



SISO <Ant.2>

UNII 3- 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5644.8	56.4	-11.9	68.3	40.93	35.6	12.54	32.67	100	112	P	H
		5684	58.3	-35.2	93.5	42.75	35.65	12.6	32.7	100	112	P	H
		5719.2	62.29	-48.39	110.68	46.66	35.7	12.65	32.72	100	112	P	H
		5724.8	69.61	-52.23	121.84	53.96	35.72	12.65	32.72	100	112	P	H
		5746	110.96	-	-	95.27	35.75	12.67	32.73	100	112	P	H
		5746	103.05	-	-	87.36	35.75	12.67	32.73	100	112	A	H
		5638	55.91	-12.39	68.3	40.64	35.4	12.54	32.67	283	95	P	V
		5693.6	56.57	-44.01	100.58	41.32	35.35	12.6	32.7	283	95	P	V
		5717.2	60.03	-50.09	110.12	44.78	35.34	12.63	32.72	283	95	P	V
		5724.4	67.53	-53.4	120.93	52.28	35.32	12.65	32.72	283	95	P	V
		5746	108.81	-	-	93.56	35.31	12.67	32.73	283	95	P	V
		5746	101.06	-	-	85.81	35.31	12.67	32.73	283	95	A	V



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5852.4	59.32	-57.51	116.83	43.44	35.9	12.79	32.81	100	113	P	H
		5874.4	58.57	-46.9	105.47	42.67	35.9	12.82	32.82	100	113	P	H
		5875.1	58.2	-47.03	105.23	55.12	35.9	12.82	32.82	100	113	P	H
		5981.2	58.68	-9.62	68.3	42.76	35.88	12.92	32.88	100	113	P	H
		5824	110.34	-	-	94.51	35.85	12.77	32.79	100	113	P	H
		5824	102.45	-	-	86.62	35.85	12.77	32.79	100	113	A	H
		5852.4	59.32	-57.51	116.83	41.72	35.9	14.51	32.81	100	113	P	V
		5874.4	58.57	-46.9	105.47	40.93	35.9	14.56	32.82	100	113	P	V
		5875.1	58.2	-47.03	105.23	40.56	35.9	14.56	32.82	100	113	P	V
		5981.2	58.68	-9.62	68.3	41	35.88	14.68	32.88	100	113	P	V
		5830	107.9	-	-	92.69	35.23	12.77	32.79	273	92	P	V
		5830	100.57	-	-	85.36	35.23	12.77	32.79	273	92	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149		11489.48	49.58	-24.42	74	51.88	39.19	19	60.49	300	0	P	H
5745MHz		11489.48	56.42	-17.58	74	59.32	38.59	19	60.49	100	226	P	V
802.11a CH 157		11569.56	51.51	-22.49	74	53.55	39.42	19.07	60.53	300	0	P	H
5785MHz		11569.56	56.6	-17.4	74	59.38	38.68	19.07	60.53	100	194	P	V
802.11a CH 165		11649.64	50.97	-23.03	74	52.78	39.64	19.12	60.57	300	0	P	H
5825MHz		11654.65	55.72	-18.28	74	58.37	38.79	19.14	60.58	100	194	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a LF		32.91	18.14	-21.86	40	26.54	23.68	0.62	32.7	-	-	P	H
		32.91	18.14	-21.86	40	26.54	23.68	0.62	32.7	-	-	P	H
		128.94	16.09	-27.41	43.5	30.31	16.79	1.83	32.84	-	-	P	H
		157.07	19.11	-24.39	43.5	32.95	16.98	2.02	32.84	-	-	P	H
		224.97	17.99	-28.01	46	31.92	16.75	2.42	33.1	-	-	P	H
		313.24	27.34	-18.66	46	37.75	19.62	2.87	32.9	313	258	P	H
		30	19.04	-20.96	40	25.86	25.3	0.58	32.7	-	-	P	V
		96.93	14.51	-28.99	43.5	30.02	15.68	1.59	32.78	-	-	P	V
		264.74	16.16	-29.84	46	27.83	18.74	2.63	33.04	-	-	P	V
		459.71	20.78	-25.22	46	26.72	23.29	3.49	32.72	-	-	P	V
		614.91	24.65	-21.35	46	27.03	26.14	4.04	32.56	-	-	P	V
		911.73	28.87	-17.13	46	26.87	29.53	4.92	32.45	185	346	P	V
Remark	3. No other spurious found. 4. All results are PASS against limit line.												



MIMO <Ant.1+2>

UNII 3- 5725~5850MHz

WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT20 CH 149 5745MHz		5601.6	56.16	-12.14	68.3	40.74	35.57	12.49	32.64	104	266	P	H
		5698	57.78	-46.05	103.83	42.21	35.67	12.6	32.7	104	266	P	H
		5720	61.47	-49.43	110.9	45.84	35.7	12.65	32.72	104	266	P	H
		5721.2	66.76	-46.88	113.64	51.13	35.7	12.65	32.72	104	266	P	H
		5746	109.7	-12.6	122.3	94.01	35.75	12.67	32.73	104	266	P	H
		5746	102.25	-	-	86.56	35.75	12.67	32.73	104	266	A	H
		5617.6	56.04	-12.26	68.3	40.81	35.38	12.51	32.66	274	95	P	V
		5679.2	57.07	-32.88	89.95	41.81	35.37	12.58	32.69	274	95	P	V
		5720	63.51	-47.39	110.9	48.26	35.32	12.65	32.72	274	95	P	V
		5724	69.89	-50.13	120.02	54.64	35.32	12.65	32.72	274	95	P	V
		5746	111.35	-10.95	122.3	96.1	35.31	12.67	32.73	274	95	P	V
		5746	103.58	-	-	88.33	35.31	12.67	32.73	274	95	A	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz		5850	60.5	-61.8	122.3	44.62	35.9	12.79	32.81	111	325	P	H
		5867.6	57.71	-49.66	107.37	41.81	35.9	12.81	32.81	111	325	P	H
		5883.2	57.43	-41.78	99.21	41.53	35.9	12.82	32.82	111	325	P	H
		5971.2	57.66	-10.64	68.3	41.74	35.89	12.91	32.88	111	325	P	H
		5824	109.56	-	-	93.73	35.85	12.77	32.79	111	325	P	H
		5824	102.22	-	-	86.39	35.85	12.77	32.79	111	325	A	H
		5850	61.5	-60.8	122.3	46.3	35.22	12.79	32.81	276	106	P	V
		5870	56.83	-49.87	106.7	41.64	35.2	12.81	32.82	276	106	P	V
		5898.8	56.52	-31.13	87.65	41.31	35.21	12.84	32.84	276	106	P	V
		5947.6	56.42	-11.88	68.3	41.18	35.22	12.89	32.87	276	106	P	V
		5826	110.16	-	-	94.95	35.23	12.77	32.79	276	106	P	V
		5826	102.39	-	-	87.18	35.23	12.77	32.79	276	106	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20		11490	49.92	-24.08	74	52.22	39.19	19	60.49	300	0	P	H
CH 149 5745MHz		11490	56.87	-17.13	74	59.77	38.59	19	60.49	100	360	P	V
802.11ac VHT20		11570	48.66	-25.34	74	50.7	39.42	19.07	60.53	300	0	P	H
CH 157 5785MHz		11570	57.08	-16.92	74	59.86	38.68	19.07	60.53	100	226	P	V
802.11ac VHT20		11650	47.95	-26.05	74	49.76	39.64	19.12	60.57	300	0	P	H
CH 165 5825MHz		11650	56.28	-17.72	74	58.96	38.77	19.12	60.57	100	219	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5625.6	55.93	-12.37	68.3	40.49	35.59	12.51	32.66	101	328	P	H
		5694.8	57.31	-44.16	101.47	41.74	35.67	12.6	32.7	101	328	P	H
		5719.6	68.01	-42.78	110.79	52.38	35.7	12.65	32.72	101	328	P	H
		5724.4	68.48	-52.45	120.93	52.83	35.72	12.65	32.72	101	328	P	H
		5854	55.35	-57.83	113.18	39.45	35.9	12.81	32.81	101	328	P	H
		5862.4	56.05	-52.78	108.83	40.15	35.9	12.81	32.81	101	328	P	H
		5922.4	56.12	-14.1	70.22	40.21	35.89	12.87	32.85	101	328	P	H
		5958.8	55.9	-12.4	68.3	39.97	35.89	12.91	32.87	101	328	P	H
		5758	105.66	-	-	89.94	35.78	12.69	32.75	101	328	P	H
		5758	97.72	-	-	82	35.78	12.69	32.75	101	328	A	H
		5642	55.16	-13.14	68.3	39.89	35.4	12.54	32.67	312	106	P	V
		5670	56.24	-26.9	83.14	40.98	35.37	12.58	32.69	312	106	P	V
		5716.4	66.26	-43.63	109.89	51.01	35.34	12.63	32.72	312	106	P	V
		5720.4	65.27	-46.54	111.81	50.02	35.32	12.65	32.72	312	106	P	V
		5850.1	55.76	-66.31	122.07	38.84	35.22	14.51	32.81	312	106	P	V
		5856.8	55.76	-54.64	110.4	38.84	35.2	14.53	32.81	312	106	P	V
		5884	56.08	-42.54	98.62	39.14	35.2	14.56	32.82	312	106	P	V
		5995.6	55.3	-13	68.3	38.27	35.23	14.7	32.9	312	106	P	V
		5758	106.46	-	-	91.23	35.29	12.69	32.75	312	106	P	V
		5758	86.86	-	-	84.32	35.29	0	32.75	312	106	A	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 159 5795MHz		5649.6	55.71	-12.59	68.3	40.22	35.6	12.56	32.67	101	328	P	H
		5685.6	55.69	-38.99	94.68	40.14	35.65	12.6	32.7	101	328	P	H
		5707.2	55.74	-51.58	107.32	40.13	35.7	12.63	32.72	101	328	P	H
		5722.8	55.84	-61.44	117.28	40.19	35.72	12.65	32.72	101	328	P	H
		5854.8	58.01	-53.35	111.36	42.11	35.9	12.81	32.81	101	328	P	H
		5856.8	58.01	-52.39	110.4	42.11	35.9	12.81	32.81	101	328	P	H
		5916.8	57.2	-17.15	74.35	41.3	35.89	12.86	32.85	101	328	P	H
		5963.2	57.61	-10.69	68.3	41.68	35.89	12.91	32.87	101	328	P	H
		5794	104.95	-	-	89.14	35.83	12.74	32.76	101	328	P	H
		5794	95.6	-	-	79.79	35.83	12.74	32.76	101	328	A	H
		5647.6	55.86	-12.44	68.3	40.59	35.4	12.54	32.67	299	89	P	V
		5692	55.42	-43.98	99.4	40.17	35.35	12.6	32.7	299	89	P	V
		5709.6	55.68	-52.31	107.99	40.43	35.34	12.63	32.72	299	89	P	V
		5720.4	55.51	-56.3	111.81	40.26	35.32	12.65	32.72	299	89	P	V
		5850	54.84	-67.46	122.3	39.64	35.22	12.79	32.81	299	89	P	V
		5864.4	58.31	-49.96	108.27	43.11	35.2	12.81	32.81	299	89	P	V
		5884	56.53	-42.09	98.62	41.33	35.2	12.82	32.82	299	89	P	V
		5935.6	56.45	-11.85	68.3	41.21	35.22	12.87	32.85	299	89	P	V
		5788	106.29	-	-	91.05	35.26	12.74	32.76	299	89	P	V
		5788	98.44	-	-	83.2	35.26	12.74	32.76	299	89	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40		11510	46.29	-27.71	74	48.57	39.2	19.01	60.49	300	0	P	H
CH 151 5755MHz		11510	49.23	-24.77	74	52.11	38.6	19.01	60.49	100	360	P	V
802.11ac VHT40		11590	46.03	-27.97	74	48.01	39.48	19.08	60.54	300	0	P	H
CH 159 5795MHz		11590	47.66	-26.34	74	50.42	38.7	19.08	60.54	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5646	59.27	-9.03	68.3	43.8	35.6	12.54	32.67	127	324	P	H
		5696.4	65.23	-37.42	102.65	49.66	35.67	12.6	32.7	127	324	P	H
		5713.2	65.88	-43.12	109	50.27	35.7	12.63	32.72	127	324	P	H
		5720.4	65.36	-46.45	111.81	49.73	35.7	12.65	32.72	127	324	P	H
		5850.8	64.15	-56.33	120.48	48.27	35.9	12.79	32.81	127	324	P	H
		5857.2	63.6	-46.68	110.28	47.7	35.9	12.81	32.81	127	324	P	H
		5886.8	58.98	-37.56	96.54	43.08	35.9	12.82	32.82	127	324	P	H
		5927.6	57.36	-10.94	68.3	41.45	35.89	12.87	32.85	127	324	P	H
		5776	100.28	-	-	84.52	35.8	12.72	32.76	127	324	P	H
		5776	91.95	-	-	76.19	35.8	12.72	32.76	127	324	A	H
		5643.2	60.28	-8.02	68.3	45.01	35.4	12.54	32.67	295	104	P	V
		5695.6	64.19	-37.87	102.06	48.94	35.35	12.6	32.7	295	104	P	V
		5720	64.88	-46.02	110.9	49.63	35.32	12.65	32.72	295	104	P	V
		5724	65.46	-54.56	120.02	50.21	35.32	12.65	32.72	295	104	P	V
		5851.2	64.05	-55.51	119.56	48.85	35.22	12.79	32.81	295	104	P	V
		5872.8	60.5	-45.42	105.92	45.3	35.2	12.82	32.82	295	104	P	V
		5881.6	60.96	-39.44	100.4	45.76	35.2	12.82	32.82	295	104	P	V
		5961.2	56.33	-11.97	68.3	41.07	35.22	12.91	32.87	295	104	P	V
		5782	101.64	-	-	86.4	35.28	12.72	32.76	295	104	P	V
		5782	91.88	-	-	76.64	35.28	12.72	32.76	295	104	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**UNII 35725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11550	46.49	-27.51	74	48.65	39.31	19.05	60.52	300	0	P	H
CH 155 5775MHz		11550	45.04	-28.96	74	47.85	38.66	19.05	60.52	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



UNII 35725~5850MHz

Emission below 1GHz

5GHz WIFI 802.11ac VHT80 (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11ac VHT80 LF		31.94	19.41	-20.59	40	27.28	24.22	0.61	32.7	-	-	P	H
		128.94	16.02	-27.48	43.5	30.24	16.79	1.83	32.84	-	-	P	H
		157.07	17.85	-25.65	43.5	31.69	16.98	2.02	32.84	-	-	P	H
		186.17	16.7	-26.8	43.5	31.88	15.63	2.21	33.02	-	-	P	H
		270.56	16.87	-29.13	46	28.4	18.83	2.66	33.02	-	-	P	H
		881.66	27.95	-18.05	46	26.36	29.29	4.84	32.54	341	256	P	H
		30	19.04	-20.96	40	25.86	25.3	0.58	32.7	342	158	P	V
		96.93	14.51	-28.99	43.5	30.02	15.68	1.59	32.78	-	-	P	V
		157.07	13.7	-29.8	43.5	27.54	16.98	2.02	32.84	-	-	P	V
		264.74	16.16	-29.84	46	27.83	18.74	2.63	33.04	-	-	P	V
		485.9	21.14	-24.86	46	26.52	23.81	3.58	32.77	-	-	P	V
		614.91	24.65	-21.35	46	27.03	26.14	4.04	32.56	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
1	802.11a	98.28	-	-	10Hz
2	802.11a	98.28	-	-	10Hz
1+2	802.11ac VHT20	98.16	-	-	10Hz
1+2	802.11ac VHT40	96.35	0.957	1.045	1.1KHz
1+2	802.11ac VHT80	92.20	0.462	2.163	2.2KHz



802.11a Ant 1




802.11a Ant 2




<MIMO Ant.1+2>

802.11ac VHT20



802.11ac VHT40



802.11ac VHT80

