



# FCC Test Report

APPLICANT : Xiaomi Communications Co., Ltd.  
EQUIPMENT : Mobile Phone  
BRAND NAME : POCO  
MODEL NAME : 22041216G  
FCC ID : 2AFZZ1216  
STANDARD : 47 CFR Part 15 Subpart B  
CLASSIFICATION : Certification  
TEST DATE(S) : May 06, 2022 ~ May 07, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 7

    1.6. Test Location ..... 7

    1.7. Test Software ..... 8

    1.8. Applicable Standards ..... 8

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1. Test Mode ..... 9

    2.2. Connection Diagram of Test System ..... 10

    2.3. Support Unit used in test configuration and system ..... 11

    2.4. EUT Operation Test Setup ..... 12

**3. TEST RESULT ..... 13**

    3.1. Test of AC Conducted Emission Measurement ..... 13

    3.2. Test of Radiated Emission Measurement ..... 17

**4. LIST OF MEASURING EQUIPMENT ..... 22**

**5. UNCERTAINTY OF EVALUATION ..... 23**

**APPENDIX A. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 6.06 dB at 0.151 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 8.22 dB at 46.490 MHz

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1. General Description

## 1.1. Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2. Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	POCO
Model Name	22041216G
FCC ID	2AFZZ1216
EUT supports Radios application	GSM/WCDMA/LTE/5G NR/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 2.4GHz 802.11ax HE20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 WLAN 5GHz 802.11ax HE20/HE40/HE80 Bluetooth BR/EDR/LE GNSS/FM Receiver
IMEI Code	Conduction: 861508060020732/861508060020778 Radiation: 861508060020732/861508060020778 for Sample 1 861508060033776/861508060033784 for Sample 2
HW Version	P2
SW Version	MIUI13
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT. The different between them refer to the 22041216G\_Operational Description of Product Equality Declaration which is exhibit separately. For sample 1(8+256G) and sample 2(8+128G), the different is memory capacity, according to the difference, we choose sample 1 perform full test and sample 2 verify the worst case.





<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna NFC: Coil Antenna FM : External Earphone Antenna
<b>Type of Modulation</b>	GSM/GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM / 256QAM 5G NR: DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac/ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK FM

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH07-KS	CN1257	314309



### 1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	6.2009-8-24
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle + WLAN Idle + Camera(Rear) + Earphone + Battery + USB Cable 1(Charging from Adapter) + ANT 1 + SIM 1 for Sample 1
	Mode 2: WCDMA Band V Rx(Low) + Bluetooth Idle + WLAN Idle+Camera(Front) + Earphone + Battery + USB Cable 1(EUT (eMMC) USB Data Link to NB) + ANT 0 + SIM 2 for Sample 1
	Mode 3: LTE Band 5 Rx(Low) + Bluetooth Idle + WLAN Idle + MPEG4(Run Color Bar) + Earphone + Battery + USB Cable 1(NB USB Data Link to EUT (eMMC)) + ANT 0 + SIM 1 for Sample 1
	Mode 4: n5 Rx(High) + Bluetooth Idle + WLAN Idle + GNSS Rx + NFC On + FM(98MHz)Rx + Earphone + Battery + USB Cable 1(EUT (eMMC) USB Data Link to NB) + ANT 1 + SIM 2 for Sample 1
	Mode 5: WCDMA Band V Rx(Low) + Bluetooth Idle + WLAN Idle+Camera(Front) + Earphone + Battery + USB Cable 2(EUT (eMMC) USB Data Link to NB) + ANT 0 + SIM 2 for Sample 1
Radiated Emissions	Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle + WLAN Idle + Camera(Rear) + Earphone + Battery + USB Cable 1(Charging from Adapter) + ANT 1 + SIM 1 for Sample 1
	Mode 2: WCDMA Band V Rx(Low) + Bluetooth Idle + WLAN Idle+Camera(Front) + Earphone + Battery + USB Cable 1(EUT (eMMC) USB Data Link to NB) + ANT 0 + SIM 2 for Sample 1
	Mode 3: LTE Band 5 Rx(Low) + Bluetooth Idle + WLAN Idle + MPEG4(Run Color Bar) + Earphone + Battery + USB Cable 1(NB USB Data Link to EUT (eMMC)) + ANT 0 + SIM 1 for Sample 1
	Mode 4: n5 Rx(High) + Bluetooth Idle + WLAN Idle + GNSS Rx + NFC On + FM(88MHz)Rx + Earphone + Battery + USB Cable 1(Charging from Adapter) + ANT 1 + SIM 2 for Sample 1
	Mode 5: WCDMA Band V Rx(Low) + Bluetooth Idle + WLAN Idle+Camera(Front) + Earphone + Battery + USB Cable 1(EUT (eMMC) USB Data Link to NB) + ANT 0 + SIM 2 for Sample 2
	Mode 6: LTE Band 5 Rx(Low) + Bluetooth Link + WLAN (2.4G) Link + Camera(Rear) + Earphone + Battery + USB Cable 2(Charging from Adapter) + ANT 0 + SIM 1 for Sample 1
	Mode 7: LTE Band 5 Rx(Low) + Bluetooth Link + WLAN (5G Band IV) Link + MPEG4(Run Color Bar) + Earphone + Battery + USB Cable 2(EUT

	(eMMC) USB Data Link to NB) + ANT 0 + SIM 1 for Sample 1
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. The worst case of AC is mode 1; only the test data of this mode is reported.</li> <li>2. The worst case of RE is mode 6; only the test data of this mode is reported.</li> <li>3. Data Link with Notebook means data application transferred mode between EUT and Notebook</li> <li>4. Pre-scanned Low/Middle/High channel for all frequency bands which operate within the frequency range of 30MHz ~ 960MHz, only the worst channel was recorded in this report.</li> </ol>	

## 2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application



### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	5G NR Base Station	Anritus	MT8000A	N/A	N/A	Unshielded,1.8m
3.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
4.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
5.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
6.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
7.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
8.	Notebook	Lenovo	S730-13IWL	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
9.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
10.	SD Card	Kingston	8GB	N/A	N/A	N/A
11.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
12.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
13.	Earphone	Xiaomi	N/A	N/A	N/A	N/A



## **2.4. EUT Operation Test Setup**

The EUT was in GSM or WCDMA or LTE or 5G NR idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
5. Turn on NFC function
6. Turn on FM function



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-060105-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.151	59.90	-6.06	65.96	49.40	0.02	10.48	QP
2	0.151	40.40	-15.56	55.96	29.90	0.02	10.48	Average
3	0.242	48.19	-13.85	62.04	37.80	0.05	10.34	QP
4	0.242	30.99	-21.05	52.04	20.60	0.05	10.34	Average
5	0.327	48.57	-10.96	59.53	38.20	0.08	10.29	QP
6	0.327	31.57	-17.96	49.53	21.20	0.08	10.29	Average
7	0.383	43.86	-14.35	58.21	33.51	0.08	10.27	QP
8	0.383	25.56	-22.65	48.21	15.21	0.08	10.27	Average
9	1.441	43.57	-12.43	56.00	33.20	0.14	10.23	QP
10	1.441	32.67	-13.33	46.00	22.30	0.14	10.23	Average
11	1.918	42.57	-13.43	56.00	32.20	0.14	10.23	QP
12	1.918	32.67	-13.33	46.00	22.30	0.14	10.23	Average
13	2.779	44.19	-11.81	56.00	33.80	0.15	10.24	QP
14	2.779	36.29	-9.71	46.00	25.90	0.15	10.24	Average
15	3.310	41.60	-14.40	56.00	31.19	0.16	10.25	QP
16	3.310	33.00	-13.00	46.00	22.59	0.16	10.25	Average
17	4.202	42.63	-13.37	56.00	32.20	0.17	10.26	QP
18	4.202	34.03	-11.97	46.00	23.60	0.17	10.26	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS  
 Condition : FCC CLASS-B LISN-060105-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.151	55.09	-10.87	65.96	44.50	0.11	10.48	QP
2	0.151	38.79	-17.17	55.96	28.20	0.11	10.48	Average
3	0.161	53.86	-11.57	65.43	43.30	0.11	10.45	QP
4	0.161	34.66	-20.77	55.43	24.10	0.11	10.45	Average
5	0.332	38.89	-20.51	59.40	28.50	0.10	10.29	QP
6	0.332	23.69	-25.71	49.40	13.30	0.10	10.29	Average
7	1.197	43.26	-12.74	56.00	32.90	0.13	10.23	QP
8	1.197	30.56	-15.44	46.00	20.20	0.13	10.23	Average
9	1.511	42.86	-13.14	56.00	32.50	0.13	10.23	QP
10	1.511	31.56	-14.44	46.00	21.20	0.13	10.23	Average
11	1.908	42.57	-13.43	56.00	32.20	0.14	10.23	QP
12	1.908	32.17	-13.83	46.00	21.80	0.14	10.23	Average
13	2.487	44.18	-11.82	56.00	33.80	0.15	10.23	QP
14 *	2.487	35.68	-10.32	46.00	25.30	0.15	10.23	Average
15	2.884	43.89	-12.11	56.00	33.50	0.15	10.24	QP
16	2.884	34.29	-11.71	46.00	23.90	0.15	10.24	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### **3.2.3. Test Procedures**


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Feng Wang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#5 is system simulator signal which can be ignored.		




Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m CBL 6111D 59913 HORIZONTAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	102.750	26.94	-16.56	43.50	41.75	16.10	1.49	32.40	---	---	Peak
2	168.710	28.77	-14.73	43.50	43.88	15.40	1.89	32.40	---	---	Peak
3	332.640	30.59	-15.41	46.00	40.58	19.72	2.69	32.40	---	---	Peak
4	428.670	28.23	-17.77	46.00	34.95	22.60	3.08	32.40	---	---	Peak
5	870.990	37.62			35.87	29.12	4.36	31.73	---	---	Peak
6	896.210	30.64	-15.36	46.00	28.80	28.90	4.47	31.53	---	---	Peak
7	957.320	31.56	-14.44	46.00	26.87	31.10	4.60	31.01	---	---	Peak
8	2207.000	42.00	-32.00	74.00	66.58	31.20	7.06	62.84	---	---	Peak
9	5760.000	44.03	-29.97	74.00	60.75	35.29	11.73	63.74	---	---	Peak
10	7715.000	44.64	-29.36	74.00	57.33	36.63	13.85	63.17	---	---	Peak
11	11132.000	44.83	-29.17	74.00	51.29	38.33	16.74	61.53	---	---	Peak
12	14770.000	46.04	-27.96	74.00	51.14	39.06	19.36	63.52	---	---	Peak
13	17456.000	47.01	-26.99	74.00	48.23	40.85	21.18	63.25	---	---	Peak



Test Engineer :	Feng Wang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m CBL 6111D 59913 VERTICAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	46.490	31.78	-8.22	40.00	47.32	15.90	0.96	32.40	---	---	Peak
2	166.770	25.67	-17.83	43.50	40.59	15.60	1.88	32.40	---	---	Peak
3	334.580	29.33	-16.67	46.00	39.24	19.80	2.69	32.40	---	---	Peak
4	428.670	26.27	-19.73	46.00	32.99	22.60	3.08	32.40	---	---	Peak
5	862.260	30.10	-15.90	46.00	28.54	29.04	4.32	31.80	---	---	Peak
6	870.990	38.72			36.97	29.12	4.36	31.73	---	---	Peak
7	953.440	31.44	-14.56	46.00	26.90	31.00	4.59	31.05	---	---	Peak
8	2105.000	39.47	-34.53	74.00	64.69	30.65	6.89	62.76	---	---	Peak
9	5386.000	42.78	-31.22	74.00	60.10	35.16	11.48	63.96	---	---	Peak
10	7732.000	44.04	-29.96	74.00	56.69	36.64	13.86	63.15	---	---	Peak
11	10146.000	44.78	-29.22	74.00	53.28	37.61	16.06	62.17	---	---	Peak
12	11812.000	44.64	-29.36	74.00	49.68	38.97	17.41	61.42	---	---	Peak
13	17320.000	45.25	-28.75	74.00	46.79	40.69	21.13	63.36	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 20, 2022	May 06, 2022	Apr. 19, 2023	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 14, 2021	May 06, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Oct. 14, 2021	May 06, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 14, 2021	May 06, 2022	Oct. 13, 2022	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 16, 2021	May 07, 2022	Oct. 15, 2022	Radiation (03CH07-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 10, 2021	May 07, 2022	Oct. 09, 2022	Radiation (03CH07-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Dec. 19, 2021	May 07, 2022	Dec. 28, 2022	Radiation (03CH07-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	218652	1GHz~18GHz	Nov. 01, 2021	May 07, 2022	Oct. 30, 2022	Radiation (03CH07-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2022	May 07, 2022	Jan. 04, 2023	Radiation (03CH07-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2022	May 07, 2022	Jan. 04, 2023	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 13, 2022	May 07, 2022	Jan. 12, 2023	Radiation (03CH07-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5G Hz	Apr. 13, 2022	May 07, 2022	Apr. 12, 2023	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	May 07, 2022	NCR	Radiation (03CH07-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	May 07, 2022	NCR	Radiation (03CH07-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	May 07, 2022	NCR	Radiation (03CH07-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.94 dB
---	---------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0 dB
---	--------