



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Redmi  
**MODEL NAME** : 2201116SR  
**FCC ID** : 2AFZZ16SR  
**STANDARD** : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(F), 27(H)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)  
**TEST DATE(S)** : Dec. 26, 2021 ~ Jan. 01, 2022

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY...3
SUMMARY OF TEST RESULT...4
1 GENERAL DESCRIPTION...5
1.1 Applicant...5
1.2 Manufacturer...5
1.3 Product Feature of Equipment Under Test...5
1.4 Product Specification of Equipment Under Test...6
1.5 Modification of EUT...7
1.6 Re-use of Measured Data...7
1.7 Maximum ERP/EIRP Power and Emission Designator...8
1.8 Testing Location...9
1.9 Test Software...9
1.10 Applicable Standards...10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST...11
2.1 Test Mode...11
2.2 Connection Diagram of Test System...13
2.3 Support Unit used in test configuration and system...13
2.4 Measurement Results Explanation Example...13
2.5 Frequency List of Low/Middle/High Channels...14
3 CONDUCTED TEST ITEMS...17
3.1 Measuring Instruments...17
3.2 Test Setup...17
3.3 Test Result of Conducted Test...17
3.4 Conducted Output Power and ERP/EIRP...18
3.5 Peak-to-Average Ratio...19
3.6 Occupied Bandwidth...20
3.7 Conducted Band Edge...21
3.8 Conducted Spurious Emission...22
3.9 Frequency Stability...23
4 RADIATED TEST ITEMS...24
4.1 Measuring Instruments...24
4.2 Test Setup...24
4.3 Test Result of Radiated Test...25
4.4 Radiated Spurious Emission...26
5 LIST OF MEASURING EQUIPMENT...27
6 UNCERTAINTY OF EVALUATION...28
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS
APPENDIX D. REFERENCE REPORT





## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power (Band 5) (Band 26)	ERP < 7 Watt	PASS	-
	§27.50(b)(10) §27.50(c)(10)	Effective Radiated Power (Band 12) (Band 13) (Band 17)	ERP < 3 Watt		-
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	EIRP < 2Watt		-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt		-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	Report Only	-
3.7	§2.1051 §27.53(h)	Conducted Band Edge Measurement (Band 4)	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.8	§2.1051 §27.53(h)	Conducted Spurious Emission (Band 4)	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.9	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(f) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 26)	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 10.56 dB at 1560.000 MHz

**Declaration of Conformity:**  
 The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**  
 The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	2201116SR
FCC ID	2AFZZ16SR
IMEI Code	Conducted: 861288050015360/861288050015378 Radiation: 861288050015741/861288050015758
HW Version	P1.1
SW Version	MIUI 13
EUT Stage	Identical Prototype



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 17 : 704 MHz ~ 716 MHz LTE Band 26 : 824 MHz ~ 849 MHz
<b>Rx Frequency</b>	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 13 : 746 MHz ~ 756 MHz LTE Band 17 : 734 MHz ~ 746 MHz LTE Band 26 : 869 MHz ~ 894 MHz
<b>Bandwidth</b>	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 13 : 5MHz / 10MHz LTE Band 17 : 5MHz / 10MHz LTE Band 26 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
<b>Maximum Output Power to Antenna</b>	<b>Ant. 0:</b> LTE Band 2 : 23.31 dBm LTE Band 4 : 23.67 dBm LTE Band 5 : 24.35 dBm LTE Band 12 : 24.69 dBm LTE Band 13 : 24.55 dBm LTE Band 17 : 24.68 dBm LTE Band 26 : 24.44 dBm <b>Ant. 4:</b> LTE Band 2 : 22.53 dBm LTE Band 4 : 23.46 dBm LTE Band 5 : 24.41 dBm LTE Band 12 : 24.76 dBm LTE Band 13 : 24.68 dBm LTE Band 17 : 24.74 dBm LTE Band 26 : 24.48 dBm
<b>Antenna Gain</b>	<b>Ant. 0:</b> LTE Band 2 : -3.7 dBi LTE Band 4 : -2.9 dBi LTE Band 5 : -4.7 dBi LTE Band 12 : -5.5 dBi LTE Band 13 : -5.7 dBi LTE Band 17 : -5.5 dBi LTE Band 26 : -4.7 dBi <b>Ant. 4:</b> LTE Band 2 : -4.0 dBi LTE Band 4 : -5.6 dBi LTE Band 5 : -5.5 dBi LTE Band 12 : -7.3 dBi LTE Band 13 : -7.0 dBi LTE Band 17 : -7.3 dBi LTE Band 26 : -5.5 dBi



Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM(Downlink Only)
--------------------	--

**Note:** The ERP/EIRP is calculated from Output power and antenna gain, so the maximum ERP/EIRP is shown in the report, LTE Band 2/4/5/12/13/17/26 for Antenna 0.

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Re-use of Measured Data

### 1.6.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: 2201116SR, FCC ID: 2AFZZ16SR) is electrically identical to the reference device (Model: 2201116SG, FCC ID: 2AFZZ16SG) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

### 1.6.2 Difference Section

The **main** difference between FCC ID: 2AFZZ16SG and FCC ID: 2AFZZ16SR is as below:

- Remove LTE Band 32/66 and 5G NR n66.
- Add LTE Band 42

Other differences and all the details of similarity and difference can be found in the confidential documents (2AFZZ16SR\_Operational Description of Product Equality Declaration).

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FG1N1013B for the reference device Model: 2201116SG, FCC ID: 2AFZZ16SG).

### 1.6.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
PCE	2AFZZ16SG	Part22H.24E.27L.27F.27H (Report No. FG1N1013B)	All conducted test sections applicable for LTE Band 2/5/12/13/17/26

### 1.6.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for the following test items, the test result were consistent with FCC ID: 2AFZZ16SG.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination



that verification test data are sufficient to support it.

Test Item	Mode	2AFZZ16SG Worst Result	2AFZZ16SR Worst Result	Difference (dB)
Average Conducted Power (dBm)	LTE Band 2_Ant0	23.31	23.31	0
	LTE Band 4_Ant0	24.25	23.67	0.58
	LTE Band 5_Ant0	24.35	24.35	0
	LTE Band 12_Ant0	24.69	24.69	0
	LTE Band 13_Ant0	24.55	24.55	0
	LTE Band 17_Ant0	24.68	24.68	0
	LTE Band 26_Ant0	24.44	24.44	0

Based on the spot check test result, the test data from the original model is representative for the variant model. The power level spot check are shown within expected level compliant to limit line.

We confirm that the test data reuse policy of FCC KDB 484596 D01 Referencing Test Data v01 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.

### 1.7 Maximum ERP/EIRP Power and Emission Designator

LTE Band 2		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	1860.0 ~ 1900.0	0.0914	-	0.0764	-
LTE Band 4		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	1720.0 ~ 1745.0	0.1194	17M9G7D	0.0991	17M8W7D
LTE Band 5		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
10	829.0 ~ 844.0	0.0562	-	0.0452	-
LTE Band 12		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
10	704.0 ~ 711.0	0.0506	-	0.0417	-





LTE Band 13		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
10	782.0	0.0468	-	0.0383	-
LTE Band 17		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
10	709.0 ~ 711.0	0.0505	-	0.0448	-
LTE Band 26		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
15	831.5 ~ 841.5	0.0574	-	0.0484	-
CH26765	821.5	0.0565	-	0.0492	-

**Note:**

1. All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report .
2. Based on engineering evaluation, only the maximum bandwidth and the worst modulation test results are shown in the report.

### 1.8 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH05-KS TH01-KS	CN1257	314309

### 1.9 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH05-KS	AUDIX	E3	6.2009-8-24a1



## 1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(F), 27(H)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	13	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v
	17	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	4						v	v	v	v			v		v	
26dB and 99% Bandwidth	4						v	v	v				v		v	



Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Conducted BandEdge	4	v	v	v	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	4	v	v	v	v	v	v	v			v			v	v	v
Frequency Stability	4						v	v			v				v	
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v	v			v	v	v
	4	v	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v	-	-	v	v	v	v			v	v	v
	12	v	v	v	v	-	-	v	v	v	v			v	v	v
	13	-	-	v	v	-	-	v	v	v	v			v	v	v
	17	-	-	v	v	-	-	v	v	v	v			v	v	v
	26	v	v	v	v	v	-	v	v	v	v			v	v	v
Radiated Spurious Emission	2	Worst Case												v		
	4	Worst Case												v		
	12	Worst Case												v		
	13	Worst Case												v		
	26	Worst Case												v		
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	MI	N/A	N/A	Unshielded, 1.2m	N/A

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

$$\text{Offset} = \text{RF cable loss}$$

Following shows an offset computation example with cable loss 5.5 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.5 \text{ (dB)} \end{aligned}$$



### 2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5



LTE Band 17 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23780	23790	23800
	Frequency	709	710	711
5	Channel	23755	23790	23825
	Frequency	706.5	710	713.5

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
10	Channel	26840	26915	26990
	Frequency	829	836.5	844
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3




### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5 and Band 26.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 12, Band 13 and Band 17.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



### 3.6 Occupied Bandwidth

#### 3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.  
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



### 3.7 Conducted Band Edge

#### 3.7.1 Description of Conducted Band Edge Measurement

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is  $43 + 10\log_{10}(P[\text{Watts}])$  dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

#### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)  
= P(W)- [43 + 10log(P)] (dB)  
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.



### 3.8 Conducted Spurious Emission

#### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

#### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)  
= P(W)- [43 + 10log(P)] (dB)  
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)  
= -13dBm.



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test below 30MHz




#### 4.2.2 For radiated test from 30MHz to 1GHz





#### 4.2.3 For radiated test above 1GHz



#### 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



## 4.4 Radiated Spurious Emission

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 14, 2021	Dec. 26, 2021~ Dec. 27, 2021	Oct. 13, 2022	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 12, 2021	Dec. 26, 2021~ Dec. 27, 2021	Jul. 11, 2022	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 26, 2021	Dec. 26, 2021~ Dec. 27, 2021	Aug. 25, 2022	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44G,MAX 30dB	Apr. 13, 2021	Jan. 01, 2022	Apr. 12, 2022	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Jan. 01, 2022	Oct. 29, 2022	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	Jun. 04, 2021	Jan. 01, 2022	Jun. 03, 2022	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 24, 2021	Jan. 01, 2022	Apr. 23, 2022	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2021	Jan. 01, 2022	Nov. 08, 2022	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Apr. 12, 2021	Jan. 01, 2022	Apr. 11, 2022	Radiation (03CH05-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Jan. 01, 2022	Jan. 06, 2022	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2012228	1Ghz~18Ghz	Oct. 16, 2021	Jan. 01, 2022	Oct. 15, 2022	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 16, 2021	Jan. 01, 2022	Oct. 15, 2022	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 01, 2022	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 01, 2022	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 01, 2022	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required



## 6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.1dB
---	-------



# Appendix A. Test Results of Conducted Test

## Conducted Output Power(Average power) ERP/EIRP

### LTE Band 2:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				18700	18900	19100	EIRP(W)		
Frequency (MHz)				1860	1880	1900	L	M	H
20	QPSK	1	0	23.02	23.31	23.08	0.0855	0.0914	0.0867
20	QPSK	1	99	23.23	22.99	22.99	0.0897	0.0849	0.0849
20	QPSK	100	0	22.26	22.31	22.13	0.0718	0.0726	0.0697
20	16QAM	1	0	21.95	22.18	22.53	0.0668	0.0705	0.0764
20	64QAM	1	0	21.04	21.27	21.09	0.0542	0.0571	0.0548
Channel				18675	18900	19125	EIRP(W)		
Frequency (MHz)				1857.5	1880	1902.5	L	M	H
15	QPSK	1	0	23.16	23.28	23.18	0.0883	0.0908	0.0887
15	16QAM	1	0	22.45	22.34	22.39	0.0750	0.0731	0.0740
Channel				18650	18900	19150	EIRP(W)		
Frequency (MHz)				1855	1880	1905	L	M	H
10	QPSK	1	0	23.23	23.29	23.25	0.0897	0.0910	0.0902
10	16QAM	1	0	22.42	22.45	22.15	0.0745	0.0750	0.0700
Channel				18625	18900	19175	EIRP(W)		
Frequency (MHz)				1852.5	1880	1907.5	L	M	H
5	QPSK	1	0	23.30	22.92	23.02	0.0912	0.0836	0.0855
5	16QAM	1	0	22.31	22.26	22.45	0.0726	0.0718	0.0750
Channel				18615	18900	19185	EIRP(W)		
Frequency (MHz)				1851.5	1880	1908.5	L	M	H
3	QPSK	1	0	23.17	23.30	23.09	0.0885	0.0912	0.0869
3	16QAM	1	0	22.13	22.50	22.22	0.0697	0.0759	0.0711
Channel				18607	18900	19193	EIRP(W)		
Frequency (MHz)				1850.7	1880	1909.3	L	M	H
1.4	QPSK	1	0	23.15	23.20	23.30	0.0881	0.0891	0.0912
1.4	16QAM	1	0	22.41	22.35	22.07	0.0743	0.0733	0.0687



LTE Band 4:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				20050	20175	20300	EIRP(W)		
Frequency (MHz)				1720	1732.5	1745	L	M	H
20	QPSK	1	0	23.44	23.67	23.63	0.1132	0.1194	0.1183
20	QPSK	1	99	23.44	23.44	23.26	0.1132	0.1132	0.1086
20	QPSK	100	0	22.55	22.60	22.40	0.0923	0.0933	0.0891
20	16QAM	1	0	22.53	22.81	22.86	0.0918	0.0979	0.0991
20	64QAM	1	0	21.71	21.70	21.63	0.0760	0.0759	0.0746
Channel				20025	20175	20325	EIRP(W)		
Frequency (MHz)				1717.5	1732.5	1747.5	L	M	H
15	QPSK	1	0	23.47	23.53	23.43	0.1140	0.1156	0.1130
15	16QAM	1	0	22.70	22.54	22.57	0.0955	0.0920	0.0927
Channel				20000	20175	20350	EIRP(W)		
Frequency (MHz)				1715	1732.5	1750	L	M	H
10	QPSK	1	0	23.65	23.65	23.52	0.1189	0.1189	0.1153
10	16QAM	1	0	22.75	22.62	22.55	0.0966	0.0938	0.0923
Channel				19975	20175	20375	EIRP(W)		
Frequency (MHz)				1712.5	1732.5	1752.5	L	M	H
5	QPSK	1	0	23.63	23.64	23.36	0.1183	0.1186	0.1112
5	16QAM	1	0	22.81	22.71	22.86	0.0979	0.0957	0.0991
Channel				19965	20175	20385	EIRP(W)		
Frequency (MHz)				1711.5	1732.5	1753.5	L	M	H
3	QPSK	1	0	23.64	23.53	23.48	0.1186	0.1156	0.1143
3	16QAM	1	0	22.59	22.68	22.81	0.0931	0.0951	0.0979
Channel				19950	20175	20393	EIRP(W)		
Frequency (MHz)				1710	1732.5	1754.3	L	M	H
1.4	QPSK	1	0	23.44	23.65	23.47	0.1132	0.1189	0.1140
1.4	16QAM	1	0	22.69	22.76	22.58	0.0953	0.0968	0.0929



LTE Band 5:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				20450	20525	20600	ERP(W)		
Frequency (MHz)				829	836.5	844	L	M	H
10	QPSK	1	0	24.25	24.35	24.05	0.0550	0.0562	0.0525
10	QPSK	1	49	24.29	24.11	24.17	0.0555	0.0532	0.0540
10	QPSK	50	0	23.40	23.42	23.33	0.0452	0.0454	0.0445
10	16QAM	1	0	23.15	23.40	23.32	0.0427	0.0452	0.0444
10	64QAM	1	0	22.34	22.14	22.44	0.0354	0.0338	0.0362
Channel				20425	20525	20625	ERP(W)		
Frequency (MHz)				826.5	836.5	846.5	L	M	H
5	QPSK	1	0	24.34	24.09	24.20	0.0561	0.0530	0.0543
5	16QAM	1	0	23.35	23.10	23.18	0.0447	0.0422	0.0430
Channel				20415	20525	20635	ERP(W)		
Frequency (MHz)				825.5	836.5	847.5	L	M	H
3	QPSK	1	0	24.31	24.28	24.24	0.0557	0.0553	0.0548
3	16QAM	1	0	23.30	23.30	23.34	0.0442	0.0442	0.0446
Channel				20407	20525	20643	ERP(W)		
Frequency (MHz)				824.7	836.5	848.3	L	M	H
1.4	QPSK	1	0	24.32	24.20	24.00	0.0558	0.0543	0.0519
1.4	16QAM	1	0	23.18	23.10	23.40	0.0430	0.0422	0.0452



LTE Band 12:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23060	23095	23130	ERP(W)		
Frequency (MHz)				704	707.5	711	L	M	H
10	QPSK	1	0	24.57	24.69	24.64	0.0492	0.0506	0.0500
10	QPSK	1	49	24.67	24.65	24.61	0.0504	0.0501	0.0497
10	QPSK	50	0	23.83	23.86	23.80	0.0415	0.0418	0.0412
10	16QAM	1	0	23.85	23.79	23.61	0.0417	0.0411	0.0394
10	64QAM	1	0	22.64	22.70	22.92	0.0316	0.0320	0.0337
Channel				23035	23095	23205	ERP(W)		
Frequency (MHz)				701.5	707.5	718.5	L	M	H
5	QPSK	1	0	24.68	24.58	24.44	0.0505	0.0493	0.0478
5	16QAM	1	0	23.48	23.75	23.71	0.0383	0.0407	0.0404
Channel				23025	23095	23195	ERP(W)		
Frequency (MHz)				700.5	707.5	717.5	L	M	H
3	QPSK	1	0	24.57	24.66	24.46	0.0492	0.0502	0.0480
3	16QAM	1	0	23.79	23.83	23.66	0.0411	0.0415	0.0399
Channel				23017	23095	23173	ERP(W)		
Frequency (MHz)				699.7	707.5	715.3	L	M	H
1.4	QPSK	1	0	24.47	24.65	24.51	0.0481	0.0501	0.0485
1.4	16QAM	1	0	23.56	23.84	23.68	0.0390	0.0416	0.0401

LTE Band 13:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23230			ERP(W)		
Frequency (MHz)				782				M	
10	QPSK	1	0		24.55			0.0468	
10	QPSK	1	49		24.38			0.0450	
10	QPSK	50	0		23.56			0.0372	
10	16QAM	1	0		23.68			0.0383	
10	64QAM	1	0		22.76			0.0310	
Channel				23205	23230	23255	ERP(W)		
Frequency (MHz)				779.5	782	784.5	L	M	H
5	QPSK	1	0	24.31	24.52	24.24	0.0443	0.0465	0.0436
5	16QAM	1	0	23.57	23.50	23.49	0.0373	0.0367	0.0366





**LTE Band 17:**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23780	23790	23800			
Frequency (MHz)				709	710	711	L	M	H
10	QPSK	1	0	24.50	24.68	24.42	0.0484	0.0505	0.0475
10	QPSK	1	49	24.33	24.40	24.62	0.0466	0.0473	0.0498
10	QPSK	50	0	23.79	23.90	23.58	0.0411	0.0422	0.0392
10	16QAM	1	0	23.82	24.16	23.84	0.0414	0.0448	0.0416
10	64QAM	1	0	22.81	23.14	22.90	0.0328	0.0354	0.0335
Channel				23755	23790	23825	ERP(W)		
Frequency (MHz)				706.5	710	713.5	L	M	H
5	QPSK	1	0	24.67	24.67	24.56	0.0504	0.0504	0.0491
5	16QAM	1	0	23.84	23.86	23.98	0.0416	0.0418	0.0430

**LTE Band 26:**




BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)			
Channel				26765	26865	26915	26965				
Frequency (MHz)				821.5	831.5	836.5	841.5	L	M	H	
15	QPSK	1	0	24.34	24.44	24.15	24.31	0.0561	0.0574	0.0537	0.0557
15	QPSK	1	74	24.37	24.33	24.10	24.18	0.0565	0.0560	0.0531	0.0541
15	QPSK	75	0	23.42	23.52	23.42	23.31	0.0454	0.0465	0.0454	0.0443
15	16QAM	1	0	23.77	23.70	23.51	23.64	0.0492	0.0484	0.0463	0.0478
15	64QAM	1	0	22.80	22.55	22.19	22.50	0.0394	0.0372	0.0342	0.0367
Channel				26840	26915	26990	ERP(W)				
Frequency (MHz)				829	836.5	844	L	M	H		
10	QPSK	1	0	24.35	24.33	24.20		0.0562	0.0560	0.0543	
10	16QAM	1	0	23.60	23.68	23.61		0.0473	0.0482	0.0474	
Channel				26815	26915	27015	ERP(W)				
Frequency (MHz)				826.5	836.5	846.5	L	M	H		
5	QPSK	1	0	24.40	24.32	24.20		0.0569	0.0558	0.0543	
5	16QAM	1	0	23.64	23.67	23.54		0.0478	0.0481	0.0467	
Channel				26815	26915	27025	ERP(W)				
Frequency (MHz)				825.5	836.5	847.5	L	M	H		
3	QPSK	1	0	24.37	24.27	23.89		0.0565	0.0552	0.0506	
3	16QAM	1	0	23.67	23.61	23.55		0.0481	0.0474	0.0468	
Channel				26797	26915	27033	ERP(W)				
Frequency (MHz)				824.7	836.5	848.3	L	M	H		
1.4	QPSK	1	0	24.33	24.28	24.16		0.0560	0.0553	0.0538	
1.4	16QAM	1	0	23.61	23.64	23.48		0.0474	0.0478	0.0460	



## LTE Band 4

### Peak-to-Average Ratio


Mode	LTE Band 4 / 20MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.01	5.86	5.91	<b>PASS</b>





## 26dB Bandwidth


Mode	LTE Band 4 : 26dB BW(MHz)	
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	18.90	18.90






# Occupied Bandwidth

Mode	LTE Band 4 : 99%OBW(MHz)	
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	17.90	17.82






# Conducted Band Edge






LTE Band 4 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 00:25:47

Highest Band Edge / 1 RB




Date: 27.DEC.2021 00:40:33

Lowest Band Edge / Full RB



Date: 27.DEC.2021 00:30:49

Highest Band Edge / Full RB




Date: 27.DEC.2021 00:45:36




LTE Band 4 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 00:27:28

Highest Band Edge / 1 RB




Date: 27.DEC.2021 00:42:15

Lowest Band Edge / Full RB



Date: 27.DEC.2021 00:29:09

Highest Band Edge / Full RB




Date: 27.DEC.2021 00:43:55






LTE Band 4 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 27.DEC.2021 00:51:19

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:06:05

Lowest Band Edge / Full RB



Date: 27.DEC.2021 00:59:42

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:14:27




LTE Band 4 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 00:52:59

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:07:45

Lowest Band Edge / Full RB



Date: 27.DEC.2021 00:58:01

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:12:47




LTE Band 4 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 00:54:39

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:09:26

Lowest Band Edge / Full RB



Date: 27.DEC.2021 00:56:20

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:11:06




LTE Band 4 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 01:18:30

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:33:17

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:26:53

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:41:50




LTE Band 4 / 5MHz / 16QAM

Lowest Band Edge / 1RB




Date: 27.DEC.2021 01:20:10

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:34:58

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:25:13

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:40:08




LTE Band 4 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 27.DEC.2021 01:21:51

Highest Band Edge / 1 RB




Date: 27.DEC.2021 01:36:38

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:23:32

Highest Band Edge / Full RB




Date: 27.DEC.2021 01:38:28




LTE Band 4 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 01:45:52

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:00:39

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:54:16

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:09:02




LTE Band 4 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 01:47:33

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:02:20

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:52:35

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:07:22






LTE Band 4 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 01:49:13

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:04:00

Lowest Band Edge / Full RB



Date: 27.DEC.2021 01:50:54

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:05:41




LTE Band 4 / 15MHz / QPSK

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:13:05

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:27:51

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:21:27

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:36:13




LTE Band 4 / 15MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:14:45

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:29:31

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:19:47

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:34:33




LTE Band 4 / 15MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:16:26

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:31:11

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:18:06

Highest Band Edge / Full RB




Date: 27.DEC.2021 02:32:52




LTE Band 4 / 20MHz / QPSK

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:40:16

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:55:02

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:48:39

Highest Band Edge / Full RB




Date: 27.DEC.2021 03:03:27




LTE Band 4 / 20MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:41:57

Highest Band Edge / 1 RB



Date: 27.DEC.2021 02:56:44

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:46:58

Highest Band Edge / Full RB




Date: 27.DEC.2021 03:01:46




LTE Band 4 / 20MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 27.DEC.2021 02:43:37

Highest Band Edge / 1 RB




Date: 27.DEC.2021 02:58:24

Lowest Band Edge / Full RB



Date: 27.DEC.2021 02:45:17


Highest Band Edge / Full RB



Date: 27.DEC.2021 03:00:06



# Conducted Spurious Emission









LTE Band 4 / 3MHz

Lowest Channel / QPSK

Middle Channel / QPSK




Date: 27.DEC.2021 00:49:38



Date: 27.DEC.2021 01:02:03

Highest Channel / QPSK




Date: 27.DEC.2021 01:04:24




LTE Band 4 / 5MHz

Lowest Channel / QPSK

Middle Channel / QPSK




Date: 27.DEC.2021 01:16:49



Date: 27.DEC.2021 01:29:15

Highest Channel / QPSK



Date: 27.DEC.2021 01:31:36