

FCC RF Test Report

APPLICANT	:	Xiaomi Communications Co., Ltd.
EQUIPMENT	:	Mobile Phone
BRAND NAME	:	POCO
MODEL NAME	:	22011211G
FCC ID	:	2AFZZ211G
STANDARD	:	47 CFR Part 2, and 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Jan. 12, 2022 ~ Feb. 01, 2022

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Dorque Cher

Reviewed by: Derreck Chen / Supervisor

File Shih

Approved by: Eric Shih / Manager



Sporton International Inc. (ShenZhen) 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China



TABLE OF CONTENTS

RE	EVISIO	N HISTORY	3
รเ	JMMAF	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	
	1.5	Modification of EUT	
	1.6	Maximum Conducted Power and Emission Designator	
	1.7	Testing Site	
	1.8	Test Software	
	1.9	Applied Standards	7
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	8
	2.2	Connection Diagram of Test System	9
	2.3	Support Unit used in test configuration and system	9
	2.4	Measurement Results Explanation Example	9
	2.5	Frequency List of Low/Middle/High Channels	10
3	TEST	「RESULT	11
	3.1	Conducted Output Power Measurement	11
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	
	3.3	Emissions Mask Measurement	
	3.4	Emissions Mask – Out Of Band Emissions Measurement	
	3.5	Field Strength of Spurious Radiation Measurement	16
	3.6	Frequency Stability Measurement	19
4	LIST	OF MEASURING EQUIPMENT	21
5	UNC	ERTAINTY OF EVALUATION	22

- APPENDIX A. TEST RESULTS OF CONDUCTED TEST
- APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG1D3005D	Rev. 01	Initial issue of report	Feb. 16, 2022



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	_	Report only	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	_	Report only	-
3.3	3 §2.1051 Emission masks – 3 §90.691 In-band emissions		< 50+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 37.44 dB at 2452.950 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Phone
Brand Name	POCO
Model Name	22011211G
FCC ID	2AFZZ211G
IMEI Code	Conducted: 860000050060420 Radiation: 860000050055440/860000050055457
HW Version	P2
SW Version	MIUI 13
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard							
Tx Frequency	814 ~ 824 MHz						
Rx Frequency	859 ~ 869 MHz						
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz						
Maximum Output Power to Antenna	<ant. 0="">: 25.18 dBm</ant.>						
Maximum Output Power to Antenna	<ant. 1="">: 25.00 dBm</ant.>						
Antonno Coin	<ant. 0="">: -3.88 dBi</ant.>						
Antenna Gain	<ant. 1="">: -4.54 dBi</ant.>						
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM						

Remark: Only the maximum output power for Antenna 0 is shown in the report.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

Ľ	TE Band 26	QP	SK	16QAM/64QAM/256QAM			
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)		
1.4	814.7 ~ 823.3	0.3266	1M10G7D	0.2748	1M11W7D		
3	815.5 ~ 822.5	0.3177	2M72G7D	0.2692	2M74W7D		
5	816.5 ~ 821.5	0.3048	4M49G7D	0.2667	4M50W7D		
10	819.0	0.3048	9M05G7D	0.2455	9M03W7D		
15	821.5	0.3296	13M4G7D	0.2576	13M5W7D		

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)								
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595								
	Sporton Sito No	FCC Designation No.	FCC Test Firm						
Test Site No.	Sporton Site No.	FCC Designation No.	Registration No.						
	TH01-SZ	CN1256	421272						
Test Firm	Sporton International Inc	. (Shenzhen)							
Test Site Location		et, Baoan District, Shenzhe	eng 4th Road, Fenghuang n City Guangdong Province						
	Sporton Sito No	ECC Decignation No	FCC Test Firm						
Test Site No.									
Test Site No.	Sporton Site No.	FCC Designation No.	Registration No.						



1.8 Test Software

ltem	Site	Manufacturer	Name	Version	
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24	

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.


For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

		Bandwidth (MHz)					Modulation			RB #			Test Channel				
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256 QAM	1	Half	Full	L	м	н
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v				v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v		v			v	v	v
Frequency Stability	26				v		-	v						v		v	
Radiated Spurious Emission	26	v	v	v	v	v	-	v				v				v	
Note	 The mark "v " means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP 																

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.



2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

ltem	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord		
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m		
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m		

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator. Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.0 + 10 = 14.0 (dB)



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List									
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest					
15	Channel	26765	-	-					
15	Frequency	821.5	-	-					
10	Channel	-	26740	-					
10	Frequency	-	819	-					
5	Channel	26715	26740	26765					
Ð	Frequency	816.5	819	821.5					
3	Channel	26705	26740	26775					
3	Frequency	815.5	819	822.5					
1.4	Channel	26697	26740	26783					
1.4	Frequency	814.7	819	823.3					



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.



3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log₁₀(f/6.1) decibels or 50 + 10 Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.



3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.



3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P) dB$. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10^{th} harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

Sporton International Inc. (ShenZhen) TEL : 86-755-8637-9589 FAX : 86-755-8637-9595 FCC ID : 2AFZZ211G

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.5.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)




3.5.4 Test Setup

For radiated test from 30MHz




For radiated test from 30MHz to 1GHz





For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation


- 1. The EUT was set up in the thermal chamber and connected with the base station.
- 2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- 2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.



3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 08, 2021	Jan. 12, 2022~ Jan. 24, 2022	Apr. 07, 2022	Conducted (TH01-SZ)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 26, 2021	Jan. 12, 2022~ Jan. 24, 2022	Aug. 25, 2022	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangrou p	LP-150U	H201408180 3	-40~+150°C	Jul. 14, 2021	Jan. 12, 2022~ Jan. 24, 2022	Jul. 13, 2022	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY5445008 3	20Hz~8.4GHz	Apr. 07, 2021	Feb. 01, 2022	Apr. 06, 2022	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 22, 2021	Feb. 01, 2022	Jun. 21, 2022	Radiation (03CH03-SZ)
EXA Spectrum Anaiyzer	KEYSIGHT	N9010A	MY5515024 6	10Hz~44GHz;	Apr. 07, 2021	Feb. 01, 2022	Apr. 06, 2022	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Jun. 22, 2021	Feb. 01, 2022	Jun. 21, 2022	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBE CK	BBHA9120 D	9120D-1355	1GHz~18GHz	Apr. 25, 2021	Feb. 01, 2022	Apr. 24, 2022	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 22, 2021	Feb. 01, 2022	Oct. 21, 2022	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Oct. 22, 2021	Feb. 01, 2022	Oct. 21, 2022	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 11, 2021	Feb. 01, 2022	Apr. 10, 2022	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY3950130 2	500MHz~26.5G Hz	Dec. 29, 2021	Feb. 01, 2022	Dec. 28, 2022	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	6160100019 85	N/A	NCR	Feb. 01, 2022	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 01, 2022	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Feb. 01, 2022	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	3.0dB
Confidence of 95% (U = 2Uc(y))	3.006

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	2 C4D
Confidence of 95% (U = 2Uc(y))	3.6dB

----- THE END ------



Appendix A. Test Results of Conducted Test

Test Engineer :	Yao Zhou	Temperature :	24~26°C
		Relative Humidity :	50~53%

Conducted Output Power (Average power)

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
	Channel			26765	Unit / Frieq.	
	Frequency (MHz)		821.5	-	-	
15	QPSK	1	0	25.18		
15	QPSK	1	37	25.15		
15	QPSK	1	74	25.12		
15	QPSK	36	0	23.81		
15	QPSK	36	20	23.77		
15	QPSK	36	39	23.75		
15	QPSK	75	0	23.82		
15	16QAM	1	0	24.00		
15	16QAM	1	37	24.06		
15	16QAM	1	74	24.11		
15	16QAM	36	0	22.74		
15	16QAM	36	20	22.78		
15	16QAM	36	39	22.77		
15	16QAM	75	0	22.78		
15	64QAM	1	0	22.77	-	-
15	64QAM	1	37	22.90		
15	64QAM	1	74	22.77		
15	64QAM	36	0	21.80		
15	64QAM	36	20	21.84		
15	64QAM	36	39	21.78		
15	64QAM	75	0	21.72		
15	256QAM	1	0	19.97		
15	256QAM	1	37	19.91		
15	256QAM	1	74	19.98		
15	256QAM	36	0	19.86		
15	256QAM	36	20	19.82		
15	256QAM	36	39	19.82		
15	256QAM	75	0	19.82		
	Chan	nel		-	26740	-
	Frequenc	y (MHz)		-	819	-
10	QPSK	1	0		24.84	
10	QPSK	1	25	-	24.82	-
10	QPSK	1	49		24.81	

Sporton International Inc. (ShenZhen) TEL : 86-755-8637-9589 FAX : 86-755-8637-9595 FCC ID : 2AFZZ211G Page Number: A1 of A43Report Issued Date: Feb. 16, 2022Report Version: Rev. 01



Report No. : FG1D3005D

40		05	0		00.70	
10	QPSK	25	0		23.78	
10	QPSK	25	12		23.83	
10	QPSK	25	25		23.80	
10	QPSK	50	0		23.86	
10	16QAM	1	0		23.81	
10	16QAM	1	25		23.87	
10	16QAM	1	49		23.90	
10	16QAM	25	0		22.91	
10	16QAM	25	12		22.90	
10	16QAM	25	25		22.85	
10	16QAM	50	0		22.86	
10	64QAM	1	0		22.96	
10	64QAM	1	25		23.05	
10	64QAM	1	49		23.02	
10	64QAM	25	0		21.86	
10	64QAM	25	12		21.72	
10	64QAM	25	25		21.72	
10	64QAM	50	0		21.81	
10	256QAM	1	0		19.57	
10	256QAM	1	25		19.61	
10	256QAM	1	49		19.55	
10	256QAM	25	0		19.64	
10	256QAM	25	12		19.45	
10	256QAM	25	25		19.52	
10	256QAM	50	0		19.46	
	Chan	nel		26715	26740	26765
	Frequenc	y (MHz)		816.5	819	821.5
5	QPSK	1	0	24.76	24.77	24.78
5	QPSK	1	12	24.84	24.75	24.84
5	QPSK	1	24	24.78	24.72	24.78
5	QPSK	12	0	23.77	23.84	23.87
5	QPSK	12	7	23.78	23.86	23.93
5	QPSK	12	13	23.76	23.76	23.83
5	QPSK	25	0	23.83	23.82	23.90
5	16QAM	1	0	23.77	23.84	24.17
5	16QAM	1	12	23.81	23.87	24.23
5	16QAM	1	24	23.89	23.86	24.26
5	16QAM	12	0	22.69	22.79	22.89
5	16QAM	12	7	22.77	22.80	22.90
5	16QAM	12	13	22.72	22.70	22.81
5	16QAM	25	0	22.74	22.69	22.90
5	64QAM	1	0	23.06	23.04	23.11
5	64QAM	1	12	22.83	23.09	23.08
5	64QAM	1	24	23.02	23.03	23.10
5	64QAM	12	0	21.78	21.88	21.87
				21110	21.00	21.07

Sporton International Inc. (ShenZhen) TEL : 86-755-8637-9589 FAX : 86-755-8637-9595 FCC ID : 2AFZZ211G Page Number: A2 of A43Report Issued Date: Feb. 16, 2022Report Version: Rev. 01



Report No. : FG1D3005D


5	64QAM	12	7	21.83	21.81	21.84
5	64QAM	12	13	21.79	21.77	21.82
5	64QAM	25	0	21.74	21.71	21.92
5	256QAM	1	0	19.40	19.63	19.48
5	256QAM	1	12	19.66	19.47	19.83
5	256QAM	1	24	19.64	19.59	19.49
5	256QAM	12	0	19.84	19.83	19.71
5	256QAM	12	7	19.65	19.81	19.86
5	256QAM	12	13	19.82	19.78	19.56
5	256QAM	25	0	19.62	19.52	19.90
	Chan			26705	26740	26775
	Frequency	/ (MHz)		815.5	819	822.5
3	QPSK	1	0	24.87	24.95	24.80
3	QPSK	1	8	24.99	25.02	24.91
3	QPSK	1	14	24.95	24.99	24.94
3	QPSK	8	0	23.82	23.81	23.78
3	QPSK	8	4	23.75	23.74	23.83
3	QPSK	8	7	23.74	23.80	23.88
3	QPSK	15	0	23.76	23.77	23.90
3	16QAM	1	0	24.30	24.26	24.02
3	16QAM	1	8	24.23	24.26	24.06
3	16QAM	1	14	24.26	23.94	24.06
3	16QAM	8	0	22.83	22.78	22.88
3	16QAM	8	4	22.78	22.74	22.92
3	16QAM	8	7	22.85	22.79	22.97
3	16QAM	15	0	22.83	22.81	22.80
3	64QAM	1	0	22.55	22.82	22.77
3	64QAM	1	8	22.59	22.70	22.87
3	64QAM	1	14	22.57	22.69	22.79
3	64QAM	8	0	21.78	21.62	21.70
3	64QAM	8	4	21.83	21.61	21.72
3	64QAM	8	7	21.88	21.70	21.83
3	64QAM	15	0	21.69	21.85	21.89
3	256QAM	1	0	19.84	19.65	19.40
3	256QAM	1	8	19.74	19.44	19.45
3	256QAM	1	14	19.73	19.46	19.58
3	256QAM	8	0	19.68	19.79	19.52
3	256QAM	8	4	19.48	19.70	19.95
3	256QAM	8	7	19.56	19.46	19.79
3	256QAM	15	0	19.49	19.42	19.56
	Chan	nel		26697	26740	26783
	Frequency			814.7	819	823.3
1.4	QPSK	1	0	25.10	25.12	25.05
1.4	QPSK	1	3	25.14	25.13	25.02
		1				
1.4	QPSK		5	25.09	25.09	24.97

Sporton International Inc. (ShenZhen) TEL : 86-755-8637-9589 FAX : 86-755-8637-9595 FCC ID : 2AFZZ211G Page Number: A3 of A43Report Issued Date: Feb. 16, 2022Report Version: Rev. 01



Report No. : FG1D3005D

1.4	QPSK	3	0	24.77	24.85	24.78
1.4	QPSK	3	1	24.85	24.76	24.72
1.4	QPSK	3	3	24.77	24.70	24.79
1.4	QPSK	6	0	23.90	23.88	23.90
1.4	16QAM	1	0	24.07	24.09	24.25
1.4	16QAM	1	3	24.03	24.39	24.34
1.4	16QAM	1	5	23.99	24.10	24.20
1.4	16QAM	3	0	23.88	23.78	23.78
1.4	16QAM	3	1	23.82	23.85	23.83
1.4	16QAM	3	3	23.91	23.79	23.82
1.4	16QAM	6	0	22.88	22.99	22.99
1.4	64QAM	1	0	22.79	23.19	23.20
1.4	64QAM	1	3	22.74	23.12	23.21
1.4	64QAM	1	5	22.67	23.09	22.97
1.4	64QAM	3	0	22.51	23.02	23.02
1.4	64QAM	3	1	22.65	23.08	23.00
1.4	64QAM	3	3	22.52	23.01	22.97
1.4	64QAM	6	0	21.71	21.76	21.86
1.4	256QAM	1	0	19.65	19.46	19.76
1.4	256QAM	1	3	19.40	19.64	19.62
1.4	256QAM	1	5	19.84	19.88	19.74
1.4	256QAM	3	0	19.66	19.64	19.64
1.4	256QAM	3	1	19.49	19.53	19.76
1.4	256QAM	3	3	19.95	19.54	19.79
1.4	256QAM	6	0	19.72	19.52	19.90






LTE Band 26


26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4	٨Hz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.27	1.25	2.97	2.97	4.79	4.96	-	-	14.39	14.21	-	-
Middle CH	1.25	1.31	2.96	2.98	4.94	4.87	9.73	9.69	-	-	-	-
Highest CH	1.24	1.30	3.00	2.96	4.82	4.87	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	26dB BV	V(MHz)				
BW	1.4	ИНz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.25	-	2.98	-	4.91	-	-	-	14.30	-	-	-
Middle CH	1.28	-	2.94	-	4.84	-	9.75	-	-	-	-	-
Highest CH	1.28	-	2.98	-	4.84	-	-	-	-	-	-	-







































Occupied Bandwidth


Mode		LTE Band 26 : 99%OBW(MHz)										
BW	1.4	٨Hz	3M	Hz	5N	5MHz		10MHz		ЛНz	20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.11	2.72	2.74	4.48	4.48	-	-	13.40	13.40	-	-
Middle CH	1.09	1.10	2.72	2.70	4.49	4.49	9.05	9.03	-	-	-	-
Highest CH	1.10	1.09	2.72	2.72	4.49	4.49	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	99%OBV	V(MHz)				
BW	1.4	٨Hz	3MHz		5N	IHz	10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.09	-	2.70	-	4.50	-	-	-	13.46	-	-	-
Middle CH	1.09	-	2.70	-	4.49	-	9.03	-	-	-	-	-
Highest CH	1.10	-	2.73	-	4.50	-	-	-	-	-	-	-





































Conducted Band Edge



Sporton International Inc. (ShenZhen) TEL : 86-755-8637-9589 FAX : 86-755-8637-9595 FCC ID : 2AFZZ211G





