



# EMC TEST REPORT

**Applicant**      Xiaomi Communications Co., Ltd.

**FCC ID**          2AFZZ33L2G

**Product**        Mobile Phone

**Brand**           Redmi

**Model**           220233L2G

**Report No.**      R2112A1138-E1

**Issue Date**     January 21, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2020)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Wei Liu*

Prepared by: Wei Liu

*Guangchang Fan*

Approved by: Guangchang Fan

---

**TA Technology (Shanghai) Co., Ltd.**

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report.....	4
1.2	Test facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment under Test.....	5
2.1	Applicant and Manufacturer Information.....	5
2.2	General information.....	5
2.3	Applied Standards.....	6
2.4	Test Mode.....	7
3	Test Case Results .....	8
3.1	Radiated Emission .....	8
3.2	Conducted Emission .....	15
4	Main Test Instruments .....	19
	ANNEX A: The EUT Appearance.....	20
	ANNEX B: Test Setup Photos.....	21



### Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: December 27, 2021 ~ January 7, 2022			
Date of Sample Received: December 23, 2021			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2 Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Fan Guangchang  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [fanguangchang@ta-shanghai.com](mailto:fanguangchang@ta-shanghai.com)

## 2 General Description of Equipment under Test

### 2.1 Applicant and Manufacturer Information

<b>Applicant</b>	Xiaomi Communications Co., Ltd.
<b>Applicant address</b>	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
<b>Manufacturer</b>	Xiaomi Communications Co., Ltd.
<b>Manufacturer address</b>	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

### 2.2 General information

EUT Description			
Device Type	Portable Device		
Model	220233L2G		
IMEI	IMEI 1: 862643060047788 IMEI 2: 862643060047796		
HW Version	P2		
SW Version	MIUI 12.5		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	PIFA Antenna for WWAN Fixed Internal Antenna for Bluetooth/ Wi-Fi Earphone Antenna for FM		
Frequency	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824 ~ 849	869 ~ 894
	GSM 1900	1850 ~ 1910	1930 ~ 1990
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 38	2570 ~ 2620	2570 ~ 2620
	LTE Band 41	2535 ~ 2655	2535 ~ 2655
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	WIFI 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
Auxiliary test equipment			
PC	PC Manufacturer: Microsoft Corporation Model: L20170076		
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			



## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

**FCC Code CFR47 Part15B (2020)**

**ANSI C63.4 (2014)**

## 2.4 Test Mode

Test Mode	
Mode 1	Adapter + USB cable + Front camera On
Mode 2	Adapter + USB cable + Rear camera On
Mode 3	Adapter + USB cable + Mp4
Mode 4	Adapter + USB cable + Bluetooth WLAN Traffic
Mode 5	USB Copy(EUT with PC) + USB cable + earphone
Mode 6	Front Camera On
Mode 7	MP4
Mode 8	Rear camera On
Mode 9	Bluetooth WLAN Traffic

During the test, the preliminary test was performed in all modes, mode 5 is selected as the worst condition. The test data of the worst-case condition was recorded in this report.

### 3 Test Case Results

#### 3.1 Radiated Emission

##### Ambient condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

##### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO


(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.


During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC; PC is connected to server via a long LAN cable.

## Test Setup

### Below 1GHz



### Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

## Limits

### Class B

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 <sup>th</sup> harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak


## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
30MHz~200MHz	4.17 dB
200MHz~1000MHz	4.84 dB
1GHz~18GHz	4.35 dB

## Test Results

The following graphs display the maximum values of horizontal and vertical by software.  
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.  
A font ( Level in dB  $\mu$ V/m ) in the test plot =(level in dB  $\mu$ V/m)




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
30.000000	18.26	40.00	21.74	113.0	V	196.0	12
56.222500	18.59	40.00	21.41	113.0	V	142.0	14
142.641250	21.58	43.50	21.92	105.0	V	284.0	9
193.771250	22.74	43.50	20.76	100.0	H	264.0	12
384.008750	32.73	46.00	13.27	100.0	H	189.0	17
833.683750	30.21	46.00	15.79	113.0	H	329.0	24


Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
1082.733333	---	27.35	54.00	26.65	100.0	H	210.0	-19
1177.933333	36.46	---	74.00	37.54	100.0	H	265.0	-19
1402.333333	---	29.07	54.00	24.93	200.0	V	194.0	-17
1608.033333	37.85	---	74.00	36.15	200.0	H	63.0	-16
2400.233333	---	29.87	54.00	24.13	200.0	H	8.0	-14
2528.300000	40.16	---	74.00	33.84	100.0	H	306.0	-14
4043.000000	---	32.77	54.00	21.23	100.0	H	320.0	-11
4197.700000	42.01	---	74.00	31.99	200.0	V	354.0	-11
6743.166667	47.48	---	74.00	26.52	200.0	V	207.0	-4
6783.966667	---	37.12	54.00	16.88	200.0	H	14.0	-4
10860.000000	---	42.95	54.00	11.05	100.0	V	134.0	0
11031.133333	53.37	---	74.00	20.63	100.0	H	279.0	1



Radiated Emission from 18GHz to 26.5GHz

Frequency (MHz)	Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
18612.850000	49.64	---	74.00	24.36	200.0	H	57.0	-2
18638.916667	---	38.46	54.00	15.54	200.0	H	201.0	-2
19907.116667	48.48	---	74.00	25.52	200.0	H	80.0	-1
19933.466667	---	38.67	54.00	15.33	200.0	H	0.0	-1
21444.483333	---	38.43	54.00	15.57	200.0	H	57.0	0
21465.733333	47.58	---	74.00	26.42	100.0	H	232.0	0
22745.833333	---	39.15	54.00	14.85	200.0	V	262.0	2
22823.750000	49.45	---	74.00	24.55	200.0	H	57.0	2
24343.833333	47.51	---	74.00	26.49	100.0	H	301.0	3
24381.516667	---	39.03	54.00	14.97	100.0	V	280.0	3
25933.050000	---	38.62	54.00	15.38	200.0	H	20.0	3
25949.766667	48.80	---	74.00	25.20	200.0	V	152.0	3



Radiated Emission from 26.5GHz to 40GHz

Frequency (MHz)	Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
27787.000000	52.15	---	74.00	21.85	200.0	H	226.0	6
27787.900000	---	42.46	54.00	11.54	200.0	H	179.0	6
30010.900000	54.90	---	74.00	19.10	100.0	V	174.0	7
30052.300000	---	45.08	54.00	8.92	200.0	H	281.0	7
32270.800000	---	45.65	54.00	8.35	200.0	V	74.0	8
32336.950000	55.77	---	74.00	18.23	200.0	V	170.0	8
34563.100000	55.70	---	74.00	18.30	100.0	V	0.0	8
34563.100000	---	45.94	54.00	8.06	200.0	V	22.0	8
36440.950000	54.44	---	74.00	19.56	200.0	H	39.0	8
36510.700000	---	44.98	54.00	9.02	200.0	V	138.0	8
38444.800000	---	46.33	54.00	7.67	200.0	V	355.0	11
38479.000000	55.49	---	74.00	18.51	200.0	V	201.0	11

## 3.2 Conducted Emission

### Ambient condition


Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC; PC is connected to server via a long LAN cable.

### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

### Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50
*: Decreases with the logarithm of the frequency.		




## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .  $U = 2.57$  dB.

## Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	56.49	---	65.88	9.39	70.0	9.000	L1	ON	21
0.16	---	29.58	55.63	26.05	70.0	9.000	L1	ON	21
0.63	---	26.84	46.00	19.16	70.0	9.000	L1	ON	20
0.65	34.84	---	56.00	21.16	70.0	9.000	L1	ON	20
2.11	29.44	---	56.00	26.56	70.0	9.000	L1	ON	20
2.11	---	21.39	46.00	24.61	70.0	9.000	L1	ON	20
3.26	34.66	---	56.00	21.34	70.0	9.000	L1	ON	19
4.99	---	31.33	46.00	14.67	70.0	9.000	L1	ON	19
5.42	---	31.30	50.00	18.70	70.0	9.000	L1	ON	19
5.81	36.49	---	60.00	23.51	70.0	9.000	L1	ON	19
18.85	29.85	---	60.00	30.15	70.0	9.000	L1	ON	20
19.03	---	22.07	50.00	27.93	70.0	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	54.49	---	65.88	11.39	70.0	9.000	N	ON	21
0.15	---	42.98	55.75	12.77	70.0	9.000	N	ON	21
0.63	---	27.28	46.00	18.72	70.0	9.000	N	ON	20
0.63	35.40	---	56.00	20.60	70.0	9.000	N	ON	20
2.02	27.45	---	56.00	28.55	70.0	9.000	N	ON	20
2.11	---	21.66	46.00	24.34	70.0	9.000	N	ON	20
3.40	36.21	---	56.00	19.79	70.0	9.000	N	ON	19
5.00	---	32.45	46.00	13.55	70.0	9.000	N	ON	19
5.26	---	31.88	50.00	18.12	70.0	9.000	N	ON	19
5.56	38.14	---	60.00	21.86	70.0	9.000	N	ON	19
15.56	23.60	---	60.00	36.40	70.0	9.000	N	ON	20
23.42	---	20.99	50.00	29.01	70.0	9.000	N	ON	20

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz



## 4 Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV40	100816	2021-05-15	2022-05-14
EMI Test Receiver	R&S	ESCI7	100936	2021-12-12	2022-12-11
Trilog Antenna	SCHWARZBECK	VULB 9163	1023	2020-05-05	2023-05-04
Horn Antenna	R&S	HF907	102723	2020-08-11	2023-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Standard Gain Horn	STEATITE	QSH-SL-26-40-K-15	16779	2019-12-24	2022-12-23
EMI Test Receiver	R&S	ESR	101667	2021-05-16	2022-05-15
LISN	R&S	ENV216	101171	2020-12-13	2022-12-12
Test software	EMC32	R&S	9.26.01	/	/
Test software	EMC32	R&S	10.35.10	/	/

\*\*\*\*\*END OF REPORT\*\*\*\*\*



## **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.



## **ANNEX B: Test Setup Photos**

The Test Setup Photos are submitted separately.