



# RF TEST REPORT

**Applicant**      Xiaomi Communications Co., Ltd.  
**FCC ID**          2AFZZ33SL  
**Product**        Mobile Phone  
**Brand**            Redmi  
**Model**            220733SL  
**Report No.**      R2206A0532-R2  
**Issue Date**      July 15, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2021)/ FCC CFR 47 Part 24E (2021)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

---

**TA Technology (Shanghai) Co., Ltd.**

Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

1. Test Laboratory .....	4
1.1. Notes of the test report.....	4
1.2. Test facility.....	4
1.3. Testing Location .....	4
2. General Description of Equipment under Test.....	5
2.1. Applicant and Manufacturer Information .....	5
2.2. General information .....	5
3. Applied Standards.....	7
4. Test Configuration.....	8
5. Test Case .....	10
5.1. RF Power Output and Effective Isotropic Radiated Power .....	10
5.2. Occupied Bandwidth .....	11
5.3. Band Edge Compliance.....	12
5.4. Peak-to-Average Power Ratio (PAPR) .....	13
5.5. Frequency Stability.....	14
5.6. Spurious Emissions at Antenna Terminals .....	16
5.7. Radiates Spurious Emission .....	17
6. Test Results .....	20
6.1. RF Power Output and Effective Isotropic Radiated Power .....	20
6.2. Occupied Bandwidth .....	27
6.3. Band Edge Compliance.....	37
6.4. Peak-to-Average Power Ratio (PAPR) .....	47
6.5. Frequency Stability.....	49
6.6. Spurious Emissions at Antenna Terminals .....	53
6.7. Radiates Spurious Emission .....	58
7. Main Test Instruments .....	64
ANNEX A: The EUT Appearance.....	65
ANNEX B: Test Setup Photos .....	66



## Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Isotropic Radiated Power	2.1046 24.232(c)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 /24.238(a)	PASS
4	Peak-to-Average Power Ratio	24.232/KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 24.235	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 24.238(a)	PASS
7	Radiates Spurious Emission	2.1053 / 24.238(a)	PASS

Date of Testing: June 22, 2022 ~ July 2, 2022  
Date of Sample Received: June 16, 2022

Note: PASS: The EUT complies with the essential requirements in the standard.  
FAIL: The EUT does not comply with the essential requirements in the standard.

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



## 1. Test Laboratory

### 1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### 2.1. Applicant and Manufacturer Information

Applicant	Xiaomi Communications Co., Ltd.
Applicant address	019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	Xiaomi Communications Co., Ltd.
Manufacturer address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

### 2.2. General information

EUT Description			
Model	220733SL		
IMEI	IMEI 1: 869674060135680 IMEI 2: 869674060135680		
Hardware Version	P1.1		
Software Version	Android 12		
Antenna Type	PIFA Antenna		
Antenna Gain	Band	Low Antenna	Upper Antenna
	GSM1900	-0.9 dBi	-1.0 dBi
	WCDMA Band II	-0.9 dBi	-1.0 dBi
	LTE Band 2	-0.9 dBi	-1.0 dBi
Test Mode(s)	GSM1900; WCDMA Band II; LTE Band 2;		
Test Modulation	(GSM/GPRS)GMSK, (EGPRS) GMSK/ 8PSK; (WCDMA) BPSK, QPSK; (LTE) QPSK, 16QAM;		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	24		
HSUPA UE Category	7		
LTE Category	4		
Maximum E.I.R.P	GSM 1900:	29.41 dBm	
	WCDMA Band II:	22.64 dBm	
	LTE Band 2:	22.67 dBm	
Rated Power Supply Voltage	3.85V		
Operating Voltage	Minimum: 3.6V    Maximum: 4.4V		
Operating Temperature	Lowest: 0°C    Highest: +40°C		
Testing Temperature	Lowest: -30°C    Highest: +50°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)



	GSM1900	1850 ~ 1910	1930 ~ 1990
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	LTE Band 2	1850 ~ 1910	1930 ~ 1990

Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.

2. Low antenna and Upper antenna can't transmit simultaneously.

Item	Configure 1	Configure 2
WIFI test socket	support	remove
PL sensor	support	remove

Note: This report only records data for Configure 1.

### 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**

**FCC CFR 47 Part 24E (2021)**

**FCC CFR47 Part 2 (2021)**

**Reference standard:**

**ANSI C63.26-2015**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

## 4. Test Configuration

There is more than one SIM card slot, each one should be applied throughout the compliance test respectively, and however, only the worst case (SIM 1) will be recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization for Low Antenna; Z axis, horizontal polarization for Upper Antenna GSM/WCDMA Band; X axis, horizontal polarization for Upper Antenna LTE Band) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated. Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation	
	GSM 1900	WCDMA Band II
RF Power Output and Effective Isotropic Radiated Power	GSM GPRS EGPRS	RMC HSDPA/HSUPA DC-HSDPA
Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiates Spurious Emission	GSM	RMC





Test modes are chosen to be reported as the worst case configuration below for LTE Band 2:

Test items	Bandwidth (MHz)						Modulation		RB			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	H
RF Power Output and Effective Isotropic Radiated Power	O	O	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	O	O	-	-	-	O	-
Spurious Emissions at Antenna Terminals	O	O	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	O	-	-	O	O	-	O	-	-	-	O	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

## 5. Test Case

### 5.1. RF Power Output and Effective Isotropic Radiated Power

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$$\text{EIRP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$

where:dBd refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB.)}$$

#### Test Setup



#### Limits

No specific RF power output requirements in part 2.1046.

Rule Part 24.232(c) Mobile and portable stations are limited to 2 watts EIRP.

Rule Part 24.232(e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Limit	$\leq 2 \text{ W}$ (33 dBm)
-------	-----------------------------

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4 \text{ dB}$  for RF power output,  $k = 2$ ,  $U = 1.19 \text{ dB}$  for EIRP.

#### Test Results

Refer to the section 6.1 of this report for test data.

## 5.2.Occupied Bandwidth

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to  $\geq 1\%EBW$ , VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

### Test Setup



### Limits

No specific occupied bandwidth requirements in part 2.1049.

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 624\text{Hz}$ .

### Test Results

Refer to the section 6.2 of this report for test data.

### 5.3. Band Edge Compliance

#### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to  $\geq 1\%EBW$ , VBW is set to 3x RBW.

Spectrum analyzer plots are included on the following pages.

#### Test Setup



#### Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10} (P)$  dB.”

Limit	-13 dBm
-------	---------

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U=0.684dB$ .

#### Test Results

Refer to the section 6.3 of this report for test data.

### 5.4. Peak-to-Average Power Ratio (PAPR)

#### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

Measure the total peak power and record as PPK. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = PPK (dBm) - PAvg (dBm).$$

#### Test Setup



#### Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

#### Test Results

Refer to the section 6.4 of this report for test data.

## 5.5. Frequency Stability

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

#### Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.


#### Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

**Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.6 V and 4.4 V, with a nominal voltage of 3.85V.

### Test setup



**Limits**

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 3$ ,  $U = 0.01\text{ppm}$ .

**Test Results**

Refer to the section 6.5 of this report for test data.

## 5.6. Spurious Emissions at Antenna Terminals

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.

RBW is set to 100kHz, VBW is set to 300kHz for 30MHz~1GHz

RBW is set to 1MHz, VBW is set to 3MHz for above 1GHz, Sweep is set to ATUO.

RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),


RBW is set to 10 kHz (0.15 MHz~ 30 MHz)

RBW is set to 100 kHz (30MHz~1000 MHz)

RBW is set to 1000 kHz (above 1000MHz)

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

### Test setup



### Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB.”

Limit	-13 dBm

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-20GHz	1.407 dB

### Test Results

Refer to the section 6.6 of this report for test data.



## 5.7. Radiates Spurious Emission

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26-2015.
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
Power(EIRP)=PMea- PAg - Pcl + Ga  
The measurement results are amend as described below:  
Power(EIRP)=PMea- Pcl + Ga
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dB.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

**Test setup**


**9KHz~ 30MHz**



**30MHz~ 1GHz**



**Above 1GHz**



Note: Area side: 2.4mX3.6m

**Limits**

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB.”

Limit	-13 dBm
-------	---------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

**Test Results**

Refer to the section 6.7 of this report for test data.

## 6. Test Results

### 6.1.RF Power Output and Effective Isotropic Radiated Power

GSM 1900 Low Antenna		Maximum Output Power (dBm)			EIRP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8	512/1850.2	661/1880	810/1909.8
GSM	CS	29.43	29.48	29.35	28.53	28.58	28.45
GPRS/EGPRS (GMSK)	1 Tx Slot	29.43	29.48	29.35	28.53	28.58	28.45
	2 Tx Slots	26.04	25.96	25.90	25.14	25.06	25.00
	3 Tx Slots	25.87	25.72	25.72	24.97	24.82	24.82
	4 Tx Slots	24.49	24.56	24.32	23.59	23.66	23.42
EGPRS (8PSK)	1 Tx Slot	25.82	25.79	25.72	24.92	24.89	24.82
	2 Tx Slots	23.51	23.52	23.54	22.61	22.62	22.64
	3 Tx Slots	21.82	21.94	21.82	20.92	21.04	20.92
	4 Tx Slots	20.53	20.54	20.56	19.63	19.64	19.66

GSM 1900 Upper Antenna		Maximum Output Power (dBm)			EIRP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8	512/1850.2	661/1880	810/1909.8
GSM	CS	30.40	30.41	30.15	29.40	29.41	29.15
GPRS/EGPRS (GMSK)	1 Tx Slot	30.40	30.41	30.15	29.40	29.41	29.15
	2 Tx Slots	26.66	26.77	26.42	25.66	25.77	25.42
	3 Tx Slots	26.48	26.56	26.17	25.48	25.56	25.17
	4 Tx Slots	25.00	25.11	24.76	24.00	24.11	23.76
EGPRS (8PSK)	1 Tx Slot	26.78	26.49	26.59	25.78	25.49	25.59
	2 Tx Slots	23.51	23.56	23.61	22.51	22.56	22.61
	3 Tx Slots	22.82	22.60	22.57	21.82	21.60	21.57
	4 Tx Slots	21.46	21.26	21.32	20.46	20.26	20.32



WCDMA Band II Low Antenna		Maximum Output Power (dBm)			EIRP (dBm)		
		Channel/Frenqucy(MHz)			Channel/Frenqucy(MHz)		
		9262/1852.4	9400/1880	9538/1907.6	9262/1852.4	9400/1880	9538/1907.6
RMC	12.2k	22.83	<b>22.78</b>	22.77	21.93	21.88	21.87
AMR	12.2k	22.73	22.69	22.64	21.83	21.79	21.74
HSDPA	Subtest 1	22.25	22.20	22.19	21.35	21.30	21.29
	Subtest 2	22.24	22.19	22.18	21.34	21.29	21.28
	Subtest 3	21.73	21.68	21.67	20.83	20.78	20.77
	Subtest 4	21.72	21.67	21.66	20.82	20.77	20.76
HSUPA	Subtest 1	20.81	20.76	20.75	19.91	19.86	19.85
	Subtest 2	20.40	20.35	20.34	19.50	19.45	19.44
	Subtest 3	21.38	21.34	21.33	20.48	20.44	20.43
	Subtest 4	19.77	19.73	19.72	18.87	18.83	18.82
	Subtest 5	21.36	21.32	21.31	20.46	20.42	20.41
DC-HSDPA	Subtest 1	22.17	22.14	22.11	21.27	21.24	21.21
	Subtest 2	22.16	22.13	22.10	21.26	21.23	21.20
	Subtest 3	21.74	21.62	21.61	20.84	20.72	20.71
	Subtest 4	21.73	21.61	21.60	20.83	20.71	20.70

WCDMA Band II Upper Antenna		Maximum Output Power (dBm)			EIRP (dBm)		
		Channel/Frenqucy(MHz)			Channel/Frenqucy(MHz)		
		9262/1852.4	9400/1880	9538/1907.6	9262/1852.4	9400/1880	9538/1907.6
RMC	12.2k	<b>23.64</b>	23.56	23.62	22.64	22.56	22.62
AMR	12.2k	23.54	23.47	23.49	22.54	22.47	22.49
HSDPA	Subtest 1	23.06	22.98	23.04	22.06	21.98	22.04
	Subtest 2	23.05	22.97	23.03	22.05	21.97	22.03
	Subtest 3	22.54	22.46	22.52	21.54	21.46	21.52
	Subtest 4	22.53	22.45	22.51	21.53	21.45	21.51
HSUPA	Subtest 1	21.62	21.54	21.60	20.62	20.54	20.60
	Subtest 2	21.21	21.13	21.19	20.21	20.13	20.19
	Subtest 3	22.19	22.12	22.18	21.19	21.12	21.18
	Subtest 4	20.58	20.51	20.57	19.58	19.51	19.57
	Subtest 5	22.17	22.10	22.16	21.17	21.10	21.16
DC-HSDPA	Subtest 1	22.98	22.92	22.96	21.98	21.92	21.96
	Subtest 2	22.97	22.91	22.95	21.97	21.91	21.95
	Subtest 3	22.55	22.40	22.46	21.55	21.40	21.46
	Subtest 4	22.54	22.39	22.45	21.54	21.39	21.45



LTE Band 2 Low Antenna				Maximum Output Power (dBm)			EIRP (dBm)		
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18607/1850 .7	18900/1880	19193/1909 .3	18607/1850 .7	18900/1880	19193/1909 .3
1.4MHz	QPSK	1	0	22.52	22.46	22.40	21.62	21.56	21.50
		1	2	22.76	22.72	22.75	21.86	21.82	21.85
		1	5	22.28	22.29	22.51	21.38	21.39	21.61
		3	0	22.66	22.72	22.64	21.76	21.82	21.74
		3	2	22.69	22.66	22.73	21.79	21.76	21.83
		3	3	22.68	22.64	22.56	21.78	21.74	21.66
		6	0	21.72	21.76	21.70	20.82	20.86	20.80
	16QAM	1	0	21.86	21.75	21.69	20.96	20.85	20.79
		1	2	22.11	21.99	21.98	21.21	21.09	21.08
		1	5	21.68	21.56	21.72	20.78	20.66	20.82
		3	0	21.66	21.69	21.63	20.76	20.79	20.73
		3	2	21.76	21.66	21.71	20.86	20.76	20.81
		3	3	21.73	21.68	21.51	20.83	20.78	20.61
		6	0	20.72	20.77	20.71	19.82	19.87	19.81
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18615/1851 .5	18900/1880	19185/1908 .5	18615/1851 .5	18900/1880	19185/1908 .5
3MHz	QPSK	1	0	22.54	22.50	22.43	21.64	21.60	21.53
		1	7	22.74	22.75	22.79	21.84	21.85	21.89
		1	14	22.31	22.34	22.55	21.41	21.44	21.65
		8	0	21.76	21.84	21.77	20.86	20.94	20.87
		8	4	21.81	21.76	21.85	20.91	20.86	20.95
		8	7	21.78	21.75	21.66	20.88	20.85	20.76
		15	0	21.72	21.80	21.73	20.82	20.90	20.83
	16QAM	1	0	21.86	21.77	21.72	20.96	20.87	20.82
		1	7	22.11	21.99	22.02	21.21	21.09	21.12
		1	14	21.70	21.60	21.75	20.80	20.70	20.85
		8	0	20.77	20.82	20.75	19.87	19.92	19.85
		8	4	20.87	20.79	20.83	19.97	19.89	19.93
		8	7	20.83	20.80	20.64	19.93	19.90	19.74
		15	0	20.75	20.81	20.74	19.85	19.91	19.84
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18625/1852 .5	18900/1880	19175/1907 .5	18625/1852 .5	18900/1880	19175/1907 .5
5MHz	QPSK	1	0	22.51	22.48	22.39	21.61	21.58	21.49
		1	13	22.72	22.71	22.76	21.82	21.81	21.86
		1	24	22.28	22.29	22.51	21.38	21.39	21.61



	16QAM	12	0	21.73	21.79	21.73	20.83	20.89	20.83
		12	6	21.79	21.72	21.80	20.89	20.82	20.90
		12	13	21.76	21.73	21.62	20.86	20.83	20.72
		25	0	21.72	21.79	21.71	20.82	20.89	20.81
		1	0	21.86	21.73	21.69	20.96	20.83	20.79
		1	13	22.11	21.97	21.99	21.21	21.07	21.09
		1	24	21.67	21.58	21.71	20.77	20.68	20.81
		12	0	20.75	20.78	20.72	19.85	19.88	19.82
		12	6	20.84	20.74	20.79	19.94	19.84	19.89
		12	13	20.80	20.75	20.60	19.90	19.85	19.70
25	0	20.73	20.77	20.69	19.83	19.87	19.79		
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905	18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	22.53	22.49	22.42	21.63	21.59	21.52
		1	25	22.75	22.76	22.80	21.85	21.86	21.90
		1	49	22.30	22.33	22.54	21.40	21.43	21.64
		25	0	21.76	21.84	21.77	20.86	20.94	20.87
		25	13	21.82	21.77	21.84	20.92	20.87	20.94
		25	25	21.78	21.77	21.67	20.88	20.87	20.77
		50	0	21.76	21.81	21.75	20.86	20.91	20.85
	16QAM	1	0	21.90	21.76	21.71	21.00	20.86	20.81
		1	25	22.15	22.01	22.02	21.25	21.11	21.12
		1	49	21.70	21.60	21.74	20.80	20.70	20.84
		25	0	20.78	20.83	20.76	19.88	19.93	19.86
		25	13	20.86	20.78	20.82	19.96	19.88	19.92
		25	25	20.83	20.80	20.64	19.93	19.90	19.74
		50	0	20.76	20.82	20.73	19.86	19.92	19.83
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5	18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	22.52	22.45	22.40	21.62	21.55	21.50
		1	38	22.73	22.75	22.77	21.83	21.85	21.87
		1	74	22.27	22.28	22.50	21.37	21.38	21.60
		36	0	21.74	21.80	21.74	20.84	20.90	20.84
		36	18	21.79	21.72	21.80	20.89	20.82	20.90
		36	39	21.75	21.74	21.63	20.85	20.84	20.73
		75	0	21.74	21.77	21.70	20.84	20.87	20.80
	16QAM	1	0	21.88	21.74	21.69	20.98	20.84	20.79
		1	38	22.13	21.98	22.00	21.23	21.08	21.10
		1	74	21.68	21.56	21.71	20.78	20.66	20.81
		36	0	20.75	20.81	20.73	19.85	19.91	19.83
		36	18	20.83	20.73	20.78	19.93	19.83	19.88
		36	39	20.81	20.76	20.61	19.91	19.86	19.71



Bandwidth	Modulation	75	0	20.73	20.77	20.69	19.83	19.87	19.79
		RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900	18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	22.49	22.41	22.37	21.59	21.51	21.47
		1	50	22.72	22.71	22.75	21.82	21.81	21.85
		1	99	22.25	22.27	22.47	21.35	21.37	21.57
		50	0	21.71	21.75	21.70	20.81	20.85	20.80
		50	25	21.77	21.68	21.77	20.87	20.78	20.87
		50	50	21.72	21.69	21.59	20.82	20.79	20.69
		100	0	21.71	21.72	21.66	20.81	20.82	20.76
	16QAM	1	0	21.85	21.70	21.64	20.95	20.80	20.74
		1	50	22.10	21.96	21.96	21.20	21.06	21.06
		1	99	21.65	21.53	21.69	20.75	20.63	20.79
		50	0	20.72	20.77	20.70	19.82	19.87	19.80
		50	25	20.80	20.71	20.75	19.90	19.81	19.85
		50	50	20.78	20.71	20.57	19.88	19.81	19.67
		100	0	20.71	20.73	20.66	19.81	19.83	19.76

LTE Band 2 Upper Antenna				Maximum Output Power (dBm)			EIRP (dBm)		
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18607/1850	18900/1880	19193/1909	18607/1850	18900/1880	19193/1909
				.7		.3	.7		.3
1.4MHz	QPSK	1	0	23.27	23.34	23.27	22.27	22.34	22.27
		1	2	23.62	23.63	23.53	22.62	22.63	22.53
		1	5	23.15	23.16	23.28	22.15	22.16	22.28
		3	0	23.44	23.53	23.49	22.44	22.53	22.49
		3	2	23.48	23.55	23.58	22.48	22.55	22.58
		3	3	23.49	23.50	23.41	22.49	22.50	22.41
		6	0	22.51	22.59	22.58	21.51	21.59	21.58
	16QAM	1	0	22.63	22.59	22.60	21.63	21.59	21.60
		1	2	22.84	22.90	22.75	21.84	21.90	21.75
		1	5	22.45	22.50	22.59	21.45	21.50	21.59
		3	0	22.44	22.49	22.49	21.44	21.49	21.49
		3	2	22.56	22.55	22.55	21.56	21.55	21.55
		3	3	22.51	22.54	22.35	21.51	21.54	21.35
		6	0	21.57	21.66	21.60	20.57	20.66	20.60
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18615/1851	18900/1880	19185/1908	18615/1851	18900/1880	19185/1908
				.5		.5	.5		.5
3MHz	QPSK	1	0	23.29	23.38	23.30	22.29	22.38	22.30
		1	7	23.60	23.66	23.57	22.60	22.66	22.57
		1	14	23.18	23.21	23.32	22.18	22.21	22.32





		8	0	22.54	22.65	22.62	21.54	21.65	21.62
		8	4	22.60	22.65	22.70	21.60	21.65	21.70
		8	7	22.59	22.61	22.51	21.59	21.61	21.51
		15	0	22.51	22.63	22.61	21.51	21.63	21.61
	16QAM	1	0	22.63	22.61	22.63	21.63	21.61	21.63
		1	7	22.84	22.90	22.79	21.84	21.90	21.79
		1	14	22.47	22.54	22.62	21.47	21.54	21.62
		8	0	21.55	21.62	21.61	20.55	20.62	20.61
		8	4	21.67	21.68	21.67	20.67	20.68	20.67
		8	7	21.61	21.66	21.48	20.61	20.66	20.48
		15	0	21.60	21.70	21.63	20.60	20.70	20.63

Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18625/1852.5	18900/1880	19175/1907.5	18625/1852.5	18900/1880	19175/1907.5

5MHz	QPSK	1	0	23.26	23.36	23.26	22.26	22.36	22.26
		1	13	23.58	23.62	23.54	22.58	22.62	22.54
		1	24	23.15	23.16	23.28	22.15	22.16	22.28
		12	0	22.51	22.60	22.58	21.51	21.60	21.58
		12	6	22.58	22.61	22.65	21.58	21.61	21.65
		12	13	22.57	22.59	22.47	21.57	21.59	21.47
		25	0	22.51	22.62	22.59	21.51	21.62	21.59
	16QAM	1	0	22.63	22.57	22.60	21.63	21.57	21.60
		1	13	22.84	22.88	22.76	21.84	21.88	21.76
		1	24	22.44	22.52	22.58	21.44	21.52	21.58
		12	0	21.53	21.58	21.58	20.53	20.58	20.58
		12	6	21.64	21.63	21.63	20.64	20.63	20.63
		12	13	21.58	21.61	21.44	20.58	20.61	20.44
		25	0	21.58	21.66	21.58	20.58	20.66	20.58

Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18650/1855	18900/1880	19150/1905	18650/1855	18900/1880	19150/1905

10MHz	QPSK	1	0	23.28	23.37	23.29	22.28	22.37	22.29
		1	25	23.61	23.67	23.58	22.61	22.67	22.58
		1	49	23.17	23.20	23.31	22.17	22.20	22.31
		25	0	22.54	22.65	22.62	21.54	21.65	21.62
		25	13	22.61	22.66	22.69	21.61	21.66	21.69
		25	25	22.59	22.63	22.52	21.59	21.63	21.52
		50	0	22.55	22.64	22.63	21.55	21.64	21.63
	16QAM	1	0	22.67	22.60	22.62	21.67	21.60	21.62
		1	25	22.88	22.92	22.79	21.88	21.92	21.79
		1	49	22.47	22.54	22.61	21.47	21.54	21.61
		25	0	21.56	21.63	21.62	20.56	20.63	20.62
		25	13	21.66	21.67	21.66	20.66	20.67	20.66
		25	25	21.61	21.66	21.48	20.61	20.66	20.48



Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18675/1857.5	18900/1880	19125/1902.5	18675/1857.5	18900/1880	19125/1902.5
				50	0	21.61	21.71	21.62	20.61
15MHz	QPSK	1	0	23.27	23.33	23.27	22.27	22.33	22.27
		1	38	23.59	23.66	23.55	22.59	22.66	22.55
		1	74	23.14	23.15	23.27	22.14	22.15	22.27
		36	0	22.52	22.61	22.59	21.52	21.61	21.59
		36	18	22.58	22.61	22.65	21.58	21.61	21.65
		36	39	22.56	22.60	22.48	21.56	21.60	21.48
		75	0	22.53	22.60	22.58	21.53	21.60	21.58
	16QAM	1	0	22.65	22.58	22.60	21.65	21.58	21.60
		1	38	22.86	22.89	22.77	21.86	21.89	21.77
		1	74	22.45	22.50	22.58	21.45	21.50	21.58
		36	0	21.53	21.61	21.59	20.53	20.61	20.59
		36	18	21.63	21.62	21.62	20.63	20.62	20.62
		36	39	21.59	21.62	21.45	20.59	20.62	20.45
		75	0	21.58	21.66	21.58	20.58	20.66	20.58
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				18700/1860	18900/1880	19100/1900	18700/1860	18900/1880	19100/1900
				50	0	23.24	23.29	23.24	22.24
20MHz	QPSK	1	50	23.58	23.62	23.53	22.58	22.62	22.53
		1	99	23.12	23.14	23.24	22.12	22.14	22.24
		50	0	22.49	22.56	22.55	21.49	21.56	21.55
		50	25	22.56	22.57	22.62	21.56	21.57	21.62
		50	50	22.53	22.55	22.44	21.53	21.55	21.44
		100	0	22.50	22.55	22.54	21.50	21.55	21.54
		16QAM	1	0	22.62	22.54	22.55	21.62	21.54
	1		50	22.83	22.87	22.73	21.83	21.87	21.73
	1		99	22.42	22.47	22.56	21.42	21.47	21.56
	50		0	21.50	21.57	21.56	20.50	20.57	20.56
	50		25	21.60	21.60	21.59	20.60	20.60	20.59
	50		50	21.56	21.57	21.41	20.56	20.57	20.41
	100		0	21.56	21.62	21.55	20.56	20.62	20.55







### 6.2.Occupied Bandwidth







Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
<b>GSM 1900 (GMSK)</b>	512	1850.2	0.243	0.314
	661	1880.0	0.253	0.316
	810	1909.8	0.244	0.308
<b>GPRS 1900 (GMSK)</b>	512	1850.2	0.244	0.313
	661	1880.0	0.251	0.317
	810	1909.8	0.242	0.309
<b>EGPRS 1900 (8PSK)</b>	512	1850.2	0.255	0.319
	661	1880.0	0.248	0.310
	810	1909.8	0.255	0.319
<b>WCDMA Band II (RMC)</b>	9262	1852.4	4.176	4.691
	9400	1880	4.165	4.706
	9538	1907.6	4.178	4.704







LTE Band 2						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	18607	1850.7	1.096	1.272
			18900	1880.0	1.091	1.268
			19193	1909.3	1.096	1.286
		3	18615	1851.5	2.704	2.914
			18900	1880	2.699	2.911
			19185	1908.5	2.686	2.932
		5	18625	1852.5	4.520	4.924
			18900	1880	4.504	4.914
			19175	1907.5	4.501	4.848
		10	18650	1855	8.987	9.713
			18900	1880	9.007	9.672
			19150	1905	9.002	9.741
		15	18675	1857.5	13.489	14.527
			18900	1880	13.482	14.555
			19125	1902.5	13.439	14.536
		20	18700	1860	17.958	19.439
			18900	1880	17.938	19.260









			19100	1900	17.868	19.210
	16QAM	1.4	18607	1850.7	1.092	1.277
			18900	1880.0	1.101	1.311
			19193	1909.3	1.091	1.275
		3	18615	1851.5	2.700	2.933
			18900	1880	2.692	2.940
			19185	1908.5	2.690	2.946
		5	18625	1852.5	4.498	4.866
			18900	1880	4.520	4.946
			19175	1907.5	4.517	4.900
		10	18650	1855	8.993	9.687
			18900	1880	8.985	9.700
			19150	1905	9.005	9.553
		15	18675	1857.5	13.487	14.508
			18900	1880	13.467	14.396
			19125	1902.5	13.479	14.415
		20	18700	1860	17.974	19.347
			18900	1880	18.041	19.194
			19100	1900	17.946	19.267







































LTE Band 2 15MHz 16QAM CH-Low




LTE Band 2 20MHz 16QAM CH-Low




LTE Band 2 15MHz 16QAM CH-Middle




LTE Band 2 20MHz 16QAM CH-Middle




LTE Band 2 15MHz 16QAM CH-High



LTE Band 2 20MHz 16QAM CH-High



### 6.3. Band Edge Compliance





### WCDMA Band II RMC CH-Low




### WCDMA Band II RMC CH-High






LTE Band 2 1.4MHz QPSK 1RB CH-Low



LTE Band 2 1.4MHz QPSK 1RB CH-High




LTE Band 2 1.4MHz QPSK 100%RB CH-Low




LTE Band 2 1.4MHz QPSK 100%RB CH-High



LTE Band 2 3MHz QPSK 1RB CH-Low




LTE Band 2 3MHz QPSK 1RB CH-High







LTE Band 2 3MHz QPSK 100%RB CH-Low




LTE Band 2 3MHz QPSK 100%RB CH-High




LTE Band 2 5MHz QPSK 1RB CH-Low




LTE Band 2 5MHz QPSK 1RB CH-High



LTE Band 2 5MHz QPSK 100%RB CH-Low



LTE Band 2 5MHz QPSK 100%RB CH-High









LTE Band 2 10MHz QPSK 1RB CH-Low




LTE Band 2 10MHz QPSK 1RB CH-High



LTE Band 2 10MHz QPSK 100%RB CH-Low




LTE Band 2 10MHz QPSK 100%RB CH-High




LTE Band 2 15MHz QPSK 1RB CH-Low



LTE Band 2 15MHz QPSK 1RB CH-High




LTE Band 2 15MHz QPSK 100%RB CH-Low



LTE Band 2 15MHz QPSK 100%RB CH-High




LTE Band 2 20MHz QPSK 1RB CH-Low



LTE Band 2 20MHz QPSK 1RB CH-High



LTE Band 2 20MHz QPSK 100%RB CH-Low




LTE Band 2 20MHz QPSK 100%RB CH-High







LTE Band 2 1.4MHz 16QAM 1RB CH-Low



LTE Band 2 1.4MHz 16QAM 1RB CH-High



LTE Band 2 1.4MHz 16QAM 100%RB CH-Low




LTE Band 2 1.4MHz 16QAM 100%RB CH-High



LTE Band 2 3MHz 16QAM 1RB CH-Low




LTE Band 2 3MHz 16QAM 1RB CH-High






LTE Band 2 3MHz 16QAM 100%RB CH-Low




LTE Band 2 3MHz 16QAM 100%RB CH-High




LTE Band 2 5MHz 16QAM 1RB CH-Low




LTE Band 2 5MHz 16QAM 1RB CH-High



LTE Band 2 5MHz 16QAM 100%RB CH-Low



LTE Band 2 5MHz 16QAM 100%RB CH-High






### LTE Band 2 10MHz 16QAM 1RB CH-Low




### LTE Band 2 10MHz 16QAM 1RB CH-High




### LTE Band 2 10MHz 16QAM 100%RB CH-Low




### LTE Band 2 10MHz 16QAM 100%RB CH-High



### LTE Band 2 15MHz 16QAM 1RB CH-Low




### LTE Band 2 15MHz 16QAM 1RB CH-High






LTE Band 2 15MHz 16QAM 100%RB CH-Low




LTE Band 2 15MHz 16QAM 100%RB CH-High



LTE Band 2 20MHz 16QAM 1RB CH-Low



LTE Band 2 20MHz 16QAM 1RB CH-High



LTE Band 2 20MHz 16QAM 100%RB CH-Low



LTE Band 2 20MHz 16QAM 100%RB CH-High



### 6.4. Peak-to-Average Power Ratio (PAPR)

Mode	Channel	Frequency (MHz)	Peak(dBm)	Avg(dBm)	PAPR(dB)	Limit(dB)	Conclusion
GSM 1900 (GMSK)	512	1850.2	30.75	27.92	2.83	≤13	PASS
	661	1880	30.67	27.82	2.85	≤13	PASS
	810	1909.8	30.48	25.63	4.85	≤13	PASS
GPRS 1900 (GMSK)	512	1850.2	30.73	27.90	2.83	≤13	PASS
	661	1880	30.54	27.70	2.84	≤13	PASS
	810	1909.8	30.41	25.63	4.78	≤13	PASS
EGPRS 1900 (8PSK)	512	1850.2	29.58	23.95	5.63	≤13	PASS
	661	1880	29.48	23.83	5.65	≤13	PASS
	810	1909.8	29.66	22.27	7.39	≤13	PASS
WCDMA Band II (RMC)	9262	1852.4	26.25	23.52	2.73	≤13	PASS
	9400	1880	26.08	23.54	2.54	≤13	PASS
	9538	1907.6	25.88	23.73	2.15	≤13	PASS

LTE Band 2								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	18607	1850.7	27.85	22.75	5.10	≤13	PASS
		18900	1880.0	27.49	22.70	4.79	≤13	PASS
		19193	1909.3	27.24	22.76	4.48	≤13	PASS
	3	18615	1851.5	27.86	22.71	5.15	≤13	PASS
		18900	1880	27.48	22.61	4.87	≤13	PASS
		19185	1908.5	27.19	22.68	4.51	≤13	PASS
	5	18625	1852.5	27.94	22.72	5.22	≤13	PASS
		18900	1880	27.58	22.60	4.98	≤13	PASS
		19175	1907.5	27.13	22.68	4.45	≤13	PASS
	10	18650	1855	27.96	22.76	5.20	≤13	PASS
		18900	1880	27.64	22.66	4.98	≤13	PASS
		19150	1905	27.10	22.67	4.43	≤13	PASS
	15	18675	1857.5	28.25	22.80	5.45	≤13	PASS
		18900	1880	28.10	22.75	5.35	≤13	PASS
		19125	1902.5	27.61	22.75	4.86	≤13	PASS
	20	18700	1860	27.96	22.67	5.29	≤13	PASS
		18900	1880	27.92	22.68	5.24	≤13	PASS
		19100	1900	27.55	22.53	5.02	≤13	PASS



16QAM	1.4	18607	1850.7	27.70	21.77	5.93	≤13	PASS
		18900	1880.0	27.24	21.66	5.58	≤13	PASS
		19193	1909.3	27.13	21.75	5.38	≤13	PASS
	3	18615	1851.5	27.74	21.72	6.02	≤13	PASS
		18900	1880	27.38	21.67	5.71	≤13	PASS
		19185	1908.5	27.06	21.67	5.39	≤13	PASS
	5	18625	1852.5	27.72	21.74	5.98	≤13	PASS
		18900	1880	27.36	21.65	5.71	≤13	PASS
		19175	1907.5	26.95	21.67	5.28	≤13	PASS
	10	18650	1855	27.78	21.78	6.00	≤13	PASS
		18900	1880	27.40	21.62	5.78	≤13	PASS
		19150	1905	26.89	21.65	5.24	≤13	PASS
	15	18675	1857.5	27.84	21.75	6.09	≤13	PASS
		18900	1880	27.69	21.71	5.98	≤13	PASS
		19125	1902.5	27.24	21.69	5.55	≤13	PASS
	20	18700	1860	27.68	21.68	6.00	≤13	PASS
		18900	1880	27.70	21.70	6.00	≤13	PASS
		19100	1900	27.33	21.54	5.79	≤13	PASS



### 6.5. Frequency Stability

GSM 1900						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
Normal (25°C)	Normal	4.76	1.55	0.00253	0.00082	PASS
Extreme (50°C)		3.51	8.18	0.00187	0.00435	PASS
Extreme (40°C)		15.32	2.69	0.00815	0.00143	PASS
Extreme (30°C)		10.08	11.72	0.00536	0.00623	PASS
Extreme (20°C)		1.36	5.31	0.00072	0.00283	PASS
Extreme (10°C)		16.01	5.17	0.00852	0.00275	PASS
Extreme (0°C)		1.90	17.18	0.00101	0.00914	PASS
Extreme (-10°C)		14.67	17.19	0.00780	0.00914	PASS
Extreme (-20°C)		15.62	13.72	0.00831	0.00730	PASS
Extreme (-30°C)		5.81	9.60	0.00309	0.00510	PASS
25°C	LV	2.34	9.04	0.00125	0.00481	PASS
	HV	6.62	17.84	0.00352	0.00949	PASS

WCDMA Band 2						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal (25°C)	Normal	3.84	14.64	0.00204	0.00779	PASS
Extreme (50°C)		5.70	6.38	0.00303	0.00339	PASS
Extreme (40°C)		9.01	4.67	0.00479	0.00248	PASS
Extreme (30°C)		7.44	12.41	0.00396	0.00660	PASS
Extreme (20°C)		14.58	8.15	0.00775	0.00434	PASS
Extreme (10°C)		11.58	14.05	0.00616	0.00747	PASS
Extreme (0°C)		17.54	12.25	0.00933	0.00652	PASS
Extreme (-10°C)		7.09	13.68	0.00377	0.00728	PASS
Extreme (-20°C)		4.03	15.16	0.00215	0.00806	PASS
Extreme (-30°C)		12.63	7.99	0.00672	0.00425	PASS
25°C	LV	2.89	16.49	0.00154	0.00877	PASS
	HV	5.89	1.19	0.00313	0.00063	PASS

LTE Band 2						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	14.12	3.76	0.00751	0.00200	PASS
Extreme (50°C)		9.92	15.08	0.00528	0.00802	PASS
Extreme (40°C)		4.66	5.84	0.00248	0.00311	PASS
Extreme (30°C)		3.49	15.02	0.00186	0.00799	PASS
Extreme (20°C)		3.81	12.58	0.00203	0.00669	PASS
Extreme (10°C)		3.24	6.94	0.00173	0.00369	PASS
Extreme (0°C)		9.24	2.75	0.00491	0.00146	PASS
Extreme (-10°C)		5.32	11.67	0.00283	0.00621	PASS
Extreme (-20°C)		13.95	3.53	0.00742	0.00188	PASS
Extreme (-30°C)		16.90	10.96	0.00899	0.00583	PASS
25°C		LV	16.46	1.94	0.00876	0.00103
	HV	15.79	4.25	0.00840	0.00226	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	11.41	10.99	0.00607	0.00584	PASS
Extreme (50°C)		2.05	14.79	0.00109	0.00787	PASS
Extreme (40°C)		8.33	17.44	0.00443	0.00928	PASS
Extreme (30°C)		7.79	17.44	0.00414	0.00928	PASS
Extreme (20°C)		4.75	13.28	0.00253	0.00706	PASS
Extreme (10°C)		7.33	5.28	0.00390	0.00281	PASS
Extreme (0°C)		4.38	5.73	0.00233	0.00305	PASS
Extreme (-10°C)		17.86	10.39	0.00950	0.00553	PASS
Extreme (-20°C)		13.48	6.84	0.00717	0.00364	PASS
Extreme (-30°C)		16.98	4.38	0.00903	0.00233	PASS
25°C		LV	1.27	4.26	0.00068	0.00227
	HV	7.41	5.90	0.00394	0.00314	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	14.38	7.28	0.00765	0.00387	PASS
Extreme (50°C)		12.66	6.98	0.00673	0.00371	PASS
Extreme (40°C)		8.46	6.28	0.00450	0.00334	PASS
Extreme (30°C)		13.07	16.73	0.00695	0.00890	PASS
Extreme (20°C)		11.44	9.09	0.00609	0.00484	PASS




Extreme (10°C)		13.59	9.68	0.00723	0.00515	PASS
Extreme (0°C)		10.43	9.06	0.00555	0.00482	PASS
Extreme (-10°C)		9.33	8.84	0.00496	0.00470	PASS
Extreme (-20°C)		9.87	4.04	0.00525	0.00215	PASS
Extreme (-30°C)		16.76	15.68	0.00891	0.00834	PASS
25°C	LV	15.49	13.49	0.00824	0.00717	PASS
	HV	1.36	5.13	0.00072	0.00273	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	1.66	5.00	0.00089	0.00266	PASS
Extreme (50°C)		15.79	13.88	0.00840	0.00738	PASS
Extreme (40°C)		2.91	12.99	0.00155	0.00691	PASS
Extreme (30°C)		6.69	9.58	0.00356	0.00509	PASS
Extreme (20°C)		15.32	5.26	0.00815	0.00280	PASS
Extreme (10°C)		4.71	3.84	0.00251	0.00204	PASS
Extreme (0°C)		16.83	10.67	0.00895	0.00568	PASS
Extreme (-10°C)		15.53	1.79	0.00826	0.00095	PASS
Extreme (-20°C)		17.03	12.59	0.00906	0.00670	PASS
Extreme (-30°C)		4.81	14.90	0.00256	0.00793	PASS
25°C	LV	16.89	1.56	0.00898	0.00083	PASS
	HV	8.13	8.62	0.00432	0.00459	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	15MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	10.90	3.72	0.00580	0.00198	PASS
Extreme (50°C)		6.13	14.48	0.00326	0.00770	PASS
Extreme (40°C)		17.92	10.02	0.00953	0.00533	PASS
Extreme (30°C)		8.74	17.00	0.00465	0.00904	PASS
Extreme (20°C)		13.75	4.38	0.00731	0.00233	PASS
Extreme (10°C)		12.16	2.53	0.00647	0.00135	PASS
Extreme (0°C)		13.42	6.07	0.00714	0.00323	PASS
Extreme (-10°C)		14.50	3.96	0.00771	0.00211	PASS
Extreme (-20°C)		16.83	4.99	0.00895	0.00266	PASS
Extreme (-30°C)		11.08	1.62	0.00589	0.00086	PASS
25°C	LV	10.96	1.99	0.00583	0.00106	PASS
	HV	15.80	3.91	0.00840	0.00208	PASS



Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	20MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	11.53	2.80	0.00613	0.00149	PASS
Extreme (50°C)		13.39	13.44	0.00712	0.00715	PASS
Extreme (40°C)		4.05	7.80	0.00216	0.00415	PASS
Extreme (30°C)		7.09	11.34	0.00377	0.00603	PASS
Extreme (20°C)		7.01	3.96	0.00373	0.00211	PASS
Extreme (10°C)		2.40	13.32	0.00128	0.00709	PASS
Extreme (0°C)		8.47	1.40	0.00451	0.00074	PASS
Extreme (-10°C)		1.37	7.97	0.00073	0.00424	PASS
Extreme (-20°C)		11.16	11.72	0.00593	0.00624	PASS
Extreme (-30°C)		9.38	1.55	0.00499	0.00083	PASS
25°C		LV	4.75	2.26	0.00253	0.00120
	HV	4.44	8.14	0.00236	0.00433	PASS


### 6.6. Spurious Emissions at Antenna Terminals

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported. The signal beyond the limit is carrier.






### EGPRS 1900 CH-Low 9kHz ~ 20GHz




10:48:10 28.06.2022

### WCDMA BAND II CH-Low 9kHz ~ 20GHz




10:57:25 28.06.2022

### EGPRS 1900 CH- Middle 9kHz ~ 20GHz




10:48:43 28.06.2022

### WCDMA BAND II CH- Middle 9kHz ~ 20GHz




10:58:09 28.06.2022

### EGPRS 1900 CH-High 9kHz ~ 20GHz




10:49:07 28.06.2022

### WCDMA BAND II CH-High 9kHz ~ 20GHz




10:58:55 28.06.2022


LTE Band 2 1.4MHz CH-Low 9kHz~20GHz




LTE Band 2 3MHz CH-Low 9kHz~20GHz




LTE Band 2 1.4MHz CH-Middle 9kHz~20GHz




LTE Band 2 3MHz CH-Middle 9kHz~20GHz




LTE Band 2 1.4MHz CH-High 9kHz~20GHz




LTE Band 2 3MHz CH-High 9kHz~20GHz




LTE Band 2 5MHz CH-Low 9kHz~20GHz




LTE Band 2 10MHz CH-Low 9kHz~20GHz




LTE Band 2 5MHz CH-Middle 9kHz~20GHz




LTE Band 2 10MHz CH-Middle 9kHz~20GHz



LTE Band 2 5MHz CH-High 9kHz~20GHz




LTE Band 2 10MHz CH-High 9kHz~20GHz







LTE Band 2 15MHz CH-Low 9kHz~20GHz




LTE Band 2 20MHz CH-Low 9kHz~20GHz




LTE Band 2 15MHz CH-Middle 9kHz~20GHz




LTE Band 2 20MHz CH-Middle 9kHz~20GHz



LTE Band 2 15MHz CH-High 9kHz~20GHz



LTE Band 2 20MHz CH-High 9kHz~20GHz



### 6.7. Radiates Spurious Emission

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

#### Upper Antenna

GSM 1900 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.00	-65.13	2.60	12.50	Horizontal	-55.23	-13.00	42.23	315
3	5640.00	-57.05	3.30	12.50	Horizontal	-47.85	-13.00	34.85	90
4	7520.00	-59.29	4.20	12.20	Horizontal	-51.29	-13.00	38.29	225
5	9400.00	-54.74	4.30	11.10	Horizontal	-47.94	-13.00	34.94	0
6	11280.00	-51.93	5.90	11.90	Horizontal	-45.93	-13.00	32.93	180
7	13160.00	-51.79	5.70	14.00	Horizontal	-43.49	-13.00	30.49	45
8	15040.00	-47.70	5.80	13.10	Horizontal	-40.40	-13.00	27.40	135
9	16920.00	-49.46	6.10	14.60	Horizontal	-40.96	-13.00	27.96	225
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.

#### WCDMA Band II CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.00	-65.90	2.60	12.50	Horizontal	-56.00	-13.00	43.00	315
3	5640.00	-63.59	3.30	12.50	Horizontal	-54.39	-13.00	41.39	45
4	7520.00	-59.47	4.20	12.20	Horizontal	-51.47	-13.00	38.47	225
5	9400.00	-53.62	4.30	11.10	Horizontal	-46.82	-13.00	33.82	0
6	11280.00	-50.78	5.90	11.90	Horizontal	-44.78	-13.00	31.78	180
7	13160.00	-52.20	5.70	14.00	Horizontal	-43.90	-13.00	30.90	135
8	15040.00	-47.76	5.80	13.10	Horizontal	-40.46	-13.00	27.46	45
9	16920.00	-50.09	6.10	14.60	Horizontal	-41.59	-13.00	28.59	270
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.



## LTE Band 2 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.00	-64.18	2.60	12.50	Horizontal	-54.28	-13.00	41.28	135
3	5638.88	-61.33	3.30	12.50	Horizontal	-52.13	-13.00	39.13	270
4	7520.00	-58.55	4.20	12.20	Horizontal	-50.55	-13.00	37.55	0
5	9400.00	-54.36	4.30	11.10	Horizontal	-47.56	-13.00	34.56	180
6	11280.00	-50.35	5.90	11.90	Horizontal	-44.35	-13.00	31.35	45
7	13160.00	-53.20	5.70	14.00	Horizontal	-44.90	-13.00	31.90	135
8	15040.00	-47.11	5.80	13.10	Horizontal	-39.81	-13.00	26.81	225
9	16920.00	-50.09	6.10	14.60	Horizontal	-41.59	-13.00	28.59	90
10	18800.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2. The worst emission was found in the antenna is Horizontal position.

## LTE Band 2 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3755.00	-65.87	2.60	12.50	Horizontal	-55.97	-13.00	42.97	315
3	5632.20	-61.00	3.30	12.50	Horizontal	-51.80	-13.00	38.80	45
4	7510.00	-59.69	4.20	12.20	Horizontal	-51.69	-13.00	38.69	180
5	9387.50	-53.66	4.30	11.10	Horizontal	-46.86	-13.00	33.86	315
6	11265.00	-50.86	5.90	11.90	Horizontal	-44.86	-13.00	31.86	90
7	13142.50	-52.55	5.70	14.00	Horizontal	-44.25	-13.00	31.25	270
8	15020.00	-47.58	5.80	13.10	Horizontal	-40.28	-13.00	27.28	45
9	16897.50	-49.84	6.10	14.60	Horizontal	-41.34	-13.00	28.34	135
10	18800.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2. The worst emission was found in the antenna is Horizontal position.



## LTE Band 2 20MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3740.00	-65.81	2.60	12.50	Horizontal	-55.91	-13.00	42.91	180
3	5610.00	-62.12	3.30	12.50	Horizontal	-52.92	-13.00	39.92	135
4	7480.00	-58.92	4.20	12.20	Horizontal	-50.92	-13.00	37.92	90
5	9350.00	-51.88	4.30	11.10	Horizontal	-45.08	-13.00	32.08	270
6	11220.00	-52.27	5.90	11.90	Horizontal	-46.27	-13.00	33.27	45
7	13090.00	-53.56	5.70	14.00	Horizontal	-45.26	-13.00	32.26	225
8	14960.00	-47.67	5.80	13.10	Horizontal	-40.37	-13.00	27.37	0
9	16830.00	-48.84	6.10	14.60	Horizontal	-40.34	-13.00	27.34	135
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

**Low Antenna**

GSM 1900 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.00	-58.47	2.60	12.50	Horizontal	-48.57	-13.00	35.57	135
3	5640.00	-45.39	3.30	12.50	Horizontal	-36.19	-13.00	23.19	180
4	7520.00	-59.98	4.20	12.20	Horizontal	-51.98	-13.00	38.98	45
5	9400.00	-53.19	4.30	11.10	Horizontal	-46.39	-13.00	33.39	315
6	11280.00	-51.38	5.90	11.90	Horizontal	-45.38	-13.00	32.38	225
7	13160.00	-52.45	5.70	14.00	Horizontal	-44.15	-13.00	31.15	90
8	15040.00	-48.30	5.80	13.10	Horizontal	-41.00	-13.00	28.00	0
9	16920.00	-49.84	6.10	14.60	Horizontal	-41.34	-13.00	28.34	270
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.

WCDMA Band II CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.00	-60.43	2.60	12.50	Horizontal	-50.53	-13.00	37.53	315
3	5640.00	-50.78	3.30	12.50	Horizontal	-41.58	-13.00	28.58	45
4	7520.00	-59.43	4.20	12.20	Horizontal	-51.43	-13.00	38.43	0
5	9400.00	-54.06	4.30	11.10	Horizontal	-47.26	-13.00	34.26	180
6	11280.00	-51.17	5.90	11.90	Horizontal	-45.17	-13.00	32.17	270
7	13160.00	-52.97	5.70	14.00	Horizontal	-44.67	-13.00	31.67	45
8	15040.00	-48.61	5.80	13.10	Horizontal	-41.31	-13.00	28.31	315
9	16920.00	-51.41	6.10	14.60	Horizontal	-42.91	-13.00	29.91	225
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.00	-57.85	2.60	12.50	Horizontal	-47.95	-13.00	34.95	225
3	5638.88	-47.96	3.30	12.50	Horizontal	-38.76	-13.00	25.76	45
4	7520.00	-58.70	4.20	12.20	Horizontal	-50.70	-13.00	37.70	0
5	9400.00	-52.83	4.30	11.10	Horizontal	-46.03	-13.00	33.03	90
6	11280.00	-49.25	5.90	11.90	Horizontal	-43.25	-13.00	30.25	45
7	13160.00	-52.80	5.70	14.00	Horizontal	-44.50	-13.00	31.50	0
8	15040.00	-47.46	5.80	13.10	Horizontal	-40.16	-13.00	27.16	135
9	16920.00	-49.49	6.10	14.60	Horizontal	-40.99	-13.00	27.99	0
10	18800.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3755.63	-60.22	2.60	12.50	Horizontal	-50.32	-13.00	37.32	45
3	5633.63	-48.41	3.30	12.50	Horizontal	-39.21	-13.00	26.21	90
4	7520.00	-59.01	4.20	12.20	Horizontal	-51.01	-13.00	38.01	135
5	9400.00	-54.69	4.30	11.10	Horizontal	-47.89	-13.00	34.89	0
6	11280.00	-51.98	5.90	11.90	Horizontal	-45.98	-13.00	32.98	45
7	13160.00	-53.18	5.70	14.00	Horizontal	-44.88	-13.00	31.88	225
8	15040.00	-47.96	5.80	13.10	Horizontal	-40.66	-13.00	27.66	45
9	16920.00	-49.03	6.10	14.60	Horizontal	-40.53	-13.00	27.53	225
10	18800.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
 2. The worst emission was found in the antenna is Horizontal position.



## LTE Band 2 20MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3742.13	-62.93	2.60	12.50	Horizontal	-53.03	-13.00	40.03	45
3	5613.38	-48.10	3.30	12.50	Horizontal	-38.90	-13.00	25.90	45
4	7484.63	-58.39	4.20	12.20	Horizontal	-50.39	-13.00	37.39	45
5	9400.00	-53.86	4.30	11.10	Horizontal	-47.06	-13.00	34.06	0
6	11280.00	-52.54	5.90	11.90	Horizontal	-46.54	-13.00	33.54	135
7	13160.00	-52.18	5.70	14.00	Horizontal	-43.88	-13.00	30.88	0
8	15040.00	-48.15	5.80	13.10	Horizontal	-40.85	-13.00	27.85	225
9	16920.00	-49.75	6.10	14.60	Horizontal	-41.25	-13.00	28.25	0
10	18800.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



## 7. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	150415	2022-05-14	2023-05-13
Spectrum Analyzer	Keysight	N9020A	MY50510203	2021-12-12	2022-12-11
Universal Radio Communication Tester	Agilent	E5515C	GB44400275	2021-12-12	2022-12-11
Signal Analyzer	R&S	FSV3030	101411	2021-12-12	2022-12-11
Climatic Chamber	ESPEC	SU-242	93000506	2021-12-12	2022-12-11
<b>Radiates Spurious Emission</b>					
Signal Analyzer	R&S	FSV30	100815	2021-12-12	2022-12-11
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2022-12-15
Horn Antenna	R&S	HF907	102723	2020-08-11	2023-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Software	R&S	EMC32	10.35.10	/	/

\*\*\*\*\*END OF REPORT \*\*\*\*\*





## **ANNEX A: The EUT Appearance**

**The EUT Appearance is submitted separately.**



## **ANNEX B: Test Setup Photos**

**The Test Setup Photos is submitted separately.**