SGS SGS-CS

Report No.: ZR/2020/5004201 Page: 1 of 28

FCC TEST REPORT

Application No:	ZR/2020/50042
Applicant:	Xiaomi Communications Co., Ltd.
Address of Applicant	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer:	Xiaomi Communications Co., Ltd.
Address of Manufacturer:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
EUT Description:	Mobile Phone
Model No.:	M2006C3LVG
Trade Mark:	Redmi
FCC ID:	2AFZZC3LVG
Standards:	47 CFR Part 2 47 CFR Part 22 subpart H 47 CFR Part 24 subpart E 47 CFR Part 27 subpart C
Test Method:	FCC KDB 971168 D01 Power Meas License Digital Systems V03r01 C63.26 (2015)
Date of Receipt:	2020/6/1
Date of Test:	2020/6/2 to 2020/7/4
Date of Issue:	2020/7/4
Test Result:	PASS *

In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derde yang

Derek Yang Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Conditions/Te



Report No.: ZR/2020/5004201 Page: 2 of 28

1 Version

Revision Record							
Version Chapter Date Modifier Remark							
01		2020/7/4		Original			

Authorized for issue by:		
Tested By	Mike Mu (Mike Hu) /Project Engineer	
Checked By	David Chen (David Chen) /Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certific to the such extenses of the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: ZR/2020/5004201 Page: 3 of 28

Content

1	1 VERSION					
2	TES	Г SUMMARY	5			
2	2.1	GSM850/UMTS BAND 5 & LTE BAND 5	5			
2	2.2	GSM 1900/UMTS BAND 2 /LTE BAND 2	5			
2	2.3	UMTS BAND 4 /LTE BAND 4	6			
2	2.4	LTE BAND 7/38	6			
3	GEN	ERAL INFORMATION	8			
3	3.1	CLIENT INFORMATION	8			
3	3.2	TEST LOCATION	8			
3	3.3	TEST FACILITY	8			
3	3.4	GENERAL DESCRIPTION OF EUT	9			
3	3.5	TEST MODE	9			
3	3.6	TEST ENVIRONMENT	10			
3	3.7	TECHNICAL SPECIFICATION	10			
3	3.8	TEST FREQUENCIES	12			
4	DES	CRIPTION OF TESTS	16			
4	4.1	CONDUCTED OUTPUT POWER	16			
4	1.2	EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	16			
4	1.3	OCCUPIED BANDWIDTH	16			
4	1.4	BAND EDGE AT ANTENNA TERMINALS	17			
4	1.5	SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	17			
۷	1.6	PEAK-AVERAGE RATIO				
۷	1.7	FIELD STRENGTH OF SPURIOUS RADIATION	19			
۷	1.8	FREQUENCY STABILITY / TEMPERATURE VARIATION	20			
۷	1.9	TEST SETUPS	21			
	4.9.1	Test Setup 1	21			
	4.9.2	Test Setup 2	21			
	4.9.3	Test Setup 3	22			
	4.9.4	Test Setup 4	22			
4	4.10	TEST CONDITIONS	23			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnotic atom and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unavual and bilgations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlavual and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / Inspection report & certificate, piezae contact us at letephone: (86-755) 26710594 www.sgsgroup.com.cn no. No.1Workshop. M-10.Midd Beckin, Science & TechnologyPark, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.com

Member of the SGS Group (SGS SA)



Report No.: ZR/2020/5004201 Page: 4 of 28

5	MAIN TEST INSTRUMENTS	.25
6	MEASUREMENT UNCERTAINTY	28
Ū		0
-		
1	APPENDIXES	.28



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certified to the some content of the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: ZR/2020/5004201 Page: 5 of 28

2 Test Summary

2.1 GSM850/UMTS Band 5 & LTE Band 5

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W	Section 1 of Appendix B	Pass
Peak-Average Ratio		Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Section 8 of Appendix B	Pass
Remark: For the verd		es "not applicable", the "N/T" denotes "not te		<u> </u>

2.2 GSM 1900/UMTS Band 2 /LTE Band 2

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§2.1046, §24.232	Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	 ≤ -13 dBm/1 MHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges. 	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §24.235	≤ ±2.5 ppm.	Section 8 of Appendix B	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-enD-countent.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

Report No.: ZR/2020/5004201 Page: 6 of 28

Test Item	FCC Rule No.	Requirements	Test Result	Verdict			
Remark: For the verd	Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".						

2.3 UMTS Band 4 /LTE Band 4

S

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP ≤ 1 W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§2.1046, §27.50(d)	Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	 ≤ -13 dBm/1 MHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges. 	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §27.54	≤ ±2.5 ppm.	Section 8 of Appendix B	Pass
Remark: For the verd	lict, the "N/A" denote	es "not applicable", the "N/T" denotes "not	tested".	

2.4 LTE Band 7/38

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§27.50(a)	≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge,	Section 5 of Appendix B	Pass



arloof available on request or accessible at http://	(human sas com/on/T	ompany subject to i	is General Condition	ns of Service printed
bject to Terms and Conditions for Electronic Do	cuments at http://ww	w.sgs.com/en/Terms	-and-Conditions/Tern	ns-e-Document.aspx.
ention is drawn to the limitation of liability, inde	mnification and juris	diction issues define	d therein. Any holde	er of this document is
cept in full, without prior written approval of the	Company. Any una	authorized alteration,	forgery or falsificat	ion of the content or
pearance of this document is unlawful and offend	lers may be prosecu	ted to the fullest exte	ent of the law. Unless	otherwise stated the
ults shown in this test report refer only to the sam	ple(s) tested and suc	ch sample(s) are retai	ned for 30 days only.	e: (86-755) 8307 1443
email: CN.Doccheck@sgs.com		ertinoute, preuse ee	inder de di terephen	10. (00 100) 0001 1110,
.1 Workshop, M-10, Middle Section, Science & Technology Park, Sh	enzhen, China 518057	t (86-755) 26012053	f (86-755) 26710594	www.sgsgroup.com.cn
	邮编: 518057	t (86-755) 26012053	f (86-755) 26710594	sgs.china@sgs.com
	oject to Terms and Conditions for Electronic Do ention is drawn to the limitation of liability, inde- vised that information contained hereon reflects ent's instructions, if any. The Company's sole nsaction from exercising all their rights and ob pet in full, without prior written approval of the bearance of this document is unlawful and offenc uluts shown in this test report refer only to the sam tention. To check the authenticity of testing /in email: CR.Doccheck@gs.com	oject to Terms and Conditions for Electronic Documents at <u>http://ww</u> ention is drawn to the limitation of liability, indemnification and juris vised that information contained hereon reflects the Company's find ent's instructions, if any. The Company's sole responsibility is to i nsaction from exercising all their rights and obligations under the j apet in full, without prior written approval of the Company. Any un pearance of this document is unlawful and offenders may be prosecu jutts shown in this test report refer only to the sample(s) tested and suc tention: To check the authenticity of testing /inspection report & c email: CD.Deccheck@gs.com .1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057	oject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms</u> ention is drawn to the limitation of liability, indemnification and jurisdiction issues define vised that information contained hereon reflects the Company's findings at the time of its ent's instructions, if any. The Company's sole responsibility is to its Client and this dc nsaction from exercising all their rights and obligations under the transaction documen pet in full, without prior written approval of the Company. Any unauthorized alteration, pearance of this document is unlawful and offenders may be prosecuted to the fullest exte lutis shown in this test report refer only to the sample(s) tested and such sample(s) are retai tention: To check the authenticity of testing /Inspection report & certificate, please co email: CD-Doccheck@gs.com .1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053	.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594



Report No.: ZR/2020/5004201 Page: 7 of 28

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
		where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.		
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	Channel Edge -25dBm/ 1 MHz 9 kHz 9.5 MHz XMHz 10th harmonics X=Max {6MHz, EBW}	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	P kHz 9 5 MHz XMHz 10 th harmonics X=Max {6MHz, EBW}	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Section 8 of Appendix B	Pass
Remark: For the verd	lict, the "N/A" denote	es "not applicable", the "N/T" denotes "not "	tested".	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certified to the some content of the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: ZR/2020/5004201 Page: 8 of 28

3 General Information

3.1 Client Information

Applicant:	Xiaomi Communications Co., Ltd.
Address of Applicant:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer:	Xiaomi Communications Co., Ltd.
Address of Manufacturer:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

3.2 Test Location

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
E-mail:	ee.shenzhen@sgs.com

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



	Unless otherwise agreed in writing, this document is i overleaf, available on request or accessible at <u>http://www</u> subject to Terms and Conditions for Electronic Docume Attention is drawn to the limitation of liability, indemnifi advised that information contained hereon reflects the i Client's instructions, if any. The Company's sole resp transaction from exercising all their rights and obligati sccept in full, without prior written approval of the Co appearance of this document is unlawful and offenders i results shown in this test report refer only to the sample(s Attention: To check the authenticity of testing /inspe- or email: CN.Doccheck@ags.com	<u>w.sgs.com/en/To</u> ants at <u>http://wv</u> cation and juris Company's find onsibility is to i ons under the i mpany. Any una may be prosecu) tested and suc	erms-and-Conditions. ww.sgs.com/en/Terms. diction issues define ings at the time of its ts Client and this do transaction documen authorized alteration, ted to the fullest exte h sample(s) are retai	aspx and, for electror -and-Conditions/Tern d therein. Any holde s intervention only ar ocument does not e> ts. This document c. , forgery or falsificat ant of the law. Unless ned for 30 days only.	nic format documents, ns-e-Document.aspx. r of this document is nd within the limits of conerate parties to a annot be reproduced ion of the content or otherwise stated the	
	No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhe	n, China 518057	t (86-755) 26012053	f (86-755) 26710594	www.sgsgroup.com.cn	
rv.	中国 · 深圳 · 科技园中区M-10栋一号厂房	邮编: 518057	t (86-755) 26012053	f (86-755) 26710594	sgs.china@sgs.com	



Report No.: ZR/2020/5004201 Page: 9 of 28

3.4 General Description of EUT

EUT Description::	Mobile Phone
Model No.:	M2006C3LVG
Trade Mark:	Redmi
Hardware Version:	P2
Software Version:	MIUI 12
Sample Type:	Portable Device, Module
Antenna Type:	External, 🛛 Integrated
	GSM850: Main/ -3.04dBi; Div/-4.45 dBi,
	GSM1900:0dBi
	WCDMA Band II:0dBi
	WCDMA Band IV:-0.5dBi
Antenna Gain:	WCDMA Band V: Main/ -3.04dBi; Div/-4.45 dBi,
Antenna Gain.	LTE Band 2:0dBi;
	LTE Band 4:-0.5dBi;
	LTE Band 5: Main/ -3.04dBi; Div/-4.45 dBi,
	LTE Band 7: 0.7dBi
	LTE Band 38:0dBi;
Accsessories	AC Adapter 1:Model :MDY-09-EQ; Input:100-240V,0.35A;Output:5V,2A AC Adapter 2:Model :MDY-09-EQ; Input:100-240V,0.35A;Output:5V,2A Li-ion Battery: Model :BN56;3.85V,4900mAh
	USB: Model :H52210; 0.8 meter, shielded cable, with-out ferrite core

3.5 Test Mode

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS, GMSK modulation
GSM/TM2	GSM system, EGPRS, 8PSK modulation
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
UMTS/TM2	UMTS system, WCDMA, 16QAM modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation
LTE/TM3	LTE system, 64QAM modulation

Remark: The test mode(s) are selected according to relevant radio technology specifications.

中国·深圳·科技园中区M-10栋一号厂房



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: Ch.Doccheck@sgs.com

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

Member of the SGS Group (SGS SA)

sgs.china@sgs.com



Report No.: ZR/2020/5004201 Page: 10 of 28

3.6 Test Environment

Environment Parameter	Selected Values During Tests		
Relative Humidity	52%		
Atmospheric Pressure:	101.32 KPa		
Temperature	NT 25 °C		
	LV 3.6V		
Voltage:	NV	3.85V	
	HV	4.4V	

Remark: LV= lower extreme test voltage; NV= nominal voltage

HV= upper extreme test voltage; NT= normal temperature

3.7 Technical Specification

Characteristics	Description				
	GSM				
Radio System Type	UMTS				
	🛛 LTE				
	Band	TX	RX		
	GSM850	824 to 849 MHz	869 to 894 MHz		
	GSM1900	1850 to 1910 MHz	1930 to 1990 MHz		
	UMTS Band II	1850 to 1910 MHz	1930 to 1990 MHz		
	UMTS Band IV	1710 to 1755 MHz	2110 to 2155 MHz		
Supported Frequency Range	UMTS Band V	824 to 849 MHz	869 to 894 MHz		
Range	LTE Band 2	1850 to 1910 MHz	1930 to 1990 MHz		
	LTE Band 4	1710 to 1755 MHz	2110 to 2155 MHz		
	LTE Band 5	824 to 849 MHz	869 to 894 MHz		
	LTE Band 7	2500 to 2570 MHz	2620 to 2690 MHz		
	LTE Band 38	2570 to 2620 MHz	2570 to 2620 MHz		
Target TX Output Power	GSM850:33 dBm GSM1900: 30dBm UMTS Band II: 23dBm UMTS Band IV: 23dBm UMTS Band V: 23dBm LTE Band 2: 23dBm LTE Band 4: 23dBm LTE Band 5: 23.5dBm LTE Band 7: 23dBm LTE Band 38: 23dBm				
Supported Channel	GSM system:	⊠0.2 MHz			
Bandwidth	UMTS system: LTE Band 2	5 MHz 5 MHz: ⊠3 MHz: №	75 MHZ: M10 MHZ:		
+ + m					
Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Document aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is adtention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a rearching and obligations under the transaction documenter. This document does not exconerate parties to a transaction form exercision and built print of the transaction document.					





Report No.: ZR/2020/5004201 Page: 11 of 28

		⊠15 MHz, ⊠20 MHz
		X 1.4 MHz; X 3 MHz; X 5 MHz; X 10 MHz;
	LTE Band 4	⊠15 MHz, ⊠20 MHz
	LTE Band 5	🛛 1.4 MHz; 🖾 3 MHz; 🖾 5 MHz; 🖾 10 MHz
	LTE Band 7	⊠5 MHz; ⊠10 MHz; ⊠15 MHz, ⊠20 MHz
	LTE Band38	⊠5 MHz; ⊠10 MHz; ⊠15 MHz, ⊠20 MHz
Characteristics	Description	
	GSM850	249KGXW; 252KG7W
	GSM1900	245KGXW; 256KG7W
	UMTS Band II	4M17F9W;
	UMTS Band IV	4M18F9W;
	UMTS Band V	4M20F9W;
		1M09G7D;1M09W7D;
		2M69G7D;2M69W7D;
	LTE Band 2	4M48G7D;4M49W7D;
Decimpation of	LIE Band 2	8M93G7D;8M97W7D;
Designation of		13M5G7D;13M5W7D;
Emissions		18M0G7D;17M9W7D;
(Remark: the necessary		1M09G7D;1M09W7D;
bandwidth of which is		2M69G7D;2M68W7D;
the worst value from	LTE Band 4	4M48G7D;4M49W7D;
		8M95G7D;8M93W7D;
the measured occupied		13M6G7D;13M5W7D;
bandwidths for each		18M0G7D;17M9W7D;
type of channel		1M09G7D;1M09W7D;
bandwidth	LTE Band 5	2M69G7D;2M68W7D;
configuration.)		4M49G7D;4M50W7D;
- ·		8M95G7D;8M93W7D;
		4M49G7D;4M49W7D;
	LTE Band 7	8M97G7D;8M95W7D;
		13M6G7D;13M6W7D;
		18M1G7D;18M1W7D;
		4M49G7D;4M49W7D;
	LTE Band 38	8M97G7D;8M97W7D;
		13M6G7D;13M6W7D;
		18M1G7D;18M1W7D;



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certific to Decode the full set of the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: ZR/2020/5004201 Page: 12 of 28

3.8 Test Frequencies

Test Mode	TX / RX	RF Channel		
Test Mode		Low (L)	Middle (M)	High (H)
	M850 TX -	Channel 128	Channel 190	Channel 251
		824.2MHz	836.6 MHz	848.8 MHz
GSIVIOSU		Channel 128	Channel 190	Channel 251
		869.2 MHz	881.6 MHz	893.8 MHz

Test Mode	TX / RX		RF Channel	
Test Mode		Low (L)	Middle (M)	High (H)
	ту	Channel 512	Channel 661	Channel 810
GSM1900	ТХ	1850.2MHz	1880.0 MHz	1909.8 MHz
G21011900	RX	Channel 512	Channel 661	Channel 810
	۲A	1930.2 MHz	1960.0 MHz	1989.8 MHz

Teet Mede	Mode TX / RX RF Channel			
Test Mode	ΙΛ / ΚΛ	Low (L)	Middle (M)	High (H)
	τv	Channel 9262	Channel 9400	Channel 9538
WCDMA	d II	1852.4 MHz	1880.0 MHz	1907.6 MHz
Band II		Channel 9662	Channel 9800	Channel 9938
	RX	1932.4 MHz	1960.0 MHz	1987.6 MHz

Test Mode	t Mode TX / RX RF Channel			
Test Mode	ΙΛ / ΚΛ	Low (L)	Middle (M)	High (H)
	τv	Channel 1312	Channel 1413	Channel 1513
WCDMA	TX	1712.4MHz	1732.6 MHz	1752.6 MHz
Band IV		Channel 1537	Channel 1638	Channel 1738
	RX	2112.4 MHz	2132.6 MHz	2152.6 MHz

Test Mode	TY / DY	TX / RX RF Channel				
Test Mode		Low (L)	Middle (M)	High (H)		
	ТХ	Channel 4132	Channel 4182	Channel 4233		
WCDMA		826.4MHz	836.4 MHz	846.6 MHz		
Band V	RX -	Channel 4357	Channel 4407	Channel 4458		
		871.4 MHz	881.4 MHz	891.6 MHz		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or completed and the dome the same tested of the same completed and the same contact or the same contact or the same tested of the difference of the same contact or the same contact



Report No.: ZR/2020/5004201 Page: 13 of 28

Test Mode	Bandwidth	TX / RX		RF Channel	
Test Mode	Danuwiuth		Low (L)	Middle (M)	High (H)
		ТХ	Channel 18607	Channel 18900	Channel 19193
	1.4MHz		1850.7 MHz	1880 MHz	1909.3 MHz
	1.4IVITZ	RX	Channel 607	Channel 900	Channel 1193
		ΓA	1930.7 MHz	1960 MHz	1989.3 MHz
		ТΧ	Channel 18615	Channel 18900	Channel 19185
	3MHz		1851.5 MHz	1880 MHz	1908.5 MHz
	SIVIEZ	RX	Channel 615	Channel 900	Channel 1185
		ΓΛ	1931.5 MHz	1960 MHz	1988.5 MHz
		ТХ	Channel 18625	Channel 18900	Channel 19175
	5MHz		1852.5 MHz	1880 MHz	1907.5 MHz
		RX	Channel 625	Channel 900	Channel1175
LTE Band 2			1932.5 MHz	1960 MHz	1987.5 MHz
LIE Dallu Z		TX	Channel 18650	Channel 18900	Channel 19150
	10MHz		1855 MHz	1880 MHz	1905 MHz
	TOWITZ	RX	Channel 650	Channel 900	Channel 1150
		ΓΛ	1935 MHz	1960 MHz	1985 MHz
		ТΧ	Channel 18675	Channel 18900	Channel 19125
	15MHz		1857.5 MHz	1880 MHz	1902.5 MHz
		DV	Channel 675	Channel 900	Channel 1125
		RX	1937.5 MHz	1960 MHz	1982.5 MHz
		ΤХ	Channel 18700	Channel 18900	Channel 19100
	20MHz		1860 MHz	1880 MHz	1900 MHz
		BV	Channel 700	Channel 900	Channel 1100
		RX	1940 MHz	1960 MHz	1980 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/5004201 Page: 14 of 28

Test Mode	Bandwidth	TX / RX		RF Channel		
Test Mode	Danuwiuun		Low (L)	Middle (M)	High (H)	
		ТХ	Channel 19957	Channel 20175	Channel 20393	
	1.4MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
	1.4IVITZ	RX	Channel 1975	Channel 2175	Channel 2375	
		ΓΛ	2112.5 MHz	2132.5MHz	2152.5 MHz	
		ТΧ	Channel 19965	Channel 20175	Channel 20385	
	3MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
	SIVIEZ	RX	Channel 2000	Channel 2175	Channel 2350	
		ΓΛ	2115 MHz	2132.5MHz	2150 MHz	
		ТΧ	Channel 19975	Channel 20175	Channel 20375	
	5MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
		RX	Channel 1975	Channel 2175	Channel 2375	
LTE Band 4			2112.5 MHz	2132.5MHz	2152.5 MHz	
LTE Danu 4		10MHz RX	Channel 20000	Channel 20175	Channel 20350	
	10MH-		1715 MHz	1732.5 MHz	1750 MHz	
	TOWITZ		Channel 2000	Channel 2175	Channel 2350	
			ΓA	2115 MHz	2132.5MHz	2150 MHz
		ΤХ	Channel 20025	Channel 20175	Channel 20325	
	15MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
	TOIVITIZ	RX	Channel 2025	Channel 2175	Channel 2325	
		ΓA	2117.5 MHz	2132.5MHz	2147.5 MHz	
		ТХ	Channel 20050	Channel 20175	Channel 20300	
	20MHz		1720 MHz	1732.5 MHz	1745 MHz	
		RX	Channel 2050	Channel 2175	Channel 2300	
		ΓΛ	2120 MHz	2132.5MHz	2145 MHz	

Test Mode	Bandwidth			RF Channel	
Test Mode	Danuwiuth	TX/RX	Low (L)	Middle (M)	High (H)
		ТХ	Channel 20407	Channel 20525	Channel 20643
	1.4MHz		824.7 MHz	836.5 MHz	848.3 MHz
		RX	Channel 2407	Channel 2525	Channel 2643
		ΓΛ	869.7 MHz	881.5 MHz	893.3 MHz
		τv	Channel 20415	Channel 20525	Channel 20635
	3MHz	TX	825.5 MHz	836.5 MHz	847.5 MHz
	SIVITIZ	RX	Channel 2415	Channel 2525	Channel 2635
LTE Band 5			870.5 MHz	881.5 MHz	892.5 MHz
LIE Dallu S		ТХ	Channel 20425	Channel 20525	Channel 20625
	5MHz		826.5 MHz	836.5 MHz	846.5 MHz
		SIMITZ RX	Channel 2425	Channel 2525	Channel 2625
		ΓΛ	871.5 MHz	881.5 MHz	891.5 MHz
		ту	Channel 20450	Channel 20525	Channel 20600
	10MHz	TX	829 MHz	836.5 MHz	844 MHz
		RX	Channel 2450	Channel 2525	Channel 2600
		ΓΛ	874 MHz	881.5 MHz	889 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and <u>urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certific 04 Depechedments.</u>



Report No.: ZR/2020/5004201 Page: 15 of 28

Test Mode	Bandwidth	TX / RX		RF Channel	
Test Mode	Danuwiuti		Low (L)	Middle (M)	High (H)
		ΤХ	Channel 20775	Channel 21100	Channel 21425
	5MHz		2502.5 MHz	2535 MHz	2567.5 MHz
	SIVILIZ	RX	Channel 2775	Channel 3100	Channel 5825
			2622.5 MHz	2655 MHz	2687.5 MHz
		ΤХ	Channel 20800	Channel 21100	Channel 21400
	10MHz		2505 MHz	2535 MHz	2565 MHz
	TOMITZ	RX	Channel 2800	Channel 3100	Channel 3400
LTE Band 7			2625 MHz	2655 MHz	2685 MHz
		TX -	Channel 20825	Channel 21100	Channel 21375
	15MHz		2507.5 MHz	2535 MHz	2562.5 MHz
	TOIVITIZ	RX	Channel 2825	Channel 3100	Channel 3375
	20MHz	NA NA	2627.5 MHz	2655 MHz	2682.5 MHz
		ТХ	Channel 20850	Channel 21100	Channel 21350
			2510 MHz	2535 MHz	2560 MHz
		RX	Channel 2850	Channel 3100	Channel 3350
			2630 MHz	2655 MHz	2680 MHz

Test Mode	Bandwidth	TX / RX			
Test Mode	Danuwiuth		Low (L)	Middle (M)	High (H)
	5MHz	TX/RX	Channel 37775	Channel38000	Channel 38225
		SIVINZ I A/KA	2572.5 MHz	2595 MHz	2617.5 MHz
		10MHz TX/RX	Channel 37800	Channel38000	Channel 38200
LTE Band 38	TOMITZ		2575 MHz	2595 MHz	2615 MHz
LIE Dallu So		15MHz TX/RX	Channel 37825	Channel38000	Channel 38175
	TOIVIEZ		2577.5 MHz	2595 MHz	2612.5 MHz
	2014	20MHz TX/RX	Channel 37850	Channel38000	Channel 38150
	2010172		2580 MHz	2595 MHz	2610 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, recommit (M). Depocherviers and references and report accessing in the testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, recommit this set open references.

Report No.: ZR/2020/5004201 Page: 16 of 28

4 Description of Tests

4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Remark: Reference test setup 1

4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 ; C63.26 (2015) Calculate power in dBm by the following formula: ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd) EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi) EIRP=ERP+2.15dB

4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unavful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone. (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

No.1 Workhon, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057
t (86-755) 26012053 f (86-755) 26710594

www.sgsgroup.com.com
meail: 518057
t (86-755) 26012053 f (86-755) 26710594



Report No.: ZR/2020/5004201 Page: 17 of 28

Test Settings

- The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within

1 - 5% of the 99% occupied bandwidth observed in Step 7

4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

Remark: Reference test setup 1

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW ≥ 1% of the emission bandwidth
- 4. $VBW \ge 3 \times RBW$
- 5. Detector = RMS
- 6. Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unavful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

 No.1 Workhon, M-10 Middle Section, Science & Technology Park, Shenzhen, China 518057
 t (86-755) 26012053 f (86-755) 26710594
 www.sgsgroup.com.cm

 中国 • 梁圳 • 科技图中区M-10栋 - 号厂房
 邮编: 518057
 t (86-755) 26012053 f (86-755) 26710594
 sgs.china@sgs.com



Report No.: ZR/2020/5004201 Page: 18 of 28

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Remark: Reference test setup 1

Test Settings

- Start frequency was set to 30MHz and stop frequency was set to at least 10 * the fundamental frequency (separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.1

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@egs.com

SGS SC Br

Report No.: ZR/2020/5004201 Page: 19 of 28

Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- 3. Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

4.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] – cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log 10$ (Power [Watts]).

Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic

Chamber to fully Anechoic Chamber



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's old responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisfication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN_Doccheck@sgs.com} [No.1Workhon_NI-01.Midd Beckin, Science & TechnologyPark, Shenzhen, China 518057 to (86-755) 26012053 for (86-755) 26710594 www.sggs.com plane). Any space and such as the state of the fulles accontact us at telephone: (86-755) 26012053 for (86-755) 26710594 www.sggs.com plane). Any tage plane and such as the state of the fulles accontact as the state of the state of



Report No.: ZR/2020/5004201 Page: 20 of 28

2) Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete

Remark: Reference test setup 3

4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; ANSI/C63.26 (2015)

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Remark: Reference test setup 4




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation or liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this ter report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@gs.com
[No.1Workshop.M-10,Midde Section, Science & Technology Park, Shenzhen, China 518057] t (86-755) 26012053 f (86-755) 26710594] www.sgsgroup.com.cn



Report No.: ZR/2020/5004201 Page: 21 of 28

4.9 Test Setups

4.9.1 Test Setup 1



Ground Reference Plane

4.9.2 Test Setup 2





Figure 1. 30MHz to 1GHz





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ggs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ggs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing //inspection report & certificate, please contact us at telephone; (86-755) 260710594 www.sgsgroup.com.cn. https://www.sgs.com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 www.sgsgroup.com.cn. https://www.sgs.com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral complex.com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral complex.com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26012053 ff (86-755) 26710594 spectral com/emails.518057 tf (86-755) 26710594 spectral com/emails.518057 tf

Member of the SGS Group (SGS SA)



Report No.: ZR/2020/5004201 Page: 22 of 28

4.9.3 Test Setup 3




Figure 1. Below 30MHz





Figure 2. 30MHz to 1GHz

Figure 3. above 1GHz



Ground Reference Plane



4.9.4 Test Setup 4

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN Doccheck@gs.com



Report No.: ZR/2020/5004201 Page: 23 of 28

4.10 Test Conditions

Test Case		Test Condition	s	
		Test Environment	Ambient Climate & Rated Voltage	
	Average	Test Setup	Test Setup 1	
	Power, Total	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
Transmit Output		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2	
Power Data	Average	Test Environment	Ambient Climate & Rated Voltage	
	Power,	Test Setup	Test Setup 1	
	Spectral Density (if	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
	required)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2	
		Test Environment	Ambient Climate & Rated Voltage	
Peak-to-Ave	erane Ratio	Test Setup	Test Setup 1	
(if required)	-	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel	
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2	
		Test Environment	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
Modulation Characteris	tics	RF Channels (TX)	M (M= middle channel)	
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2	
		Test Environment	Ambient Climate & Rated Voltage	
	Occurried	Test Setup	Test Setup 1	
Bandwidth	Occupied Bandwidth	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unavful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report referontly is the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

No.1 Workhon, M-10, Midde Section, Science & Technology Park, Shenzhen, China 518057
t (86-755) 26012053 f (86-755) 26710594

www.sgsgroup.com.cn

ngl - 家训·补按图中区M-10核一号厂房
邮编: 518057
t (86-755) 26012053 f (86-755) 26710594

SGS B

SGS-CSTC Standards Technical Services Co., Ltd.Shenzhen Branch

Report No.: ZR/2020/5004201 Page: 24 of 28

		Test Environment	Ambient Climate & Rated Voltage		
	Emission Bandwidth	Test Setup	Test Setup 1		
	(if required)	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
	loquiou)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
David Edward	_	Test Setup	Test Setup 1		
Band Edges Compliance		RF Channels (TX)	L, H (L= low channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Spurious Er	mission at	Test Setup	Test Setup 1		
Antenna Te	rminals	RF Channels	L,M, H		
		(TX)	(L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;UMTS/TM1; LTE/TM1		
		Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 2		
Field Streng Spurious Ra		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;UMTS/TM2; LTE/TM1;LTE/TM2;		
opunouo ra		Test Mode	Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;		
		Environment	(2) VL, VN and VH of Rated Voltage at Ambient Climate.		
		Test Setup	Test Setup 4		
Frequency	Stability	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document lives otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: Ch.Doccheck@sg.com

No.1 Workshon, M.10. Midde Section, Science & Technology Park, Shenzhen, China 518057
t (86-755) 26012053 f (86-755) 26710594

www.sgsgroup.com.cn

nga : \$\pi_1 \nightarrow it is \$\pi_2 \nightarrow it is \$\p



Report No.: ZR/2020/5004201 Page: 25 of 28

5 Main Test Instruments

	RE in (Chamber			
Test Equipment	Manufacturer	Model No.	Inventory	Cal. date	Cal.Due date
rest Equipment	Manufacturer	moder No.	No.	(yyyy-mm- dd)	(yyyy-mm- dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12
Spectrum Analyzer (20Hz-43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2020/4/16	2021/4/15
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2020/6/12	2023/6/11
Horn Antenna (800MHz- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/412
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2019/7/14	2020/7/14
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2019/7/14	2020/7/14
Pre-Amplifier (0.1- 26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	EMC2063	2019/9/20	2020/9/19
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP-2640- 50	SEM005-08	2020/4/16	2021/4/15
Band filter	N/A	N/A	N/A	N/A	N/A
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020/6/12	2021/6/11
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2020/1/13	2021/1/2



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) test end sub sample(s) in retrained to 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN Doccheck@ass.com].



Report No.: ZR/2020/5004201 Page: 26 of 28

	RF conducted test						
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal.Due date		
			NO.	(yyyy-mm- dd)	(yyyy-mm- dd)		
Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	2019/10/22	2020/10/21		
Signal Analyzer	Rohde & Schwarz	FSV	W005-02	2020/4/16	2021/4/15		
Coaxial Cable	SGS	N/A	SEM031-01	2020/6/12	2021/6/11		
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A		
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019/10/22	2020/10/21		
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	HTC-1	W006-17	2019/10/22	2020/10/21		
Temperature Chamber	GIANT FORCE	ICT-150- 40-CP-AR	W027-03	2019/10/22	2020/10/21		
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15		
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/10/22	2020/10/21		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: **ON Doccheck@ass.com**

S

Report No.: ZR/2020/5004201 Page: 27 of 28

Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm- dd)	Cal. Due date (yyyy- mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2020/1/3	2021/1/2
EXA Signal Analyzer (10Hz- 26.5GHz)	Agilent Technologies Inc	N9010A	SEM004-09	2020/3/13	2021/3/12
Spectrum Analyzer (20Hz- 43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2020/4/16	2021/4/15
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26
Horn Antenna (800MHz-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2019/7/25	2020/7/24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP- 0126	SEM004-11	2019/7/25	2020/7/24
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP- 2640-50	SEM005-08	2020/4/16	2021/4/15
Band filter	N/A	N/A	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020/6/12	2021/6/11
Tunable Notch Filter WRCD1700/2000-0.2/40-10EEK	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
Tunable Notch Filter WRCD800/960-0.2/40-10EEK	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
HighPass Filter WHK1.2/15G-10SS	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
HighPass Filter WHKX10-2700-3000-18000-40SS	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
HighPass Filter WHKX7.0/26.5G-6SS	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
Band Reject Filter WRCG 824/849-814/859-40/8SS	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
Band Reject Filter WRCG 1850/1910-1835/1925- 40/8SS	WAINRIGHT Instruments GMBH	N/A	N/A	N/A	N/A
Measurement Software	AUDIX	e3 V8.2014- 6-27	N/A	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and <u>urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or certific 04 Depechedments.</u>



Report No.: ZR/2020/5004201 Page: 28 of 28

6 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data	
Transmit Output Power Data	Power [dBm]	U =±0.37 dB	
Bandwidth	Magnitude [%]	U =± 0.2%	
Band Edge Compliance	Disturbance Power [dBm]	U = ±2.0 dB	
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = ±2.0 dB	
		For 3 m Chamber:	
		$U = \pm 4.5 \text{ dB}$ (30 MHz to 1GHz)	
Field Strength of Spurious		$U = \pm 3.3 \text{ dB}$ (above 1 GHz)	
Radiation	ERP[dBm]/EIRP [dBm]	For 10 m Chamber:	
		$U = \pm 4.5 \text{ dB}$ (30 MHz to 1GHz)	
		$U = \pm 3.2 \text{ dB}$ (above 1 GHz)	
Frequency Stability	Frequency Accuracy [ppm]	U = ±0.24 ppm	

7 Appendixes

Appendix A	Photographs of Set-Up for ZR202050042.	
Appendix B.1	GSM 850 & 1900	
Appendix B.2	WCDMA Band II & IV & V	
Appendix B.3	LTE Band 2	
Appendix B.4	LTE Band 4	
Appendix B.5	LTE Band 5	
Appendix B.6	LTE Band 7	
Appendix B.7	LTE Band 38	

The End



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) presented for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ses.com