

RF Exposure Report

(Part 0: SAR Char Evaluation)

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : POCO
MODEL NAME : 23013PC75G
FCC ID : 2AFZZC75G
STANDARD : FCC 47 CFR PART 2 (2.1093)

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. Introduction	4
2. Product Description	5
3. SAR Characterization.....	6
3.1 SAR design target and uncertainty.....	6
3.2 SAR Char Table	9



1. Introduction

The 2nd generation of Smart Transmit (GEN2) operates based on pre-defined sub6 antenna groups (AG). This Device is enabled with the Qualcomm® Smart Transmit Gen2 feature. The RF exposure limit is defined based on time-averaged RF exposure. The product implements Qualcomm Smart Transmit feature which controls the instantaneous transmitting power for WWAN transmitter to ensure the product in compliance with RF exposure limit over a defined time window, for SAR (transmit frequency \leq 6GHz) to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is compliant to the regulation requirement. Smart Transmit cannot operate without SAR characterization at the device level, beforehand.

This report describes the procedures for the SAR char generation, and the parameters obtained from SAR characterization (referred to as SAR char, respectively) will be used as input for Smart Transmit. Both SAR char will be entered via the Embedded File System (EFS) to enable the Smart Transmit GEN2 Feature.

Terminologies in this report

P_{limit}	The time-averaged RF power which corresponds to SAR_design_target.
P_{max}	Maximum target power level
SAR_design_target:	The design target for SAR compliance. It should be less than regulatory power density limit to account for all device design related uncertainty.
SAR char	P_{limit} for all the technologies/bands for all applicable DSI



2. Product Description

Product Feature & Specification	
Equipment Name	Mobile Phone
Brand Name	POCO
Model Name	23013PC75G
FCC ID	2AFZZC75G
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz 5G NR n5: 824 MHz ~ 849 MHz 5G NR n7: 2500 MHz ~ 2570 MHz 5G NR n38 : 2570 MHz ~ 2620 MHz 5G NR n41: 2496 MHz ~ 2690 MHz 5G NR n77: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3980 MHz 5G NR n78: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3800 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is supported) LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR : CP-OFDM / DFT-s-OFDM, PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC: ASK



3. SAR Characterization

SAR char must be generated to cover all radio configurations and usage scenarios that the wireless device supports for operating at 6 GHz or below. It will then be used as input for Smart Transmit to control and manage RF exposure for f < 6 GHz.

3.1 SAR design target and uncertainty

SAR design Target :

Band	Antenna	Head DSI 1	Hotspot DSI 5	Body Worn DSI 4	Sensor On DSI 3
GSM850	Ant 0	0.87	0.87	0.87	2.07
GSM850	Ant 1	0.68	0.26	0.78	1.84
GSM1900	Ant 4	0.69	0.42	0.78	1.84
GSM1900	Ant 5	0.87	0.87	0.87	2.07
WCDMA II	Ant 4	0.79	0.40	0.78	1.84
WCDMA II	Ant 5	0.87	0.82	0.87	2.10
WCDMA IV	Ant 2	0.80	0.48	0.26	2.10
WCDMA IV	Ant 3	0.61	0.44	0.12	1.84
WCDMA IV	Ant 4	0.69	0.29	0.78	1.84
WCDMA IV	Ant 5	0.78	0.68	0.78	1.84
WCDMA V	Ant 0	0.87	0.87	0.87	2.07
WCDMA V	Ant 1	0.66	0.22	0.78	1.84
LTE Band 2	Ant 4	0.67	0.39	0.78	1.84
LTE Band 2	Ant 5	0.94	0.87	0.94	2.21
LTE Band 4	Ant 2	0.86	0.53	0.36	2.21
LTE Band 4	Ant 3	0.69	0.37	0.94	2.21
LTE Band 4	Ant 4	0.89	0.37	0.94	2.21
LTE Band 4	Ant 5	0.94	0.83	0.94	2.21
LTE Band 5	Ant 0	0.87	0.87	0.87	2.07
LTE Band 5	Ant 1	0.74	0.18	0.83	1.97
LTE Band 7	Ant 2	0.81	0.44	0.29	2.21
LTE Band 7	Ant 3	0.71	0.57	0.78	1.84
LTE Band 7	Ant 4	0.77	0.32	0.87	2.07
LTE Band 7	Ant 5	0.94	0.54	0.94	2.21
LTE Band 66	Ant 2	0.86	0.53	0.36	2.21
LTE Band 66	Ant 3	0.58	0.37	0.94	2.21
LTE Band 66	Ant 4	0.89	0.37	0.94	2.21
LTE Band 66	Ant 5	0.94	0.83	0.94	2.21
LTE Band 38	Ant 2	0.82	0.52	0.94	2.21
LTE Band 38	Ant 3	0.47	0.41	0.94	2.21
LTE Band 38	Ant 4	0.93	0.31	0.94	2.21
LTE Band 38	Ant 5	0.94	0.55	0.94	2.21
LTE Band 41	Ant 2	0.82	0.52	0.16	2.21
LTE Band 41	Ant 3	0.67	0.41	0.94	2.21
LTE Band 41	Ant 4	0.55	0.22	0.94	2.21
LTE Band 41	Ant 5	0.94	0.53	0.94	2.21
FR1 n5	Ant 0	0.87	0.87	0.87	2.07
FR1 n5	Ant 1	0.78	0.33	0.83	1.97
FR1 n7	Ant 2	0.85	0.55	0.22	2.21
FR1 n7	Ant 3	0.77	0.71	0.78	1.84
FR1 n7	Ant 4	0.80	0.32	0.50	2.07
FR1 n7	Ant 5	0.94	0.46	0.94	2.21
FR1 n38	Ant 2	0.88	0.49	0.17	2.07
FR1 n38	Ant 3	0.91	0.97	0.94	1.97
FR1 n38	Ant 4	0.83	0.34	0.94	2.07



FR1 n38	Ant 5	0.94	0.55	0.94	1.97
FR1 n41	Ant 2	0.88	0.51	0.17	2.21
FR1 n41	Ant 3	0.91	0.97	0.94	2.21
FR1 n41	Ant 4	0.83	0.34	0.94	2.21
FR1 n41	Ant 5	0.94	0.55	0.94	2.21
FR1 n77 PC3	Ant 4	0.76	0.31	0.78	1.84
FR1 n77 PC3	Ant 6	0.74	0.28	0.64	1.84
FR1 n77 PC3	Ant 7	0.80	0.33	0.15	1.97
FR1 n77 PC3	Ant 8	0.76	0.36	0.73	1.84
FR1 n78 PC2	Ant 4	0.73	0.26	0.78	1.84
FR1 n78 PC2	Ant 6	0.63	0.39	0.71	1.84
FR1 n78 PC2	Ant 7	0.69	0.27	0.18	1.84
FR1 n78 PC2	Ant 8	0.66	0.70	0.81	1.84
FR1 n78 PC3	Ant 4	0.73	0.26	0.78	1.84
FR1 n78 PC3	Ant 6	0.63	0.39	0.71	1.84
FR1 n78 PC3	Ant 7	0.69	0.27	0.18	1.84
FR1 n78 PC3	Ant 8	0.66	0.70	0.81	1.84

Uncertainty:

Band	Antenna				
GSM 850	Main Ant0	AuX Ant1	NA	NA	NA
GSM 1900	Main Ant5	AuX Ant4	NA	NA	NA
WCDMA B2	Main Ant5	AuX1 Ant4	NA	NA	NA
WCDMA B4	Main Ant2	AuX1 Ant5/4/3	NA	NA	NA
WCDMA B5	Main Ant0	AuX1 Ant1	NA	NA	NA
LTE B2	Main Ant5	AuX1 Ant4	NA	NA	NA
LTE B5	Main Ant0	AuX1 Ant1	NA	NA	NA
LTE B4/7/66/38/41	Main Ant2	AuX1 Ant5	AuX2 Ant4/3	AuX3 Ant3	AuX4 An4
5G NR n5	Main Ant0	AuX1 Ant1	NA	NA	NA
5G NR n7/38/41	Main Ant2	AuX1 Ant5	AuX2 Ant4	AuX3 Ant3	NA
5G NR n77/78	Main Ant7	AuX1 Ant4	AuX2 Ant6	AuX3 Ant8	NA



Tech	Antenna	Total Uncertainty (dB)	Description	
			Antenna Number	Frequency
GSM	Main	1.00	Ant 0/5	All Frequency
	Aux	1.50	Ant 1/4	All Frequency
WADMA	Main	1.00	Ant 5/2/0	All Frequency
	Aux 1	1.50	Ant 1/3/4/5	All Frequency
LTE	Main	1.00	Ant 0	Fre < 1GHz
		0.70	Ant 2/5	All Frequency
	Aux 1	1.20	Ant 1	Fre < 1GHz
		0.70	Ant 5	All Frequency
		1.50	Ant 4	All Frequency
		0.70	Ant 4/3	All Frequency
	Aux 3	1.50	Ant 3	only band7
	Aux 4	1.00	Ant 4	only band7
5GNR	Main	1.00	Ant0	f < 1GHz
		1.00	Ant2	only for 5GNR n38
		0.70	Ant2	1GHz < f < 3GHz (Except 5GNR n38)
		0.70	Ant7	f ≥ 3GHz (Except 5GNR n78 PC2)
		1.50	Ant7	only for 5GNR n78 PC2
	Aux 1	1.20	Ant1	f < 1GHz
		1.20	Ant5	only for 5GNR n38
		0.70	Ant5	1GHz < f < 3GHz (Except 5GNR n38)
		1.50	Ant4	f ≥ 3GHz
	Aux 2	0.70	Ant4	1GHz < f < 3GHz (Except 5GNR n7/n38)
		1.00	Ant4	only for 5GNR n7/n38
		1.50	Ant6	f ≥ 3GHz (Except 5GNR n78 PC3)
		1.20	Ant6	only for 5GNR n78 PC3
	Aux 3	1.50	Ant 8	f ≥ 3GHz
		0.70	Ant 3	1GHz < f < 3GHz (Except 5GNR n7/n38)
		1.50	Ant 3	only for 5GNR n7
		1.20	Ant 3	only for 5GNR n38

Antenna Group:

Antenna Group 0 (AG0)	ANT1 & ANT2& ANT3& ANT4& ANT6 & ANT7 & ANT8
Antenna Group 1 (AG1)	ANT0 & ANT5 & ANT2 & ANT3

Note: Ant2 and Ant3 as shared antenna(s) among AG0 and AG1.

To account for total uncertainty, SAR_design_target should be determined as:

$$SAR_{design_target} < SAR_{regulatory_limit} \times 10^{\frac{-total\ uncertainty}{10}}$$



3.2 SAR Char Table

SAR char must be generated to cover all radio configurations and usage scenarios that the wireless device supports for operating at 6 GHz or below. It will then be used as input for Smart Transmit to control and manage RF exposure for $f < 6$ GHz.

<P_{limit} for supported technologies and bands (P_{limit} in EFS file)>

Band	Antenna	Head DSI 1 Power	Hotspot DSI 5 Power	Body Worn DSI 4 Power	Sensor On DSI 3 Power	Pmax
GSM850	Ant 0	24.0	24.00	24.00	24.00	24.0
GSM850	Ant 1	21.50	21.50	23.50	23.50	23.5
GSM1900	Ant 4	19.00	19.00	19.50	19.50	19.5
GSM1900	Ant 5	21.00	21.00	21.00	21.00	21.0
WCDMA II	Ant 4	18.00	18.00	23.00	21.00	23.0
WCDMA II	Ant 5	24.00	21.50	24.00	22.50	24.0
WCDMA IV	Ant 2	17.50	17.50	22.00	22.00	24.0
WCDMA IV	Ant 3	21.50	21.50	22.00	22.00	23.0
WCDMA IV	Ant 4	17.00	17.00	23.00	20.00	23.0
WCDMA IV	Ant 5	24.00	21.00	24.00	22.50	24.0
WCDMA V	Ant 0	24.00	24.00	24.00	24.00	24.0
WCDMA V	Ant 1	22.00	22.00	24.00	24.00	24.0
LTE Band 2	Ant 4	17.50	17.50	23.50	19.50	23.5
LTE Band 2	Ant 5	25.00	22.50	25.00	23.00	25.0
LTE Band 4	Ant 2	18.50	18.50	23.00	23.00	25.0
LTE Band 4	Ant 3	21.00	19.00	25.00	22.00	25.0
LTE Band 4	Ant 4	18.00	18.00	25.00	20.00	25.0
LTE Band 4	Ant 5	25.00	22.00	25.00	23.00	25.0
LTE Band 5	Ant 0	24.50	24.50	24.50	24.50	24.5
LTE Band 5	Ant 1	23.00	23.00	24.50	24.50	24.5
LTE Band 7	Ant 2	19.50	19.50	22.00	22.00	25.0
LTE Band 7	Ant 3	20.50	20.50	24.00	20.50	24.0
LTE Band 7	Ant 4	17.00	17.00	24.00	19.50	24.0
LTE Band 7	Ant 5	25.00	21.00	25.00	21.00	25.0
LTE Band 66	Ant 2	18.50	18.50	23.00	23.00	25.0
LTE Band 66	Ant 3	20.00	20.00	25.00	21.00	25.0
LTE Band 66	Ant 4	18.00	18.00	25.00	20.00	25.0
LTE Band 66	Ant 5	25.00	22.00	25.00	22.50	25.0
LTE Band 38	Ant 2	19.50	19.50	23.00	23.00	23.0
LTE Band 38	Ant 3	17.50	17.50	23.00	20.50	23.0
LTE Band 38	Ant 4	18.00	18.00	23.00	19.00	23.0
LTE Band 38	Ant 5	23.00	21.00	23.00	21.00	23.0
LTE Band 41	Ant 2	20.00	20.00	21.00	21.00	23.0
LTE Band 41	Ant 3	19.00	19.00	23.00	20.00	23.0
LTE Band 41	Ant 4	16.50	16.50	23.00	18.50	23.0
LTE Band 41	Ant 5	23.00	20.50	23.00	20.50	23.0
FR1 n5	Ant 0	24.50	24.50	24.50	24.50	24.5
FR1 n5	Ant 1	23.00	23.00	24.50	24.50	24.5
FR1 n7	Ant 2	20.50	20.50	21.00	21.00	25.0
FR1 n7	Ant 3	21.00	20.50	24.00	20.50	24.0
FR1 n7	Ant 4	17.00	17.00	23.50	18.50	24.0
FR1 n7	Ant 5	25.00	20.00	25.00	20.00	25.0
FR1 n38	Ant 2	19.00	19.00	21.50	21.50	24.5
FR1 n38	Ant 3	20.00	20.00	24.50	21.00	24.5
FR1 n38	Ant 4	17.00	17.00	24.50	19.50	24.5
FR1 n38	Ant 5	25.00	19.50	25.00	19.50	24.5
FR1 n41	Ant 2	19.00	19.00	22.00	22.00	25.0
FR1 n41	Ant 3	22.00	22.00	25.00	22.00	25.0
FR1 n41	Ant 4	17.50	17.50	25.00	19.50	25.0



FR1 n41	Ant 5	25.00	20.50	25.00	20.50	25.0
FR1 n77 PC3	Ant 4	16.00	16.00	23.00	19.50	23.0
FR1 n77 PC3	Ant 6	17.00	17.00	23.00	17.00	24.0
FR1 n77 PC3	Ant 7	15.60	15.50	18.00	18.00	25.0
FR1 n77 PC3	Ant 8	19.50	14.50	21.50	14.50	24.0
FR1 n78 PC2	Ant 4	15.50	15.50	24.00	18.00	24.0
FR1 n78 PC2	Ant 6	18.00	18.00	23.00	19.00	27.0
FR1 n78 PC2	Ant 7	14.50	14.50	17.00	17.00	25.5
FR1 n78 PC2	Ant 8	19.50	13.00	19.00	14.00	24.5
FR1 n78 PC3	Ant 4	15.50	15.50	24.00	18.00	23.0
FR1 n78 PC3	Ant 6	18.00	18.00	23.00	19.00	24.5
FR1 n78 PC3	Ant 7	14.50	14.50	17.00	17.00	25.0
FR1 n78 PC3	Ant 8	19.50	13.00	19.00	14.00	24.0

- Note: 1) *P_{max} is used for RF tune up procedure. The maximum allowed output power is equal to P_{max} + uncertainty.
- 2) **All P_{limit} power levels entered in the Table correspond to average power levels after accounting for duty cycle in the case TDD modulation schemes (for e.g., GSM).
- 3) The max allowed output power is the P_{limit} + device uncertainty, and if P_{limit} is higher than P_{max}, the device output power will be P_{max} instead.
- 4) GSM/WCDMA applies force peak method. if force peak is set to 'x' for a given tech/band/antenna/DSI in the EFS, then the Smart Transmit feature limits the maximum instantaneous Tx power to P_{limit} for the selected tech/band/antenna/DSI. In other words, with force peak set to 'x', under static condition (i.e., fixed tech/band /antenna/DSI) and in single active Tx scenario, Smart Transmit can guarantee Tx power level of P_{limit} at all times.
- 5) The following table is duty cycle and factor used for calculating time average power.

GSM/FDD/TDD	Duty Cycle	Time average calculation factor(dB)
GSM 1TX	12.50%	-9.0
GSM 2TX	25%	-6.0
GSM 3TX	37.50%	-4.3
GSM 4TX	50%	-3.0
FDD LTE	100%	0.0
TDD LTE	63.30%	-2.0
NR FDD/TDD	100%	0.0