





<2Mbps>



<3Mbps>



## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup







### 3.7.5 Test Result of Conducted Spurious Emission


<Ant. 11>


<1Mbps>






<2Mbps>









<3Mbps>






<Ant. 7>

<1Mbps>















<2Mbps>





<3Mbps>







### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.


**3.8.3 Test Procedures**

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz







### **3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### **3.8.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C and D.

### **3.8.7 Duty Cycle**

Please refer to Appendix E.

### **3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix C and D.

### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Jan. 13, 2021~ Jan. 26, 2021	Jul. 13, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N -06	47020 & 06	30MHz to 1GHz	Oct. 11, 2020	Jan. 13, 2021~ Jan. 26, 2021	Oct. 10, 2021	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Sep. 30, 2020	Jan. 13, 2021~ Jan. 26, 2021	Sep. 29, 2021	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1522	1G~18GHz	Sep. 29, 2020	Jan. 13, 2021~ Jan. 26, 2021	Sep. 28, 2021	Radiation (03CH16-HY)
Amplifier	EMCI	EMC051845S E	980729	1-18GHz	Jul. 10, 2020	Jan. 13, 2021~ Jan. 26, 2021	Jul. 09, 2021	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170576	18GHz ~40GHz	May 22, 2010	Jan. 13, 2021~ Jan. 26, 2021	May 21, 2021	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 10, 2020	Jan. 13, 2021~ Jan. 26, 2021	Dec. 09, 2021	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Dec. 11, 2020	Jan. 13, 2021~ Jan. 26, 2021	Dec. 10, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/4PE	NA	Aug. 29, 2020	Jan. 13, 2021~ Jan. 26, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/4PE	NA	Aug. 29, 2020	Jan. 13, 2021~ Jan. 26, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300-575 7	NA	Aug. 29, 2020	Jan. 13, 2021~ Jan. 26, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Jan. 13, 2021~ Jan. 26, 2021	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Jan. 13, 2021~ Jan. 26, 2021	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jan. 13, 2021~ Jan. 26, 2021	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jan. 13, 2021~ Jan. 26, 2021	N/A	Radiation (03CH16-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 22, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 11, 2020	Jan. 22, 2021	Sep. 10, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Jan. 22, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2020	Jan. 22, 2021	Nov. 15, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 22, 2021	N/A	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Jan. 22, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	ESHVTS 9561-F N3-Z2	109561-F N003730851	9kHz~200MHz	Nov. 02, 2020	Jan. 22, 2021	Nov. 01, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Jan. 11, 2021~ Jan. 15, 2021	Mar. 01, 2021	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	Jan. 11, 2021~ Jan. 15, 2021	Jul. 21, 2021	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Jan. 11, 2021~ Jan. 15, 2021	Mar. 16, 2021	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	1036004	N/A	Aug. 12, 2020	Jan. 11, 2021~ Jan. 15, 2021	Aug. 11, 2021	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GH z	Aug. 12, 2020	Jan. 11, 2021~ Jan. 15, 2021	Aug. 11, 2021	Conducted (TH05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.3
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7
---	-----

### Appendix A. Test Result of Conducted Test Items

Test Engineer:	Rebecca Li / Hank Hsu	Temperature:	21~25	°C
Test Date:	2021/1/11~1/15	Relative Humidity:	51~54	%

<Ant.11>

<b>TEST RESULTS DATA</b>									
<b>20dB and 99% Occupied Bandwidth and Hopping Channel Separation</b>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.888	0.827	0.998	0.5920	Pass
DH	1Mbps	1	39	2441	0.891	0.824	0.694	0.5940	Pass
DH	1Mbps	1	78	2480	0.891	0.827	0.846	0.5940	Pass
2DH	2Mbps	1	0	2402	1.263	1.163	0.998	0.8420	Pass
2DH	2Mbps	1	39	2441	1.285	1.166	0.872	0.8567	Pass
2DH	2Mbps	1	78	2480	1.285	1.163	0.998	0.8567	Pass
3DH	3Mbps	1	0	2402	1.228	1.149	0.994	0.8187	Pass
3DH	3Mbps	1	39	2441	1.228	1.146	1.150	0.8187	Pass
3DH	3Mbps	1	78	2480	1.228	1.149	1.015	0.8187	Pass

<b>TEST RESULTS DATA</b>						
<b>Dwell Time</b>						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

<b>TEST RESULTS DATA</b>					
<b>Peak Power Table</b>					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	19.07	20.97	Pass
	39	1	19.48	20.97	Pass
	78	1	19.57	20.97	Pass
2DH1	0	1	18.65	20.97	Pass
	39	1	19.04	20.97	Pass
	78	1	19.23	20.97	Pass
3DH1	0	1	18.79	20.97	Pass
	39	1	19.08	20.97	Pass
	78	1	19.26	20.97	Pass

<b>TEST RESULTS DATA</b>				
<b>Average Power Table</b>				
<b>(Reporting Only)</b>				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	18.84	5.22
	39	1	19.41	5.22
	78	1	19.49	5.22
2DH1	0	1	16.50	5.16
	39	1	16.77	5.16
	78	1	17.03	5.16
3DH1	0	1	16.61	5.17
	39	1	16.84	5.17
	78	1	17.12	5.17

<b>TEST RESULTS DATA</b>			
<b>Number of Hopping Frequency</b>			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



<Ant.7>

<b>TEST RESULTS DATA</b>									
<b>20dB and 99% Occupied Bandwidth and Hopping Channel Separation</b>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.888	0.827	1.002	0.5920	Pass
DH	1Mbps	1	39	2441	0.888	0.824	0.998	0.5920	Pass
DH	1Mbps	1	78	2480	0.891	0.824	0.850	0.5940	Pass
2DH	2Mbps	1	0	2402	1.224	1.163	1.002	0.8160	Pass
2DH	2Mbps	1	39	2441	1.215	1.166	0.998	0.8100	Pass
2DH	2Mbps	1	78	2480	1.224	1.166	1.002	0.8160	Pass
3DH	3Mbps	1	0	2402	1.228	1.149	0.994	0.8187	Pass
3DH	3Mbps	1	39	2441	1.228	1.146	0.846	0.8187	Pass
3DH	3Mbps	1	78	2480	1.228	1.149	0.850	0.8187	Pass

<b>TEST RESULTS DATA</b>						
<b>Dwell Time</b>						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

<b>TEST RESULTS DATA</b>					
<b>Peak Power Table</b>					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	17.25	20.97	Pass
	39	1	18.06	20.97	Pass
	78	1	18.49	20.97	Pass
2DH1	0	1	17.22	20.97	Pass
	39	1	17.94	20.97	Pass
	78	1	18.47	20.97	Pass
3DH1	0	1	17.32	20.97	Pass
	39	1	17.99	20.97	Pass
	78	1	18.53	20.97	Pass

<b>TEST RESULTS DATA</b>				
<b>Average Power Table</b>				
<b>(Reporting Only)</b>				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	16.93	5.22
	39	1	17.76	5.22
	78	1	18.31	5.22
2DH1	0	1	14.40	5.15
	39	1	15.18	5.15
	78	1	15.94	5.15
3DH1	0	1	14.38	5.15
	39	1	15.22	5.15
	78	1	15.98	5.15

<b>TEST RESULTS DATA</b>			
<b>Number of Hopping Frequency</b>			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	23~26°C
		Relative Humidity :	40~50%

## EUT Information

Report NO : 110409  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.174750	---	27.99	54.73	26.74	L1	OFF	19.7
0.174750	32.42	---	64.73	32.31	L1	OFF	19.7
0.234510	---	31.95	52.29	20.34	L1	OFF	19.7
0.234510	35.10	---	62.29	27.19	L1	OFF	19.7
0.504960	---	27.81	46.00	18.19	L1	OFF	19.9
0.504960	31.29	---	56.00	24.71	L1	OFF	19.9
1.488390	---	23.38	46.00	22.62	L1	OFF	20.2
1.488390	25.59	---	56.00	30.41	L1	OFF	20.2
4.832970	---	25.35	46.00	20.65	L1	OFF	20.1
4.832970	27.56	---	56.00	28.44	L1	OFF	20.1
11.573250	---	27.03	50.00	22.97	L1	OFF	20.2
11.573250	29.83	---	60.00	30.17	L1	OFF	20.2

## EUT Information

Report NO : 110409  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.166200	---	30.68	55.15	24.47	N	OFF	19.7
0.166200	36.00	---	65.15	29.15	N	OFF	19.7
0.235770	---	31.96	52.24	20.28	N	OFF	19.8
0.235770	35.54	---	62.24	26.70	N	OFF	19.8
0.502980	---	30.21	46.00	15.79	N	OFF	19.9
0.502980	33.24	---	56.00	22.76	N	OFF	19.9
2.455170	---	23.87	46.00	22.13	N	OFF	20.2
2.455170	25.95	---	56.00	30.05	N	OFF	20.2
6.083250	---	26.00	50.00	24.00	N	OFF	20.1
6.083250	28.33	---	60.00	31.67	N	OFF	20.1
12.534000	---	26.80	50.00	23.20	N	OFF	20.3
12.534000	29.78	---	60.00	30.22	N	OFF	20.3



### Appendix C. Radiated Spurious Emission

Test Engineer :	Karl Hou, Caster Liao and Andy Yang	Temperature :	20~25°C
		Relative Humidity :	50~60%

<Ant. 11>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2386.965	47.61	-26.39	74	41.75	27.58	8.56	30.28	120	91	P	H
		2386.965	22.82	-31.18	54	-	-	-	-	-	-	A	H
	*	2402	108.3	-	-	102.5	27.5	8.58	30.28	120	91	P	H
		2402	83.51	29.51	54	-	-	-	-	-	-	A	H
		2313.99	46.94	-27.06	74	40.95	27.87	8.42	30.3	376	71	P	V
		2313.99	22.15	-31.85	54	-	-	-	-	-	-	A	V
	*	2402	106.07	-	-	100.27	27.5	8.58	30.28	376	71	P	V
		2402	81.28	27.28	54	-	-	-	-	-	-	A	V
													V
BT CH 39 2441MHz		2335.62	46.81	-27.19	74	40.82	27.83	8.46	30.3	105	145	P	H
		2335.62	22.02	-31.98	54	-	-	-	-	-	-	A	H
	*	2441	107.37	-	-	101.56	27.42	8.66	30.27	105	145	P	H
		2441	82.58	28.58	54	-	-	-	-	-	-	A	H
		2493.91	47.5	-26.5	74	41.59	27.4	8.76	30.25	105	145	P	H
		2493.91	22.71	-31.29	54	-	-	-	-	-	-	A	H
		2315.88	46.76	-27.24	74	40.77	27.87	8.42	30.3	324	72	P	V
		2315.88	21.97	-32.03	54	-	-	-	-	-	-	A	V
	*	2441	107.83	-	-	102.02	27.42	8.66	30.27	324	72	P	V
		2441	83.04	29.04	54	-	-	-	-	-	-	A	V
		2495.17	47.43	-26.57	74	41.51	27.4	8.77	30.25	324	72	P	V
		2495.17	22.64	-31.36	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	107.17	-	-	101.29	27.4	8.74	30.26	100	144	P	H
		2480	82.38	28.38	54	-	-	-	-	-	-	A	H
		2483.56	51.89	-22.11	74	46	27.4	8.74	30.25	100	144	P	H
		2483.56	27.1	-26.9	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	107.18	-	-	101.3	27.4	8.74	30.26	356	72	P	V
		2480	82.39	28.39	54	-	-	-	-	-	-	A	V
		2483.6	52.51	-21.49	74	46.62	27.4	8.74	30.25	356	72	P	V
		2483.6	27.72	-26.28	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH 00 2402MHz		4804	40.68	-33.32	74	51.57	31.11	13.36	55.36	100	0	P	H	
		4804	15.89	-38.11	54	-	-	-	-	-	-	A	H	
													H	
													H	
		4804	40.25	-33.75	74	51.14	31.11	13.36	55.36	100	0	P	V	
		4804	15.46	-38.54	54	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		4882	39.47	-34.53	74	50.35	31.14	13.36	55.38	100	0	P	H	
		4882	14.68	-39.32	54	-	-	-	-	-	-	A	H	
		7323	46.31	-27.69	74	49.93	36.45	16.19	56.26	100	0	P	H	
		7323	21.52	-32.48	54	-	-	-	-	-	-	A	H	
		4882	39.71	-34.29	74	50.59	31.14	13.36	55.38	100	0	P	V	
		4882	14.92	-39.08	54	-	-	-	-	-	-	-	A	V
		7323	45.99	-28.01	74	49.61	36.45	16.19	56.26	100	0	P	V	
		7323	21.2	-32.8	54	-	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	39.64	-34.36	74	50.33	31.34	13.36	55.39	100	0	P	H	
		4960	14.85	-39.15	54	-	-	-	-	-	-	A	H	
		7440	46.46	-27.54	74	49.96	36.4	16.39	56.29	100	0	P	H	
		7440	21.67	-32.33	54	-	-	-	-	-	-	A	H	
		4960	39.78	-34.22	74	50.47	31.34	13.36	55.39	100	0	P	V	
		4960	14.99	-39.01	54	-	-	-	-	-	-	A	V	
		7440	45.28	-28.72	74	48.78	36.4	16.39	56.29	100	0	P	V	
		7440	20.49	-33.51	54	-	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													





Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BT LF		62.98	16.68	-23.32	40	36.35	11.96	1.16	32.79	-	-	P	H	
		78.5	22.09	-17.91	40	40.13	13.25	1.31	32.71	-	-	P	H	
		97.9	23.66	-19.84	43.5	38.87	15.49	1.5	32.62	-	-	P	H	
		184.23	26.84	-16.66	43.5	42.45	15.05	2.23	32.86	-	-	P	H	
		310.33	23.35	-22.65	46	33.52	19.37	2.95	32.53	-	-	P	H	
		746.83	33.11	-12.89	46	32.91	27.25	4.63	32.49	100	0	P	H	
														H
														H
														H
														H
														H
														H
														H
			44.55	25.17	-14.83	40	40.13	11.96	1.16	32.79	-	-	P	V
			63.95	26.69	-13.31	40	46.36	13.25	1.31	32.71	-	-	P	V
			78.5	30.98	-9.02	40	49.02	15.06	2.24	32.87	100	0	P	V
			184.23	25.54	-17.96	43.5	41.15	21.94	3.37	32.38	-	-	P	V
			562.53	27.79	-18.21	46	30.18	26.1	4.09	32.67	-	-	P	V
			746.83	33.25	-12.75	46	33.05	28.13	4.69	32.62	-	-	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



<Ant. 7>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2341.08	47.55	-26.45	74	41.55	27.82	8.47	30.29	119	93	P	H
		2341.08	22.76	-31.24	54	-	-	-	-	-	-	A	H
	*	2402	109.08	-	-	103.28	27.5	8.58	30.28	119	93	P	H
		2402	84.29	30.29	54	-	-	-	-	-	-	A	H
		2369.01	47.37	-26.63	74	41.45	27.69	8.52	30.29	375	71	P	V
		2369.01	22.58	-31.42	54	-	-	-	-	-	-	A	V
	*	2402	107.84	-	-	102.04	27.5	8.58	30.28	375	71	P	V
		2402	83.05	29.05	54	-	-	-	-	-	-	A	V
													V
BT CH 39 2441MHz		2362.64	47.86	-26.14	74	41.92	27.72	8.51	30.29	100	92	P	H
		2362.64	23.07	-30.93	54	-	-	-	-	-	-	A	H
	*	2441	110.06	-	-	104.25	27.42	8.66	30.27	100	92	P	H
		2441	85.27	31.27	54	-	-	-	-	-	-	A	H
		2485.23	47.82	-26.18	74	41.92	27.4	8.75	30.25	100	92	P	H
		2485.23	23.03	-30.97	54	-	-	-	-	-	-	A	H
		2333.24	46.59	-27.41	74	40.6	27.83	8.46	30.3	364	70	P	V
		2333.24	21.8	-32.2	54	-	-	-	-	-	-	A	V
	*	2441	108.74	-	-	102.93	27.42	8.66	30.27	364	70	P	V
		2441	83.95	29.95	54	-	-	-	-	-	-	A	V
		2486.77	47.87	-26.13	74	41.97	27.4	8.75	30.25	364	70	P	V
		2486.77	23.08	-30.92	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	108.82	-	-	102.94	27.4	8.74	30.26	111	91	P	H
		2480	84.03	30.03	54	-	-	-	-	-	-	A	H
		2483.52	53.47	-20.53	74	47.58	27.4	8.74	30.25	111	91	P	H
		2483.52	28.68	-25.32	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	108.33	-	-	102.45	27.4	8.74	30.26	356	70	P	V
		2480	83.54	29.54	54	-	-	-	-	-	-	A	V
		2483.56	53.53	-20.47	74	47.64	27.4	8.74	30.25	356	70	P	V
		2483.56	28.74	-25.26	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	40.96	-33.04	74	51.85	31.11	13.36	55.36	100	0	P	H
		4804	16.17	-37.83	54	-	-	-	-	-	-	A	H
													H
													H
		4804	40.88	-33.12	74	51.77	31.11	13.36	55.36	100	0	P	V
		4804	16.09	-37.91	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	39.78	-34.22	74	50.66	31.14	13.36	55.38	100	0	P	H
		4882	14.99	-39.01	54	-	-	-	-	-	-	A	H
		7323	45.74	-28.26	74	49.36	36.45	16.19	56.26	100	0	P	H
		7323	20.95	-33.05	54	-	-	-	-	-	-	A	H
		4882	39.88	-34.12	74	50.76	31.14	13.36	55.38	100	0	P	V
		4882	15.09	-38.91	54	-	-	-	-	-	-	A	V
		7323	45.4	-28.6	74	49.02	36.45	16.19	56.26	100	0	P	V
		7323	20.61	-33.39	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	39.96	-34.04	74	50.65	31.34	13.36	55.39	100	0	P	H
		4960	15.17	-38.83	54	-	-	-	-	-	-	A	H
		7440	45.42	-28.58	74	48.92	36.4	16.39	56.29	100	0	P	H
		7440	20.63	-33.37	54	-	-	-	-	-	-	A	H
		4960	40.38	-33.62	74	51.07	31.34	13.36	55.39	100	0	P	V
		4960	15.59	-38.41	54	-	-	-	-	-	-	A	V
		7440	45.7	-28.3	74	49.2	36.4	16.39	56.29	100	0	P	V
		7440	20.91	-33.09	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BT LF		62.98	19.1	-20.9	40	38.77	11.96	1.16	32.79	-	-	P	H	
		77.53	23.31	-16.69	40	41.46	13.25	1.31	32.71	-	-	P	H	
		96.93	23.65	-19.85	43.5	39.06	15.26	1.48	32.63	-	-	P	H	
		184.23	25.92	-17.58	43.5	41.53	15.03	2.22	32.86	-	-	P	H	
		303.54	23.39	-22.61	46	33.7	19.25	2.89	32.56	-	-	P	H	
		891.36	32.54	-13.46	46	30.66	27.82	4.65	32.54	100	0	P	H	
														H
														H
														H
														H
														H
														H
			45.52	26.06	-13.94	40	41.49	16.97	0.89	32.82	-	-	P	V
			63.95	25.74	-14.26	40	45.41	11.93	1.14	32.79	-	-	P	V
			77.53	30.73	-9.27	40	48.88	13.35	1.32	32.71	100	0	P	V
			183.26	24.39	-19.11	43.5	39.97	15.03	2.22	32.86	-	-	P	V
			557.68	28.22	-17.78	46	30.72	19.24	2.89	32.57	-	-	P	V
			714.82	31.99	-14.01	46	32.89	27.96	4.66	32.56	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**






## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Karl Hou, Caster Liao and Andy Yang	Temperature :	20~25°C
		Relative Humidity :	50~60%



<Ant. 11>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)








BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p data-bbox="430 712 702 772">Date: 2021-01-16 Site : 03CH16-HY Condition : PEAK_8E_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 110409</p>	 <p data-bbox="901 712 1173 772">Date: 2021-01-16 Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 110409</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>
Peak	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
Horizontal		Fundamental
Peak	 <p>Date: 2021-01-16</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Date: 2021-01-16</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2021-01-16</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Date: 2021-01-16</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>





2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 110409</p>	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 110409</p>



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
	<b>BT CH39 2441MHz</b>	
	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 110409</p>







BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BT CH78 2480MHz		
Horizontal		Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH16-HY          Condition : PEAK_74 3m 91200_1522 HORIZONTAL          Detector : Peak          Project : 110409</p>	 <p>Site : 03CH16-HY          Condition : PEAK_74 3m 91200_1522 VERTICAL          Detector : Peak          Project : 110409</p>



Emission below 1GHz  
2.4GHz BT (LF)



BT	2.4GHz 2400~2483.5MHz	
BT LF		
Horizontal		Vertical
QP / Peak	 <p>Site : 03CH16-1FY Condition : QP 3m BTL06_47020406 HORIZONTAL Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-1FY Condition : QP 3m BTL06_47020406 VERTICAL Detector : Peak Project : 110409</p>





<Ant. 7>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Date: 2021-01-15</p> <p>Site : 03CH15-1FV            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 110409</p>	 <p>Date: 2021-01-15</p> <p>Site : 03CH15-1FV            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            Detector : Peak            Project : 110409</p>






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2021-01-15</p> <p>Site : 03CH16-HY            Condition : PEAK_8E_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Date: 2021-01-15</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>
<p><b>Peak</b></p>	 <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Vertical	Fundamental
Peak	 <p>           Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409         </p>	 <p>           Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409         </p>
Peak	 <p>           Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409         </p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 110409</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2021-01-15</p> <p>Site : 03CH16-HY            Condition : PEAK_BE_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>	 <p>Date: 2021-01-15</p> <p>Site : 03CH16-HY            Condition : PEAK_74 3m 91200_1522 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 110409</p>







2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 110409</p>	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 110409</p>





<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
	<b>BT CH39 2441MHz</b>	
	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 110409</p>



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
	<b>BT CH78 2480MHz</b>	
	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 110409</p>




Emission below 1GHz  
2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
<p>QP / Peak</p>	 <p>Site : 03CH16-1FY Condition : QP 3m BTLOG_47020406 HORIZONTAL Detector : Peak Project : 110409</p>	 <p>Site : 03CH16-1FY Condition : QP 3m BTLOG_47020406 VERTICAL Detector : Peak Project : 110409</p>



# Appendix E. Duty Cycle Plots

<Ant. 11>



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = 2 \* 2.88 / 100 = 5.76 %
2. Worst case Duty cycle correction factor = 20\*log(Duty cycle) = -24.79 dB
3. DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.6 ms ] = 2 hops

Thus, the maximum possible ON time:


$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$



<Ant. 7>



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = 2 \* 2.88 / 100 = 5.76 %
2. Worst case Duty cycle correction factor = 20\*log(Duty cycle) = -24.79 dB
3. **3DH5** has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.6 ms] = 2 hops

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$