



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Redmi
MODEL NAME : A101XM
FCC ID : 2AFZZK19KR
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Aug. 18, 2021 ~ Sep. 09, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, and Emission Designator	6
1.7 Testing Location	7
1.8 Test Software	7
1.9 Applicable Standards	7
2 RE-USE OF MEASURED DATA	8
2.1 Introduction Section.....	8
2.2 Model Difference Information	8
2.3 Reference detail Section:	8
2.4 Spot Check Verification Data Section	9
3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
3.1 Test Mode.....	10
3.2 Connection Diagram of Test System	11
3.3 Support Unit used in test configuration	11
3.4 Measurement Results Explanation Example	11
3.5 Frequency List of Low/Middle/High Channels	12
4 CONDUCTED TEST RESULT	13
4.1 Measuring Instruments.....	13
4.2 Test Setup	13
4.3 Test Result of Conducted Test.....	13
4.4 Conducted Output Power and ERP/EIRP	14
4.5 Peak-to-Average Ratio	15
4.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	16
4.7 Conducted Band Edge	17
4.8 Conducted Spurious Emission	18
4.9 Frequency Stability	19
5 RADIATED TEST ITEMS	20
5.1 Measuring Instruments.....	20
5.2 Test Setup	20
5.3 Test Result of Radiated Test.....	20
5.4 Field Strength of Spurious Radiation Measurement	21
6 LIST OF MEASURING EQUIPMENT	22
7 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG122708-01A	Rev. 01	Initial issue of report	Sep. 22, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §24.235	Frequency Stability for Temperature & Voltage	Within Authorized Band	PASS	-
5.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 3.92 dB at 2510.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	A101XM
FCC ID	2AFZZK19KR
HW Version	P0.1
SW Version	MIUI13
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE:
	850: 824 MHz ~ 849 MHz
	1900: 1850MHz ~ 1910MHz
	WCDMA:
	Band V: 824 MHz ~ 849 MHz
Rx Frequency	Band II: 1850 MHz ~ 1910 MHz
	Band IV: 1710 MHz ~ 1755 MHz
	GSM/GPRS/EDGE:
	850: 869 MHz ~ 894 MHz
	1900: 1930 MHz ~ 1990 MHz
	WCDMA:
	Band V: 869 MHz ~ 894 MHz
	Band II: 1930 MHz ~ 1990 MHz
	Band IV: 2110 MHz ~ 2155 MHz

Maximum Output Power to Antenna	Antenna 4: GSM/GPRS/EDGE: 1900: 29.41 dBm Antenna 1: GSM/GPRS/EDGE: 1900: 29.57 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Antenna 4: Cellular Band: -4.12 dBi PCS Band: -1.11 dBi AWS Band: -1.55 dBi Antenna 1: Cellular Band: -5.13 dBi PCS Band: -1.14 dBi AWS Band: -1.12 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM (16QAM uplink is not supported)

Note: The ERP/EIRP is calculated from Output power and antenna gain, so the maximum ERP/EIRP is shown in the report, GSM1900 for Antenna 1.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 24E	GSM1900 (GSM)	1850.2 ~ 1909.8	GMSK	0.6966	244KGXW

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Re-use of Measured Data

2.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: A101XM, FCC ID: 2AFZZK19KR) is electrically identical to the reference device (Model: XIG02, FCC ID: 2AFZZK19JR) for the portions of the circuitry corresponding to the data being re-used. Based on their similarity, FCC Part 22, 24, 27 (equipment class: PCE) reuse the original model's result and do spot-check, following the FCC KDB 484596 D01 v01.

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID: 2AFZZK19KR .

2.2 Model Difference Information

The main difference between FCC ID: 2AFZZK19JR and FCC ID: 2AFZZK19KR is that the two models support different WWAN bands /NFC / WIFI 5G U-NII-3.

Other differences and all the details of similarity and difference can be found in the confidential documents (A101XM_Operational Description of Product Equality Declaration).

2.3 Reference detail Section:

Rule Part	Equipment Class	Frequency Band (MHz)	Reference FCC ID(Parent)	Type Grant/ Permissive Change	Reference Title	FCC ID Filling (Variant)	Report Title/Section
22, 24, 27,	PCE (GSM)	GSM 850	2AFZZK19JR	Original Grant	FG122708A	2AFZZK19KR	All sections applicable except RSE
	PCE (WCDMA)	Band II, IV, V	2AFZZK19JR	Original Grant	FG122708A	2AFZZK19KR	All sections applicable except RSE



2.4 Spot Check Verification Data Section

Conducted power test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model

Summary for power spot check for each rule entry and technology is listed as below:

Test Item	Mode	2AFZZK19JR Parent Worst Result	2AFZZK19KR Variant Check Result	Difference (dB)
Conducted Power (dBm)	GSM 850	32.77	32.70	-0.07
	EDGE 850	26.78	26.56	-0.22
	WCDMA Band II	23.27	22.84	-0.43
	WCDMA Band IV	24.68	24.81	0.23
	WCDMA Band V	24.85	25.07	0.22

Conclusion:

Radiated spurious emission test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

Based on the spot check test result, the test data from the original model is representative for the variant model. The power level and RSE spot check are shown within expected level compliant to limit line.

We are using power and ERP/EIRP measurements from the original parent model reports to list on the grant.

We confirm that the test data reuse policy of FCC KDB 484596 D01 Referencing Test Data v01 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.

3 Test Configuration of Equipment Under Test

3.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link 	
GSM 1900	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link 	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	

3.2 Connection Diagram of Test System



3.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Anritsu	MT8821C/MT8000	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	Xiaomi	N/A	N/A	N/A	N/A
4.	Adapter	Xiaomi	N/A	N/A	N/A	N/A

3.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 5.4 dB and a 10dB attenuator.

Example :



$Offset(dB) = RF\ cable\ loss(dB) + attenuator\ factor(dB).$

$= 54 + 10 = 15.4\ (dB)$

3.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8


4 Conducted Test Result

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 Conducted Output Power



4.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



4.2.3 Frequency Stability



4.3 Test Result of Conducted Test

Please refer to Appendix A.

4.4 Conducted Output Power and ERP/EIRP

4.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



4.5 Peak-to-Average Ratio

4.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

4.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

4.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

4.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

4.7 Conducted Band Edge

4.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

4.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

4.8 Conducted Spurious Emission

4.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

4.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

4.9 Frequency Stability

4.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

4.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

4.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


5 Radiated Test Items

5.1 Measuring Instruments


See list of measuring instruments of this test report.

5.2 Test Setup

5.2.1 For radiated test from 30MHz to 1GHz



5.2.2 For radiated test above 1GHz



5.3 Test Result of Radiated Test

Please refer to Appendix B.

5.4 Field Strength of Spurious Radiation Measurement

5.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

5.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



6 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	Sep. 09, 2021	Oct. 31, 2021	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 26, 2021	Sep. 09, 2021	Aug. 25, 2022	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 27, 2020	Sep. 09, 2021	Oct. 26, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44G, MAX 30dB	Apr. 13, 2021	Aug. 18, 2021	Apr. 12, 2022	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 01, 2020	Aug. 18, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jan. 02, 2021	Aug. 18, 2021	Jan. 01, 2022	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 18, 2021	Aug. 18, 2021	Apr. 17, 2022	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	Aug. 18, 2021	Nov. 08, 2021	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 02, 2021	Aug. 18, 2021	Jan. 01, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Aug. 18, 2021	Jan. 06, 2022	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 02, 2021	Aug. 18, 2021	Jan. 01, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Aug. 18, 2021	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 18, 2021	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 18, 2021	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 18, 2021	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

7 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.3dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	-------

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power) and ERP/EIRP)


GSM1900	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	29.40	29.54	29.41	0.6699	0.6918	0.6714
GPRS 1 Tx slot	29.42	29.57	29.44	0.6730	0.6966	0.6761
GPRS 2 Tx slots	26.47	26.51	26.50	0.3412	0.3443	0.3436
GPRS 3 Tx slots	24.98	25.11	25.01	0.2421	0.2495	0.2438
GPRS 4 Tx slots	23.14	23.36	23.03	0.1585	0.1667	0.1545
EDGE 1 Tx slot	25.27	25.47	25.45	0.2588	0.2710	0.2698
EDGE 2 Tx slots	24.36	24.42	24.38	0.2099	0.2128	0.2109
EDGE 3 Tx slots	22.94	22.97	23.00	0.1514	0.1524	0.1535
EDGE 4 Tx slots	21.86	21.91	21.96	0.1180	0.1194	0.1208



A1. GSM

Peak-to-Average Ratio

Mode	GSM1900	Limit: 13dB
Mod.	GSM	Result
Lowest CH	0.20	PASS
Middle CH	0.20	
Highest CH	0.23	






26dB Bandwidth

Mode	GSM1900
Mod.	GSM (MHz)
Lowest CH	0.3157
Middle CH	0.3077
Highest CH	0.3157




GSM1900 (GSM)


Lowest Channel



Middle Channel



Highest Channel






Occupied Bandwidth

Mode	GSM1900
Mod.	GSM (MHz)
Lowest CH	0.2428
Middle CH	0.2438
Highest CH	0.2418




GSM1900 (GSM)


Lowest Channel




Middle Channel




Highest Channel



**Conducted Band Edge****GSM1900 (GSM)****Lowest Band Edge**


Date: 9 SEP. 2021 18:56:28

Highest Band Edge

Date: 9 SEP. 2021 18:59:09



Conducted Spurious Emission



Frequency Stability

Test Conditions	Middle Channel	GSM1900 (GPRS 1 Tx slots)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Result	
50	Normal Voltage	0.0058	PASS
40	Normal Voltage	0.0015	
30	Normal Voltage	0.0119	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0145	
0	Normal Voltage	0.0136	
-10	Normal Voltage	0.0089	
-20	Normal Voltage	0.0021	
-30	Normal Voltage	0.0118	
20	Maximum Voltage	0.0052	
20	Normal Voltage	0.0011	
20	Battery End Point	0.0124	

Note:

1. Normal Voltage = 3.87V. ; Battery End Point (BEP) =3.65V. ; Maximum Voltage =4.45V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

GSM850 (GPRS 1 Tx slots)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-54.53	-13	-41.53	-61.50	1.58	10.70	H
	2508	-20.78	-13	-7.78	-29.27	1.86	12.50	H
	3345.6	-57.22	-13	-44.22	-66.76	2.21	13.90	H
	4182	-38.12	-13	-25.12	-46.58	2.69	13.30	H
	5016	-54.39	-13	-41.39	-62.15	3.09	13.00	H
	5856	-48.02	-13	-35.02	-56.79	3.18	14.10	H
	1672	-52.94	-13	-39.94	-59.91	1.58	10.70	V
	2510	-20.44	-13	-7.44	-28.93	1.86	12.50	V
	3348	-57.46	-13	-44.46	-67.00	2.21	13.90	V
	4182	-50.77	-13	-37.77	-59.23	2.69	13.30	V
	5016	-54.18	-13	-41.18	-61.94	3.09	13.00	V
	5856	-53.99	-13	-40.99	-62.76	3.18	14.10	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM850 (EDGE 1 Tx slots)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-58.50	-13	-45.50	-65.47	1.58	10.70	H
	2510	-16.92	-13	-3.92	-25.41	1.86	12.50	H
	3345.6	-58.19	-13	-45.19	-67.73	2.21	13.90	H
	4182	-38.38	-13	-25.38	-46.84	2.69	13.30	H
	5018.4	-54.70	-13	-41.70	-62.46	3.09	13.00	H
	5856	-52.44	-13	-39.44	-61.21	3.18	14.10	H
	1672	-59.04	-13	-46.04	-66.01	1.58	10.70	V
	2508	-43.08	-13	-30.08	-51.57	1.86	12.50	V
	3348	-58.03	-13	-45.03	-67.57	2.21	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band V(RMC 12.2Kbps)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-65.41	-13	-52.41	-72.38	1.58	10.70	H
	2510	-59.76	-13	-46.76	-68.25	1.86	12.50	H
	3348	-60.09	-13	-47.09	-69.63	2.21	13.90	H
	1672	-64.09	-13	-51.09	-71.06	1.58	10.70	V
	2510	-58.53	-13	-45.53	-67.02	1.86	12.50	V
	3348	-58.55	-13	-45.55	-68.09	2.21	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-56.70	-13	-43.70	-68.96	2.64	14.90	H
	5640	-38.21	-13	-25.21	-50.07	2.94	14.80	H
	7524	-52.67	-13	-39.67	-62.44	3.39	13.16	H
	3759	-54.50	-13	-41.50	-66.76	2.64	14.90	V
	5640	-35.93	-13	-22.93	-47.79	2.94	14.80	V
	7524	-52.90	-13	-39.90	-62.67	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (EDGE 1 Tx slots)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-54.09	-13	-41.09	-66.35	2.64	14.90	H
	5640	-36.41	-13	-23.41	-48.27	2.94	14.80	H
	7524	-52.83	-13	-39.83	-62.60	3.39	13.16	H
	3759	-53.83	-13	-40.83	-66.09	2.64	14.90	V
	5640	-55.51	-13	-42.51	-67.37	2.94	14.80	V
	7524	-52.46	-13	-39.46	-62.23	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-55.75	-13	-42.75	-68.01	2.64	14.90	H
	5640	-54.61	-13	-41.61	-66.47	2.94	14.80	H
	7524	-52.13	-13	-39.13	-61.90	3.39	13.16	H
	3759	-55.43	-13	-42.43	-67.69	2.64	14.90	V
	5640	-55.38	-13	-42.38	-67.24	2.94	14.80	V
	7524	-52.31	-13	-39.31	-62.08	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-57.98	-13	-44.98	-68.72	2.604	13.34	H
	5197.8	-54.53	-13	-41.53	-65.04	3.011	13.52	H
	6936	-54.66	-13	-41.66	-64.86	3.271	13.47	H
	3465	-58.20	-13	-45.20	-68.94	2.604	13.34	V
	5197.8	-54.69	-13	-41.69	-65.20	3.011	13.52	V
	6936	-54.39	-13	-41.39	-64.59	3.271	13.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.