

RF Exposure Evaluation Report

FCC ID	:	2AFZZK1G
EQUIPMENT	:	Mobile Phone
Brand Name	:	Xiaomi
Model Name	:	M2102K1G
Applicant	:	Xiaomi Communications Co., Ltd.
		#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	:	Xiaomi Communications Co., Ltd. #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
STANDARD	:	FCC CFR 47 part 1, 1.1307(b) and 1.1310 KDB 680106 D01v03

The product was received on Dec. 30, 2020 and testing was completed on Feb. 08, 2021. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in KDB 680106 D01v03 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Rosa Wang

Reviewed by: Rose Wang / Supervisor

Kat, Kin

Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc. No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China



Table of Contents

1.	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2.	ADMINISTRATION DATA	4
3.	RF EXPOSURE LIMIT INTRODUCTION	5
4.	TEST MODE	6
5.	MEASUREMENT EQUIPMENT	6
6.	RF EXPOSURE EVALUATION	6
Ар	pendix A. Test Setup Photo	



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE	
FA0D3003A	Rev. 01	Initial issue of report	Feb. 10, 2021	



1. Description of Equipment Under Test (EUT)

Product Feature & Specification					
EUT Type	EUT Type Mobile Phone				
Brand Name	Xiaomi				
Model Name	M2102K1G				
FCC ID	2AFZZK1G				
Frequency Range	110 kHz ~ 148 kHz				
Moudlation Type	•ASK				
HW Version	P2				
SW Version	MIUI12				
EUT Stage	Identical Prototype				
Date of Test	Feb. 08, 2021				

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

2. Administration Data

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory					
Test Firm	Sporton International (Kunshan) Inc.				
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158				
	FAX : +86-512-57900958				
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.			
	CN1257	314309			



3. RF Exposure Limit Introduction

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

Frequency range Electric field strength (MHz) (V/m)		Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	
and the second second	(A) Limits for (Occupational/Controlled Expos	ure	2	
0.3-3.0	614	1.63	* 100	6	
3.0-30	1842/f	4.89/f	* 900/f ²		
30-300	61.4	0.163	1.0	6	
300-1,500			f/300	6	
1,500-100,000			5	6	
	(B) Limits for Gene	ral Population/Uncontrolled Ex	posure		
0.3-1.34	614	1.63	* 100	30	
1.34-30	824/f	2.19/f	* 180/f ²	30	
30-300	27.5	0.073	0.2	30	
300-1,500			f/1500	30	
1,500-100,000			1.0	30	

f = frequency in MHz

* = Plane-wave equivalent power density

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for transient persons, but they must receive written and/or verbal information (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase exercise control means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



4. <u>Test Mode</u>

The device has been tested in the following sharging conditions de below.							
Test Mode	Test Setup Configuration	Charging Current Condition					
TM1	Test w/ Client Device installed	< 1% Battery status					
TM2	2 Test w/ Client Device installed 50% Battery status						
ТМЗ	Test w/ Client Device installed	Near 100% Battery status					

This device has been tested in the following charging conditions as below:

5. Measurement Equipment

Instrument	Manufacturer	Model No.	Serial No.	Freq Rang	Last Cal.	Due Date
Electric and Magnetic field Probe-Analyzer	Narda S.T.S / PMM	EHP 200AC	170WX80309	3KHz~30MHz	Sep. 12, 2020	Sep. 11, 2021

6. <u>RF Exposure Evaluation</u>

- 1. The device support Wireless Power Consortium (WPC or commonly referred to as Qi) standard EPP (Extended Power Profile) as a receiver, with a maximum power transfer of 67W to the phone. the device can be used in reverse, as a transmitter to another wireless charging receiver. In this case, up to 10W (BPP) can be transmitted to the external receiver.
- 2. According to 202010 TCBC workshop, for portable devices that do not physically attach to phone, desktop WPT testing guidance from FCC KDB 680106 D01v03 is applied.
- 3. Per KDB 680106 D01v03 and 202010 TCBC workshop, RF exposure evaluation at 15cm surrounding the device and 20cm above the top surface. Emissions between 50 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 1.63 A/m and aggregate H-field strengths from all simultaneous transmitting coils.
- 4. The equipment under test was placed on a wooden desk inside of shield room. The isotropic field probe was used to measure the field strength for 6 EUT surfaces. The detailed setup photo please refer to Appendix A.

Position (Distance 10cm)	H-Field Measurement (A/m)						
	A (15cm)	B (15cm)	C (15cm)	D (15cm)	E 20cm	F 20cm	Limit (A/m)
TM1	0.2230	0.2101	0.2125	0.2140	0.223	0.2164	
TM2	0.2164	0.2065	0.2134	0.2197	0.2177	0.2222	1.63
TM3	0.2125	0.2160	0.2230	0.2160	0.2317	0.2102	

Conclusion:

The field strength limit refers to Part 1.1310 and the test result of exposure evaluation is compliant.